DESCRIPTION:

SOLICITATION NUMBER:

BID DUE DATE AND TIME:

South Delta Bulldozer

1464-18-R-IFBD-00013

December 21, 2017 AT 2:00 P.M. local time The Mississippi Department of Wildlife, Fisheries and Parks will accept sealed bids until **2:00 p.m., December 21, 2017** to be opened immediately.

Bid Opening Location:

MS Department of Wildlife, Fisheries and Parks Attn: Purchasing Department 1505 Eastover Dr. Jackson, MS 39211-6374

For questions regarding Specifications and General Terms and Conditions contact: **Keith Harkins Office of Purchasing, Travel, & Asset Management** (601) 432-2119 **KeithH@mdwfp.state.ms.us**

1.1 INTRODUCTION

1.1.1 The Mississippi Department of Wildlife, Fisheries and Parks requests sealed bids for the purchase and delivery of new, 2017 or newer Crawler Dozer(s).

1.1.2 The initial purchase described by this Invitation to Bid shall be for new, current-year Crawler Dozer(s).

1.1.3 The agency reserves the right to define equals, reject any and/or all bids, or any part of any/or all bids, and to waive any informality.

1.1.4 Awards will be made based on the lowest and best bid. It is the intent of the agency to purchase new, current-year Crawler Dozer(s). The Invitation to Bid consists of one (1) bid proposal form. Bidders must submit a completed bid proposal form. However, we reserve the right to award in the best interest of the Mississippi Department of Wildlife, Fisheries and Parks.

1.1.5 The bidder agrees to begin delivery within **60 days** of award. Failure to do so may result in cancellation of award. If cancellation of award occurs, new award will be made to the next lowest bidder meeting required specifications.

1.2 GENERAL SPECIFICATIONS

1.2.1 The specifications set forth herein represent a minimum of required equipment and operational needs of the Mississippi Department of Wildlife, Fisheries and Parks. The bidder may propose options above and beyond these specifications that best suit MDWFP's interests as determined by the agency.

1.2.2 Please respond "Yes" or "No" to indicate compliance to the specifications for each listed criterion, and add comments as needed.

1.3 SUBMISSION REQUIREMENTS

1.3.1 Bids may be submitted electronically. Please refer to the links below for the Vendor Registration website as well as tutorials. Please contact the MASH Help Desk (601-359-1343) if you require any assistance.

Bid Submissions may be mailed to: Keith Harkins at 1505 Eastover Drive, Jackson, MS 39211. Please write the solicitation number, 1464-18-R-IFBD-00013, on the outside of the envelope. Bid responses received after the bid opening date and time will be returned unopened.

Terms and Conditions

1. The Mississippi Department of Wildlife, Fisheries and Parks reserves the right to reject any and/or all bids, to waive any informality in bids, and unless otherwise specified by the bidders, to accept any items on the bid. If the bidders fail to state the time within bids must be

accepted, it is understood and agreed that the Mississippi Department of Wildlife, Fisheries and Parks shall have sixty (60) days to accept.

- 2. A written purchase order or contract award letter mailed or otherwise furnished to the successful bidder within the time of acceptance specified in the Invitation to Bid, results in a binding contract without further action by either party.
- 3. No bid shall be altered or amended after the specified time for opening bids.
- 4. Contracts and purchases will be made or entered into with the lowest, responsible bidder meeting specifications.
- 5. If purchase orders or contracts are canceled because of the awarded vendor's failure to perform or request for price increase, that vendor shall be removed from our bidders' list for a period of twenty-four (24) months.
- 6. Bid openings will be conducted open to the public. However, they will serve only to open bids. No discussion will be entered into with any vendor as to the quality or provisions of the specifications, and no award will be made either stated or implied at the bid opening. All bidders are invited and encouraged to attend the bid opening meeting to review the submitted bids. After the close of the bid opening meeting, the bids will be considered to be in the evaluation process and will not be available for review by bidders. Questions shall not be answered as a result of telephone inquiries.
- 7. Invoices are to be mailed to:

Accounts Payable Mississippi Department of Wildlife, Fisheries and Parks 1505 Eastover Drive, First Floor Jackson, Mississippi 39211-6374

Payment will be made 45 days after receipt of merchandise and original invoice.

 It shall be incumbent upon the bidders to understand the specifications. Any requests for clarifications shall be in writing and shall be submitted to our Purchasing Office at least five (5) days prior to the date and time set for the bid opening. Requests for clarifications and/or questions should be emailed to our Purchasing Office Email Address: <u>KeithH@mdwfp.state.ms.us</u> 9. Questions or problems arising from bid procedures or subsequent order and delivery procedures should be directed to:

Keith Harkins 1505 Eastover Drive, First Floor Jackson, MS 39211 Email address: KeithH@mdwfp.state.ms.us

- 10. The minimum specifications are used to set a standard and in no case are used with the intention to discriminate against any manufacturer. Bidders should note the name of the manufacturer and model number of the product they propose to furnish and **submit descriptive literature.**
- 11. Protests. Protest regarding this Invitation to Bid is governed by the Mississippi Procurement Manual, Section 6.

The manual may be viewed at http://www.dfa.state.ms.us/Purchasing/ProcurementManual.html

Pursuant to Section 6.101.02 and 6.101.03, Vendors must protest within seven (7) days after they know or should have known of the facts giving rise to the protest. Protests involving the Invitation to Bid and any of its contents should be made within seven (7) days of the posting of the Invitation to Bid. When all *Proposals* have been read, recorded and results posted, a Proposing Firm may choose to protest the award.

All protests must be made in writing to the Mississippi Department of Wildlife, Fisheries and Parks contact provided herein above (page 2), with copy to:

Chief Procurement Officer Woolfolk Building, Suite 701 501 North West Street Jackson, Mississippi 39201

No protests will be considered later than seven (7) days following the posting of the INTENT TO AWARD notification.

The letter of protest should identify the Project, include what is being protested, why it is being protested, and be signed by the individual who is protesting.

12. E-Verify. Contractor/Seller represents and warrants that it will ensure its compliance with the Mississippi Employment Protection Act, Section 71-11-1, et seq of the Mississippi Code Annotated (Supp 2008), and will register and participate in the status verification system for all newly hired employees. The term "employee" as used herein means any person that is hired to perform work within the State of Mississippi. As used herein, "status verification system" means the illegal Immigration Reform and Immigration Responsibility Act of 1996 that is operated by the United States Department of Homeland Security, also known as the EVerify Program, or any other successor electronic verification system replacing the E-Verify Program. Contractor/Seller agrees to maintain records of such compliance and, upon

request of the State and approval of the Social Security Administration or Department of Homeland Security, where required, to provide a copy of each such verification to the State. Contractor/Seller further represents and warrants that any person assigned to perform services hereunder meets the employment eligibility requirements of all immigration laws of the State of Mississippi. Contractor/Seller understands and agrees that any breach of these warranties may subject Contractor/Seller to the following: (a) termination of this Agreement and ineligibility for any state or public contract in Mississippi for up to three (3) years, with notice of such cancellation/termination being made public, or (b) the loss of any license, permit certification or other document granted to Contractor/Seller by an agency, department or governmental entity for the right to do business in Mississippi for up to one (1) year, or (c) both. In the event of such termination/cancellation, Contractor/Seller would also be liable for any additional costs incurred by the State due to contract cancellation or loss of license or permit."

The State requires the Contractor to submit invoices electronically throughout the term of the agreement. Vendor invoices shall be submitted to the state agency using the processes and procedures identified by the State. Payments by state agencies using the Mississippi Accountability System for Government Information and Collaboration (MAGIC) shall be made and remittance information provided electronically as directed by the State. These payments shall be deposited into the bank account of the Contractor's choice. Contractor understands and agrees that the State is exempt from the payment of taxes. All payments shall be in United States currency.

13. If the agency is closed for any reason, including but not limited to: acts of God, strikes, lockouts, riots, acts of war, epidemics, governmental regulations superimposed after the fact, fire, earthquakes, floods, or other natural disasters (the "Force Majeure Events"), which closure prevents the opening of bids at the advertised date and time, all bids received shall be publicly opened and read aloud on the next business day that the agency shall be open and at the previously advertised time. The new date and time of the bid opening, as determined in accordance with this paragraph, shall not be advertised, and all Vendors/Contractors, upon submission of a bid proposal, shall be deemed to have knowledge of and shall have agreed to the provisions of this paragraph. Bids shall be received by the agency until the new date and time of the bid opening as set forth herein. The agency shall not be held responsible for the receipt of any bids for which the delivery was attempted and failed due to the closure of the agency as a result of a Force Majeure Event. Each Vendor/Contractor shall be required to ensure the delivery and receipt of its bid by the agency prior to the new date and time of the bid opening

Specifications for One (1) or Two (2), New, Current-Year Crawler Dozer(s) (Must meet or exceed the following minimum specifications and requirements)

yes no The crawler engine shall be Tier 4 Final emissions standard with at least 4 cylinders and turbocharger with air to air aftercooling. yes no Engine horsepower will be a minimum SAE Net Rated of 127 hp (95 kW). yes no Dozer engine shall have a programmable automatic engine shutdown system. yes no Dozer shall have an automatic turbo cool-down system that protects the engine from damage. yes no The fuel system shall have a fuel shut-off valve to prevent fuel loss during filter changes. The system shall have a water separator located between the fuel tank outlet and the fuel filters. yes no Primary fuel-water separator includes a heating element to prevent freezing of separated water. yes no Fuel system shall include an automatic electronic priming pump to eliminate manual priming. yes no Unit shall have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan. yes no The unit will have a fan-guard. The pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). wes no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts.			Engine			
yes no Dozer engine shall have a programmable automatic engine shutdown system. yes no The fuel system shall have a programmable automatic engine shutdown system. yes no The fuel system shall have a fuel shut-off valve to prevent fuel loss during filter changes. The system shall have a water separator located between the fuel tank outlet and the fuel filters. yes no Primary fuel-water separator includes a heating element to prevent freezing of separated water. yes no Air intake shall be pre-screened through perforated side shields. yes no Air intake shall be pre-screened through perforated side shields. yes no Unit shall have a proportionally controlled, hydraulically driven, swing-out or till out radiator fan. yes no The unit will have a least one hinged engine panel door for easy access. yes no Unit shall have a coolant recovery tank provided. yes no Unit shall have a funguard. yes no The presurized liquid cooling system shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). yes no Alternator shall bave a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Alternator shall	yes	no	The crawler engine shall be Tier 4 Final emissions standard with at least 4			
yes no Dozer engine shall have a programmable automatic engine shutdown system. yes no Dozer shall have an automatic turbo cool-down system that protects the engine from damage. yes no The fuel system shall have a fuel shut-off valve to prevent fuel loss during filter changes. The system shall have a water separator located between the fuel tank outlet and the fuel filters. yes no Primary fuel-water separator includes a heating element to prevent freezing of separated water. yes no Fuel system shall include an automatic electronic priming pump to eliminate manual priming. yes no Air intake shall be pre-screened through perforated side shields. ves no Unit shall have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan. yes no The unit will have a least one hinged engine panel door for easy access. yes no Unit shall have a colant recovery tank provided. yes no Unit shall have a a funguard. yes no In the pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). yes no Alternator shall be a minimum capacity of 900 CCA. Electrical system must be 24 volts.	yes	no				
yes no Dozer shall have an automatic turbo cool-down system that protects the engine from damage. yes no The fuel system shall have a fuel shut-off valve to prevent fuel loss during filter changes. The system shall have a water separator located between the fuel tank outlet and the fuel filters. yes no Primary fuel-water separator includes a heating element to prevent freezing of separated water. yes no Fuel system shall include an automatic electronic priming pump to eliminate manual priming. yes no Versystem shall include an automatic electronic priming pump to eliminate manual priming. yes no Versystem shall include an automatic electronic priming pump to eliminate manual priming. yes no Unit shall have a proportionally controlled, hydraulically driven, swing-out or till out radiator fan. yes no Unit shall have a fan-guard. yes no Unit shall have a fan-guard. yes no Unit shall have a fan-guard. yes no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no Alternator shall be a solid-state electrical power distribution system using circuit board technology and solid-state switches.	yes	no				
yes no changes. The system shall have a water separator located between the fuel tank outlet and the fuel filters. yes no Primary fuel-water separator includes a heating element to prevent freezing of separated water. yes no Fuel system shall include an automatic electronic priming pump to eliminate manual priming. yes no Air intake shall be pre-screened through perforated side shields. yes no Unit shall have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan. yes no Unit shall have a coolant recovery tank provided. yes no Unit shall have a fan-guard. yes no Unit shall have a fan-guard. yes no Interpressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). yes no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Sealed transmission electrical connectors.	yes		Dozer shall have an automatic turbo cool-down system that protects the engine			
yes no separated water. yes no Fuel system shall include an automatic electronic priming pump to eliminate manual priming. yes no Air intake shall be pre-screened through perforated side shields. yes no Air intake shall be pre-screened through perforated side shields. yes no Air intake shall be pre-screened through perforated side shields. yes no Unit shall have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan. yes no Unit shall have a teast one hinged engine panel door for easy access. yes no Unit shall have a coolant recovery tank provided. yes no Unit shall have a fan-guard. The pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). U Electrical yes no Alternator shall be a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no Unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes <	yes	no	changes. The system shall have a water separator located between the fuel tank			
yes no Manual priming. yes no Air intake shall be pre-screened through perforated side shields. yes no Air intake shall be pre-screened through perforated side shields. yes no Unit shall have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan. yes no The unit will have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan. yes no Unit shall have a teast one hinged engine panel door for easy access. yes no Unit shall have a coolant recovery tank provided. yes no Unit shall have a fan-guard. The pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). U Electrical yes no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Sealed transmission electrical connectors. yes no	yes	no				
Cooling yesno Unit shall have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan. yesno no The unit will have at least one hinged engine panel door for easy access. yesno Unit shall have a coolant recovery tank provided. yesno Unit shall have a fan-guard. yesno The pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). Ves no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Unit shall have a minimum of two front and two rear work lights and a lighted instrument panel. yes no Sealed transmission electrical connectors. yes no Sealed transmission electrical connectors.	yes	no				
yesnoUnit shall have a proportionally controlled, hydraulically driven, swing-out or tilt out radiator fan.yesnoThe unit will have at least one hinged engine panel door for easy access.yesnoUnit shall have a coolant recovery tank provided.yesnoUnit shall have a fan-guard.yesnoThe pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C).yesnoBatteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts.yesnoAlternator shall be a minimum of 85 amps.yesnoThe unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches.yesnoSealed transmission electrical connectors.yesnoSealed transmission electrical connectors.	yes	no	Air intake shall be pre-screened through perforated side shields.			
ves no The unit will have at least one hinged engine panel door for easy access. yes no Unit shall have a coolant recovery tank provided. yes no Unit shall have a fan-guard. yes no Unit shall have a fan-guard. yes no The pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). ves no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Unit shall have a minimum of two front and two rear work lights and a lighted instrument panel. yes no Sealed transmission electrical connectors. The unit shall be provided with a master electrical disconnect switch. The unit shall be provided with a master electrical disconnect switch.			Cooling			
yes no Ine unit will have at least one hinged engine panel door for easy access. yes no Unit shall have a coolant recovery tank provided. yes no Unit shall have a fan-guard. yes no The pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). yes no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no No Unit shall have a minimum of two front and two rear work lights and a lighted instrument panel. yes no Sealed transmission electrical connectors. The unit shall be provided with a master electrical disconnect switch.	yes	no	Unit shall have a proportionally controlled, hydraulically driven, swing-out or tilt- out radiator fan.			
yes no Unit shall have a fan-guard. yes no The pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C). ves no Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Unit shall have a minimum of two front and two rear work lights and a lighted instrument panel. yes no Sealed transmission electrical connectors. The unit shall be provided with a master electrical disconnect switch.	yes	no				
yesnoThe pressurized liquid cooling system shall have a water pump driven with an automatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C).yesnoBatteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts.yesnoAlternator shall be a minimum of 85 amps.yesnoThe unit shall have a solid-state electrical power distribution system using circuit 	yes		Unit shall have a coolant recovery tank provided.			
yesnoautomatically adjusting belt. Radiator shall be filled with manufacturer's approve anti-freeze solution that provides protection to at least -34° F (-37° C).yesnoBatteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts.yesnoAlternator shall be a minimum of 85 amps.yesnoThe unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches.yesnoUnit shall have a minimum of two front and two rear work lights and a lighted instrument panel.yesnoSealed transmission electrical connectors.yesnoSealed transmission electrical connectors.	yes		··+ ··· ··· ··· ··· ··· ··· ··· ··· ···			
yesnoBatteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts.yesnoAlternator shall be a minimum of 85 amps.yesnoThe unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches.yesnoUnit shall have a minimum of two front and two rear work lights and a lighted instrument panel.yesnoSealed transmission electrical connectors.yesnoSealed transmission electrical connectors.The unit shall be provided with a master electrical disconnect switch.	yes	no	_ automatically adjusting belt. Radiator shall be filled with manufacturer's approve			
yes no 24 volts. yes no Alternator shall be a minimum of 85 amps. yes no The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Unit shall have a minimum of two front and two rear work lights and a lighted instrument panel. yes no Sealed transmission electrical connectors. The unit shall be provided with a master electrical disconnect switch.			Electrical			
yes no The unit shall have a solid-state electrical power distribution system using circuit board technology and solid-state switches. yes no Unit shall have a minimum of two front and two rear work lights and a lighted instrument panel. yes no Sealed transmission electrical connectors. The unit shall be provided with a master electrical disconnect switch.	yes	no	Batteries shall have a minimum capacity of 900 CCA. Electrical system must be 24 volts.			
yes no board technology and solid-state switches. yes no Unit shall have a minimum of two front and two rear work lights and a lighted instrument panel. yes no Sealed transmission electrical connectors. The unit shall be provided with a master electrical disconnect switch.	yes	no	Alternator shall be a minimum of 85 amps.			
yesnoUnit shall have a minimum of two front and two rear work lights and a lighted instrument panel.yesnoSealed transmission electrical connectors.The unit shall be provided with a master electrical disconnect switch.	yes	no	The unit shall have a solid-state electrical power distribution system using circuit			
The unit shall be provided with a master electrical disconnect switch.	yes	no	Unit shall have a minimum of two front and two rear work lights and a lighted			
	yes	no	Sealed transmission electrical connectors.			
	yes	no	The unit shall be provided with a master electrical disconnect switch.			
Transmission						

	1			
		Dual-path hydrostatic drive with infinite speed capability, dynamic braking, full-		
yes	no	power turns and counter rotation is required. The dozer shall have minimum forward speed of 5.5 mph forward and reverse. Design must permit unrestricted		
		speed and direction changes under full engine rpm and load.		
		Transmission shall have the ability for the operator to easily adjust operating		
yes	no	parameters such as: FNR shift rate, Steering rate, Steering Modulation, Decel		
J 05		pedal response and Reverse Ratio.		
	1	A load sensing system that works to downshift and up shift automatically is		
yes	no	required.		
Vec	10	In extreme cold weather the tractor shall include an automatic protection system to		
yes	no	prevent over speeding the transmission until operating temperature is reached.		
		Dozer shall have an automatic hill hold feature that automatically applies the		
yes	no	parking brake when the transmission is in neutral and motion is detected. Parking		
		must automatically be released upon shifting from neutral.		
		The single pedal decelerator will allow the operator to choose between slowing		
yes	no	travel speed and engine rpm or travel speed only to help maintain traction without affecting engine power and hydraulic response. Fully depressing the pedal applies		
		the brakes.		
		Transmission shall automatically derate if an extreme overheat condition is		
yes	no	detected.		
yes	no	A sight gauge shall be provided for checking the hydrostatic fluid.		
yes	no	Transmission filter restriction shall be displayed in the cab.		
NOG	no	There shall be adequate filtration and cooling of the transmission system to support		
yes	no	2,000 hour oil and filter changes.		
	-	Steering		
		Hydrostatic drive is required for full power turns and counter rotation. Steering		
yes	no	will have a single lever and shall be fully modulated at all speeds to provide		
	<u> </u>	smooth operation. Steering brakes shall be oil-cooled.		
	· <u>·</u>	Final Drive		
yes	no	Triple reduction, double reduction, or planetary bull gear final drives must be		
·		isolated from the track frames.		
Hydraulic System				
yes	no	There shall be adequate filtration and cooling of the hydraulic system to support		
		2,000 hour oil and filter changes.		
yes	no	If equipped, the grade control interface shall be factory installed regardless of machine control supplier.		
Vec	no	All hoses shall be of an o-ring seal design to reduce leakage and facilitate repairs.		
yes	no	Tracks and Undercarriage		
	1	Tracks and Underearringe		
yes	no	Minimum of seven track rollers per side with front and rear track guides and		
	 	sprocket guards. Sealed and life-time lubricated rollers, idlers and track chain.		
yes	no	Track must be designed to extend undercarriage life in abrasive working		
		conditions. Undercarriage must be the maximum life system available from the		
		bidder for the unit being bid.		
yes	no	The track gauge shall be a minimum of 74 inches for an LGP machine.		

ves no The track length on the ground shall be a minimum of 101 inches					
yes no The track length on the ground shall be a minimum of 101 inches.					
yes					
yes	no	The crawler will have a minimum grouser width of 28 inches and maximum width of 20 inches (LCP), closed center single her			
of 50 menes (LGP), closed center, single bar.					
yes no The ground clearance with single-bar grouser shall be at least 15 inches					
		grouser height).			
yes		Smooth-surface track frame covers shall cover the full length of the track.			
yes	no	Front and rear chain guides.			
yes	no	Rock guards, full length.			
		Dozer			
		The dozer shall be a hydraulically actuated, inside mounted, all hydraulic blade			
yes	no	(power-angle-tilt PAT). The blade hydraulic system shall provide raise, lower, tilt,			
JUS		angle and float. The blade capacity shall be a minimum -of 4.1 yd ³ for an LGP			
		machine.			
yes		The minimum blade height shall be 36 inches.			
yes	no	The minimum blade width shall be 132 inches for an LGP machine.			
yes	no	The dozer moldboard must be equipped with replaceable cutting edges.			
		Operator's Station			
	1	Operator s Station			
		DODS CAD and shall be compliant with OSUA (MSUA monlation and most			
yes	no	ROPS CAB and shall be compliant with OSHA/MSHA regulation and meet ROPS/FOPS criteria, and be isolation mounted for vibration reduction.			
		Operators' station shall include air-conditioning and heat with air recirculation and fresh air filters.			
VAG	no	The footrests and full-length armrests shall be adjustable.			
yes	no	The operator seat shall be cloth or vinyl, air suspension, comfort control with high			
yes	no	back ride style and have adjustments for operator height and weight, and lumbar			
yes	110	adjustment in the backrest.			
		The operator station shall have an electronic monitor system with audible and			
		visual warning for: low alternator voltage; engine oil pressure; engine coolant			
yes	no	temperature; indicator; hydraulic oil filter restriction; transmission oil filter			
J		restriction; transmission oil temperature; engine air restriction indicator; fasten seat			
		belt and park brake warning.			
	1	Unit shall have dash mounted gauges and/or monitoring system that will include:			
		transmission temperature, engine coolant temperature, engine oil pressure,			
yes	no	transmission charge pressure, hydraulic filter restriction, transmission filter			
		restriction, electric voltage, engine RPM, transmission speed range/direction and			
		electric hour meter.			
NO.		Cab shall have cup holder. Personal cooler holder/storage compartment for			
yes	no	operator's manual, and a rubber floor mat.			
yes	no	The operator station shall have a padded headliner.			
yes	no	The operator station shall have a standard rear-view mirror.			
yes	no	The operator station shall have a rear-view camera system.			
	·	General Specifications			
		Ocheral Specifications			

	1				
yes	no	Periodic maintenance and lube chart shall be posted for easy reference to ensure			
		that maintenance is performed according to schedule.			
yes	no	Operating weight with standard equipment shall be no more than 31,500 lbs (LGP).			
yes	no	The fuel tank shall have a capacity no less than 69 gallons and be equipped with a lockable cap.			
	1	Additional Equipment			
	1	Unit shall be equipped with all standard equipment and shall include:			
yes	no	Horn.			
yes	 no	12 Volt power port.			
yes	 no	Cold weather starting aid.			
yes		Dry-type air cleaner with safety element and restriction indicator.			
yes	no no	Reverse warning alarm.			
yes		Heavy duty engine fuel water separator with heating element.			
yes	no no	Mounting steps and safety hand holds.			
yes	<u></u>	Vandal protection providing lockable protection to all openable panels and fuel			
yes	no	fill.			
yes	no	Fuel tank guard, heavy duty.			
yes	no	Front pull hooks or eyes on ends of blade.			
· ·		Full forestry package to include: limb risers, front screens, side screens, and rear			
yes	no	screens. Screens will meet minimum specifications of 3/16-inch, grade 50 plate			
		with reinforcement where needed.			
yes	no	External mounted shovel holder.			
yes	no	Drawbar, extended rigid, with pin and pin locking mechanism.			
yes	no	One pair of auxiliary hydraulic disconnects mounted above drawbar and plumbed to an in-cab control.			
	1	Warranty			
	1	Crawler unit shall include, in the original purchase price, a 60 month/3,000-hour			
yes	no	(to expire whichever comes first) comprehensive, total machine warranty.			
	1	Maintenance			
		Crawler unit shall include, in the original purchase price, a comprehensive service			
yes		and preventative maintenance (PM) agreements for a minimum of 36 months or up			
		to 2,000 hours. The winning bidder must perform any and all of the preventative			
		maintenance for the duration of the maintenance agreement. Preventative			
		maintenance shall include any and all manufacturer's maintenance			
		recommendations and shall include all parts, fluids, fluid sampling, labor, and			
		travel. Preventative maintenance shall be performed at the recommended time			
	no	intervals as per the manufacturer's specifications. However, engine oil change			
		interval shall be no more than every 500 hours. The dealer shall be responsible for			
		performing PM in the field or hauling the unit to a designated area. Although the			
		units will be delivered to specific sites when purchased, the crawler units will be			
		operated at multiple locations throughout the state of Mississippi. The dealer shall			
		provide, for a minimum of 60 months, a GPS remote equipment monitoring and			
		management system which provides for monitoring and recording machine			
		management system which provides for monitoring and recording machine			

	maintenance and operational data, remote diagnostics and programming capability, maintenance tracking, equipment use and equipment load data, fuel consumption data, diagnostic trouble code alerts, and dealer third party access.		
		Literature	
yes	no	One (1) complete paper set of operator's manual, service and parts catalog per unit.	
Other Requirements			
yes	no	Crawler dozer(s) is to be delivered fully assembled and ready to operate within 60 days of issuance of the purchase order.	
yes	no Winning bidder must provide parts/warranty/service within 90-mile radius of Mayersville, Mississippi.		
yes	no Must provide on-site equipment orientation training at delivery locations.		
Delivery Location(s)			
yes	no	Delivery of the unit will be to the following location: (1) Shipland Wildlife Management Area, Hwy 1 near Mayersville, MS. Delivery location for any other unit that may be purchased will be determined at a later date.	

BID PROPOSAL FORM 1

Mississippi Department of Wildlife, Fisheries, and Parks Attention: Keith Harkins 1505 Eastover Drive Jackson, MS 39211

Having examined the specifications for New, Current-Year Crawler Dozer(s). To be delivered to: Shipland Wildlife Management Area Hwy 1 near Mayersville, MS..

The undersigned proposes to furnish as per specifications for the prices shown below.

Description

New, Current-Year Crawler Dozer(s)

Proposed Item Unit Cost

_____\$_____

The undersigned agrees to begin delivery within 60 days of award. Failure to do so may result in cancellation of award. If cancellation of award occurs, new award will be made to the next lowest bidder meeting required specifications.

Print Name		
Signature		
Title		
Company		
Address		
City	State	Zip
Telephone Number		
Fax Number		
Email		