

Medium Duty Single Spindle Mowers

2012

5, 6 & 7 Foot Smooth Top Rotary Cutters

Bush-Whacker is proud to introduce our new line of medium-duty smooth deck mowers.

The Premier Series is designed with the same innovation as the Elite Series, but a better fit for medium-duty jobs and the price conscious consumer.

Bush-Whacker mowers are best known for their innovative design, superior performance and proven durability. That's why state highway departments have been using them for over 40 years and still cutting.



- **Quick Hitch adaptable**
- **10 Gauge Smooth top deck for easy cleaning.**
- **4-bolt mounting on gearboxes - Gearbox Bolt heads are tackwelded to the bottom of the deck for easy maintenance, tightening the nuts or changing the gearbox.**
- **1/4" Thick deck ring on bottom for increased safety and rigidity.**
- **Blades are 1/2" by 3 1/2"**
- **Drive Shaft - 2 friction disks with a steel spacer.**



Bush-Whacker
KICKS GRASS!

Hall Manufacturing

3706 East Washington

PH: 501-945-7550

• P.O. Box 5638

• North Little Rock, AR 72119

• www.bush-whacker.com



Bush-Whacker®

Model MD-60 - 5-Foot Smooth Deck Medium Duty Rotary Cutter

Model MD-72 - 6-Foot Smooth Deck Medium Duty Rotary Cutter

Model MD-84 - 7-Foot Smooth Deck Medium Duty Rotary Cutter

Specifications*

Gearboxes — 120HP, 540 RPM Base Mounted, 1:1.46 Ratio. Malleable housing; forged alloy steel; carburized and hardened gears and shafts; 1 3/8"-6 input shaft, tapered bearings.

Drive Shafts - Category 4 Made from the finest quality propeller shaft materials and needle bearing universal joints.

Slip Clutch Heavy duty spring-type adjustment with four friction discs.

Quick Hitch Adaptable MD-60 & MD-72 = CAT 1, MD-84 = CAT 2

Blades 1/2" by 4" material, alloy spring steel, airlift design. Free swinging when encountering obstructions.
Blade tip speed: 14,000 FPM

Tail Wheel For 3-point hitch: Extra heavy duty, tapered bearings, 4" by 8" laminated puncture-proof tire. MD-84 optional dual tail wheel.

For Pull Type: Extra heavy duty, tapered bearings, two 6" by 9" laminated puncture-proof tire.

Bush-Whacker Special Deck 10 Gauge Smooth top deck for easy cleaning.

Flat Steel Plate Sides- 10 Gauge Material Shaped to form sides of cutter.

Rubber Guards Chain Guards Optional.

Dimensions MD-60 - Cutting height: adjustable from 1.5" to 6.5". Overall width: 60". Overall length: 109".
Transportation width: 64.5".

MD-72 - Cutting height: adjustable from 1.5" to 6.5". Overall width: 74 1/8". Overall length: 121".
Transportation width: 76.5".

MD-84 - Cutting height: adjustable from 1.5" to 6.5". Overall width: 85". Overall length: 129".
Transportation width: 88.5".

Weight MD-60 - 700lb. | MD-72 - 780lb | MD-84 - 840lb

Recommended PTO HP MD-60 - 35HP | MD-72 - 40HP | MD-84 - 45HP

**These specifications are standard; however, any State Department of Transportation Specifications that may differ from standard Bush-Whacker Specifications will take precedence and be implemented into productions*

WARRANTY: Guaranteed for 12 months against defective materials and workmanship. Defective parts must be returned prepaid to the factory. Guarantee is void if failure is due to operators negligence, abuse or using other than genuine Bush-Whacker parts.