



60" ,75" and 90" Side Cutting Widths



90" and 102" Rear Cutting Widths

SIDE & REAR HD FLAILS



SIDE-MOUNTED FLAIL

Cutter Assembly - Hydraulically driven - 1,800 RPM

- Designed to cut grass and brush up to 2"
- Cutter Head - 3/16" bonnet, 1/2" sidewalls
- Cutter shaft is dynamically balanced
- Cutter heads width and weight
**60" - 1040 lbs & 75" - 1146 lbs.
90" - 1290 Lbs**
- Cutter shaft bearing guards are standard
- Roller height can be adjusted 1/2" to 6"
- 60" Cutter head has 64 all purpose self-cleaning, reversible knives, or 32 smooth cut cutting knives.
- 75" Cutter head has 80 all purpose self-cleaning, reversible knives, or 40 smooth cut cutting knives.
- 90" Cutter head has 96 all purpose self-cleaning, reversible knives, or 48 smooth cut cutting knives.
- Skid shoes are replaceable

REAR-MOUNTED FLAIL

Cutter Assembly - PTO Driven

- Designed to cut grass and brush up to 2"
- Built in either center cut or offset design
- Cutter Head 3/16" bonnet, 1/2" sidewalls
- Cutter shaft is dynamically balanced
- Cutter heads width and weight
90" - 1442 lbs & 102" - 1500 lbs
- 90" Cutter head has 96 all purpose self-cleaning, reversible knives, or 48 smooth cut cutting knives.
- 102" Cutter Head has 112 all purpose self-cleaning, reversible knives, or 56 smooth cut cutting knives.
- Skid shoes are replaceable

Three-Point Hitch Mounting- Category II

One-Year Warranty



Diamond Mowers, Inc.

27134 Parklane Drive • Sioux Falls, SD 57106

Toll-Free: (800) 658-5561

(605) 368-5865

Fax: (605) 498-1222

www.diamondmowers.com

Email: info@diamondmowers.com

The Leader In Integrated Roadside Vegetation Management