TOSHIBA
Leading Innovation

- Up to 25 PPM
- Color MFP
- Small/Med. Workgroup
- Copy, Print, Scan, Fax
- Secure MFP
- Eco Friendly

e-STUDIO™2551c series

e-STUDIO™2051c/2551c

TOSHIBA
Leading Innovation

- Color MFP
- Up to 25 PPM
- Small/Medium Workgroup
- Copy, Print, Scan, Fax
- Secure MFP
- Eco Friendly

Specifications

Copying Process	Indirect Electrostatic Photographic Transfer System with Internal Transfer Belt
Copying Type	LED Head Printing
Copy/Print Resolution	600 x 600 dpi
Copy/Print Speed	e-STUDIO2051C –20PPM Color/B&W e-STUDIO2551C –25PPM Color/B&W
Warm-Up Time	Approx. 35 Seconds
First Copy Out Time	e-STUDIO2051C –10.3 Seconds Color/ 8.2 Seconds B&W e-STUDIO2551C –10.3 Seconds Color/ 8.2 Seconds B&W
Duty Cycle	56K / 70K / Copies
Multiple Copying	Up to 999 Copies
Acceptable Paper Size and Weight	Cassette: ST-R to LD (16 lb Bond - 90 lb Index) Bypass: 3.9" x 5.2" to LD (16 lb Bond - 110 lb Index) PFP: ST-R to LD (16 lb Bond - 90 lb Index)
Memory (Max)	Main Memory: 2 GB SSD: 8GB
Reduction/Enlargement	25% to 400%
Bypass	100-Sheet "Smart" Bypass (16 lb Bond - 110 lb Index)
Control Panel	Color 7" LCD Touch Panel
Paper Supply	Up to 2,000-Sheet Input Capacity Standard 250-Sheet Cassettes 100-Sheet Bypass Optional 1 x 550-Sheet PFU (2nd Cassette), 1 x 550-Sheet PFP (3rd Cassette), 1 x 550-Sheet Cassette (4th Cassette) for PFP
Duplex	Optional Automatic Duplex Unit (16 lb Bond - 90 lb Index)
Dimensions	Approx. 22.6" x 23.2" x 26.1" (W x D x H)
Weight	Approx. 123.5 lb
CMYK Toner Yield	5% Coverage, CMY: 33.6K, BK: 38.4K 6% Coverage, CMY: 28K, BK: 32K
Power Supply	120 V, 12 Amps
Power Consumption	Maximum 1.5 kW

Print Specifications

PDL Support	PCL6
Operating Systems	Netware 6.5, Windows XP, Vista, 7 Windows Server 2003, 2008, 2008R2
Protocol Support	IPX/SPX, TCP/IP NetBIOS Over TCP/IP, LPR/LPD, IPP, SMB, SNMP, Netware, Port 9100,
Drivers	Windows XP, Vista, 7, Windows Server 2003/2008/2008R2
Connectivity	10/100/1000BaseTX Ethernet
Device Management	TopAccess
Certification	Windows (XP, Vista, 2003, 2008, 2008R2) (WHQL) Novell

Scan Specifications

Scan Resolution	100 dpi, 150 dpi, 200dpi, 300 dpi, 400 dpi, 600 dpi
Scan Speed	50 SPM Color / 50 SPM B&W (@ 300 dpi)
File Format	TIFF, PDF, Secure PDF, JPEG

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH / MR / MMR /JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	33.6 Kbps
Memory Transmission	50 Jobs, 2,000 Destinations Max. 400 Destinations /Job
Scan Speed	.7 Seconds Per Page, Maximum 50 SPM

Security (Standard)

Authentication	LDAP, SMTP, Windows Server Domain, Local

Accessories (Options)

Additional Paper Options	
Platen Cover	KA1640PC
Job Separator	MJ5004
RADF: 100 Sheets	MR3024
Paper Feed Unit: 550-Sheet Pedestal, Statement-R to Ledger	MY1040
Paper Feed Pedestal: 550-Sheet Pedestal, Statement-R to Ledger	KD1032
Paper Drawer: 550-Sheet Pedestal, Statement-R to Ledger	MY1039
Paper Feed Controller	GH1080
Automatic Duplex Unit	MD0105
Connectivity/Security Options	
Fax Board	GD1320
2nd Line Fax	GD1260F
Advanced Scanning (ReRite)	GB1280V8
Miscellaneous Options	
SmartCard Reader, HID iClass	ART11236
SmartCard Reader, HID Prox	ART11230
SmartCard Reader, Inditag	ART12161
SmartCard Reader, LEGIC	ART11248
SmartCard Reader, Multi ISO/Mifare	ART11443
SmartCard Reader, Multi 125	ART11242
Accessible Arm Handle	KK2550
Harness Kit for Coin Controller	GQ1260

Corporate Office	2 Musick, Irvine, CA 92618-1631 Tel: 949-462-6000
East Coast	959 Route 46 East, 5th Floor, Parsippany, NJ 07054 Tel: 973-3136-2700
Midwest	8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Tel: 773-380-6000
South	2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385
West Coast	142 Technology, Suite 150, Irvine, CA 92618 Tel: 949-462-6262
Web Site	www.business.toshiba.com

Designs and Specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.

© 2012 Toshiba America Business Solutions, Inc. Electronic Imaging Division
Inv. Code: ES2051C2551C2