



BUSH HOG[®]

Performance You Can Count OnSM MACHINE PRICE LIST & SPECIFICATIONS

PRICES F.O.B. FACTORY AND SUBJECT TO CHANGE WITHOUT NOTICE
PRICES EFFECTIVE JANUARY 6, 2014

Revised December 1, 2014

(QUICKE PRICE PAGES UNDER SEPARATE COVER)



IMPORTANT NOTICE

Prices shown in this book are list prices and do not include freight, setup, or handling unless specifically noted. Shipping weights listed in this book are approximate and include crating or skids where applicable. All prices are F.O.B. factory; freight shipments arranged by Bush Hog® will be per the published rate chart and subject to change. Bush Hog® reserves the right to ship items via motor freight collect at its discretion. Dealers should reference their whole good invoices and billing statements for freight amount and due dates.

Prices, terms, and discounts are subject to change without notice. Orders placed will be accepted based on the price in effect at the time of shipment unless otherwise specified. Prices shown in this book do not include any applicable federal, provincial, state, or local taxes, or levies.

Machines included in this price book conform to safety standards applicable to the products at the time of manufacture and may include safety devices such as shields, guards, or operator protective devices. Under no circumstances should machines be operated without the safety devices in place.

This document is confidential and is for use by authorized Bush Hog® dealership personnel only. It is not to be distributed for any purpose other than selling Bush Hog® branded products.

Bush Hog® reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation. Bush Hog® guarantees each piece of equipment against defective materials and workmanship for a period of one year from date of delivery unless otherwise noted.

ROTARY CUTTER OR FLAIL MOWER THROWN OBJECT PROTECTION

Bush Hog offers three types of shielding to protect the operator, passersby, livestock, and property from mower thrown objects: deflectors, single chain guards, and double chain guards. Shielding should be selected based on the intended use of the mower. Double chain guards or deflectors should be used for highway, right-of-way, parks, or greenbelt mowing or other mowing where human dwellings, vehicles, or livestock could be within 300 feet of the mower. Chain guards are more durable, provide longer service life, and require less maintenance than deflectors. Single chain guards should be sufficient for agricultural and other mowing where passersby or property are not within 300 feet of the mower during operation.

No shielding is completely effective in preventing thrown objects. The possibility of injury or property damage from this hazard can be substantially reduced by selecting proper shielding, maintaining the mower and shielding in good operating condition, inspecting the area for foreign debris before mowing, operating the mower at a minimum cutting height of 4", and keeping people at least 300 feet from the mower at all times during operation.

PRICE LIST INDEX

MACHINES AND DESCRIPTIONS	PAGE NO.	MACHINES AND DESCRIPTIONS	PAGE NO.
FINISHING MOWERS		BOOM MOWERS	
ATH 900 Series Air Tunnel Finishing Mower	5	Rear mounted boom mowers	42
RDTH Series Rear Discharge Finishing Mower	6	DITCH BANK MOWERS	
RDTH84 Series Rear Discharge Finishing Mower	7	SM60	44
TD Series Tri Deck Finishing Mower	8		
TURF & GROUNDS MAINTENANCE EQUIPMENT		LANDSCAPING AND TILLAGE EQUIPMENT	
Residential Series Zero Turn Mower	9	RT Series Rotary Tillers	45
Estate Series Zero Turn Riding Mower	11	Disc Harrows, Lift	47
Estate Commercial Series Zero Turn Riding Mower	13	Disc Harrows, Pull	50
Professional Series Zero Turn Riding Mower	15	All Purpose Plow	52
		Subcompact Series Attachments	53
		Subsoilers Heavy Duty	55
SINGLE SPINDLE ROTARY MOWERS		Cultivator	56
Razorback Series Rotary Cutters	16A	Layoff Plow	56
RD5 & RD6 Series Rotary Cutters	<u>DISCONTINUED</u>	Subsoiler, Standard Duty	56
BH14 Series Rotary Cutters	<u>Limited Availability</u>	35 Series Utility Rear Blades	57
BH15 Series Rotary Cutters	19	50 Series Medium Duty Rear blades	57
BH16 Series Rotary Cutters	19	70 Series Heavy Duty Rear Blades	58
SQ84T Twin Spindle Series Rotary Cutters	20	91 Series Medium Duty Rear Blades	58
BH17 Series Rotary Cutters	20	100 Series Heavy Duty Blades	59
BH25 Series Rotary Cutters	21	160 Series Heavy Duty Blades	59
BH26 Series Rotary Cutters	21	225/300 series Heavy Duty Blades	60
BH27 Series Rotary Cutters	22	LLR Economy Landscape Rake	61
326 Series Rotary Cutters	23	MLR Medium Duty Landscape Rake	62
327 Series Rotary Cutters	23	BBX Box Blades	63
		SBX Box Blades	64
MULTI-SPINDLE RIGID DECK ROTARY MOWERS		MBX Box Blades	65
2008 Series Rotary Cutters	24	Roll-Over Box Blades	66
2010 Series Rotary Cutters	25	Road Grader	67
3008 Series Rotary Cutters	26	Dirt Scraper, Pull	68
3008 SH Series Rotary Cutters	27	Pulverizers	69
3210 Offset Series Rotary Cutters	28	Pluggers	70
3210 Series Rotary Cutters	29	MPG Pluggers	70
3414 Series Rotary Cutters	30	Pasture Aerators	70A
FLEX-WING ROTARY CUTTERS			
2212 Series Rotary Cutters	<u>DISCONTINUED</u>		
1812 Series Rotary Cutters	32A		
RF15 Series Rotary Cutters	<u>DISCONTINUED</u>		
1815 Series Rotary Cutters	34		
2515 Series Rotary Cutters	<u>DISCONTINUED</u>		
2810 Series Rotary Cutters	35		
3810 Series Rotary Cutters	36		
2815 Series Rotary Cutter	37		
3815 Series Rotary Cutters	38		
2820 Series Rotary Cutters	39		
2720 Series Rotary Cutters	<u>Limited Availability</u>		
	41A		

HOW TO ORDER: The ATH-Series mower is available as a lift-type implement only. It is priced as a basic unit with a choice of tire selection bundles and options. Your order must specify basic unit number and tire selection bundle to receive a complete unit.

Freight **NOT** included in list price

ATH-900 Air Tunnel Finishing Mowers

BASIC UNIT SELECTION				
Model	Description	Approx.	Ship	List
ATH9002R	Bush Hog Red	1164 lbs.	1214 lbs.	\$4,330
ATH9002O	Kubota Orange	1164 lbs.	1214 lbs.	\$4,330
ATH9002G	John Deere Green	1164 lbs.	1214 lbs.	\$4,330
ATH9002B	New Holland Blue	1164 lbs.	1214 lbs.	\$4,330

TIRE SELECTION BUNDLE		
50021370	Solid Tire Bundle	\$1,169

	Options	
98747	Front Roller Kit	\$94

MODEL	ATH900
Cutting Width	90"
Cutting Height	1 to 6"
Horsepower Range	35 to 55 PTO
Hitch	Category 1
Size Blade	1/4" x 3" x 31-1/2"
Number of Blades	3
Blade Tip Speed	15,621 fpm
Blade Overlap	2-1/4"
Blade Uplift	Parallel
Driveline Size	ASAE Category 3
Front Roller Size	3" x 5" (2)
Discharge	Right Side
Deck Plate	7 Gauge
Tire Size	13 x 5" (Solid)
Belt	"C" Size/Kevlar
Gearbox RPM	540
Gearbox Ratio	1:1.71
Gearbox	55 HP
Belt Adjustment	Spring Loaded Idler

Five Year Limited Gearbox Warranty

MACHINE PRICES AND SPECIFICATIONS

EFFECTIVE January 6, 2014

Revised June 23, 2014

HOW TO ORDER: The RDTH-Series mower is available as a lift-type implement only. It is priced as a complete unit with a choice of options. Includes driveline.

Freight **NOT** included in list price

RDTH FINISH MOWERS

BASIC UNIT SELECTION				
Model Number	Description	Approx. Weight	Ship Weight*	List Price
RDTH60R	Bush Hog Red	536 lbs.	566 lbs.	\$3,127
RDTH60O	Kubota Orange	536 lbs.	566 lbs.	\$3,127
RDTH60G	John Deere Green	536 lbs.	566 lbs.	\$3,127
RDTH60B	New Holland Blue	536 lbs.	566 lbs.	\$3,127
RDTH72R	Bush Hog Red	588 lbs.	618 lbs.	\$3,273
RDTH72O	Kubota Orange	588 lbs.	618 lbs.	\$3,273
RDTH72G	John Deere Green	588 lbs.	618 lbs.	\$3,273
RDTH72B	New Holland Blue	588 lbs.	618 lbs.	\$3,273

OPTIONS

90871 Front Roller Kit
Special Paint

\$63
Call Before Quote

MODEL	RDTH60	RDTH72
Cutting Width	60"	72"
Cutting Height	1-1/2" - 6-1/2" (1/2" incr.)	1-1/2" - 6-1/2" (1/2" incr.)
Horsepower Range	15 to 35 PTO	20 to 40 PTO
Hitch	Category 1	Category 1
Size Blade	1/4" x 2-1/2" x 21"	1/4" x 2-1/2" x 25"
Number of Blades	3	3
Blade Tip Speed	18,231 fpm	18,272 fpm
Blade Overlap	1-1/2"	1-1/2"
Blade Uplift	Parallel	Parallel
Driveline Size	ASAE Category 3	ASAE Category 3
Front Roller Size	3" x 5" (Opt.)	3" x 5" (Opt.)
Discharge	Rear	Rear
Deck Plate	7 Gauge	7 Gauge
Tire Size (Solid)	3-1/4" x 10-1/4"	3-1/4" x 10-1/4"
Belt	"B" Size/Kevlar	"B" Size/Kevlar
Gearbox RPM	540	540
Gearbox Ratio	1:2.16	1:2.16
Gearbox	45 HP	45 HP
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler

Five Year Limited Gearbox Warranty

HOW TO ORDER: The RDTH-Series mower is available as a lift-type implement only. It is priced as a basic unit with a choice of tire selection bundles and options. Your order must specify basic unit number and tire selection bundle to receive a complete unit. Includes driveline.

Freight **NOT** included in list price

RDTH 84 FINISH MOWERS

BASIC UNIT SELECTION

Model Number	Description	Approx. Weight	Ship Weight*	List Price
RDTH84R	Bush Hog Red	874 lbs.	904 lbs.	\$3,045
RDTH84O	Kubota Orange	874 lbs.	904 lbs.	\$3,045
RDTH84G	John Deere Green	874 lbs.	904 lbs.	\$3,045
RDTH84B	New Holland Blue	874 lbs.	904 lbs.	\$3,045

TIRE SELECTION BUNDLE

50034134	Solid Tire, smooth, 10"			\$696
----------	-------------------------	--	--	--------------

OPTIONS

50034137	Front Roller Kit			\$86
----------	------------------	--	--	-------------

MODEL	RDTH84
Cutting Width	84"
Cutting Height	1-1/2" to 5-1/2" (1/2" incr.)
Horsepower Range	30 to 55 PTO
Hitch	Category 1
Size Blade	5/16" x 2-1/2" x 29"
Number of Blades	3
Blade Tip Speed	18,266 fpm
Blade Overlap	1-1/2"
Blade Uplift	Parallel
Driveline Size	ASAE Cat. 3
Front Roller Size	3" x 13" (Opt.)
Discharge	Rear
Deck Plate	7 gauge
Tire Size (Solid)	4" x 10"
Belt	"B" Size/Kevlar
Gearbox RPM	540
Gearbox Ratio	1:2.15
Gearbox	55 HP
Belt Adjustment	Spring Loaded Idler

Five Year Limited Gearbox Warranty

HOW TO ORDER: The Tri-Deck Series Mowers are available as pull type units only. They are priced as complete units and are shipped fully assembled. Order by Model Number and add the price of any desired option.

Freight **NOT** included in list price

TD-Series Tri-Deck Finishing Mowers

Model Number	Description	Approximate Weight	List Price
TD-1100	11' Cutting Width	2450 lbs.	\$17,069
OPTIONS for TD1100 ONLY			
50026888	Underside Roller Kit (Includes three 13" x3" anti-scalp rollers, one for each deck, and all mounting hardware.)		\$196
50023283	Double acting hydraulic cylinder conversion kit. Recommended for tractors without a float feature.		\$432
TD-1500	15' Cutting Width	2752 lbs.	\$17,560
TD-1700	17' Cutting Width	2855 lbs.	\$19,058
	TD1100	TD1500	TD1700
Cutting Width	11'	15'	17'
Cutting Height	3/4" to 4-1/4"	1-1/2" to 4-1/2"	1-1/2" to 4-1/2"
Deck Widths	(3) 4'	(1) 72" Deck, (2) 60" Decks	(3) 72" Decks
Deck Constructions	7 Gauge	7 Gauge	7 Gauge
Deck Overlap	6"	6"	6"
Blade Overlap	1-1/2"	1-1/2"	1-1/2"
Material Discharge	Rear	Rear	Rear
Rear Chains	Standard	Standard	Standard
Belts	(1) per Deck "B" size Kevlar	(1) per Deck "B" size Kevlar	(1) per Deck "B" size Kevlar
Gauge Wheels	(12) 11" X 4" Pneumatic w/Tapered Bearings	(12) 13" x 5" x 6" w/roller Bearings	(12) 13" x 5" x 6" w/roller Bearings
* Tractor PTO HP Required	30 PTO	40 HP Minimum	45 HP Minimum
Gearbox RPM	540	540	540
Transport Width	6 ft 6 inches	95-1/2"	95-1/2"
Transport Height	6 ft 3 inches	95-1/2"	107-1/2"
Transport Length	12 ft	166"	166"
Transport Tires	(2) 23" x 9-1/2"	(2) 23" x 9-1/2"	(2) 23" x 9-1/2"
Wing Flex	30° Up and 10° Down	30° Up and 10° Down	30° Up and 10° Down
Hitch	Pull Type, Clevis Hitch, Three-Position Adjustment	Pull Type, Clevis Hitch, Three-Position Adjustment	Pull Type, Clevis Hitch, Three-Position Adjustment
Driveline Size	Cat. 4 80° CV (Main), Cat. 3 (Decks)	Cat. 4 80° CV (Main), Cat. 3 (Decks)	Cat. 4 80° CV (Main), Cat. 3 (Decks)
Wing Deck Flex	10° Side to Side, 10° Front to Rear Independent of the Wing Frame	10° Side to Side, 10° Front to Rear Independent of the Wing Frame	10° Side to Side, 10° Front to Rear Independent of the Wing Frame
Front Roller Size	3" x 5" (Standard)	3" x 5" (Standard)	3" x 5" (Standard)
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler	Spring Loaded Idler
Blade Tip Speed	18,468 fpm	18,231 fpm	18,271 fpm
Gearbox	45 HP - Center & Wings 80 HP - Transfer	45 HP - Center & Wings 80 HP - Transfer	45 HP - Center & Wings 80 HP - Transfer
Parking Jack	Standard	Standard	Standard

*Minimum horsepower subject to change due to mowing conditions.

Five Year Limited Gearbox Warranty (Five Year Transfer Box Warranty)

Special Paint

Call Before Quote

MACHINE PRICES AND SPECIFICATIONS**EFFECTIVE January 6, 2014****Revised June 23, 2014**

HOW TO ORDER: The Bush Hog Estate Commercial Series Zero Turn Mower is available with a choice of 2 engine / deck combinations, two tire package and two seat options. You must order from Group 1, 2 and 3 to get a complete Zero Turn Mower. Add all prices for a total list price.

Freight **NOT** included in list price

Estate Commercial Series Zero Turn Mower

BASIC UNIT SELECTION

Model Number	Description	Ship Weight	List Price
** EC2555KH5	Kohler KT740 + Pro Filtration Courage Pro engine (Gross 25 H.P.*) and 55" mower deck	955 lbs	\$8,278
** EC2761KH5	Kohler KT745 + Pro Filtration Courage Pro engine (Gross 26 H.P.*) and 61" mower deck	980 lbs	\$8,452

* Engine rated at 3600 RPM per SAE J1940 Gross

GROUP 2 TIRE SELECTION

50068091	Turf Tire Bundle 22 x 10.5 -12 Turf Smart™		\$103
50068840	Bar Tire Bundle - 23x10.50-12		\$303

GROUP 3 SEAT SELECTION

50068557	Non suspension seat, complete	20 lbs.	\$175
50068794	Full suspension seat, complete	50 lbs.	\$495

OPTIONS / Shipped Separately

Part No.	Description	Ship Weight*	List Price
50048625	Mulching Kit, 55"		\$194
50048626	Mulching Kit-61" deck (includes Mulching Blades)		\$194
50070541	Canopy (50068105 ROPS Fold down Required)		\$392
50052952	Deck Caster Wheel Kit (61" Deck Only)		\$160
50052102	Work Light Kit		\$101
50048630	Rear Hitch Bundle		\$36

Due to varied conditions, the following blades may enhance performance:

Part No.	Description	
50025382	19" Corner Uplift (for 55" decks)	(See Part Price List)
50034298	19" Hi-Corner Uplift (for 55" decks)	(See Part Price List)
97235	19" Parallel Uplift (for 55" decks)	(See Part Price List)
50029158	19" " Gator™ Mulching (for 55" decks)	(See Part Price List)
95754	21" Corner Uplift (for 61" decks)	(See Part Price List)
50034299	21" Hi Corner Uplift (for 61" decks)	(See Part Price List)
82324	21" CW Parallel Uplift (for 61" decks)	(See Part Price List)
50029159	21" Gator™ Mulching (for 61" decks)	(See Part Price List)

**** This model does not meet CARB exhaust emissions requirements. Not available for sale in CA.**

FEATURES AND SPECIFICATION

1. The way your zero turn mower performs the first day on the job is important, but the way it performs years from now is just as important.
2. All Bush Hog Zero Turn Mowers are equipped with Fusion blades. This means less blade sharpening and a cleaner cut for a better lawn appearance.
3. Welded steel decks with reinforced edges that are designed to deliver performance that will stand up to the years of use,

SAFETY: Operator Presence Controls, Non-Slip Mounting Pads, Large "easy-to-grasp" Controls, ROPS standard, easy to use Parking Brake.

DECK SIZES 55" and 61"

ENGINE Kohler KT740 + Pro Filtration Courage Pro engine (Gross 25 H.P.*)

OPTIONS Kohler KT745 + Pro Filtration Courage Pro engine (Gross 26 H.P.*)

* Engine rated at 3600 RPM per SAE J1940 Gross

Drive System	Dual hydrostats, Hydro-Gear® ZT 3400TM's Dual hydrostats	PTO	Electromagnetic clutch rated at 175 ft lbs
Front Axle	Fixed	Fuel Capacity	Twin fuel tanks 8 gallons
Brakes	Hydraulics provides dynamic braking disc type parking brake	Std Seat	High-back, foam padded seat with flip- up High-back
Steering Motor Control	Dampened twin levers, adjustable Dampened twin levers fore, aft and vertically	Deck Const.	10 gauge, reinforced steel with reinforced 10 gauge, fully floating, 5 inch deep, side discharge
Front Caster Tires	13 x 5.06-4 ply tubeless	Deck lift	Quick Foot™ height adjustment
Drive Tires	22 x 10.50-12 Turf Master™	Blades	(3) .204 inch thick, heat-treated high alloy steel,
Speed	Infinitely variable 0-10 MPH forward, 0-4 mph reverse	Cutting Height	1-1/2 to 4-1/2 inches, adjustable in 1/4 inch increments
Blade Tip Speed	17,800 FPM	Safety	Certified Operator presence controls (OPC), certified ROPS with seatbelt
Controls	Key ignition, throttle, choke, PTO switch,	Accessories	Working Working Lights, Trailer Hitch Kit
Battery	12 volt, Rated 230 CCA		

Features Molded-in large beverage holder, molded in storage tray, tethered gas tank cap,

Warranty Residential/Commercial Use -

Three (3) year limited 3 year limited warranty (third year parts only). Lifetime limited warranty on deck weldment. See dealer for details.

Transport Width 60" for 55" deck (w/deflector up)

Transport Width 66" for 61" deck (w/deflector up)

BUSH HOG, INC. ? 2501 GRIFFIN AVE. ? SELMA, AL. 36703 Tel: 334 874-2700 ? www.bushhog.com

HOW TO ORDER: The Bush Hog Professional Series Zero Turn Mower is available with a choice of 3 engine / deck combinations, two tire package and one seat option. You must order from Group 1, and 2 to get a complete Zero Turn Mower. Add all prices for a total list price.

Freight **NOT** included in list price

Professional-Series Zero Turn Mower

BASIC UNIT SELECTION

Model Number	Description	Ship Weight	List Price
** PZ2761KH5	Kohler CV742 Command Pro engine (Gross 25 H.P.*) and 61" mower deck	1400 lbs.	\$10,671
** PZ3061KH5	Kohler CV752 Command Pro engine (Gross 27 H.P.*) and 61" mower deck	1400 lbs.	\$11,038
** PZ3073KH5	Kohler CV752 Command Pro engine (Gross 27 H.P.*) and 73" mower deck	1550 lbs	\$11,614

* Engine rated at 3600 RPM per SAE J1940 Gross

GROUP 2 TIRE SELECTION

50070817	Turf Tire Bundle - 24x12.0 x12 Turf Smart™	\$103
50070818	Bar Tire Bundle - 24x12.0 x12	\$303

GROUP 3 SEAT STANDARD

	Full suspension seat, complete	50 lbs.	Included
--	--------------------------------	---------	----------

OPTIONS / Shipped Separately

Part No.	Description	Ship Weight*	List Price
50048986	Electric Actuator Bundle		\$407
50048626	Mulching Kit-61" deck (includes Mulching Blades)		\$194
50074343	Canopy		\$392
50052952	Deck Caster Wheel Kit (61" Deck Only)		\$160
50052102	Work Light Kit		\$101
50048630	Rear Hitch Bundle		\$36
99263	Rear Weight Kit (105 lbs.)		\$168

Due to varied conditions, the following blades may enhance performance:

Part No.	Description	
95754	21" Corner Uplift (for 61" decks)	(See Part Price List)
50034299	21" Hi Corner Uplift (for 61" decks)	(See Part Price List)
82324	21" CW Parallel Uplift (for 61" decks)	(See Part Price List)
50029159	21" Gator™ Mulching (for 61" decks)	(See Part Price List)
95755	25" CW Corner Uplift (for 73" decks)	(See Part Price List)
50034300	25" Hi-Corner Uplift (for 73" decks)	(See Part Price List)
82325	25" CW Parallel Uplift (for 73" decks)	(See Part Price List)
50029160	25" "Gator™" Mulching (for 73" decks)	(See Part Price List)

**** This model does not meet CARB exhaust emissions requirements. Not available for sale in CA.**

FEATURES AND SPECIFICATION

1. The way your zero turn mower performs the first day on the job is important, but the way it performs years from now is just as important.
2. All Bush Hog Zero Turn Mowers are equipped with Fusion blades. This means less blade sharpening and a cleaner cut for a better lawn appearance.
3. Welded steel decks with reinforced edges that are designed to deliver performance that will stand up to the years of use,

SAFETY: Operator Presence Controls, Non-Slip Mounting Pads, Large “easy-to-grasp” Controls, ROPS standard, easy to use Parking Brake.

DECK SIZES 61" and 73"
ENGINE Kohler CV742 Command Pro engine (Gross 25 H.P.)*
OPTIONS Kohler CV752 Command Pro engine (Gross 27 H.P.)*
 * Engine rated at 3600 RPM per SAE J1940 Gross

Drive System	Dual Hydro-Gear® ZT5400 Hydrostats	PTO	Electromagnetic clutch rated at 200 ft lbs
Front Axle	Pivoting	Fuel Capacity	Twin fuel tanks 12 gallons
Brakes	Hydraulics provides dynamic braking disc type parking brake	Std Seat	Deluxe high-back, vinyl full suspension seat, equipped with arm rests, operator weight adjustment, lumbar adjustment, and fore aft adjustment
Steering Motor Control	Dampened twin levers, adjustable Dampened twin levers fore, aft and vertically	Deck Const.	7 gauge reinforced steel, fully floating, 5 1/2 inch deep, side discharge
Front Caster Tires	13 x 6.50-6-4 ply tubeless	Deck lift	Quick Foot™ height adjustment
Drive Tires	24 x 12.0-12 Turf Smart™	Blades	(3) .204 inch thick, heat-treated high alloy steel,
Speed	Infinitely variable 0-14 MPH forward, 0-4 mph reverse	Cutting Height	1-1/2 to 5 inches, adjustable in 1/4 inch increments
Blade Tip Speed	18,000 FPM	Safety	Certified Operator presence controls (OPC), certified ROPS with seatbelt
Controls	Key ignition, throttle, choke, PTO switch,	Accessories	Working Working Lights, Trailer Hitch Kit
Battery	12 volt, Rated 230 CCA		

Features Molded-in large beverage holder, molded in storage tray, tethered gas tank cap,

Warranty Residential/Commercial Use -

Three (3) year limited 3 year limited warranty (third year parts only). Lifetime limited warranty on deck weldment. See dealer for details.

Transport Width 66" for 61" deck (w/deflector up)

Transport Width 78" for 73" deck (w/deflector up)

BUSH HOG, INC. 2501 GRIFFIN AVE. SELMA, AL. 36703 Tel: 334 874-2700 www.bushhog.com

HOW TO ORDER: To receive a complete cutter, you must order from each group.
Freight **NOT** included in list price

Five Year Limited Gearbox Warranty
BH25 Series
Rotary Cutter
CUTTING WIDTH: 5'

Five Year Limited Gearbox Warranty
BH26 Series
Rotary Cutter
CUTTING WIDTH: 6'

GROUP 1 - BASE UNIT		
Model Number	Approx. Weight	List Price
BH25-1R (Bush Hog Red)	867 lbs.	\$3,003
BH25-1O (Kubota Orange)	867 lbs.	\$3,003
BH25-1G (John Deere Green)	867 lbs.	\$3,003
BH25-1B (New Holland Blue)	867 lbs.	\$3,003

GROUP 1 - BASE UNIT		
Model Number	Approx. Weight	List Price
BH26-1R (Bush Hog Red)	992 lbs.	\$3,402
BH26-1O (Kubota Orange)	992 lbs.	\$3,402
BH26-1G (John Deere Green)	992 lbs.	\$3,402
BH26-1B (New Holland Blue)	992 lbs.	\$3,402

Group 2 ENCLOSURE SELECTION		
A front and rear safety shield must be chosen and price added.		
50070729	Deflector Kit, Front & Rear, 40 lbs	\$102
50070730	Single Row Chains Complete, 98 lb:	\$396
50070731	Dbl row chains, complete, 139 lbs	\$594
50073327	Front chain, Rear band, 70 lb	\$217

Group 2 ENCLOSURE SELECTION		
A front and rear safety shield must be chosen and price added.		
50070735	Deflector kit, Front & Rear, 45 lbs	\$115
50070737	Single Row Chain complete, 106 lbs.	\$463
50070738	Dbl Row Chains, complete, 159 lbs.	\$694
50073328	Front chain, Rear band, 77 lb	\$239

Note: Safety shieldings are non-returnable items.
Special Paint Call Before Quote

Note: Safety shieldings are non-returnable items.
Special Paint Call Before Quote

STANDARD EQUIPMENT AND SPECIFICATIONS	
Cutting Width:	5 ft
Overall Width:	5 ft 6 inches
Overall Length:	8 ft 8 inches
Cutting Height :	1 1/2" to 10 1/2"
Cutting Capacity:	3" diameter
Hitch:	3 pt. Cat. I & II Standard & Quick Hitch
Deck Thickness:	10 Gauge Steel
Side Bands	1/4" x 13"
Gearbox:	130 HP, (540 RPM)
Driveshaft:	ASAE Category 4
Driveline Protection	Slip Clutch Std
Blade Holder:	Round
Blades:	1/2" x 4", Heat Uplift
Blade Tip Speed:	14,600 FPM (540 RPM)
Wheels:	Laminated
Minimum Tractor HP	35 (PTO)
Front & Rear Deflector Kit: See enclosure selection	

STANDARD EQUIPMENT AND SPECIFICATIONS	
Cutting Width:	6 Ft.
Overall Width:	6 ft 6 inches
Overall Length:	9 ft 8 inches
Cutting Height :	1 1/2" to 10 1/2"
Cutting Capacity:	Up to 3" diameter
Hitch:	Cat I & II Standard and Quick Hitch
Deck Thickness:	10 Gauge Steel
Side Bands	1/4" x 13"
Gearbox:	130 HP, (540 RPM)
Driveshaft:	ASAE Category 4
Driveline Protection	Slip Clutch Std
Blade Holder:	Round
Blades:	1/2" x 4", Heat Uplift
Blade Tip Speed:	15,000 FPM (540 RPM)
Wheels:	Laminated
Minimum Tractor HP	45 (PTO)
Front & Rear Deflector Kit: See enclosure selection	

Five Year Limited Gearbox Warranty
Notice: PTO adapter must not be used in any application.

Five Year Limited Gearbox Warranty
Notice: PTO adapter must not be used in any application.

WARNING: Deflector kit or chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property.

HOW TO ORDER: To receive a complete cutter, you must order from each group.
Freight **NOT** included in list price

Five Year Limited Gearbox Warranty

**BH27 Series
Rotary Cutter**

CUTTING WIDTH: 7'

GROUP 1 - BASE UNIT

Model Number	Tail Wheel	Approx. Weight	List Price
BH27-1R (Bush Hog Red)	Single tailwheel	1251 lbs.	\$4,461
BH27-1O (Kubota Orange)	Single tailwheel	1251 lbs.	\$4,461
BH27-1G (John Deere Green)	Single tailwheel	1251 lbs.	\$4,461
BH27-1B (New Holland Blue)	Single tailwheel	1251 lbs.	\$4,461
BH27D-1R, (Bush Hog Red)	Dual tail wheel	1328 lbs.	\$4,843
BH27D-1O, (Kubota Orange)	Dual tail wheel	1328 lbs.	\$4,843
BH27D-1G, (John Deere Green)	Dual tail wheel	1328 lbs.	\$4,843
BH27D-1B, New Holland Blue)	Dual tail wheel	1328 lbs.	\$4,843

Group 2 ENCLOSURE SELECTION

A front and rear safety shield must be chosen and price added.

50070740	Deflector Kit complete, 52 lbs.	\$146
50070741	Single Row Chains, complete, 131 lbs.	\$559
50050742	Double Row Chains complete, 198 lbs.	\$784
50073329	Front chain, Rear band, 92 lb	\$314

Note: Safety shieldings are non-returnable items.

Special Paint **Call Before Quote**

STANDARD EQUIPMENT AND SPECIFICATIONS

Cutting Width:	7 ft
Overall Width:	7 ft 6 inches
Overall Length:	10 ft 8 inches (Single)
Overall Length:	10 ft 1 inches (Double)
Tail wheel	Single or Dual
Cutting Height :	1 1/2" to 10 1/2"
Cutting Capacity:	3" diameter
Hitch:	3 pt. Cat. II & III Standard & Quick Hitch
Deck Thickness:	10 Gauge Steel
Side Bands	1/4" x 13"
Gearbox:	130 HP, (540 RPM only)
Driveshaft:	ASAE Category 4
Driveline Protection	Slip Clutch Std
Blade Holder:	Round
Blades:	1/2" x 4", Heat Uplift
Blade Tip Speed:	14,450 FPM (540 RPM)
Wheels:	Laminated
Minimum Tractor HP	55 (PTO)
Front & Rear Deflector Kit:	See enclosure selection

Five Year Limited Gearbox Warranty

Notice: PTO adapter must not be used in any application.

WARNING: Deflector kit is standard equipment. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property.

HOW TO ORDER: To receive a complete cutter, you must order from each group.
 Freight **NOT** included in list price

Five Year Limited Gearbox Warranty

**326 Series
 Rotary Cutter**
 CUTTING WIDTH: 6'

GROUP 1 - BASE UNIT

Model	Approx. Weight	List
326-01	1400 lbs.	\$4,600

Five Year Limited Gearbox Warranty

**327 Series
 Rotary Cutter**
 CUTTING WIDTH: 7'

GROUP 1 - BASE UNIT

Model	Approx. Weight	List
327R-1	1612 lbs	\$5,997

GROUP 2--HITCH SELECTION

(Must Make a Selection)		
50055277	Lift w/driveline & #500 tires	338 lbs \$993

Group 2 DRIVELINE SELECTION

50050576	Drive Line w/slipclutch, ASAE5	\$470
----------	--------------------------------	-------

GROUP 3-- HEIGHT ADJUSTMENT SELECTIONS

1817	Manual ratchet bundle	\$130
64830	Hydraulic cyl. Bundle	\$298

Group 3 FRONT ENCLOSURE SELECTION

50050645	Single Row Chains Front, 41 lbs	\$203
50050659	Double Row Chains Front , 79 lbs	\$316

GROUP 4 - FRONT ENCLOSURE SELECTION

50055316	Single Row Chains Front, 51 lbs.	\$231
50055329	Double Row Chains Front, 90 lbs.	\$361

GROUP 4 - REAR ENCLOSURE SELECTION

50050644	Single Row Chains Rear, 55 lbs.	\$290
50050658	Double Row Chains Rear, 92 lbs.	\$417

GROUP 5 - REAR ENCLOSURE SELECTION

50055315	Single Row Chains Rear, 69 lbs.	\$361
50055330	Double Row Chains Rear, 105 lbs.	\$463

Note: Safety shieldings are non-returnable items.

Note: Safety shieldings are non-returnable items.

STANDARD EQUIPMENT AND SPECIFICATIONS

Cutting Width:	6 Ft.
Overall Width:	78"
Overall Length:	118 1/2"
Cutting Height :	2" to 12"
Cutting Capacity:	Up to 4" Diameter
Hitch:	HD 3 pt. Cat. I & II Standard & Quick Hitch
Deck Thickness:	7 Gauge
Side Bands	1/4" x 12 1/2"
Gearbox:	Heavy Duty 210 HP, 540 RPM
Driveshaft:	ASAE Cat. 5, with
Driveline Protection	Slip Clutch Std
Blade Holder:	Round
Blades:	1/2" x 4", Heat Treated
Blade Tip Speed:	13,996 ft/min. - 540RPM
Wheels:	Laminated Caster Wheel Single
Minimum Tractor HP	60 HP PTO
Front & Rear Deflector Kit:	See enclosure selection

Notice: PTO adapter must not be used in any application.

STANDARD EQUIPMENT AND SPECIFICATIONS

Cutting Width:	7 ft
Overall Width:	90"
Overall Length:	131" lift
Tail wheel	Dual
Cutting Height :	2" to 12"
Cutting Capacity:	Up to 4" Diameter
Hitch:	HD 3 Point Category Cat. II & III Standard and QH.
Deck Thickness:	7 Gauge
Side	1/4" x 12 1/2"
Gearbox:	Extra Heavy Duty 210 HP, 540 RPM
Driveshaft:	ASAE Cat. 5, with slip clutch
Driveline Protection	Heavy Duty Slip Clutch Std
Blade Holder:	Round
Blades:	1/2" x 4" Heat Treated
Blade Tip Speed:	11,875 ft/min. - 540RPM
Wheels:	Laminated, dual Lift; Large Laminated,
Minimum Tractor HP	70 (PTO)
Front & Rear Deflector Kit:	See enclosure selection

Notice: PTO adapter must not be used in any application.

WARNING: Deflector kit or chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

HOW TO ORDER: Your order must include items from group 1 through 5 to receive a complete cutter.

Freight **NOT** included in list price

2008 Series Rotary Cutter: Cutting Width 99"
5 YEAR LIMITED GEARBOX WARRANTY

Cutting Width: 8 ft 3 inches
 Transport Width: 8ft 10 inches
 Overall Width: 8 ft 10 inches
 Length: 8 ft 2 inches
 Hitch: Cat 1 & 2 Standard & QH,
 Pull is self leveling
 Cutting Height: 2" to 12"
 Cutting Capacity: 1 1/2 " Diameter
 Deck Thickness: 10 Gauge
 Side Band: 10 ga. X 10"
 Min. Tractor PTO HP: Pull 35,
 Lift 45
 Driveshaft: ASAE Category 4
 No. of Gearboxes: 3
 Gearbox: 100 HP Center, 75 HP Outboard
 PTO Driveline Protection: 2
 Plate Slip Clutch
 Blade Holder: Oval
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 4.75"
 Blade Tip Speed: 15,962 ft/min.
 Type Wheels: Laminated
 Safety Shielding: see selection
 Safety Tow Chain (pull): Standard

**Notice: PTO adapter must not
 be used in any application**

GROUP ONE---Model selection				
Model selection	Blade Holder	PTO	Weight	List Price
2008R-1	Oval	540	966 lbs	\$4,111
GROUP TWO--Hitch Selection (All bundles include tires)				
Part No.	Description	Weight	List Price	
50068365	Lift bundle w/ (2)15" laminated tires	255 lbs.	\$1,103	
50068366	Semi-mnt bundle w/ (2)15" laminated tires	180 lbs	\$938	
50068367	Pull bundle with (2) 20" laminated tires & CV driveline	612 lbs.	\$2,726	
GROUP THREE--Height adjustment (Pull model only)				
		Weight	List Price	
1817	Manual Ratchet	11 lbs..	\$130	
64830	Hydraulic cylinder and hose	30 lbs.	\$298	
GROUP FOUR--Front Enclosure				
		Weight	List Price	
50064600	Front Rubber Deflector Kit	17 lbs	\$80	
50064604	Front Single Row Chains	39 lbs.	\$208	
GROUP FIVE-----Rear Enclosure				
		Weight	List Price	
50064601	Rear Metal Deflector Kit	34 lbs.	\$63	
50064606	Rear Single Row Chains	43 lbs.	\$176	

Warning: Deflector kit or chain shielding must be selected. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property.

HOW TO ORDER: Your order must include items from group 1 through 8 to receive a complete cutter.

Freight **NOT** included in list price

SPECIFICATIONS

Cutting Width: 9 ft. 9 inches
 Transport Width: 10 ft. 3 inches
 Overall Width: 10 ft. 3 inches
 Length: 9 ft 4 inches (lift), 13 ft. (pull)
 Axle suspension: rubber cushion
 Hitch: Cat 2 & 3 standard & QH
 Pull self leveling
 Cutting Height: 2" to 12"
 Cutting Capacity: 2 " Diameter
 Deck Thickness: 11 Gauge
 Side Skirt Thickness: 7 ga."
 Side Skirt Depth: 10"
 Min. Tractor PTO HP: pull 40, lift 60
 Driveshaft: ASAE Category 4
 No. of Gearboxes: 3
 Gearbox: 120 HP Center, 90 HP
 Outboard
 Driveline Protection: 4 Plate Slip
 Clutch
 Blade Holder: Round
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 3"
 Blade Tip Speed: 15,778 ft/min. @
 540 pto
 Type Wheels: Laminated, & Aircraft
 Safety Shielding: see selection

Notice: PTO Adaptor must not be used in any application

Warning: Deflector kit or chain shielding is standard equipment. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

2010 Series Rotary Cutter: Cutting Width 9ft. 9"
5 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE--MODEL SELECTION				
Model selection	Blade Holder	PTO	Weight	Price
2010R	Round	540	1631 lbs	\$6,544

GROUP TWO--HITCH SELECTION (Lift & semi-mount include tires)				
Part No.	Description	Weight	List Price	
50068346	Lift bundle, with 15" laminated tires	127 lbs	\$677	
50068348	Semi-mnt bndl, w/ 15" laminated tires	88 lbs	\$464	
50068347	Pull bundle, includes CV, for 540 pto	176 lbs	\$1,355	

GROUP THREE--DRIVELINE SELECTION (Lift & SEMI-MOUNT ONLY)				
76981	Lift & semi-mount, 1 3/8-6, 540 pto	55 lbs	\$404	

GROUP FOUR--AXLE SELECTION (pull only)				
50044184	Hvy duty single axle arm bundle	144 lbs	\$568	

GROUP FIVE--HEIGHT ADJUSTMENTSELECTION				
89045	Hydraulic cylinder bundle	45 lbs.	\$304	
1817	Manual ratchet bundle	15 lbs.	\$130	

GROUP SIX--WHEEL SELECTION (Pull models only)				
294	20" Laminated tire (priced ea.)	70 lbs.	\$183	
50050727	Used aircraft tire, 29x9x15 (priced ea.)	65 lbs.	\$231	

GROUP SEVEN--FRONT ENCLOSURE SELECTION				
50043489	Front rubber deflector	38 lbs	\$159	
50043493	Front single row chains	79 lbs	\$243	

GROUP EIGHT--REAR ENCLOSURE SELECTION				
50043491	Rear metal band	49 lbs	\$103	
50043495	Rear single row chains	68 lbs	\$220	

Note: Safety shieldings are non-returnable

HOW TO ORDER: Your order must include items from group 1 through 8 to receive a complete cutter.

Freight **NOT** included in list price

3008 Series Rotary Cutter: Cutting Width 8'
5 YEAR LIMITED GEARBOX WARRANTY

Cutting Width: 8 ft 2 inches
 Transport Width: 8ft 10 inches
 Overall Width: 8 ft 10 inches
 Length: 8 ft 2 inches
 Axle suspension: see selection
 Hitch: Cat 1 & 2 Standard & QH,
 Pull is self leveling
 Cutting Height: 2" to 13"
 Cutting Capacity: 2 " Diameter
 Deck Thickness: 10 Gauge
 Side Skirt Thickness: 1/4"
 Side Skirt Depth: 10"
 Min. Tractor PTO HP: 40 (Pull),
 50 (Lift)
 Driveshaft: ASAE Category 4
 No. of Gearboxes: 3
 Gearbox: 120 HP Center, 90 HP Outboard
 Driveline Protection: 4 Plate Slip
 Clutch
 Blade Holder: Round
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 3"
 Blade Tip Speed: 16,345 ft/min. (540)
 Type Wheels: See Selection
 Safety Shielding: see selection
 Safety Tow Chain: Standard (pull)

**Notice: PTO adapter must not
 be used in any application**

Warning: Deflector kit or chain
 shielding is standard equipment.
 Must be used for all non-
 agricultural uses or in areas
 where the possibility of thrown
 objects could be hazardous to
 persons or property. Use 5/16"
 double row highway chains for all
 roadside mowing operations.

GROUP ONE--MODEL SELECTION				
Model selection	Blade Holder	PTO	Weight	Price
3008R-2	Round	540	1155 lbs	\$4,874

GROUP TWO--HITCH SELECTION (Lift & semi-mount include tires)				
Part No.	Description	Weight	List Price	
50040433	Lift bundle with 15" laminated tire	115 lbs.	\$646	
50040439	Semi-mount bndl w/ 15" laminated tire	72 lbs	\$396	
50040437	Pull bundle for a CV driveline	231 lbs.	\$2,012	

GROUP THREE--DRIVELINE SELECTION				
76966	Lift and semi-mount, 540 pto	55 lbs.	\$363	
50072251	Pull, C.V. , 1 3/8-6, 540 pto	73 lbs.	\$798	

GROUP FOUR--AXLE SELECTION (Lift & Semi-mount only)				
94157	Rigid twin beam axle	137 lbs	\$671	
94159	Hvy duty axle w/ shock absorber	247 lbs.	\$989	

GROUP FIVE--HEIGHT ADJUSTMENTSELECTION (Not for rigid beam axle)				
For pull, lift & S.M except with rigid beam axle				
89045	Hydraulic cyl. Bundle	45 lbs.	\$304	
1817	Manual ratchet bundle	15 lbs.	\$130	

GROUP SIX--WHEEL SELECTION (Pull models only)				
294	20" Laminated tire (priced ea.)	70 lbs.	\$183	
50050727	Used aircraft tire, 29x9x15 (priced ea.)	65 lbs.	\$231	
50068834	Foam filled A/C tire, 26x6.6x14 (priced ea.)	90 lbs.	\$323	

GROUP SEVEN--FRONT ENCLOSURE SELECTION				
91606	Front single row chains	140 lbs.	\$244	
91607	Front double row chains	165 lbs.	\$483	

GROUP EIGHT--REAR ENCLOSURE SELECTION				
91522	Rear metal band	40 lbs.	\$89	
91615	Rear single row chains	155 lbs,	\$259	
91620	Rear double row chains	180 lbs.	\$530	

Note: Safety shieldings are non-returnable items.

HOW TO ORDER: Your order must include items from group 1 through 8 to receive a complete cutter.
Freight **NOT** included in list price

Cutting Width: 8 ft 2 inches
 Transport Width: 8ft 5 inches
 Overall Width: 8 ft 10 inches
 Length: 7 ft 11 inches
 Axle suspension: see selection
 Hitch: Cat 1 & 2 semi-mount only
 Maximum offset: 13" to the right
 Cutting Height: 2" to 13"
 Cutting Capacity: 2" Diameter
 Deck Thickness: 10 Gauge
 Side Skirt Thickness: 1/4"
 Side Skirt Depth: 10"
 Min. Tractor pto HP: 40 (Pull), 50 (Lift)
 Driveshaft: ASAE Category 4
 No. of Gearboxes: 3
 Gearbox: 120 HP Center, 90 HP Outboard
 Driveline Protection: 4 Plate Slip Clutch
 Blade Holder: Round
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 3"
 Blade Tip Speed: 16,345 ft/min. (540)
 Type Wheels: Laminated
 Safety Shielding: see selection

Safety Tow Chain: Standard (pull model)

Notice: PTO Adaptor must not be used in

Warning: Deflector kit or chain shielding is standard equipment. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

SWING HITCH MODEL
3008SH Series Rotary Cutter: Cutting Width 8'
5 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE--MODEL SELECTION				
Model selection	Blade Holder	PTO	Weight	Price
3008SHR2	Round	540	1155 lbs	\$5,025

GROUP TWO--HITCH SELECTION (semi-mount include tires)			
Part No.	Description	Weight	List Price
50040448	Swing hitch, Semi-mount bundle with 15" laminated tires	172 lbs	\$1,565

GROUP THREE--DRIVELINE SELECTION
 Included in Hitch Bundle

GROUP FOUR--AXLE SELECTION			
94159	Heavy duty axle bundle	247 lbs.	\$989

GROUP FIVE--HEIGHT ADJUSTMENTSELECTION --FOR ALL AXLES			
89045	Hydraulic cylinder bundle	45 lbs.	\$304
1817	Manual ratchet bundle	15 lbs.	\$130

GROUP SEVEN--FRONT ENCLOSURE SELECTION			
91606	Front single row chains	140 lbs.	\$244
91607	Front double row chains	165 lbs.	\$483

GROUP EIGHT--REAR ENCLOSURE SELECTION			
91522	Rear metal band	40 lbs.	\$89
91615	Rear single row chains	155 lbs,	\$259
91620	Rear double row chains	180 lbs.	\$530

Note: Safety shieldings are non-returnable items.

HOW TO ORDER: Your order must include items from group 1 through 8 to receive a complete cutter.

Freight **NOT** included in list price

OFFSET 3210 MODEL

3210-O Series Rotary Cutter: Cutting Width 10 1/2 ft
5 YEAR LIMITED GEARBOX WARRANTY

SPECIFICATIONS

Offset from center, 7ft 10"
 Cutting Width: 10 1/2 FT.
 Transport Width: 10 FT 11 inches
 Overall Width: 11 FT 1 inches
 Axle suspension: Rubber cushion
 Hitch: Pull, self leveling

Cutting Height: 2" to 13"
 Cutting Capacity: 3" Diameter
 Deck Thickness: 10 Gauge
 Side Skirt Thickness: 1/4"
 Side Skirt Depth: 10"
 Min. Tractor PTO HP: Pull 50
 Driveshaft: ASAE Cat 5, 540 PTO
 1000 pto pull, ASAE cat 4
 Cross shafts: ASAE cat 5
 No. of Gearboxes: 2
 Gearbox: 210HP Center, 205 HP
 Outboard
 Driveline Protection: 4 Plate Slip Clutch
 Blade Holder: Round
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 3"
 Blade Tip Speed: 16,881 ft/min. (540)
 17,400 @ 1000 pto
 Type Wheels: See Selection
 Safety Shielding: see selection
 Notice: PTO Adaptor must not be used
 any application

Warning: Deflector kit or chain shielding is standard equipment. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

GROUP ONE--MODEL SELECTION

Model selection	Blade Holder	PTO	Weight	Price
3210-OR1	Round	540	1937	\$6,358

GROUP TWO--HITCH SELECTION

50068332	Pull w/ CV, Cat 5, 540 pto		90 lbs.	\$2,334
----------	----------------------------	--	---------	---------

**GROUP THREE--DRIVELINE SELECTION
 INCLUDED IN HITCH SELECTION**

GROUP FOUR--AXLE SELECTION (Pull)

50068235	PULL, single wheel axle arms (pair)		162 lbs	\$830
50068236	PULL, dual wheel axle arms, (pair)		194 lbs	\$1,055

GROUP FIVE--HEIGHT ADJUSTMENTSELECTION (All models)

90492	Hydraulic cyl. Bundle		45 lbs.	\$347
1817	Manual ratchet bundle		15 lbs.	\$130

GROUP SIX--WHEEL SELECTION (Pull models only)

294	20" Laminated tire (priced ea.)		70 lbs.	\$183
50050727	Used aircraft tire, 29x9x15 (priced ea.)		65 lbs.	\$231
50068834	Foam filled A/C tire, 26x6.6x14 (priced ea.)		90 lbs.	\$323

GROUP SEVEN--FRONT ENCLOSURE SELECTION

90425	Front single row chains		140 lbs.	\$382
90426	Front double row chains		165 lbs.	\$640

GROUP EIGHT--REAR ENCLOSURE SELECTION

90199BH	Rear metal band		40 lbs.	\$96
90435	Rear single row chains		155 lbs,	\$452
90436	Rear double row chains		180 lbs.	\$702

Note: Safety shieldings are non-returnable items.

HOW TO ORDER: Your order must include items from group 1 through 8 to receive a complete cutter.

Freight **NOT** included in list price

SPECIFICATIONS

Cutting Width: 10 1/2 FT.
 Transport Width: 10 FT 11 inches
 Overall Width: 11 FT 1 inches
 Axle suspension: Rubber cushion
 Hitch: Cat 2 & 3 Standard & QH
 Pull, self leveling
 Cutting Height: 2" to 13"
 Cutting Capacity: 3" Diameter
 Deck Thickness: 10 Gauge
 Side Skirt Thickness: 1/4"
 Side Skirt Depth: 10"
 Min. Tractor PTO HP: Pull 50 , Lift 60
 Driveshaft: ASAE Cat 5, 540 PTO
 1000 pto pull, ASAE cat 4
 Cross shafts: ASAE cat 5
 No. of Gearboxes: 3
 Gearbox: 210HP Center, 205 HP
 Outboard
 Driveline Protection: 4 Plate Slip
 Clutch
 Blade Holder: Round
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 3"
 Blade Tip Speed: 16,881 ft/min. (540)
 17,400 (1000)
 Type Wheels: See Selection
 Safety Shielding: See selection
 Notice: PTO Adaptor must not be used
 any application

Warning: Deflector kit or chain shielding is standard equipment. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

3210 Series Rotary Cutter: Cutting Width 10 1/2 ft
5 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE--MODEL SELECTION				
Model selection	Blade Holder	PTO	Weight	Price
3210R-2	Round	540	2054 lbs	\$6,686
13210R-2	Round	1000	2054 lbs	\$6,755
GROUP TWO--HITCH SELECTION				
50036639	Lift bundle		225 lbs.	\$1,199
50068324	Semi-mount bundle		8 lbs	\$199
50036646	Pull bundle		260 lbs	\$1,387
GROUP THREE--DRIVELINE SELECTION				
76729	Lift & semi-mount, 1 3/8-6, 540 pto		69 lbs.	\$709
76730	Lift & semi-mount, 1 3/8-21, 1000 pto		69 lbs.	\$709
76625	Pull, C.V. , 1 3/8-6, 540 pto		73 lbs.	\$998
GROUP FOUR--AXLE SELECTION (Lift , Semi-mount & Pull)				
50068235	PULL, single wheel axle arms (pair)		162 lbs	\$830
50068236	PULL, dual wheel axle arms, (pair)		194 lbs	\$1,055
50068237	L & SM, caster & arms(pair) with #500 tire		230 lbs	\$1,113
50068238	L & SM, caster & arms(pair) with #294 tire		269 lbs	\$1,621
GROUP FIVE--HEIGHT ADJUSTMENTSELECTION (All models)				
90492	Hydraulic cyl. Bundle		45 lbs.	\$347
1817	Manual ratchet bundle		15 lbs.	\$130
GROUP SIX--WHEEL SELECTION (Pull models only)				
294	20" Laminated tire (priced ea.)		70 lbs.	\$183
50050727	Used aircraft tire, 29x9x15 (priced ea.)		65 lbs.	\$231
50068834	Foam filled A/C tire, 26x6.6x14 (priced ea.)		90 lbs.	\$323
GROUP SEVEN--FRONT ENCLOSURE SELECTION				
90425	Front single row chains		140 lbs.	\$382
90426	Front double row chains		165 lbs.	\$640
GROUP EIGHT--REAR ENCLOSURE SELECTION				
90199BH	Rear metal band		40 lbs.	\$96
90435	Rear single row chains		155 lbs,	\$452
90436	Rear double row chains		180 lbs.	\$702

Note: Safety shieldings are non-returnable items.

HOW TO ORDER: Your order must include items from group 1 through 8 to receive a complete cutter.

Freight **NOT** included in list price

3414 Series Rotary Cutter: Cutting Width 14 ft

5 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE--MODEL SELECTION

All units have shear bolt cross shafts.

Model selection	Blade Holder	PTO	Weight	Price
3414RS-1	round	540	2590 lbs.	\$7,896
13414RS1	round	1000	2590 lbs.	\$8,379
13414SS1	bar	1000	2559 lbs	\$8,379

GROUP TWO--HITCH SELECTION

50068336	Lift bundle, includes # 294 tires		530 lbs	\$3,571
50035727	Pull bundle		281 lbs	\$2,513

GROUP THREE--DRIVELINE SELECTION

76729	Lift , 1 3/8-6, 540 pto, Cat5		69 lbs.	\$709
76730	Lift , 1 3/8-21, 1000 pto, Cat5		69 lbs.	\$709
76731	Lift , 1 3/4-20, 1000 pto, Cat5		70 lbs.	\$709
76625	Pull, C.V. , 1 3/8-6, 540 pto		73 lbs.	\$998
76624	Pull, C.V. , 1 3/8-21, 1000 pto		70 lbs	\$992

GROUP FOUR--AXLE SELECTION (Pull only)

50068369	PULL , single wheel axle (pair) Use #294 tire		162 lbs	\$890
50068370	PULL , dual wheel axle , (pair). Use either tire		194 lbs	\$1,109

GROUP FIVE--HEIGHT ADJUSTMENTSELECTION (All models)

90492	Hydraulic cyl. bundle		45 lbs.	\$347
1817	Manual ratchet bundle		15 lbs.	\$130

GROUP SIX--WHEEL SELECTION (Pull models only)

294	20" Laminated tire (priced ea.)		70 lbs.	\$183
50068834	Foam filled A/C tire, 26x6.6x14 (priced ea.)		90 lbs.	\$323

GROUP SEVEN--FRONT ENCLOSURE SELECTION

90473	Front belting		73 lbs	\$362
90215BH	Front single row chains		160 lbs	\$492

GROUP EIGHT---REAR ENCLOSURE SELECTION

90294	Rear metal band		55 lbs	\$182
90468	Rear single row chains		170 lbs	\$541
90611	Rear rubber belting for row crops		65 lbs.	\$413

**Note: Safety shieldings are non-returnable items.
See next page for options**

SPECIFICATIONS

Cutting Width: 14 FT. *
 Transport Width: 14 FT 8 inches
 Overall Width: 14 FT 7 inches
 Axle suspension: Rubber cushion
 Hitch: Cat 2 & 3 Standard & QH
 Pull, self leveling
 Cutting Height: 2" to 13"
 Cutting Capacity: 2 1/2" Diameter
 Deck Thickness: 10 Gauge
 Side Skirt Thickness: 1/4"
 Side Skirt Depth: 10"
 Min. Tractor PTO HP: Pull 75 , Lift 90
 Driveshaft: ASAE Cat 5, 540 PTO
 1000 pto pull, ASAE cat 4
 Cross shafts: ASAE Cat 5 rubber
 element with Cat 4 shearpin.

No. of Gearboxes: 3
 Gearbox: 210HP Center, 205 HP
 Outboard
 Driveline Protection: 4 Plate Slip Clutch
 Blade Holder: Round
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 3"
 Blade Tip Speed: 15,242 ft/min.
 (540)/1000
 Type Wheels: Laminated, & Aircraft
 Safety Shielding: see selection
 Notice: PTO Adaptor must not be used
 in any application.
 Highway Light Kit---Standard

Warning: Deflector kit or chain shielding
 is standard equipment. Must be used for
 all non-agricultural uses or in areas
 where the possibility of thrown objects
 could be hazardous to persons or
 property.

SPECIFICATIONS

Cutting Width: 14 FT.
 Transport Width: 14 FT 8 inches
 Overall Width: 14 FT 7 inches
 Axle suspension: Rubber cushion
 Hitch: Cat 2 & 3 Standard & QH
 Pull, self leveling
 Cutting Height: 2" to 13"
 Cutting Capacity: 3" Diameter
 Deck Thickness: 10 Gauge
 Side Skirt Thickness: 1/4"
 Side Skirt Depth: 10"
 Min. Tractor PTO HP: Pull 75 , Lift 90
 Driveshaft: ASAE Cat 5, 540 PTO
 1000 pto pull, ASAE cat 4
 Cross shafts: ASAE Cat 5 rubber
 element with Cat 4 shearpin
 No. of Gearboxes: 3
 Gearbox: 210HP Center, 205 HP Outboard
 Driveline Protection: 4 Plate Slip Clutch
 Blade Holder: Round
 Size & Type of Blades: 1/2" x 4" Uplift
 Blade Overlap: 3"
 Blade Tip Speed: 15,242 ft/min. (540)/1000
 Type Wheels: Laminated, pneum. &
 Aircraft
 Safety Shielding: see selection
 Notice: PTO Adaptor must not be used in
 any application.
 Highway Light Kit---Standard

Warning: Deflector kit or chain shielding is standard equipment. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

3414 Series Rotary Cutter: Cutting Width 14 ft

5 YEAR LIMITED GEARBOX WARRANTY

GROUP NINE-- OPTIONS

90604	Shredder kit for 38" & 40" rows	\$398
90607	Shredder kit for 30" rows	\$398
50050192	Single tailwheel bundle for lift model, includes #294 tire	\$761
50068369	PULL, single wheel axle (pair) Use #294 tire 162 lbs	\$890

HOW TO ORDER: Your order must include items from group 1 through 6 to receive a complete cutter.

SPECIFICATIONS

*Transport Height: 5 ft., 8 in.
 **Transport Width: 6 ft 8 in.
 Cutting Width: 12ft
 Cutting height: 2 in. to 14 in.
 Overall width: 12 ft. 8 in.
 Length: 13 ft. 3 in.
 Hitch: Cast swivel clevis
 Min. Tractor H.P., 50 (PTO)
 Cutting capacity 1-1/2 in.
 Deck: 10 gauge
 Blades: 1/2 in. x 3 in., parallel uplift
 Blade overlap: 6"
 Side Band Thickness: 1/4 in.x 10 in.
 Wing flex: 87° Up to 22° Down
 Splitter gearbox: 160 h.p
 Cutting gearboxes: 65 h.p
 Jack Stand: Standard
 Blade Tip Speed: 14,464 / 13,930
 Center Hydraulic Lift: Standard
 Wing hydraulic lift: Standard
 Slipclutch: (3) muti-plate
 Wing flex: 87° Up to 22° Down
 Axle tube pivots: greaseable bushings
 Axle cushioned: Rubber bumper on each center axle arm
 Wing Adjustment: greaseable turnbuckles
 Safety tow chain: standard
 Safety shielding: see selection

Assembly: Included in list price

*Measured at max. transport height
 **Measured at outside of wing skids

Warning: Chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property.

Freight **NOT** included in list price

1812 Flexwing Series Rotary Cutter: Cutting Width 12'

5 YEAR LIMITED GEARBOX WARRANTY

NOT FOR COMMERCIAL APPLICATION

GROUP ONE - BASE MODEL SELECTIONS

Model Selection	PTO	Deck rings	Weight	List Price
1812	540	No	2554	\$11,298

Model includes center and wing hydraulic cylinders & hoses, cast swivel hitch, tow chain, wing drivelines and CV, ASAE Cat 4 driveline

GROUP TWO - CENTER AXLE SELECTIONS

Part No.	Description	Weight	List Price
50074514	Dual axle arms (4 tires)	88 lbs	\$592
50074515	Single axle arms (2 tires)	69 lbs	\$441

GROUP THREE - WING AXLE SELECTIONS

Part No.	Description	Weight	List Price
50072771	Dual axle arms, (4 tires)	38 lbs	\$302
50072772	Single axle arms, (2 tires)	19 lbs	\$151

GROUP FOUR - WHEEL SELECTIONS

Part No.	Description	Weight	List Price
294	20 in. Laminated Tire	70 lbs	\$183
	4-tires	280 lbs	\$732
	6- tires	420 lbs	\$1,098
50074504	Used aircraft tire 20.5 x 6.75--10	43 lbs	\$165
	4- tires	172 lbs	\$660
	6- tires	258 lbs	\$990
50074505	Used aircraft tire, 20.5 x 6.75--10	60 lbs.	\$272
	Foam Filled 4- tires	240 lbs.	\$1,088
	6- tires	360 lbs.	\$1,632

GROUP FIVE- ENCLOSURES

Part No.	Description	Weight	List Price
50074511	Single row chains, complete	197 lbs	\$526
50074512	Double row chains, complete	315 lbs.	\$795

Note: Safety shieldinings are non-returnable

GROUP SIX - OPTIONS

Part No.	Description	Weight	List Price
50074762	Hydraulic hose kit to raise wings independent of center section Requires two sets of hydraulic remotes		\$29

1812 Spec Colors: Call for quote

1815 FLEXWING

5 YEAR LIMITED GEARBOX WARRANTY

HOW TO ORDER: Your order must include items from group 1 through 6 plus any options to receive a complete cutter.
Assembly: Included in list price. Freight NOT included in list price.

SPECIFICATIONS

*Transport Height: 7 ft.
 **Transport Width: 7 ft. 7 inches
 Cutting Width: 15 ft.
 Cutting Height: 2" to 14"
 ***Length: 15 ft. 2 inches
 Hitch: See Selection
 Tongue Weight: 1,623 lbs.
 Cutting Capacity 2 1/2" Diameter
 Deck Thickness: 10 Gauge
 Size and Type of Blades: 1/2" x 4" Parallel Uplift
 Blade Overlap: 6"
 Side Band Thickness: 1/4"
 WingFlex: 87° Up to 22° Down
 Splitter Gearbox: 160 HP
 Cutting Gearboxes: 130 HP
 PTO Driveline: See Selection
 Wings: ASAE Category 4
 Jack Stand: Standard
 Blade Tip Speed: 15,000 ft./min. @ 540 PTO
 15,600 ft./min. @ 1000 PTO
 Slipclutch: (3) Multi-Plate
 Wing Flex: 87° Up to 22° Down
 Axle Tube Pivots: Greaseable Bushings
 Axle Cushioned: Rubber on each center axle
 Wing Adjustment: Greaseable Turnbuckles
 Grass Baffles: Optional
 Safety Tow Chain: Standard
 Safety Shielding: See Selection
 *Measured at max. transport height
 **Measured at outside of wing skids---folded
 *** Measured from hitch pin to axle spindle at transport height.

Warning: Chain shielding must be selected. Must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property.

NOT FOR COMMERCIAL APPLICATION

GROUP ONE - Base Model Selections

Model Selection	PTO	Deck Rings	Weight	List Price
1815R1	540	No	3421 lbs.	\$12,583
1815RR1	540	Yes	3630 lbs.	\$13,022
11815R1	1000	No	3421 lbs.	\$12,583
11815RR1	1000	Yes	3630 lbs.	\$13,022

Model includes center and wing hydraulic cylinders & hoses, tow chain and wing drivelines.

GROUP TWO - Hitch Selection

Part No.	Description	Weight	List Price
50054574	Cast Clevis	39 lbs.	\$180
50054505	Perma-Level Hitch	53 lbs.	\$328

GROUP THREE - PTO Driveline Selection

Part No.	Description	Weight	List Price
50069764	540 PTO, 1 3/8-6, Cat 6, CV	90 lbs.	\$1,044
50069765	1000 PTO, 1 3/8-21, CAT 6, CV	90 lbs.	\$1,125

GROUP FOUR - Wing Axle Selection

Part No.	Description	Weight	List Price
50072772	Single axle arms, (use 2 tires)	19 lbs.	\$151
50072771	Dual axle arms, (use 4 tires)	38 lbs.	\$302

GROUP FIVE - WHEEL SELECTIONS

Part No.	Description	Weight	List Price
294	20" Laminated Tire (priced ea.)	70 lbs.	\$183
	6- tires	420 lbs.	\$1,098
	8 tires	560 lbs.	\$1,464
50068834	Foam filled A/C tire, 26x6.6-14 (priced ea.)	90 lbs.	\$323
	6 tires	540 lbs.	\$1,938
	8 tires	720 lbs.	\$2,584
97708	Pneumatic A/C tire, 24 x 7.7 x10, (priced each)	72 lbs.	\$211
	6 tires	450 lbs.	\$1,266
	8 tires	600 lbs.	\$1,688

GROUP SIX - ENCLOSURE SELECTIONS

Part No.	Description	Weight	List Price
50072776	Single Row Chains, Front and Rear	269 lbs.	\$998
50073433	Double Row Chains, Front and rear	431 lbs.	\$1,248

Note: Safety shieldings are non-returnable items.

GROUP SEVEN - OPTIONS

50073353	Grass distribution kit	74 lbs.	\$296
1815 Spec	Colors:		Call for quote

HOW TO ORDER: Your order must include items from group 1 through 7 to receive a complete cutter.

SPECIFICATIONS

*Transport Height: 7 ft. 3 in.
 **Transport Width: 8 ft 2 in.
 Cutting Width: 10.5ft
 Cutting height: 2 in. to 14 in.
 Hitch: See Hitch Selection
 Tongue weight: 2,108 lbs.
 Minimum Tractor HP: 60 (PTO)
 Side Band: 1/4 in. x 12 1/2 in.
 Blade Holder: round
 Blades: 1/2 in. x 4 in.
 Blade overlap: 6 in.
 PTO drivelines: Constant Velocity
 Wing driveline: ASAE cat 5
 Wing flex: 87° Up to 22° Down
 Splitter gearbox: 250 h.p
 Cutting gearboxes: 225 h.p
 Jack Stand: Standard
 Blade Tip Speed: 16,286 ft./min
 @ 540, 16000 ft/min @ 1000
 Cutting capacity: 4.5 in. diameter
 Center Top deck: 11 ga.
 Center Bottom deck: 7 ga.
 Wing deck: 7 ga.
 Axle tube pivots: greaseable
 bushings
 Axle arms pivots: greaseable
 Axle cushioned: springs at
 each wheel
 Wing Adjustment: greaseable
 turnbuckles
 Grass baffles: Optional
 Wing & center hydraulics: standard
 Safety tow chain: standard

Assembly: Included in list price

***Measured at max. transport height**

****Measured at outside of wng skids**

Warning: Chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

Freight **NOT** included in list price

3810 Series Rotary Cutter: Cutting Width 10.5 ft.

6 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE - RIGHT WING ONLY BASE MODEL SELECTIONS

Model	PTO	Deck rings	Weight	List Price
3810R2	540	No	4500	\$15,713
3810RR2	540	Yes	4708	\$16,199
13810R2	1000	No	4500	\$15,713
13810RR2	1000	Yes	4708	\$16,199

All models include center and wing hydraulic cylinders & hoses, tow chain and wing driveline

GROUP TWO - HITCH SELECTION

Part No.	Description	Weight	List Price
50072803	Ball hitch with 2 5/16" ball	45 lbs.	\$281
50054505	Perma Level Hitch	53 lbs	\$328

GROUP THREE - PTO DRIVELINES

Part No.	Description	Weight	List Price
50069764	540 PTO, 1 3/8-6, Cat 6, CV	90 lbs.	\$1,044
50069765	1 3/8-21, Cat 6, CV	90 lbs.	\$1,125
50054670	1 3/4-20, Cat 6, CV	90 lbs.	\$1,125

GROUP FOUR - CENTER AXLE SELECTIONS

Part No.	Description	Weight	List Price
50028400	Dual axle arms (4 tires)	171 lbs	\$1,156
50035976	Tandem walking axle arms (4 tires)	392 lbs	\$1,684

GROUP FIVE - WING AXLE SELECTIONS

Part No.	Description	Weight	List Price
50068208	Single axle arms, (1 tire)	69 lbs	\$470
50068209	Dual axle arms, (2 tires)	86 lbs	\$585
50068210	Tandem axle arms, (2 tires)	196 lbs	\$842

GROUP SIX- WHEEL SELECTIONS

Part No.	Description	Weight	List Price	
294	20 in. Laminated Tire	70 lbs	\$183	
		5- tires	350 lbs	\$915
		6 tires	420 lbs	\$1,098
50050727	Used aircraft tire, 29x9x15	75 lbs	\$231	
		5- tires	375 lbs	\$1,155
		6-tires	450 lbs.	\$1,386
50068834	Foam filled A/C tire, 26x6.6x14	90 lbs.	\$323	
		5-tires	450 lbs	\$1,615
		6-tires	540 lbs	\$1,938

GROUP SEVEN- ENCLOSURES

Part No.	Description	Weight	List Price
50070418	Single row chains, front and rear	185 lbs	\$730
50070419	Double row chains, front and rear	310 lbs	\$932

Note: Safety shieldings are non-returnable items.

GROUP EIGHT - OPTIONS

Part No.	Description	Weight	List Price
50070395	Grass & Crop Distribution baffles	59 lbs	\$264

Order through Service Parts. Field conversion single wing axle to dual axles. Order (1) kit per wing. Also order tire of choice.

3810 Spec

Colors

Call for quote

HOW TO ORDER: Your order must include items from group 1 through 6 to receive a complete cutter.

SPECIFICATIONS

*Transport Height: 7 ft. 3 in.
 **Transport Width: 8 ft 2 in.
 Cutting Width: 15ft
 Cutting height: 2 in. to 14 in.
 Hitch: Self-Leveling with
 Perma-Level® Hitch
 Tongue weight: 1,866 lbs.
 Minimum Tractor HP: 60 (PTO)
 Side Band: 1/4 in. x 12 1/2 in.
 Blade Holder: round
 Blades: 1/2 in. x 4 in.
 Blade overlap: 6 in.
 PTO drivelines: Constant Velocity
 Wing drivelines: ASAE cat 4
 Wing flex: 87° Up to 22° Down
 Splitter gearbox: 250 h.p
 Cutting gearboxes: 225h.p
 Jack Stand: Standard
 Blade Tip Speed: 16,286 ft./min
 @ 540, 15,906 ft/min @ 1000
 Cutting capacity: 4 in. diameter
 Center Top deck: 11 ga.
 Center Bottom deck: 7 ga.
 Wing deck: 7 ga.
 Axle tube pivots: greaseable
 bushings
 Axle arms pivots: greaseable
 Axle cushioned: springs at
 each wheel
 Wing Adjustment: greaseable
 turnbuckles
 Grass baffles: Optional
 Wing & center hydraulics: standard
 Safety tow chain: standard

Assembly: Included in list price

***Measured at max. transport height**
****Measured at outside of wng skids**

Warning: Chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

Freight **NOT** included in list price

2815 Series Rotary Cutter: Cutting Width 15'
6 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE - BASE MODEL SELECTIONS

Model Selection	PTO	Deck rings	Weight	List Price
2815R3	540	No	4324	\$17,673
2815RR3	540	Yes	4533	\$18,250
12815R3	1000	No	4324	\$17,673
12815RR3	1000	Yes	4533	\$18,250

All models include center and wing hydraulic cylinders & hoses, Perma-Level hitch, tow chain and wing drivelines

GROUP TWO - PTO DRIVELINES

Part No.	Description	Weight	List Price
50069764	540 PTO, 1 3/8-6, Cat 6, CV	90 lbs.	\$1,044
50069765	1000 PTO, 1 3/8-21, Cat 6, CV	90 lbs.	\$1,125
50054670	1000 PTO, 1 3/4-20, Cat 6, CV	90 lbs.	\$1,125

GROUP THREE - CENTER AXLE SELECTIONS

Part No.	Description	Weight	List Price
50070267	Dual axle arms (4 tires)	126 lbs	\$1,127
50068190	Tandem walking axle arms (4 tires)	209 lbs	\$1,585

GROUP FOUR - WING AXLE SELECTIONS

Part No.	Description	Weight	List Price
50068188	Single axle arms, (2 tires)	98 lbs	\$875
50070267	Dual axle arms, (4 tires)	126 lbs	\$1,127
50068190	Tandem axle arms, (4 tires)	209 lbs	\$1,585

GROUP FIVE - WHEEL SELECTIONS

Part No.	Description	Weight	List Price
294	20 in. Laminated Tire	70 lbs	\$183
	6- tires	420 lbs	\$1,098
	8 tires	560 lbs	\$1,464
50050727	Used aircraft tire, 29x9x15	75 lbs	\$231
	6- tires	450 lbs	\$1,386
	8-tires	600 lbs.	\$1,848
50068834	Foam filled A/C tire, 26x6.6x14	90 lbs.	\$323
	6-tires	540 lbs	\$1,938
	8-tires	720 lbs	\$2,584

GROUP SIX - ENCLOSURES

Part No.	Description	Weight	List Price
50069457	Single row chains, front and rear	285 lbs	\$1,123
50069458	Double row chains, front and rear	477 lbs	\$1,390

Note: Safety shieldings are non-returnable items.

GROUP SEVEN - OPTIONS

Part No.	Description	Weight	List Price
50069451	Grass & Crop Distribution baffles	76 lbs	\$351
50071905	Order through Service Parts. Field conversion single wing axle to dual axles. Order (1) kit per wing. Also order tire of choice.		

2815 Spec

Colors

Call for quote

HOW TO ORDER: Your order must include items from group 1 through 7 to receive a complete cutter.

SPECIFICATIONS

*Transport Height: 7 ft. 3 in.
 **Transport Width: 8 ft 2 in.
 Cutting Width: 15ft
 Cutting height: 2 in. to 14 in.
 Hitch: See Hitch Selection
 Tongue weight: 2,108 lbs.
 Minimum Tractor HP: 60 (PTO)
 Side Band: 1/4 in. x 12 1/2 in.
 Blade Holder: round
 Blades: 1/2 in. x 4 in.
 Blade overlap: 6 in.
 PTO drivelines: Constant Velocity
 Wing drivelines: ASAE cat 5
 Wing flex: 87° Up to 22° Down
 Splitter gearbox: 250 h.p
 Cutting gearboxes: 225 h.p
 Jack Stand: Standard
 Blade Tip Speed: 16,286 ft./min
 @ 540, 16000 ft/min @ 1000
 Cutting capacity: 4.5 in. diameter
 Center Top deck: 11 ga.
 Center Bottom deck: 7 ga.
 Wing deck: 7 ga.
 Axle tube pivots: greaseable bushings
 Axle arms pivots: greaseable
 Axle cushioned: springs at each wheel
 Wing Adjustment: greaseable turnbuckles
 Grass baffles: Optional
 Wing & center hydraulics: standard
 Safety tow chain: standard

Assembly: Included in list price

*Measured at max. transport height
 **Measured at outside of wng skids

Warning: Chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

Freight NOT included in list price

3815 Series Rotary Cutter: Cutting Width 15'

6 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE - BASE MODEL SELECTIONS

Model	PTO	Deck rings	Weight	List Price
3815R2	540	No	4466	\$18,430
3815RR2	540	Yes	4675	\$19,002
13815R2	1000	No	4466	\$18,430
13815RR2	1000	Yes	4675	\$19,002

All models include center and wing hydraulic cylinders & hoses, tow chain and wing drivelines

GROUP TWO - HITCH SELECTION

Part No.	Description	Weight	List Price
50072803	Ball hitch with 2 5/16" ball	45 lbs.	\$281
50054505	Perma Level Hitch	53 lbs	\$328

GROUP THREE - PTO DRIVELINES

Part No.	Description	Weight	List Price
50069764	540 PTO, 1 3/8-6, Cat 6, CV	90 lbs.	\$1,044
50069765	1000 PTO, 1 3/8-21, Cat 6, CV	90 lbs.	\$1,125
50054670	1000 PTO, 1 3/4-20, Cat 6, CV	90 lbs.	\$1,125

GROUP FOUR - CENTER AXLE SELECTIONS

Part No.	Description	Weight	List Price
50028400	Dual axle arms (4 tires)	171 lbs	\$1,156
50035976	Tandem walking axle arms (4 tires)	392 lbs	\$1,684

GROUP FIVE - WING AXLE SELECTIONS

Part No.	Description	Weight	List Price
50028401	Single axle arms, (2 tires)	138 lbs	\$930
50028400	Dual axle arms, (4 tires)	171 lbs	\$1,156
50035976	Tandem axle arms, (4 tires)	392 lbs	\$1,684

GROUP SIX- WHEEL SELECTIONS

Part No.	Description	Weight	List Price
294	20 in. Laminated Tire	70 lbs	\$183
	6- tires	420 lbs	\$1,098
	8 tires	560 lbs	\$1,464
50050727	Used aircraft tire, 29x9x15	75 lbs	\$231
	6- tires	450 lbs	\$1,386
	8-tires	600 lbs.	\$1,848
50068834	Foam filled A/C tire, 26x6.6x14	90 lbs.	\$323
	6-tires	540 lbs	\$1,938
	8-tires	720 lbs	\$2,584

GROUP SEVEN- ENCLOSURES

Part No.	Description	Weight	List Price
50069457	Single row chains, front and rear	285 lbs	\$1,123
50069458	Double row chains, front and rear	477 lbs	\$1,390

NOTE: Safety shielding is non returnable

GROUP EIGHT - OPTIONS

Part No.	Description	Weight	List Price
50069451	Grass & Crop Distribution baffles	76 lbs	\$351

Order through Service Parts. Field conversion single wing axle to dual axles. Order (1) kit per wing. Also order tire of choice.

3815 Spec

Colors

Call for quote

HOW TO ORDER: Your order must include items from group 1 through 7 to receive a complete cutter.

SPECIFICATIONS

*Transport Height: 9 ft.
 **Transport Width: 11 ft, 10 in.
 Cutting Width: 20 ft.
 Overall width: 21 ft.
 *Overall length: 15ft, 11 in., Center
 Cutting height: 2 in. to 14 in.
 Cutting capacity: 3 in. diameter
 Deck thickness, Center: 11 ga.top,
 and 10 ga. bottom.
 Wing Deck: 10 ga,
 Side Band: 1/4 in. x 10 1/2 in.
 Hitch: See selection
 Minimum Tractor HP: 80 (PTO)
 Blade Holder: Round or shredder bar
 Blades: 1/2 in. x 4 in.
 Blade overlap: 6 in.
 PTO drivelines: Constant Velocity
 Wing flex: 87° Up to 22° Down
 Splitter gearbox: 250 h.p
 Cutting gearboxes: 225 h.p, 3" O.P. shaft
 Jack Stand: Standard
 Blade Tip Speed: 15,625 ft./min (C),
 and 15,936 ft/min (W)
 Axle pivots: greaseable with bushings
 Axle arms pivots: greaseable
 with bushings
 Axle cushioned: springs at each wheel
 axle arm
 Wing Adjustment: turnbuckles
 Grass baffles: See Options
 Wing & center hydraulics: standard
 Safety tow chain: standard
 Safety shielding: See selection

Assembly: Included in list price
***Measured at max. transport height**
****Measured at outside of wing skids**

Warning: Chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

Freight **NOT** included in list price

2820 Series Rotary Cutter: Cutting Width 20 ft.
6 YEAR LIMITED GEARBOX WARRANTY

GROUP ONE - BASE MODEL SELECTIONS						
Model	Blade Carrier	PTO	Deck rings	Weight	List Price	
2820R1	Pan	540	NO	5567	\$19,667	
2820RR1	Pan	540	YES	5851	\$20,275	
12820R1	Pan	1000	NO	5567	\$19,667	
12820RR1	Pan	1000	YES	5851	\$20,275	
12820SR1	BAR	1000	YES	5851	\$20,431	
12820S1	BAR	1000	NO	5567	\$19,823	
SR1 & S1 models have straight blade bars with 4 blades each						
GROUP TWO - HITCH SELECTION						
Part No.	Description	Weight	List Price			
50072803	Ball hitch with 2 5/16" ball	45 lbs.	\$281			
50054505	Perma Level Hitch	53 lbs	\$328			
GROUP THREE - PTO DRIVELINE SELECTION						
Part No.	Description	Weight	List Price			
50069764	540 PTO, 1 3/8-6, Cat 6, CV	90 lbs.	\$1,044			
50069765	1000 PTO, 1 3/8-21, Cat 6, CV	90 lbs.	\$1,125			
50054670	1000 PTO, 1 3/4-20, Cat 6, CV	90 lbs.	\$1,125			
GROUP FOUR - CENTER AXLE SELECTIONS						
Part No.	Description	Weight	List Price			
50074158	Dual axle arms (4 tires)	171 lbs	\$1,156			
50035976	Tandem walking axle arms (4 tires)	392 lbs	\$1,684			
GROUP FIVE - WING AXLE SELECTIONS						
Part No.	Description	Weight	List Price			
50074159	Single axle arms, (2 tires)	138 lbs	\$930			
50074158	Dual axle arms, (4 tires)	171 lbs	\$1,156			
50035976	Tandem walking axle (4 tires)	392 lbs.	\$1,684			
GROUP SIX - WHEEL SELECTIONS						
Part No.	Description	Weight	List Price			
294	Laminated Tire	70 lbs	\$183			
		6- tires	420 lbs	\$1,098		
		8 tires	560 lbs	\$1,464		
50050727	Used aircraft tire, 29x9x15	75 lbs	\$231			
		6- tires	450 lbs	\$1,386		
		8-tires	600 lbs.	\$1,848		
50068834	Foam filled A/C tire, 26x6.6x14	90 lbs.	\$323			
		6-tires	540 lbs	\$1,938		
		8-tires	720 lbs	\$2,584		
GROUP SEVEN - ENCLOSURE SELECTION						
Part No.	Description	Weight	List Price			
50074153	Single row chains, front and rear	239 lbs.	\$1,372			
50074152	Double row chains, front and rear	395 lbs.	\$1,832			

Note: Safety shieldings are non-returnable items.

SPECIFICATIONS

*Transport Height: 9 ft.
 **Transport Width: 11 ft, 10 in.
 Cutting Width: 20 ft.
 Overall width: 21 ft.
 *Overall length: 15ft, 11 in., Center
 Cutting height: 2 in. to 14 in.
 Cutting capacity: 3 in. diameter
 Deck thickness, Center: 11 ga.top,
 and 10 ga. bottom.
 Wing Deck: 10 ga,
 Side Band: 1/4 in. x 10 1/2 in.
 Hitch: See selection
 Minimum Tractor HP: 90 (PTO)
 Blade Holder: Round or shredder bar
 Blades: 1/2 in. x 4 in.
 Blade overlap: 6 in.
 PTO drivelines: Constant Velocity
 Wing flex: 87° Up to 22° Down
 Splitter gearbox: 250 h.p
 Cutting gearboxes: 225 h.p, 3" o.p. shaft
 Jack Stand: Standard
 Blade Tip Speed: 15,625 ft./min (C),
 and 15,936 ft/min (W)
 Axle pivots: greaseable with bushings
 Axle arms pivots: greaseable
 with bushings
 Axle cushioned: springs at each wheel
 axle arm
 Wing Adjustment: turnbuckles
 Grass baffles: See Options
 Wing & center hydraulics: standard
 Safety tow chain: standard
 Safety shielding: See selection

Assembly: Included in list price
***Measured at max. transport height**
****Measured at outside of wing skids**

Warning: Chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property. Use 5/16" double row highway chains for all roadside mowing operations.

**2820 Series Rotary Cutter: Cutting Width 20 ft.'
 5 YEAR LIMITED GEARBOX WARRANTY**

GROUP EIGHT - OPTIONS			
Part No.	Description	Weight	List Price
50074156	Grass distribution baffles	170 lbs	\$313
50074155	Shredder kit. Adds 2nd blade bar and 2 uplift blades to each cutting circle of SR1 and S1 models for finer shredding.	288 lbs	\$1,034
SR1 & S1 base units include a straight blade bar with 2 uplift blades and 2 flat blades per cutting circle.			
50074199	38 inch row crop spacing wheel spindle kit. Kit places both center section inside tires 5" toward the center of cutter to move tire off center of row. Location is best with 294 laminated tire. (Does not fit Tandem Walking Axle.)		\$299
50073131	Field conversion single wing axle to dual axles. Order (1) kit per wing. Also order tire of choice. Order through Service Parts.		
2720 Spec	Colors:		Call for quote

MACHINE PRICES AND SPECIFICATIONS

EFFECTIVE January 6, 2014

Revised June 23, 2014

HOW TO ORDER: To order a complete unit, select a base unit from Group 1 and the appropriate head option(s) from either Group 2, 3 or 4. Add the prices for a total List Price. The PT5 units come standard with a sickle bar head; no additional selections are required.

FOR USE ON CAB TRACTORS ONLY

REAR MOUNTED BOOM MOWERS

Model Number	Description	Approx. wt.	List Price
(includes flail head)			
Group 1 - BASE UNIT			
RMB1445-1	RMB1445 Boom Mower, 14' 1" Reach, includes Quick Detach Cable Controls and Light Kit as standard equipment	1220	\$13,237
RMB1660-1	RMB1660 Boom Mower, 16' 5" Reach, includes Quick Detach Cable Controls and Light Kit as standard equipment	2403	\$16,067
RMB1865-1	RMB1865 Boom Mower, 18' Reach, includes Quick Detach Cable Controls and Light Kit as standard equipment	2470	\$17,508
RMB1865E-1	RMB1865E [electronic controls] Boom Mower, 18' Reach, includes Quick Detach Cable Controls and Lightbar Kit as standard equipment	2470	\$20,391
PT5-2	Powertrim, 11.5' Reach, includes Flow Control Valve Kit as standard equipment; comes standard with sickle bar head only (requires 15HP engine tractor min., 1212 pound min. tractor weight, hydraulic flow range: 3.7 gal/min MIN - 5.6 gal/min MAX , and one set of hydraulic remotes)	415	\$9,191

IMPORTANT - HEAD SELECTION CRITERIA

RMB1445-1

Flailhead/Cutterbar Requires 45HP engine tractor min., 4410 pound min. tractor weight
Rotary Head Not applicable; rotary head cannot be used on RMB1445-1

RMB1660-1

Flailhead/Cutterbar Requires 60HP engine tractor min., 6614 pound min. tractor weight
Rotary Head Requires 85HP engine tractor min., 7614 pound min. tractor weight

RMB1865-1, RMB1865E-1

Flailhead/Cutterbar Requires 65HP engine tractor min., 7716 pound min. tractor weight
Rotary Head Requires 85HP engine tractor min., 8716 pound min. tractor weight

Group 2 - ROTARY HEAD OPTION

RMB1660-1, RMB1865-1, RMB1865E-1

50071277	Rotary Head, 5/8" x 6" Blades, 60" Wide Cut, 4" Capacity	915 lbs.	\$7,988
(For rotary head, protective screen material supplied must be installed)			

Group 3 - FLAILHEAD OPTIONS

RMB1445-1

50071904	Supercut Compact Flailhead, Universal Knives, 39" Wide Cut, 1" Capacity	309 lbs.	\$4,449
-----------------	---	----------	----------------

RMB1660-1, RMB1865-1, RMB1865E-1

50068497	Supercut Flailhead, Competition Knives, 47" Wide Cut, 1.5" Capacity	520 lbs.	\$5,791
50068498	Multicut Flailhead, Competition Knives, 47" Wide Cut, 2" Capacity	712 lbs.	\$6,919

Note: All flailheads come standard with front flap kits

Group 4 - CUTTERBARS AND OPTIONS / ACCESSORIES --NEXT PAGE

Group 4 - CUTTERBAR OPTIONS

RMB1445-1

50068394	Sheartrim Cutterbar, 59" Wide Cut, 1.25" Capacity	143 lbs.	\$5,176
----------	---	----------	---------

RMB1660-1, RMB1865-1, RMB1865E-1

50068397	Sheartrim Cutterbar, 59" Wide Cut, 1.25" Capacity	143 lbs.	\$5,490
----------	---	----------	---------

Group 5 - OPTIONS / ACCESSORIES

RMB1445-1

50071756	Lift Float Kit		\$465
----------	----------------	--	-------

RMB1660-1, RMB1865-1, RMB1865E-1

50068500	Lift Float Kit		\$486
50068502	Skid Kit (Supercut Flailhead)		\$447
50068503	Skid Kit (Multicut Flailhead)		\$367

HOW TO ORDER: To receive a complete cutter, you must order from each group. Also choose any desired option.

Freight **NOT** included in list price

STANDARD EQUIPMENT AND SPECIFICATIONS

Max distance from center of hitch to outside of cutter: 144 in.
 Cutting Width: 5 ft
 Transport Width: 10 ft 5 inches
 Type Hitch: Category II Standard, Category II & III Quick Hitch
 Cutting Capacity: 1 in.
 Minimum Tractor Weight: 6000 lbs.
 Minimum Tractor Lift Capacity: 3200 lbs. at 24 in. behind lift pins
 Deck Thickness: 10 Gauge
 Blade Holder: Round
 Blade Tip Speed: 17,300 ft/min.
 Blade RPM: 1100
 Blade Rotation: Shipped Clockwise, but reversible

 Type Blades: 1/2 in. x 3 in. Double Edge
 Cutter Head Movement: 90° Up, 85° Dn

 Driveline: ASAE Cat. 4, 540 or 1000 RPM
 Hydraulic Pump Mounting: Machine Only, PTO Driven
 Hydraulic Oil Capacity: 35 Gal., Factory Filled
 Hydraulic Capacity: 24GPM
 Overload Protection: Hydraulic Relief Valve
 Counterweight: 275 lbs. Standard
 Weight: 1675 lbs.
 Maximum Extension of Cutter Head: 145 in. From Tractor Center Line
 Extension Arm Travel: 31-1/4 in.
 Enclosure kit: see selection
 1 yr Pump/Motor limited warranty
 Notice: PTO Adaptor must not be used in any application.

Warning: Chain shielding must be used for all non-agricultural uses or in areas where the possibility of thrown objects could be hazardous to persons or property.

SM60 Side Mount Rotary Cutter. Cutting Width: 5'

GROUP - 1 MODEL SELECTION

Base Unit Number

SM60R-03	(540 RPM) 1675 lbs. with Hydraulic Oil	\$9,694
SM160R03	(1000 RPM) 1675 lbs. with Hydraulic Oil	\$9,694

GROUP - 2 HOSE KIT

65466	Hose Kit For use with tractors equipped with two remote outlets	\$209
--------------	--	--------------

GROUP - 3 ENCLOSURE SELECTION

A front and rear safety shield must be selected.

86809	Chain Kit (Front and rear), 170 lbs.	\$720
--------------	---------------------------------------	--------------

Note: deflector Kits are non-returnable items.

Options/Shipped Separately

86805	Tail Wheel Assembly for Main Frame (324 lbs)	\$582
79038	Side Gauge Wheel with Laminated Tire (70 lbs.)	\$416

Special Paint **Call Before Quote**



BUSH HOG[®]

2501 Griffin Avenue • Selma, AL 36703
(334) 874-2700
www.bushhog.com