

WHOLEGOODS PRICE LIST EFFECTIVE NOVEMBER 14, 2014

NOTE: Tire prices appear per piece.

2015 MISSISSIPPI GROUNDS MAINTENANCE EQUIPMENT PROPOSAL

Kubota "Standard-L Series" (L2501, L3301, L3901 & L4701)
Loaders, Implements & Attachments = 8.0% discount from indicated SLP\$

Kubota "Grand-L Series" (L3560, L4060, L4760, L5060, L5460 & L6060)
Loaders, Implements & Attachments = 10.0% discount from indicated SLP\$

L SERIES

| | PAGE NUMBER | MODEL | PTO HP | SUGGESTED LIST PRICE | |
|-------------------|------------------|--|----------|----------------------|-------------|
| STANDARD L SERIES | 6-5 | L2501F | 20.5 | \$13,191.00 | |
| | 6-6 | L2501DT | 20.5 | \$15,298.00 | |
| | 6-7 | L2501HST | 19.0 | \$16,533.00 | |
| | 6-8 | L3301F | 27.7 | \$16,890.00 | |
| | 6-9 | L3301DT | 27.7 | \$19,109.00 | |
| | 6-10 | L3301HST | 26.2 | \$19,603.00 | |
| | 6-11 | L3901F | 32.1 | \$17,860.00 | |
| | 6-12 | L3901DT | 32.1 | \$20,850.00 | |
| | 6-13 | L3901HST | 30.6 | \$21,795.00 | |
| | 6-14 | L4701F | 39.3 | \$19,032.00 | |
| | 6-15 | L4701DT | 39.3 | \$25,008.00 | |
| | 6-16 | L4701HST | 37.8 | \$26,609.00 | |
| | 6-17 | L3200F* | 26.7 | \$13,795.00 | |
| | 6-18 | L3200DT* | 26.7 | \$15,994.00 | |
| | 6-19 | L3200HST* | 25.2 | \$17,290.00 | |
| | 6-20 | L3800F* | 31.5 | \$16,001.00 | |
| | 6-21 | L3800DT* | 31.5 | \$18,037.00 | |
| | 6-22 | L3800HST* | 30.0 | \$19,335.00 | |
| | 6-23 | L4600F* | 38.3 | \$16,328.00 | |
| | 6-24 | L4600DT* | 38.3 | \$22,782.00 | |
| | 6-25 | L4600HST* | 36.8 | \$24,514.00 | |
| | 6-26 | Standard L Series Rear Remote Valve Chart | | | |
| | 6-27 | Standard L Series Rear Remote Valves | | | |
| | 6-31 | Standard L Series Dealer Installed Options | | | |
| | GRAND L60 SERIES | 6-37 | L3560DT | 29.5 | \$22,990.00 |
| | | 6-38 | L3560GST | 29.5 | \$24,100.00 |
| | | 6-39 | L3560HST | 28.0 | \$24,580.00 |
| 6-40 | | L3560HSTC | 28.0 | \$32,646.00 | |
| 6-41 | | L4060DT | 34.0 | \$26,009.00 | |
| 6-42 | | L4060GST | 34.0 | \$27,119.00 | |
| 6-43 | | L4060HST | 32.5 | \$27,599.00 | |
| 6-44 | | L4060HSTC | 32.5 | \$35,665.00 | |
| 6-45 | | L4760GST | 41.0 | \$32,511.00 | |
| 6-46 | | L4760HST | 39.5 | \$32,991.00 | |
| 6-47 | | L4760HSTC | 39.5 | \$41,057.00 | |
| 6-48 | | L5060GST | 44.0 | \$33,341.00 | |
| 6-49 | | L5460HST | 46.5 | \$34,817.00 | |
| 6-50 | | L5460HSTC | 46.5 | \$42,883.00 | |
| 6-51 | | L6060HST | 53.0 | \$36,726.00 | |
| 6-52 | | L6060HSTC | 53.0 | \$44,792.00 | |
| 6-53 | | Grand L60 Attachment Chart | | | |
| 6-54 | | Grand L60 Dealer Installed Options | | | |
| GRAND L40 SERIES | 6-59 | L3240F-1*/-2*/-3* | 26.5 | \$18,201.00 | |
| | 6-60 | L3240DT-1*/-2*/-3* | 26.5 | \$19,948.00 | |
| | 6-61 | L3240GST-1*/-2*/-3* | 26.5 | \$21,091.00 | |
| | 6-62 | L3240HST-1*/-2*/-3* | 25 | \$21,586.00 | |
| | 6-63 | L3240HSTC-1*/-3* | 25 | \$28,951.00 | |
| | 6-64 | L3540GST-1*/-2*/-3* | 29.5 | \$22,410.00 | |

* Subject to availability.

Prices and specifications subject to change without notice. F.O.B. KTC designated shipping point.

Complete revision November 14, 2014.

L SERIES

| | PAGE NUMBER | MODEL | PTO HP | SUGGESTED LIST PRICE |
|--------------------------|--|--|-------------|----------------------|
| GRAND L40 SERIES (CONT.) | 6-65 | L3540HST-1*/-2*/-3* | 28 | \$22,904.00 |
| | 6-66 | L3540HSTC-1*/-3* | 28 | \$30,270.00 |
| | 6-67 | L3940DT-1*/-2*/-3* | 33 | \$23,441.00 |
| | 6-68 | L3940GST-1*/-2*/-3* | 33 | \$24,584.00 |
| | 6-69 | L3940HST-1*/-2*/-3* | 31.5 | \$25,078.00 |
| | 6-70 | L3940HSTC-1*/-3* | 31.5 | \$32,444.00 |
| | 6-71 | L4240DT-1*/-2*/-3* | 36.5 | \$25,284.00 |
| | 6-72 | L4240GST-1*/-2*/-3* | 36.5 | \$26,428.00 |
| | 6-73 | L4240HST-1*/-2*/-3* | 35 | \$26,922.00 |
| | 6-74 | L4240HSTC-1*/-3* | 35 | \$34,288.00 |
| | 6-75 | L4740GST-1*/-2*/-3* | 41.5 | \$28,694.00 |
| | 6-76 | L4740HST-1*/-2*/-3* | 40 | \$29,188.00 |
| | 6-77 | L4740HSTC-1*/-3* | 40 | \$36,554.00 |
| | 6-78 | L5040GST-1*/-2*/-3* | 44 | \$30,537.00 |
| | 6-79 | L5240HST-1*/-2*/-3* | 45 | \$31,274.00 |
| | 6-80 | L5240HSTC-1*/-3* | 45 | \$38,639.00 |
| | 6-81 | L5740HST-1*/-2*/-3* | 50 | \$32,520.00 |
| 6-82 | L5740HSTC-1*/-3* | 50 | \$39,886.00 | |
| 6-83 | Grand L-40 Series Attachment Chart | | | |
| 6-84 | Grand L-40 Series Dealer Installed Options | | | |
| L SERIES IMPLEMENTS | 6-88 | Std. L Series Implement Matching Chart | | |
| | 6-89 | Grand L-60 Implement Matching Chart | | |
| | 6-90 | Grand L-40 Implement Matching Chart | | |
| | 6-91 | Std. L-Series Loader Matching Chart | | |
| | 6-92 | Grand L-40 Loader Matching Chart | | |
| | 6-93 | Grand L-60 Loader Matching Chart | | |
| | 6-94 | Std. L-Series Loaders | | |
| | 6-95 | Std. L-Series Replacement Loader Attachments | | |
| | 6-99 | L-Series Loader Attachments | | |
| | 6-100 | Grand L-40 Loaders | | |
| | 6-103 | Grand L-60 Loaders | | |
| | 6-106 | L-Series Backhoes | | |
| | 6-111 | L-Series Mowers | | |
| | 6-112 | L-Series Rotary Tillers | | |
| | 6-114 | L-Series Front Quick Hitch Mounted Blades | | |
| | 6-117 | L-Series Snowblower Matching Chart | | |
| | 6-118 | L-Series Front Quick Hitch Mounted Snowblowers | | |
| | 6-122 | L-Series Rear Mount Snowblowers | | |
| | 6-123 | L-Series Rotary Sweeper | | |
| 6-127 | L-Series Front Flail Mowers | | | |
| 6-132 | L-Series Replacement Engines | | | |
| 6-133 | Prior Models | | | |

* Subject to availability.

L2501F

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1703-M-DI-E4-LB2
 Direct Injection
 3 Cyl. 100.47 cu. in.
 + 24.8 Gross Eng. HP
 + 23.9 Net Eng. HP
 + 20.5 PTO HP
 @ 2200 Eng. rpm
 12V - 490 CCA Battery
 Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
 5.2 gpm Remote/3 Pt. Hitch
 3.1 gpm for Power Steering
 8.3 Total gpm
 Cat I 3-point Hitch
 At lift Point 1918 lb.
 24" Behind 1389 lb.

FRONT AXLE

Integral Power Steering
 Tubular Steel Beam, 2WD
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Sliding Gear Constant Mesh
 Transmission
 8 Forward Speeds
 4 Reverse Speeds
 Multiple Wet Disc Brakes
 Clutch – Dry Type Single Stage
 Differential Lock
 Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
 Fuel Gauge
 Temperature Gauge
 Hour Meter

FLUID CAPACITY

Fuel Tank 10.0 gal.
 Cooling System 6.3 qts.
 Crankcase 6.0 qts.
 Transmission and Hydraulics 7.1 gal.

DIMENSIONS

Overall Height w/ROPS 91.7"
 Overall Length w/3pt 119.1"
 Wheel Base 63.3"
 Crop Clearance 15.0"

POWER TAKE OFF

Transmission Driven with
 Over- running Clutch
 540 Rear PTO – 1 Speed
 Speed - 540 @ 1911 Eng. rpm
 SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
 PTO Shield
 Safety Start Switches
 Turn Signals / Hazard Lights
 Mechanical Wet Disc Brakes
 Parking Brakes
 SMV Sign
 Electric Key Shut-off
 Operator Presence Control System

OPERATOR STATION

Color Coded Controls
 Wide Platform Steps
 High Back Seat with Adjustable Suspension
 Tool Box
 Cup Holder
 Left Hand Fender Grip

TIRES AND WHEELS

Front 5.0 x 15 F2
 Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|--------|--|------|--------------|
| L2501F | 2WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 72.8" | 1970 | \$ 13,191.00 |
|--------|--|------|--------------|

| L2501F | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8865** | F-TIRE 5-15 F2 Steel Bias CA | 28 | \$ 123.00 | \$ 13,191.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8852A | F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION | 64 | \$ 194.00 | \$ 13,333.00 |
| ALR9494 | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8890A | F-TIRE 23x8.5-12 R3 TF Steel Bias AA | 32 | \$ 165.00 | \$ 13,261.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L2501DT

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1703-M-DI-E4-LB2
 Direct Injection
 3 Cyl. 100.47 cu. in.
 + 24.8 Gross Eng. HP
 + 23.9 Net Eng. HP
 + 20.5 PTO HP
 @ 2200 Eng. rpm
 12V - 490 CCA Battery
 Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
 5.2 gpm Remote/3 Pt. Hitch
 3.1 gpm for Power Steering
 8.3 Total gpm
 Cat I 3-point Hitch
 At lift Point 1918 lb.
 24" Behind 1389 lb.

FRONT AXLE

Integral Power Steering
 Bevel Gear, 4WD
 Cast Iron
 Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Sliding Gear Constant Mesh
 Transmission
 8 Forward Speeds
 4 Reverse Speeds
 Multiple Wet Disc Brakes
 Clutch – Dry Type Single Stage
 Differential Lock
 Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
 Fuel Gauge
 Temperature Gauge
 Hour Meter

FLUID CAPACITY

| | |
|-----------------------------|-----------|
| Fuel Tank | 10.0 gal. |
| Cooling System | 6.3 qts. |
| Crankcase | 6.0 qts. |
| Transmission and Hydraulics | 7.3 gal. |
| Front Axle | 4.8 qts. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 114.8" |
| Wheel Base | 63.3" |
| Crop Clearance | 13.6" |

POWER TAKE OFF

Transmission Driven with
 Over-running Clutch
 540 Rear PTO – 1 Speed
 Speed - 540 @ 1911 Eng. rpm
 SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
 PTO Shield
 Safety Start Switches
 Turn Signals / Hazard Lights
 Mechanical Wet Disc Brakes
 Parking Brakes
 SMV Sign
 Electric Key Shut-off
 Operator Presence Control System

OPERATOR STATION

Color Coded Controls
 Wide Platform Steps
 High Back Seat with Adjustable Suspension
 Tool Box
 Cup Holder
 Left Hand Fender Grip

TIRES AND WHEELS

Front 7.00 x 16 R1
 Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------------|--|------|--------------|
| L2501DT | 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 72.8" | 2090 | \$ 15,298.00 |
|----------------|--|------|--------------|

| L2501DT | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | | | SUGG. LIST |
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D** | F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 15,298.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8893A | F-TIRE 25x8.5-14 R3 TF Steel Bias CA | 38 | \$ 207.00 | \$ 15,174.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |
| AMR8977A | F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL | 53 | \$ 251.00 | \$ 15,952.00 |
| ALR8809 | ① R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset | 201 | \$ 773.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L2501HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Mdoel # D1703-M-DI-E4-LB1
 Direct Injection
 Mechanical Throttle
 3 Cyl. 100.47 cu. in.
 + 24.8 Gross Eng. HP
 + 23.9 Net Eng. HP
 + 19.0 PTO HP/HST
 @ 2200 Eng. rpm
 12V – 490 CCA Battery
 Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
 5.2 gpm Remote/3 Pt. Hitch
 3.1 gpm for Power Steering
 8.3 Total gpm
 Cat I 3-point Hitch
 At lift Point 1918 lb.
 24" Behind 1389 lb.

FRONT AXLE

Integral Power Steering
 Bevel Gear, 4WD
 Cast Iron
 Tread Spacing, Nonadjustable

 + Manufacturer Estimate

DRIVE TRAIN

Hydrostatic Drive
 3 Speed L-M-H
 Multiple Wet Disc Brakes
 Clutch – Dry Type Single Stage
 Differential Lock
 Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
 Fuel Gauge
 Temperature Gauge
 Hour Meter

FLUID CAPACITY

Fuel Tank 10.0 gal.
 Cooling System 6.3 qts.
 Crankcase 6.0 qts.
 Transmission and Hydraulics 6.2 gal.
 Front Axle 4.8 qts.

DIMENSIONS

Overall Height w/ROPS 91.7"
 Overall Length w/3pt 114.8" 4wd
 Wheel Base 63.3"
 Crop Clearance 13.6"

POWER TAKE OFF

Live Continuous Running with
 Over-running Clutch
 540 Rear PTO – 1 Speed
 Speed - 540 @ 2106 Eng. Rpm/HST
 SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
 PTO Shield
 Safety Start Switches
 Turn Signals / Hazard Lights
 Mechanical Wet Disc Brakes
 Parking Brakes
 SMV Sign
 Electric Key Shut-off
 Operator Presence Control System

OPERATOR STATION

Color Coded Controls
 Wide Platform Steps
 High Back Seat with Adjustable Suspension
 Tool Box
 Cup Holder
 Left Hand Fender Grip

TIRES AND WHEELS

Front 7.00 x 16 R1
 Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------|--|------|--------------|
| L2501HST | 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 72.8" | 2112 | \$ 16,533.00 |
|----------|--|------|--------------|

| L2501HST | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | | | |
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D** | F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 16,533.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8893A | F-TIRE 25x8.5-14 R3 TF Steel Bias CA | 38 | \$ 207.00 | \$ 16,409.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |
| AMR8977A | F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL | 53 | \$ 251.00 | \$ 17,187.00 |
| ALR8809 | ① R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset | 201 | \$ 773.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L3301F

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-LB1
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
3 Cyl. 111.4 cu. in.
+ 31.4 Net Eng. HP
+ 27.7 PTO HP
@ 2700 Eng. rpm
12V - 580 CCA Battery
Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
6.3 gpm Remote/3 Pt. Hitch
3.8 gpm for Power Steering
10.1 Total gpm
Cat I 3-point Hitch
At lift Point 1998 lb.
24" Behind 1435 lb.

FRONT AXLE

Integral Power Steering
Tubular Steel Beam, 2WD
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Synchro Shuttle with Sliding Gear
Shift Transmission
8 Forward Speeds
8 Reverse Speeds
Multiple Wet Disc Brakes
Clutch — Dry Type Single Stage
Differential Lock
Rear Axle — Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 11.1 gal. |
| Cooling System | 6.3 qts. |
| Crankcase | 7.1 qts. |
| Transmission and Hydraulics | 7.4 gal. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 119.1" |
| Wheel Base | 63.3" |
| Crop Clearance | 15.0" |

POWER TAKE OFF

Transmission Driven with Over-
running Clutch
540 Rear PTO — 1 Speed
Speed - 540 @ 2430 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and Inhibit
Buttons for DPF

TIRES AND WHEELS

Front 5.0 x 15 F2
Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|--------|--|------|--------------|
| L3301F | 2WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 73.6" | 2158 | \$ 16,890.00 |
|--------|--|------|--------------|

| L3301F | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8865** | F-TIRE 5-15 F2 Steel Bias CA | 28 | \$ 123.00 | \$ 16,890.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8852A | F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION | 64 | \$ 194.00 | \$ 17,032.00 |
| ALR9494 | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8890A | F-TIRE 23x8.5-12 R3 TF Steel Bias AA | 32 | \$ 165.00 | \$ 16,960.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L3301DT

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-LB1
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
3 Cyl. 111.4 cu. in.
+ 31.4 Net Eng. HP
+ 27.7 PTO HP
@ 2700 Eng. rpm
12V - 580 CCA Battery
Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
6.3 gpm Remote/3 Pt. Hitch
3.8 gpm for Power Steering
10.1 Total gpm
Cat I 3-point Hitch
At lift Point 1998 lb.
24" Behind 1435 lb.

FRONT AXLE

Integral Power Steering
Bevel Gear, 4WD
Cast Iron
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Synchro Shuttle with Sliding Gear
Shift Transmission
8 Forward Speeds
8 Reverse Speeds
Multiple Wet Disc Brakes
Clutch – Dry Type Single Stage
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 11.1 gal. |
| Cooling System | 6.3 qts. |
| Crankcase | 7.1 qts. |
| Transmission and Hydraulics | 7.5 gal. |
| Front Axle | 4.8 qts. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 116.3" |
| Wheel Base | 63.3" |
| Crop Clearance | 13.6" |

POWER TAKE OFF

Transmission Driven with Over-
running Clutch
540 Rear PTO – 1 Speed
Speed - 540 @ 2430 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and Inhibit
Buttons for DPF

TIRES AND WHEELS

Front 7.00 x 16 R1
Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------|-------------|------------------|----------------------|
| *** STANDARD MACHINE *** | | | |

| | | | |
|---------|--|------|--------------|
| L3301DT | 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 73.6" | 2308 | \$ 19,109.00 |
|---------|--|------|--------------|

| L3301DT | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D** | F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 19,109.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8893A | F-TIRE 25x8.5-14 R3 TF Steel Bias CA | 38 | \$ 207.00 | \$ 18,985.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |
| AMR8977A | F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL | 53 | \$ 251.00 | \$ 19,763.00 |
| ALR8809 | ① R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset | 201 | \$ 773.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L3301HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-LB2
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
3 Cyl. 111.4 cu. in.
+ 31.4 Net Eng. HP
+ 26.2 PTO HP
@ 2700 Eng. rpm
12V – 580 CCA Battery
Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
6.3 gpm Remote/3 Pt. Hitch
3.8 gpm for Power Steering
10.1 Total gpm
Cat I 3-point Hitch
At lift Point 1998 lb.
24" Behind 1435 lb.

FRONT AXLE

Integral Power Steering
Bevel Gear, 4WD
Cast Iron
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Hydrostatic Drive
3 Speed L-M-H
Multiple Wet Disc Brakes
Clutch – Dry Type Single Stage
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 11.1 gal. |
| Cooling System | 6.3 qts. |
| Crankcase | 7.1 qts. |
| Transmission and Hydraulics | 6.2 gal. |
| Front Axle | 4.8 qts. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 116.3" |
| Wheel Base | 63.3" |
| Crop Clearance | 13.6" |

POWER TAKE OFF

Live Continuous Running with Over-
running Clutch
540 Rear PTO – 1 Speed
Speed - 540 @ 2580 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and Inhibit
Buttons for DPF

TIRES AND WHEELS

Front 7.00 x 16 R1
Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------|--|------------------|----------------------|
| *** STANDARD MACHINE *** | | | |
| L3301HST | 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 73.6" | 2322 | \$ 19,603.00 |

| L3301HST | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D** | F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 19,603.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8893A | F-TIRE 25x8.5-14 R3 TF Steel Bias CA | 38 | \$ 207.00 | \$ 19,479.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |
| AMR8977A | F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL | 53 | \$ 251.00 | \$ 20,257.00 |
| ALR8809 | ① R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset | 201 | \$ 773.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L3901F

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-LB3
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
3 Cyl. 111.4 cu. in.
+ 36.3 Net Eng. HP
+ 32.1 PTO HP
@ 2700 Eng. rpm
12V – 580 CCA Battery
Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
6.3 gpm Remote/3 Pt. Hitch
3.8 gpm for Power Steering
10.1 Total gpm
Cat I 3-point Hitch
At lift Point 1998 lb.
24" Behind 1435 lb.

FRONT AXLE

Integral Power Steering
Tubular Steel Beam, 2WD
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Synchro Shuttle with Sliding Gear
Shift Transmission
8 Forward Speeds
8 Reverse Speeds
Multiple Wet Disc Brakes
Clutch – Dry Type Dual Stage
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 11.1 gal. |
| Cooling System | 6.3 qts. |
| Crankcase | 7.1 qts. |
| Transmission and Hydraulics | 7.4 gal. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 119.1" |
| Wheel Base | 63.3" |
| Crop Clearance | 15.0" |

POWER TAKE OFF

Live-Continuous Running – Dual Clutch
540 Rear PTO – 1 Speed
Speed - 540 @ 2425 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and Inhibit
Buttons for DPF

TIRES AND WHEELS

Front 5.0 x 15 F2
Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------|--|------------------|----------------------|
| *** STANDARD MACHINE *** | | | |
| L3901F | 2WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 73.6" | 2198 | \$ 17,860.00 |

| L3901F | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8865** | F-TIRE 5-15 F2 Steel Bias CA | 28 | \$ 123.00 | \$ 17,860.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8852A | F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION | 64 | \$ 194.00 | \$ 18,002.00 |
| ALR9494 | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8890A | F-TIRE 23x8.5-12 R3 TF Steel Bias AA | 32 | \$ 165.00 | \$ 17,930.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L3901DT

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-LB3
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
Electronic Throttle
3 Cyl. 111.4 cu. in.
+ 36.3 Net Eng. HP
+ 32.1 PTO HP
@ 2700 Eng. rpm
12V - 580 CCA Battery
Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
6.3 gpm Remote/3 Pt. Hitch
3.8 gpm for Power Steering
10.1 Total gpm
Cat I 3-point Hitch
At lift Point 1998 lb.
24" Behind 1435 lb.

FRONT AXLE

Integral Power Steering
Bevel Gear, 4WD
Cast Iron
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Synchro Shuttle with Sliding Gear
Shift Transmission
8 Forward Speeds
8 Reverse Speeds
Multiple Wet Disc Brakes
Clutch – Dry Type Dual Stage
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 11.1 gal. |
| Cooling System | 6.3 qts. |
| Crankcase | 7.1 qts. |
| Transmission and Hydraulics | 7.5 gal. |
| Front Axle | 4.8 qts. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 116.3" |
| Wheel Base | 63.3" |
| Crop Clearance | 13.6" |

POWER TAKE OFF

Live-Continuous Running – Dual Clutch
540 Rear PTO – 1 Speed
Speed - 540 @ 2425 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and Inhibit
Buttons for DPF

TIRES AND WHEELS

Front 7.00 x 16 R1
Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|---------|--|------|--------------|
| L3901DT | 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 73.6" | 2343 | \$ 20,850.00 |
|---------|--|------|--------------|

| L3901DT | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | | | SUGG. LIST |
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D** | F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 20,850.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8893A | F-TIRE 25x8.5-14 R3 TF Steel Bias CA | 38 | \$ 207.00 | \$ 20,726.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |
| AMR8977A | F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL | 53 | \$ 251.00 | \$ 21,504.00 |
| ALR8809 | ① R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset | 201 | \$ 773.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L3901HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-LB4
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
3 Cyl. 111.4 cu. in.
+ 36.3 Net Eng. HP
+ 30.6 PTO HP
@ 2700 Eng. rpm
12V - 580 CCA Battery
Charging Output 40 Amps

HYDRAULICS

Open Center — Gear Type Tandem Pump
6.3 gpm Remote/3 Pt. Hitch
3.8 gpm for Power Steering
10.1 Total gpm
Cat I 3-point Hitch
At lift Point 1998 lb.
24" Behind 1435 lb.

FRONT AXLE

Integral Power Steering
Bevel Gear, 4WD
Cast Iron
Tread Spacing, Nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Hydrostatic Drive
3 Speed L-M-H
Multiple Wet Disc Brakes
Clutch – Dry Type Single Stage
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 11.1 gal. |
| Cooling System | 6.3 qts. |
| Crankcase | 7.1 qts. |
| Transmission and Hydraulics | 6.2 gal. |
| Front Axle | 4.8 qts. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 116.3" |
| Wheel Base | 63.3" |
| Crop Clearance | 13.6" |

POWER TAKE OFF

Live-Continuous Running - with Over-running
Clutch
540 Rear PTO – 1 Speed
Speed - 540 @ 2580 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and Inhibit
Buttons for DPF

TIRES AND WHEELS

Front 7.00 x 16 R1
Rear 11.2 x 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|-----------------|--|------|--------------|
| L3901HST | 4WD TRACTOR with 2 Post Foldable ROPS w/Retractable Seat Belt Folded Height 73.6" | 2381 | \$ 21,795.00 |
|-----------------|--|------|--------------|

| L3901HST | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | | | |
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D** | F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 21,795.00 |
| ALR9494** | R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset | 162 | \$ 435.00 | |
| ALR8893A | F-TIRE 25x8.5-14 R3 TF Steel Bias CA | 38 | \$ 207.00 | \$ 21,671.00 |
| ALR8804A | ① R-TIRE 13.6-16 R3 TF Steel Bias AA | 127 | \$ 428.00 | |
| AMR8977A | F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL | 53 | \$ 251.00 | \$ 22,449.00 |
| ALR8809 | ① R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset | 201 | \$ 773.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L4701F

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-LB1
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
4 Cyl. 148.5 cu. in.
+ 44.8 Net Eng. HP
+ 39.3 PTO HP
@ 2600 Eng. rpm
12V, 600A CCA
Charging Output 40 Amps
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pumps Gear Type
7.8 gpm Remote/3 Pt. Hitch
4.7 gpm for Power Steering
13.5 Total gpm
Cat I 3-point Hitch
At lift Point 2870 lb.
24" Behind 2320 lb.

FRONT AXLE

Hydrostatic Power Steering
Bevel Gear, Cast Iron
Tread Spacing, nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Synchro Shuttle with Sliding Gear
Shift Transmission
8 Forward Speeds
8 Reverse Speeds
Multiple Wet Disc Brakes
Clutch – Dry Type Single Stage
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 13.5 gal. |
| Cooling System | 6.9 qts. |
| Crankcase | 8.7 qts. |
| Transmission and Hydraulics | 10.6 gal. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 130.3" |
| Wheel Base | 72.8" |
| Crop Clearance | 16.3" |

POWER TAKE OFF

Live Independent Hydraulic PTO
w/ hydraulic clutch
540 rpm Rear PTO – 1 Speed
Speed - 540 @ 2475 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and
Inhibit Buttons for DPF

TIRES AND WHEELS

Front 7.5L - 15 F2
Rear 14.9 - 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|---------------|---|------|--------------|
| L4701F | 2WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt | 2760 | \$ 19,032.00 |
|---------------|---|------|--------------|

| L4701F | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | | | |
| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8852A** | F-TIRE 7.5L-15 FIRESTONE F2 CHAMPION | 64 | \$ 194.00 | \$ 19,032.00 |
| ALR6811A** | R-TIRE 14.9-24 R1 Firestone (SAT) II | 207 | \$ 637.00 | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 19,450.00 |
| ALR6803 | ① R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |

① Not compatible with L8066A Wheel Weights.

** Standard tires.

L4701DT

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-LB1
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
4 Cyl. 148.5 cu. in.
+ 44.8 Net Eng. HP
+ 39.3 PTO HP
@ 2600 Eng. rpm
12V, 600A CCA
Charging Output 40 Amps
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pumps Gear Type
7.8 gpm Remote/3 Pt. Hitch
4.7 gpm for Power Steering
13.5 Total gpm
Cat I 3-point Hitch
At lift Point 2870 lb.
24" Behind 2320 lb.

FRONT AXLE

Hydrostatic Power Steering
Bevel Gear, Cast Iron
Tread Spacing, nonadjustable

+ Manufacturer Estimate

DRIVE TRAIN

Synchro Shuttle with Sliding Gear
Shift Transmission
8 Forward Speeds
8 Reverse Speeds
Multiple Wet Disc Brakes
Clutch – Dry Type Single Stage
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 13.5 gal. |
| Cooling System | 6.9 qts. |
| Crankcase | 8.7 qts. |
| Transmission and Hydraulics | 10.6 gal. |
| Front Axle | 6.9 qts. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 127.4" |
| Wheel Base | 72.8" |
| Crop Clearance | 16.1" |

POWER TAKE OFF

Live Independent Hydraulic PTO
w/ hydraulic clutch
540 rpm Rear PTO – 1 Speed
Speed - 540 @ 2475 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable Suspension
w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and
Inhibit Buttons for DPF

TIRES AND WHEELS

Front 8.3 - 16 R1
Rear 14.9 - 24 R1

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------|--|------------------|----------------------|
| *** STANDARD MACHINE *** | | | |
| L4701DT | 4WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt | 2760 | \$ 25,008.00 |

| L4701DT | | Price with Tire Option | | |
|--|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| TIRES AND WHEELS (priced per piece) | | | | |
| ABR8753B** | F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 25,008.00 |
| ALR6811A** | R-TIRE 14.9-24 R1 Firestone (SAT) II | 207 | \$ 637.00 | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 25,322.00 |
| ALR6803 | ① R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 25,596.00 |
| ALR6803 | ① R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 25,522.00 |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | |

** Standard tires.

① Not compatible with L8066A Wheel Weights.

L4701HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-LB1
Tier 4 Final Engine
Common Rail Direct Injection
w/ Diesel Particulate Filter
Electronic Throttle
4 Cyl. 148.5 cu. in.
+ 44.8 Net Eng. HP
+ 37.8 PTO HP
@ 2600 Eng. rpm
12V, 600A CCA
Charging Output 40 Amps
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pumps Gear Type
7.8 gpm Remote/3 Pt. Hitch
4.7 gpm for Power Steering
13.5 Total gpm
Cat I 3-point Hitch
At lift Point 2870 lb.
24" Behind 2320 lb.

FRONT AXLE

Hydrostatic Power Steering
Bevel Gear, Cast Iron
Tread Spacing, nonadjustable

DRIVE TRAIN

Feather Step HST
Hydraulic Pedal Assist
Cruise Control
Multiple Wet Disc Brakes
Differential Lock
Rear Axle – Spur Gear

DASH INSTRUMENTS

Tachometer
Fuel Gauge
Temperature Gauge
LCD Display for Hour Meter
and Warning Messages

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 13.5 gal. |
| Cooling System | 6.9 qts. |
| Crankcase | 8.7 qts. |
| Transmission and Hydraulics | 10.6 gal. |
| Front Axle | 6.9 qts. |

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 91.7" |
| Overall Length w/3pt | 127.4" |
| Wheel Base | 72.8" |
| Crop Clearance | 16.1" |

POWER TAKE OFF

Live Independent Hydraulic PTO
w/ hydraulic clutch
540 rpm Rear PTO – 1 Speed
Speed - 540 @ 2640 Eng. rpm
SAE Std 1 3/8" Six Spline

SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat Belt
PTO Shield
Safety Start Switches
Turn Signals / Hazard Lights
Mechanical Wet Disc Brakes
Parking Brakes
SMV Sign
Electric Key Shut-off
Parking Brake Indicator on Dash
Operator Presence Control System

OPERATOR STATION

Color Coded Controls
Wide Platform Steps
High Back Seat with Adjustable
Suspension w/ Water Drain Hole
Tool Box
Cup Holder
Left Hand Fender Grip
Default to Auto Regen; w/ Parked and
Inhibit Buttons for DPF

TIRES AND WHEELS

Front 8.3 - 16 R1
Rear 14.9 - 24 R1

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|-----------------|---|------|--------------|
| L4701HST | 4WD Tractor 2 Post Foldable ROPS with Retractable Seat Belt | 2840 | \$ 26,609.00 |
|-----------------|---|------|--------------|

| L4701HST | | Price with Tire Option | | |
|--|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| TIRES AND WHEELS (priced per piece) | | | | |
| ABR8753B** | F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 26,609.00 |
| ALR6811A** | R-TIRE 14.9-24 R1 Firestone (SAT) II | 207 | \$ 637.00 | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 26,923.00 |
| ALR6803 | ① R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 27,197.00 |
| ALR6803 | ① R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 27,123.00 |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | |

** Standard tires.

① Not compatible with L8066A Wheel Weights.

Standard L Series Rear Remote Valve Chart

Chart (for quick reference only) Please refer to Wholegoods numbers for complete information

| TRACTOR | VALVE OPTIONS | DESCRIPTION | VALVE TYPE | STACKABLE | OPTIONAL KITS | WHEN REQUIRED | NOTES |
|------------------------|---------------|---|---|-----------|--|---|--|
| L3301 L3901 | L7211 | One rear remote kit, first position w/ Loader | Does not include a valve | Y | L7212 2 nd Position Lever Kit L7213 3 rd Position Lever Kit | When installing one remote valve with loader or without a loader | N/A |
| | L7211 & L7344 | One rear remote kit and Adapter Kit for tractor w/o Loader | Does not include a valve | Y | L7212 2 nd Position Lever Kit L7213 3 rd Position Lever Kit | When installing an L7211 without a Loader | |
| | L7231 | One rear remote valve – any position | Spring Center Valve, Not detented or self-canceling | Y | L7211 1 st Position Kit, L7212 2 nd Position Stacking Kit or L7213 3 rd Position Stacking Kit | When installing an L7211, L7213 or L7214 Kits. Each kit requires a valve. | If you want to install 3 remotes, you must order 1 st , 2 nd , and 3 rd positions |
| | L7232 | One rear remote valve – any position | Double Acting w/ Float Detent | | | | |
| | L7233 | One rear remote valve – any position | Double Acting w/ Self-Canceling Detent | | | | |
| L4701 | L7221 | One rear remote kit, first position w/ Loader or w/o Loader | Does not include a valve | Y | L7222 2 nd Position Lever Kit L7223 3 rd Position Lever Kit | When installing one remote valve | If you want to install 3 remotes, you must order 1 st , 2 nd , and 3 rd positions |
| | L7231 | One rear remote valve – any position | Spring Center Valve, Not detented or self-canceling | Y | L7221 1 st Position Kit, L7222 2 nd Position Stacking Kit or L7223 3 rd Position Stacking Kit | When installing an L7221, L7222 or L7223 Kits. Each kit requires a valve. | |
| | L7232 | One rear remote valve – any position | Double Acting w/Float Detent | | | | |
| | L7233 | One rear remote valve – any position | Double Acting w/ Self-Canceling Detent | | | | |

| TRACTOR | VALVE OPTIONS | DESCRIPTION | VALVE TYPE | STACKABLE | OPTIONAL KITS | WHEN REQUIRED | NOTES |
|----------------------------------|--------------------|--|---|-----------|---|--|--|
| L2501 L3200 L3800 | L7334 [Ⓞ] | One rear remote valve, first position w/ Loader | Double-Acting | Y | L7364 2 nd Position Lever Kit L7384 3 rd Position Lever Kit 77700-03896 and 77700-03851 if BH77 is used | When installing an L7334 with a front loader | Must Order L7334 as first rear remote |
| | L7334 L7344 | One rear remote valve and Adapter Kit for tractor w/o Loader | Double-Acting | Y | L7364 2 nd Position Lever Kit L7384 3 rd Position Lever Kit 77700-03896 and 77700-03851 if BH77 is used | When installing an L7334 without a Loader | |
| | L7374 | One rear remote valve, second or third position | Double Acting w/ Detent, Not Self-Canceling | Y | L7364 2 nd Position Stacking Kit or L7384 3 rd Position Stacking Kit | When installing an L7364 or L7384 Stacking Kit. Each kit requires a valve. | If you want to install 3 remotes, you must order 1 st , 2 nd , and 3 rd positions |
| | L7354 | | Double Acting w/Float Detent | | | | |
| L4600 | L8303 | One remote valve, first second or third position | Double Acting | Y | L8560 Base Kit and 1 st lever | Required to install L8303 as 1 st Valve | Only 2 remote valves can be installed with BH92 Backhoe |
| | | | | | L8562 2 nd Lever | Required to install L8303 as 2 nd Valve | |
| | L8304 [Ⓞ] | One remote valve, second position | Double Acting w/Float Detent | Y | L8563A 3 rd Lever | Required to install L8303 as 3 rd Valve | |
| | | | | | L8562A 2 nd Lever | Required to install L8304 as 2 nd Valve | |

Ⓞ The L8304 can only be used in the second position.

Chart (for quick reference only) Please refer to Wholegoods numbers for complete information.

Prices and specifications subject to change without notice. F.O.B. KTC designated shipping point.
Complete revision November 14, 2014.

Standard L Series Rear Remote Valves

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|------------------|----------------------|
| L3301 / L3901 Rear Hydraulics | | | |
| L7211 | ① Lever Kit - First Position - Does not include valve Requires L7231 Spring Center Valve or L7232 Float Valve or L7233 Self -Canceling Detent Valve to complete. (All Models with or without Loader) (Without loader also requires L7344 adapter kit) | 23 | \$549.00 |
| Adapter Kit - Non-Loader | | | |
| L7344 | Adapter Kit - Required when installing First Position Kit (All Models without Loader) Requires L7211 Lever Kit | 5 | \$145.00 |
| Additional valve stacking kits, dealer installed (select a valve Stacking Kit and the Additional Valve Kit Section(s)) | | | |
| L7212 | 2nd Position Stacking Kit Includes: Hoses, O-rings, couplers and 2nd lever to install one additional valve section for L7211 Requires L7231 Spring Center Valve or L7232 Float Valve or L7233 Self -Canceling Detent Valve to complete. | 10 | \$371.00 |
| L7213 | 3rd Position Stacking Kit Includes: Hoses, hardware, O-rings, couplers and 3rd lever to install one additional valve section for L7211 Requires L7231 Spring Center Valve or L7232 Float Valve or L7233 Self -Canceling Detent Valve to complete. (for 3 remotes you need 2nd & 3rd position kits) | 10 | \$371.00 |
| Additional Valve Kit Sections | | | |
| L7231 | Spring Center Valve - (Not Detented) | 5 | \$175.00 |
| L7232 | 4-Position, FD- Float Detent Section | 5 | \$310.00 |
| L7233 | Self-Canceling Detent Valve Section | 5 | \$350.00 |
| L4701 Rear Hydraulics | | | |
| L7221 | Lever Kit - First Position - Does not include valve Requires L7231 Spring Center Valve or L7232 Float Valve or L7233 Self -Canceling Detent Valve to complete. | 23 | \$575.00 |
| L7222 | 2nd Position Stacking Kit Includes: Hoses, O-rings, couplers and 2nd lever to install one additional valve section for L7221 Requires L7231 Spring Center Valve or L7232 Float Valve or L7233 Self -Canceling Detent Valve to complete. | 10 | \$315.00 |
| L7223 | 3rd Position Stacking Kit Includes: Hoses, hardware, O-rings, couplers and 3rd lever to install one additional valve section for L7221 Requires L7231 Spring Center Valve or L7232 Float Valve or L7233 Self -Canceling Detent Valve to complete. (for 3 remotes you need 2nd & 3rd position kits) | 10 | \$315.00 |
| Additional Valve Kit Sections | | | |
| L7231 | Spring Center Valve - (Not Detented) | 5 | \$175.00 |
| L7232 | 4-Position, FD- Float Detent Section | 5 | \$310.00 |
| L7233 | Self-Canceling Detent Valve Section | 5 | \$350.00 |

Standard L Series Rear Remote Valves

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|---|------------------|----------------------|
| L2501 / L3200 / L3800 Rear Hydraulics | | | |
| REAR REMOTE HYDRAULIC VALVES | | | |
| L7334 | ① Hydraulic Valve and Lever Kit - First Position (All Models with or without Loader) (Without loader also requires L7344 adapter kit) | 18 | \$710.00 |
| ADAPTER KIT | | | |
| L7344 | Adapter Kit - Required when installing First Position Valve (All Models without Loader) Requires L7334 Hydraulic Valve Kit | 18 | \$145.00 |
| Additional valve stacking kits, dealer installed (select a valve Stacking Kit and the Additional Valve Kit Section(s)) | | | |
| L7364 | 2nd Position Stacking Kit Includes hardware, O-rings, and 2nd Lever to install one additional valve section for L7334. Requires L7354 Valve or L7374 Valve Section to complete. | 31 | \$83.00 |
| L7384 | 3rd Position Stacking Kit Includes hardware, O-rings, and 3rd Lever to install one additional valve sections to L7334. Requires L7354 or L7374 Valve Section. to complete. (for 3 remotes you need 2nd & 3rd position kits) | 37 | \$77.00 |
| Additional Valve Kit Sections | | | |
| L7374 | 3-Position, DV-Detent Valve (Not Self-canceling) Closed Detent Valve Section | 5 | \$485.00 |
| L7354 | 4-Position, FD- Float Detent Section | 5 | \$527.00 |

① Compatible with BH77 if the following parts are ordered and installed 77700-03896 Hose Section and 77700-03851 90 Degree Fitting.

Standard L Series Rear Remote Valves

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------------------|---|------------------|----------------------|
| L4400 / L4600 Rear Hydraulics | | | |
| L4400 MODELS | | | |
| L8407 | ① Single Spool Remote Hyd. Valve | 18 | \$868.00 |
| L8408 | ① Double Spool Remote Hyd. Valve Requires L8310. | 25 | \$1,252.00 |
| L8409 | ① Triple Spool Remote Hyd. Valve Requires L8310. NOTE: Remote Hydraulic Spool Valves are not stackable, i.e.: For Double Spool, only order L8408. | 37 | \$1,709.00 |
| L8310 | Hose Stay Kit | 3 | \$37.00 |
| L4400-1 | | | |
| L8561 | Base Kit & 1st Lever for L4400 Requires L8303 Valve to complete assembly. | 15 | \$512.00 |
| L8562 | Second Position Stacking Kit and 2nd Lever for L4400. Requires L8303 or L8304 Valve to complete assembly. | 7 | \$248.00 |
| L8563 | Third Position Stacking Kit and 3rd Lever for L4400. Requires L8303 Valve to complete assembly. Not compatible with BH4979 BH90A Mounting Kit | 8 | \$248.00 |
| L4600 | | | |
| L8560 | Base Kit & 1st Lever for L4600 Requires L8303 Valve to complete assembly. | 16 | \$512.00 |
| L8562A | Second Position Stacking Kit and 2nd Lever for L4600. Requires L8303 or L8304 Valve to complete assembly. | 7 | \$248.00 |
| L8563A | Third Position Stacking Kit and 3rd Lever for L4600. Requires L8303 Valve to complete assembly. Not compatible with BH4979 BH90A Mounting Kit | 8 | \$248.00 |
| Remote Valves L4400/L4600 | | | |
| L8303 | Double Acting Valve Section | | \$240.00 |
| L8304 | ② Double Acting w/Float Detent Valve Section (This valve can only be used in 2nd position) | 5 | \$302.00 |

① Backhoe applications require relocating remote couplers due to backhoe seat interference. Order from Parts Dept: L8407 requires (1) 70090-20953, L8408 requires (1) 70090-20940, L8409 requires (1) 70090-20940 and (1) 70090-20953. These kits provide new couplers connected directly to the remote valves. If male couplers are required for cylinder hoses, order appropriate quantities of 70090-20823 male couplers.

② The L8304 can only be used in the second position.

Standard L Series Rear Remote Valves

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|---|------------------|----------------------|
| PRIOR MODEL REAR REMOTE HYDRAULIC VALVES | | | |
| BL7303A* | ① Hydraulic Valve Kit (requires Hose Kit L7314/L7315) L2800, L3400, L3700SU, L3200, L3800 | 21 | \$501.00 |
| L7314* | L- Standard Series Hose Kit (required for BL7303 Hydraulic Valve Kit) L2800, L3400 (All Models with Loader), L3700SU, L3200, L3800 | 7 | \$235.00 |
| L7315* | L- Standard Series Hose Kit (required for BL7303 Hydraulic Valve Kit) L2800, L3400 (All Models without Loader), L3700SU, L3200, L3800 | 9 | \$272.00 |
| Additional valve stacking kits, dealer installed (select a valve stacking kit and the additional valve kit section(s)) | | | |
| BL7343* | 2nd Position Stacking Kit to install 2nd valve section. Hardware and o-rings to install one (1) Additional valve section for BL7303 Requires BL7373 or BL7393 Valve Section. | 2 | \$50.00 |
| BL7353* | 3rd Position Stacking Kit to install 3rd valve section. Hardware and o-rings to install two (2) additional valve sections to BL7303 or B7333 Requires BL7373 or BL7393 Valve Section(s). | 2 | \$50.00 |
| Additional valve kit sections | | | |
| BL7373* | 3-Position, DV-Detent Valve (Not Self-canceling) Closed Detent Valve Section The Valve Section features a single spool that should be used for double acting cylinders, both work ports are blocked in the neutral position with free flow oil through the valve in neutral. Important: The Detent position is not self-canceling and will not release when cylinder reaches end of stroke. Leaving this valve in detent position on a blocked circuit will cause system relief valve to remain open. | 5 | \$273.00 |
| BL7393* | 4-Position, FD- Float Detent Section Both work ports are blocked in the neutral position. The Detent "float" position allows the hydraulic cylinder to float. Both work ports are blocked in the neutral position with free flow oil through the valve in neutral. | 6 | \$319.00 |

* Subject to availability.

KUBOTA

Standard L Series Dealer Installed Options Chart

Chart (for quick reference only) Please refer to Wholegoods numbers for complete information

| Model | ROPS | Sunshade for ROPS | Front Suitcase Weights ② | Rear Wheel Weights ① | Double Element Air Cleaner | Spark Arrester | Ballast Box |
|-------------------------|----------------|-------------------|---------------------------|----------------------|----------------------------|----------------|-------------|
| L2501 L3301 L3901 | SFL-390 | E1133 E1134 | BL8060-1③ (Max. 5 pcs) | L8066A | TBA | N/A | L8170 |
| L4701 | SFL-F470 | E1133 E1134 | BL8060-1③ (Max. 5 pcs) | L8066A | Std. | N/A | L8170 |
| L3200 L3800 | Std (SFL-F380) | E1133 E1134 | BL8060-1③ (Max. 5 pcs) | L8066A | TA040-93220 | 70000-01600 | L8170 |
| L4600 | SFL-F460 | E1133 E1134 | BL8060-1③ (Max. 7 pcs) | L8066A | Std | 70000-00280 | L8170 |

① Only on 24" Rim.
 ② 4WD Models (DT and HST) require front weight bumper bracket (Standard on 2WD models). Not compatible with Front Grille Guard
 ③ Use MX8068 Front Weight Bracket.

| Model | Drawbar Clevis | Grille Guard | Block Heater | 3PT Stabilizer Kit | Extra Length Seat Belt | Draft Control |
|-------------------------|------------------|--------------|-----------------|--------------------|------------------------|---------------|
| | Swinging Drawbar | | Rear Work Light | | | Top-N-Tilt |
| L2501 L3301 L3901 | L9496G | L2258 | 70000-00297 | L8430 | 70002-06605 | N/A |
| | 35080-98501 | | L8327 | | | |
| L4701 | L9496G | MX2268 | 70000-00297 | STD | 70002-06605 | L8311C |
| | L8416 | | L8327 | | | TBA |
| L3200 L3800 | L9496G | MX8190 ④ | 70000-00297 | L8430 | 70002-06605 | N/A |
| | N/A | | L8327 | | | |
| L4600 | L9496G | L2267⑤ | 70000-00297 | STD | 70002-06605 | L8311CW |
| | N/A | | L8327 | | | L8388 |

④ For non-loader applications only, includes bracket to hold up to (4) BL8060-1 Front Suitcase Weights.

⑤ The L2267 is included with LA764.

Rear Remote Chart (for quick reference only) Please refer to Wholegoods numbers for complete information

Standard L Series Dealer Installed Options

L2501 / L3200 / L3301 / L3800 / L3901 / L2800 / L3400 / L3700SU / L4400 / L4600 / 4701 Attachments
(Listed in Alphabetical Order)

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|-----------------------------------|---|------------------|-------------------------------|
| BALLAST BOX | | | |
| L8170 | Ballast Box (1000 lbs. cap. with dry sand) (L2501 / L2800 / L3200 / L3301 / L3400 / L3700SU / L3800 / L3901 / L4400 / L4600 / L4701) | 168 | \$449.00 |
| BLOCK HEATER | | | |
| 70000-00297 | Block Heater | | (Order from Parts Department) |
| CRUISE CONTROL | | | |
| L9485 | Cruise Control Kit (L3700SU) | 25 | \$205.00 |
| L8455 | Cruise Control Kit (L3200HST and L3800HST) (L2501, L3301HST and L3901HST) | 25 | \$205.00 |
| DRAFT CONTROL | | | |
| L8311A | Draft Control Kit L4400/L4400-1 models | 25 | \$462.00 |
| L8311C | Draft Control Kit - L4600/L4701 Models | 25 | \$462.00 |
| DRAWBAR OPTIONS | | | |
| L9491 | Drawbar Assembly (L3700SU) | 25 | \$128.00 |
| L8479 | Drawbar Assembly (L4400F-1 only) | 25 | \$140.00 |
| L8416 | Swinging Drawbar (L4400) (L4701) | 21 | \$198.00 |
| 35080-98501 | Swinging Drawbar (L2501, L3301, L3901) | | (Order from Parts Department) |
| L9496G | Drawbar Clevis (All Models) | 8 | \$67.00 |
| DUAL ELEMENT AIR CLEANER ④ | | | |
| TA040-93220 | Inner Element (L2800/L3400/L3700SU/L3200/L3800) Only inner element is needed to create Dual Element Air Cleaner | | (Order from Parts Department) |
| FRONT SUITCASE WEIGHTS | | | |
| BL8060-1 | ①⑤ Front Suitcase Weight Requires (1) BL8060B Bolt Kit per Weight L3200 / L2501 / L3301 / L3800 / L3901 should only have 5 BL8060-1 weights installed. L4600 / L4701 can use up to 7. | 55 | \$71.00 |
| BL8060B | Bolt Kit (1 per Weight) Use with (5) weight bracket 32310-13810 and L2251 Grille Guard. Use with MX8068 (7) weight bracket. | 1 | \$2.00 |

① Four wheel drive models (DT and HST) require front weight bumper bracket.

④ Standard items for the L4400, L4400-1, L4600, L4701

⑤ Front weight bracket with weights is not compatible when tractor is equipped with a loader, weights must be removed.

Standard L Series Dealer Installed Options

L2501 / L3200 / L3301 / L3800 / L3901 / L2800 / L3400 / L3700SU / L4400 / L4600 / 4701 Attachments
(Listed in Alphabetical Order)

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|-------------------------------|----------------------|
| FRONT WEIGHT BRACKET KIT | | | |
| MX8068 | ③⑤ For L2501, L3200, L3301, L3800, L3901, L3400, L3700SU L3901 4WD Models - 1-5 Weights, (Std. on 2WD models) For L4400/L4600/L4701 4WD Models 1-7 Weights, (Std. on L4400/L4600/L4701 2WD models) Includes mounting hardware. | 25 | \$96.00 |
| GRILLE GUARD (Non-Loader Applications) | | | |
| L2258 | Front Grille Guard (L2501/L3301/L3901) (Non-loader applications) | 35 | \$326.00 |
| MX2268 | Front Grille Guard (L4701) (Non-loader applications) | 50 | \$275.00 |
| L2251 | ② Front Grille Guard (L2800/L3400/L3700SU) (Non-loader applications) | 36 | \$275.00 |
| L2267 | Front Grille Guard (L4400/L4600) (Non-loader applications) | 61 | \$326.00 |
| MX8190 | Front Grille Guard (L3200/L3800) (Non-loader and Loader applications) | 50 | \$275.00 |
| REAR WHEEL WEIGHTS | | | |
| L8066A | ⑥ Rear Wheel Weight 64 lbs. each Set of 2 Weights, requires L8067A Bolt Kit Maximum of 3 Sets. (Not compatible with Turf Tires or certain R4 Ind. Tires.) | 128 | \$124.00 |
| L8067A | Bolt Kit for L8066 Weight 1 Kit will hold up to (3) sets of weights | 5 | \$33.00 |
| REAR WORK LIGHT | | | |
| M9551 | Rear Work Light (one light) (L2800 / L3400 / L3700SU / L4400) | 4 | \$85.00 |
| L8327 | Rear Work Light Kit (L3200/L3800/L4600) (one light) (L2501 / L3301 / L3901 / L4701) | 4 | \$85.00 |
| REPLACEMENT ROPS | | | |
| SFL-F380 | Replacement ROPS L3200 / L3800 | 150 | \$580.00 |
| SFL-F460 | Replacement ROPS L4600 | 207 | \$785.00 |
| SFL-F390 | Replacement ROPS L3301 / L3901 | 207 | TBA |
| SFL-F470 | Replacement ROPS L4701 | 207 | TBA |
| SEAT BELT KIT | | | |
| 70002-06605 | Extra Length Seat Belt Kit | (Order from Parts Department) | |

- ② Grille Guard includes bracket to hold up to (4) BL8060-1 Front Suitcase Weights.
- ③ MX8068 Front Weight Bracket is not compatible with L2251/L2233A/MX8190/L2267/L2258/ MX2268 Grille Guard.
- ④ Standard items for the L4400, L4400-1, L4600, L4701
- ⑤ Front weight bracket with weights is not compatible when tractor is equipped with a loader, weights must be removed.
- ⑥ Not compatible w/ Turf tires or certain R4 tires. Refer to the tractor wholegood section for tractor/tire/wheel weight compatibility

Standard L Series Dealer Installed Options

L2501 / L3200 / L3301 / L3800 / L3901 / L2800 / L3400 / L3700SU / L4400 / L4600 / 4701 Attachments
(Listed in Alphabetical Order)

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---------------------------------------|--|------------------|-------------------------------|
| SPARK ARRESTOR | | | |
| 70000-01600 | Screen Type for L2800/L3400/L3700SU/L3200/L3800 | | (Order from Parts Department) |
| 77700-00280 | ④ Screen Type for L4400-1, L4600 | | (Order from Parts Department) |
| L8368 | Low Back Pressure Muffler (L4400-1) | 25 | \$228.00 |
| SUNSHADE FOR ROPS (All Models) | | | |
| E1133 | Standard Sunshade | 63 | \$437.00 |
| E1134 | Deluxe Sunshade | 63 | \$387.00 |
| | Requires E1136 Mounting Bracket Kit | | |
| E1136 | Mounting Bracket Kit for E1134 | 30 | \$191.00 |
| E1138 | Front Work Light Kit for E1134 (includes 2 lights) | 10 | \$125.00 |
| 3PT STABILIZERS | | | |
| L8430 | ③ 3 Pt. Hitch Stabilizer Kit (L2501 / L2800 / L3200 / L3301 / L3400 / L3700SU / L3800 / L3901) | 15 | \$175.00 |
| TOP-N-TILT-KIT | | | |
| L8326A | ①②⑤ Top-N-Tilt Kit (L4400-1) | 44 | \$871.00 |
| L8388 | ①⑥⑦ Top-N-Tilt Kit (L4400-1 / L4600 / L4701) | 44 | \$871.00 |
| WHEEL SPACER KIT | | | |
| L8787 | ⑧ Wheel Spacer Kit for L2800DT / L3400DT L2501, L3200, L3301, L3800, L3901 (All Models) Increases total width between rear tires by 1" each side | 20 | \$233.00 |

① L8326 Top-N-Tilt Kit: All L Series tractors will require the L8303 or L8304, L8561, and L8562 L8303 Double Acting Valve Section or L8304 Float Detent Valve Section L8561 Base Kit and First Lever: Requires L8303 or L8304 to complete assembly. L8562 Section Position Stacking Kit: Requires additional L8303 or L8304. L8563 Third Position Stacking Kit: Requires additional L8303 or L8304.

② Requires either L8408 or L8409 Remote Valves. (L8409 is required if Box Scraper has hydraulic scarifier.)

③ Standard items for the L4400, L4400-1, L4600, L4701

④ L8368 Low Back Pressure Muffler required for L4400-1.

⑤ Not compatible with BH90/BH92 and BL4690B.

⑥ The L8388 will require 2 approved double acting remote hydraulic valves, Hydraulic box scraper will require 3 approved double acting hydraulic valves and hose kit.

⑦ The L8388 is not compatible with backhoes.

⑧ The L8787 Wheel Spacer Kit should be installed with 12 studs (01517-61660), 8 nuts (02076-50160), and 8 lock washers (04512-60160). Order through the Parts Department.

* Subject to availability.

Grand L - 60 Series

| MODEL NAME | PTO H.P. | 2 OR 4 WD | Trans. Type | Synchro Shuttle | Full ② Synchro | Trans. Speeds | PTO Type | Opt. Mid PTO ③ | Hyd. Power Steering | Creep Speed | Loader Valve | Turbo |
|-----------------|----------|-----------|-------------|-----------------|----------------|---------------|----------------|----------------|---------------------|-------------|--------------|-------|
| L3560 35.0 ① | 29.5 | 4WD | FST④ | S | S | 8F X 8R | Live Ind. Hyd. | C + I | S | Opt. | S | N |
| | 29.5 | 4WD | GST | S | S | 12F X 8R | Live Ind. Hyd. | C + I | S | Opt. | S | N |
| | 28.0 | 4WD | HST | N/A | N/A | Infinite | Live Ind. Hyd. | C + I | S | N/A | S | N |
| | 28.0 | 4WD | HSTC | N/A | N/A | Infinite | Live Ind. Hyd. | C | S | N/A | S | N |
| L4060 40.0 ① | 34.0 | 4WD | FST④ | S | S | 8F X 8R | Live Ind. Hyd. | C + I | S | Opt. | S | N |
| | 34.0 | 4WD | GST | S | S | 12F X 8R | Live Ind. Hyd. | C + I | S | Opt. | S | N |
| | 32.5 | 4WD | HST | N/A | N/A | Infinite | Live Ind. Hyd. | C + I | S | N/A | S | N |
| | 32.5 | 4WD | HSTC | N/A | N/A | Infinite | Live Ind. Hyd. | C | S | N/A | S | N |
| L4760 47.0 ① | 41.0 | 4WD | GST | S | S | 12F X 8R | Live Ind. Hyd. | C + I | S | Opt. | S | N |
| | 39.5 | 4WD | HST | N/A | N/A | Infinite | Live Ind. Hyd. | C + I | S | N/A | S | N |
| | 39.5 | 4WD | HSTC | N/A | N/A | Infinite | Live Ind. Hyd. | C | S | N/A | S | N |
| L5060 50.0 ① | 44.0 | 4WD | GST | S | S | 12F X 8R | Live Ind. Hyd. | C + I | S | Opt. | S | Y |
| L5460 54.0 ① | 46.5 | 4WD | HST | N/A | N/A | Infinite | Live Ind. Hyd. | C + I | S | N/A | S | Y |
| | 46.5 | 4WD | HSTC | N/A | N/A | Infinite | Live Ind. Hyd. | C | S | N/A | S | Y |
| L6060 60.0 ① | 53.0 | 4WD | HST | N/A | N/A | Infinite | Live Ind. Hyd. | C + I | S | N/A | S | Y |
| | 53.0 | 4WD | HSTC | N/A | N/A | Infinite | Live Ind. Hyd. | C | S | N/A | S | Y |

S = Standard Equipment

OPT = Field Installed Option

① Net Engine Horsepower

② Main Transmission (4 Speed)

③ C = Cassette style installation, C + I = Cassette plus requires internal gear installation.

④ Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.

L3560DT

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-GL1
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
3 Cyl., 111.4 cu. in.
+ 35.0 Net Eng. HP
+ 29.5 PTO HP
@ 2700 Eng. rpm
12V 60Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.9 gpm Power Steering
8.3 gpm Remote/3 Pt. Hitch
13.2 gpm Total Hyd. Flow
Category I – 3 Point
Lift Capacity —
At lift Point 3968 lbs.
24" Behind 2646 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

4 Speed Manual w/Synchro Main
And Synchro Shuttle
2 Range Hi-Lo
8 Forward Speeds / 8 Reverse Speeds
Mech. Wet Disc Brakes
Clutch — Dry Single Stage
Differential Lock

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 7.1 qts.
Transmission and
Hydraulics 11.1 gal.
Front Axle Differential 6.9 qts.

DIMENSIONS

Overall Height w/ ROPS 97.2"
Overall Length w/ 3PT 124.4"
Wheel Base 71.1"
Crop Clearance 15.0"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols

TIRES AND WHEELS

Front 7.0 – 16 R1 AG
Rear 12.4 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------|---|------------------|----------------------|
| *** STANDARD MACHINE *** | | | |
| L3560DT | L3560DT 4WD TRACTOR with 2 Post Foldable ROPS (97.2" High) | | \$ 22,990.00 |

| L3560DT | | TIRES AND WHEELS (priced per piece) L3560DT | | | | Price with Tire Option | |
|------------|--|---|------------------|--------------|--|------------------------|--|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST | | | |
| ALR8866D | ** F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 22,990.00 | | | |
| ALR8821B | ** R-TIRE 12.4-24 R1 Firestone (SAT) II | 154 | \$ 533.00 | | | | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 23,102.00 | | | |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | | | | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | \$ 23,690.00 | | | |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | | | | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | \$ 24,020.00 | | | |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | | | | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 23,658.00 | | | |
| ALR8855 | R-TIRE 420/70-24 R4 F-Stone All Trc Util | 235 | \$ 777.00 | | | | |

** Standard Tires

L3560GST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-GL1
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
3 Cyl., 111.4 cu. in.
+ 35.0 Net Eng. HP
+ 29.5 PTO HP
@ 2700 Eng. rpm
12V 60Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.9 gpm Power Steering
8.3 gpm Remote/3 Pt. Hitch
13.2 gpm Total Hyd. Flow
Category I – 3 Point
Lift Capacity —
At lift Point 3968 lbs.
24" Behind 2646 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

Glide Shift Transmission
w/Syncro Shuttle
12 Forward Speeds / 8 Reverse
Speeds
Mech. Wet Disc Brakes
Clutch — Dry Single Stage
Differential Lock

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 7.1 qts.
Transmission and
Hydraulics 11.1 gal.
Front Axle Differential 6.9 qts.

DIMENSIONS

Overall Height w/ ROPS 97.2"
Overall Length w/ 3PT 124.4"
Wheel Base 71.1"
Crop Clearance 15.0"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols

TIRES AND WHEELS

Front 7.0 – 16 R1 AG
Rear 12.4 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------|--|------------------|----------------------|
| *** STANDARD MACHINE *** | | | |
| L3560GST | L3560GST 4WD TRACTOR with 2 Post Foldable ROPS (97.2" High) | | \$ 24,100.00 |

| L3560GST | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D | ** F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 24,100.00 |
| ALR8821B | ** R-TIRE 12.4-24 R1 Firestone (SAT) II | 154 | \$ 533.00 | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 24,212.00 |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | \$ 24,800.00 |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | \$ 25,130.00 |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 24,768.00 |
| ALR8855 | R-TIRE 420/70-24 R4 F-Stone All Trc Util | 235 | \$ 777.00 | |

** Standard Tires

L3560HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-GL2/GL3
 Tier 4 Final Engine
 Common Rail Direct Injection
 w/ DPF and EGR
 3 Cyl., 111.4 cu. in.
 + 35.0 Net Eng. HP
 + 28.0 PTO HP
 @ 2600 Eng. rpm
 12V 40Amp - 582CCA
 Radial Air Flow Cooling
 Dual Air Cleaner Element

HYDRAULICS

Open Center
 Tandem Pump Gear Type
 4.7 gpm Power Steering
 8.1 gpm Remote/3 Pt. Hitch
 12.8 gpm Total Hyd. Flow
 Category I 3Pt. Hitch
 Lift Capacity —
 At lift Point 3748lbs.
 24" Behind 2646lbs.

FRONT AXLE

Hydrostatic Power Steering
 Cast iron 4WD front axle
 Tread Spacing – Non-adjustable
 Bevel Gear drive

DRIVE TRAIN

HST PLUS
 3 Forward Speeds / 3 Reverse
 Speeds
 Hi-Med-Low Range
 Mech. Wet Disc Brakes
 Differential Lock

FLUID CAPACITY

Fuel Tank 13.5 gal.
 Cooling System 7.9 qts.
 Crankcase 7.1 qts.
 Transmission and
 Hydraulics 11.1 gal.
 Front Axle Differential 6.9 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
 540 rpm @ 2550 Eng. rpm
 SAE 1-3/8 6 Splines
 Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ ROPS 97.2"
 Overall Length w/ 3PT 124.4"
 Wheel Base 71.1"
 Crop Clearance 15.0"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
 Safety Start Switch
 Highback Adj. Swivel Seat w/ Deluxe
 Suspension w/Arm Rests
 Operator Presence Control System
 Parking Brakes
 Flat Deck w/ Hanging Pedals
 Electric Key Shut-off
 Tilt Steering
 Wide Anti-Slip Step
 ISO Mounted Platform
 Turn Signals / Hazard Flashers
 SMV Sign
 Telescoping Lower Links
 2 Tier Halogen Head Lights
 4 Position Loader Valve
 One Piece Metal Hood
 Cup Holder
 Cruise Control
 Auto Throttle Advance
 Hydro Dual Speed (H-DS)
 HST Response Control
 Throttle-UP Switch

IntelliPanel™

Lighted Communications Symbols
 Standard Tachometer
 Digital Read for Speed, MPH, PTO
 speeds, diagnostics system and DPF
 system
 Warning Symbols
 HST Mode Selection

TIRES AND WHEELS

Front 7.0 – 16 R1 AG
 Rear 12.4 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------|--|--|--------------|
| L3560HST | L3560HST 4WD TRACTOR with 2 Post Foldable ROPS (97.2" High) | | \$ 24,580.00 |
|----------|--|--|--------------|

| L3560HST | | TIRES AND WHEELS (priced per piece) | | | Price with Tire Option | |
|------------|--|-------------------------------------|------------------|--|------------------------|--|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | | SUGG. LIST | |
| ALR8866D | ** F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | | \$ 24,580.00 | |
| ALR8821B | ** R-TIRE 12.4-24 R1 Firestone (SAT) II | 154 | \$ 533.00 | | | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | | \$ 24,692.00 | |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | | | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | | \$ 25,280.00 | |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | | | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | | \$ 25,610.00 | |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | | | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | | \$ 25,248.00 | |
| ALR8855 | R-TIRE 420/70-24 R4 F-Stone All Trc Util | 235 | \$ 777.00 | | | |

** Standard tires.

L3560HSTC

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # D1803-CR-E4-GL2/GL3
 Tier 4 Final Engine
 Common Rail Direct Injection
 w/ DPF and EGR
 3 Cyl., 111.4 cu. in.
 + 35.0 Net Eng. HP
 + 28.0 PTO HP
 @ 2600 Eng. rpm
 12V 60Amp - 582CCA
 Radial Air Flow Cooling
 Dual Air Cleaner Element

HYDRAULICS

Open Center
 Tandem Pump Gear Type
 4.7 gpm Power Steering
 8.1 gpm Remote/3 Pt. Hitch
 12.8 gpm Total Hyd. Flow
 Category I 3Pt. Hitch
 Lift Capacity —
 At lift Point 3748lbs.
 24" Behind 2646lbs.

FRONT AXLE

Hydrostatic Power Steering
 Cast iron 4WD front axle
 Tread Spacing – Non-adjustable
 Bevel Gear drive

DRIVE TRAIN

HST PLUS
 3 Forward Speeds / 3 Reverse
 Speeds
 Hi-Med-Low Range
 Mech. Wet Disc Brakes
 Differential Lock

FLUID CAPACITY

Fuel Tank 13.5 gal.
 Cooling System 7.9 qts.
 Crankcase 7.1 qts.
 Transmission and
 Hydraulics 11.1 gal.
 Front Axle Differential 6.9 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
 540 rpm @ 2550 Eng. rpm
 SAE 1-3/8 6 Splines
 Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ Cab 90.6"
 Overall Length w/ 3PT 124.4"
 Wheel Base 71.1"
 Crop Clearance 15.0"

IntelliPanel™

Lighted Communications Symbols
 Standard Tachometer
 Digital Read for Speed, MPH, PTO
 speeds, diagnostics system and DPF
 system
 Warning Symbols
 HST Mode Selection

STANDARD EQUIPMENT

ROPS Certified Cab w/Retractable
 Seat Belt
 Highback Adj. Swivel Seat w/ Deluxe
 Suspension w/Arm Rests
 Safety Start Switches
 Operator Presence Control System
 Parking Brakes
 Flat Deck w/Hanging Pedals
 Electric Key Shut-off
 2 Front Work Lights
 Tilt Steering
 Wide Anti-Slip Step
 ISO Mounted Platform
 Turn Signals / Hazard Flashers
 SMV Sign
 Telescoping Lower Links
 2 Tier Halogen Head Lights
 4 Position Loader Valve
 One Piece Metal Hood
 Auto Throttle Advance
 Hydro Dual Speed (H-DS)
 HST Response Control
 Throttle-UP Switch
 12V Outlet and Cup Holder
 Front Wiper w/ Washer
 60 Amp Alternator
 Interior Light
 AC/Heater with Internal/External
 Ventilation
 Speakers and Radio Wired
 Horn
 Cruise Control

TIRES AND WHEELS

Front 7.2 – 16 R1 AG
 Rear 12.4 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|-----------|---|--|--------------|
| L3560HSTC | L3560HSTC 4WD CAB TRACTOR with ROPS Certified Factory Cab (90.6" Height) | | \$ 32,646.00 |
|-----------|---|--|--------------|

| L3560HSTC | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ALR8866D | ** F-TIRE 7.2-16 POWER TORQUE 8PR R1 | 56 | \$ 262.00 | \$ 32,646.00 |
| ALR8821B | ** R-TIRE 12.4-24 R1 Firestone (SAT) II | 154 | \$ 533.00 | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 32,758.00 |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | \$ 33,346.00 |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | \$ 33,676.00 |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 33,314.00 |
| ALR8855 | R-TIRE 420/70-24 R4 F-Stone All Trc Util | 235 | \$ 777.00 | |

** Standard tires.

L4060DT

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-GL1
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
+ 40.0 Net Eng. HP
+ 34.0 PTO HP
@ 2700 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.9 gpm Power Steering
9.8 gpm Remote/3 Pt. Hitch
14.7 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

4 Speed Manual w/Synchro Main
And Synchro Shuttle
2 Range Hi-Lo
8 Forward Speeds / 8 Reverse Speeds
Mech. Wet Disc Brakes
Clutch — Dry Single Stage
Differential Lock

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 8.7 qts
Transmission and
Hydraulics 11.4 gal.
Front Axle Differential 6.9 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ROPS 97.6"
Overall Length w/3pt. 129.5"
Wheel Base 74.6"
Crop Clearance 15.9"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols

TIRES AND WHEELS

Front 8.3 – 16 R1 AG
Rear 14.9 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|---------|---|------|--------------|
| L4060DT | L4060DT 4WD TRACTOR with 2 Post Foldable ROPS (97.6" High) | 2913 | \$ 26,009.00 |
|---------|---|------|--------------|

| L4060DT | | Price with Tire Option | | | |
|-------------------------------------|--|------------------------|------------------|--------------|--|
| TIRES AND WHEELS (priced per piece) | | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST | |
| ABR8753B | ** F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 26,009.00 | |
| ALR6809B | ** R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR | 233 | \$ 637.00 | | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | \$ 26,533.00 | |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | \$ 26,863.00 | |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 25,945.00 | |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 26,523.00 | |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | | |

** Standard tires.

Prices and specifications subject to change without notice. F.O.B. KTC designated shipping point.
Complete revision November 14, 2014.

L4060GST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-GL1
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
+ 40.0 Net Eng. HP
+ 34.0 PTO HP
@ 2700 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.9 gpm Power Steering
9.8 gpm Remote/3 Pt. Hitch
14.7 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

Glide Shift w/ Synchro Shuttle
12 Forward Speeds / 8 Reverse
Speeds
Mech. Wet Disc Brakes
Clutch - Single Dry Plate
Differential Lock

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 13.5 gal. |
| Cooling System | 7.9 qts. |
| Crankcase | 8.7 qts |
| Transmission and Hydraulics | 11.4 gal. |
| Front Axle Differential | 6.9 qts. |

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 97.6" |
| Overall Length w/3pt. | 129.5" |
| Wheel Base | 74.6" |
| Crop Clearance | 15.9" |

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols

TIRES AND WHEELS

Front 8.3 – 16 R1 AG
Rear 14.9 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--------------------------|--|------------------|----------------------|
| *** STANDARD MACHINE *** | | | |
| L4060GST | L4060GST 4WD TRACTOR with 2 Post Foldable ROPS (97.6" High) | | \$ 27,119.00 |

| L4060GST | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ABR8753B | ** F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 27,119.00 |
| ALR6809B | ** R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR | 233 | \$ 637.00 | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | \$ 27,643.00 |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | \$ 27,973.00 |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 27,055.00 |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 27,633.00 |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | |

** Standard tires.

L4060HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-GL2/GL3
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
+ 40.0 Net Eng. HP
+ 32.5 PTO HP
@ 2600 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

HST PLUS
3 Forward / 3 Reverse
Hi-Med-Low Range
Mech. Wet Disc Brakes
Differential Lock
Cruise Control

FLUID CAPACITY

| | |
|--------------------------------|-----------|
| Fuel Tank | 13.5 gal. |
| Cooling System | 7.9 qts. |
| Crankcase | 8.7 qts |
| Transmission and Hydraulics | 11.4 gal. |
| Front Axle Differential | 6.9 qts. |

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

| | |
|-----------------------|--------|
| Overall Height w/ROPS | 97.6" |
| Overall Length w/3pt. | 129.5" |
| Wheel Base | 74.6" |
| Crop Clearance | 15.9" |

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response Control
Throttle-UP Switch

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols
HST Mode Selection

TIRES AND WHEELS

Front 8.3 – 16 R1 AG
Rear 14.9 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------|--|--|--------------|
| L4060HST | L4060HST 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High) | | \$ 27,599.00 |
|----------|--|--|--------------|

| L4060HST | | TIRES AND WHEELS (priced per piece) | | | Price with Tire Option | |
|------------|--|-------------------------------------|------------------|--|------------------------|--|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | | SUGG. LIST | |
| ABR8753B | ** F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | | \$ 27,599.00 | |
| ALR6809B | ** R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR | 233 | \$ 637.00 | | | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | | \$ 28,123.00 | |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | | | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | | \$ 28,453.00 | |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | | | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | | \$ 27,535.00 | |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | | | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | | \$ 28,113.00 | |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | | | |

** Standard tires.

L4060HSTC

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-GL2/GL3
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
+ 40.0 Net Eng. HP
+ 32.5 PTO HP
@ 2600 Eng. rpm
12V 60Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

HST PLUS
3 Forward / 3 Reverse
Hi-Med-Low Range
Mech. Wet Disc Brakes
Differential Lock
Cruise Control

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 8.7 qts.
Transmission and
Hydraulics 11.4 gal.
Front Axle Differential 6.9 qts.

POWER TAKE OFF

Rear-1 Speed Live Hyd. Independent
540 rpm @ 2550 Eng. rpm
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/Cab 91.1"
Overall Length w/3pt. 129.5"
Wheel Base 74.6"
Crop Clearance 15.9"

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols
HST Mode Selection

STANDARD EQUIPMENT

ROPS Certified Cab w/Retractable
Seat Belt
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Safety Start Switches
Operator Presence Control System
Parking Brakes
Flat Deck w/Hanging Pedals
Electric Key Shut-off
2 Front Work Lights
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Operator Presence Control System
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
12V Outlet and Cup Holder
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response Control
Throttle-UP Switch
Front Wiper w/ Washer
60 Amp Alternator
Interior Light
AC/Heater with Internal/External
Ventilation
Speakers and Radio Wired
Horn

TIRES AND WHEELS

Front 8.3 – 16 R1 AG
Rear 14.9 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|-----------|---|----|-----------|
| L4060HSTC | L4060HSTC 4WD CAB TRACTOR with ROPS Certified Factory Cab (91.1" High) | \$ | 35,665.00 |
|-----------|---|----|-----------|

| L4060HSTC | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ABR8753B | ** F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 35,665.00 |
| ALR6809B | ** R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR | 233 | \$ 637.00 | |
| ALR6813 | F-TIRE 29x12.5-15 R3 TF Steel Bias AA | 73 | \$ 320.00 | \$ 36,189.00 |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8898 | F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl | 70 | \$ 384.00 | \$ 36,519.00 |
| ALR6804 | R-TIRE 41-18LLx16.1 R3 Galaxy Turf Special | 132 | \$ 926.00 | |
| ALR8868 | F-TIRE 27X8.5 R3 TF Steel Bias CA | 44 | \$ 215.00 | \$ 35,601.00 |
| LR6801 | R-TIRE 355/80-D20 TURF | 188 | \$ 636.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 36,179.00 |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | |

**Standard Tires

Prices and specifications subject to change without notice. F.O.B. KTC designated shipping point.
Complete revision November 14, 2014.

L4760GST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-GL4
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
+ 47.0 Net Eng. HP
+ 41.0 PTO HP
@ 2700 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.9 gpm Power Steering
9.8 gpm Remote/3 Pt. Hitch
14.7 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

Glide Shift w/ Synchro Shuttle
12 Forward Speeds / 8 Reverse
Speeds
Mech. Wet Disc Brakes
Clutch - Single Dry Plate
Differential Lock

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 8.7 qts
Transmission and
Hydraulics 11.4 gal.
Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ROPS 97.6"
Overall Length w/3pt. 129.5"
Wheel Base 74.6"
Crop Clearance 15.6"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols

TIRES AND WHEELS

Front 8.3 – 16 R1 AG
Rear 14.9 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------|--|--|--------------|
| L4760GST | L4760GST 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High) | | \$ 32,511.00 |
|----------|--|--|--------------|

| L4760GST | | Price with Tire Option | | |
|------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ABR8753B** | F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 32,511.00 |
| ALR6809B** | R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR | 233 | \$ 637.00 | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 33,103.00 |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 33,025.00 |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 33,193.00 |
| ALR6817 | R-TIRE LSW610R470 R3 TF STL RADL AA | 227 | \$ 872.00 | |

** Standard tires.

L4760HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-GL5/GL6
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
+ 47.0 Net Eng. HP
+ 39.5 PTO HP
@ 2600 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

HST PLUS
3 Forward / 3 Reverse
Hi-Med-Low Range
Mech. Wet Disc Brakes
Differential Lock
Cruise Control

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 8.7 qts
Transmission and
Hydraulics 11.4 gal.
Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ROPS 97.6"
Overall Length w/3pt. 129.5"
Wheel Base 74.6"
Crop Clearance 15.6"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response Control
Throttle-UP Switch

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols
HST Mode Selection

TIRES AND WHEELS

Front 8.3 – 16 R1 AG
Rear 14.9 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------|--|--|--------------|
| L4760HST | L4760HST 4WD TRACTOR with 2 Post Foldable ROPS (97.6" High) | | \$ 32,991.00 |
|----------|--|--|--------------|

| L4760HST | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ABR8753B** | F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 32,991.00 |
| ALR6809B** | R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR | 233 | \$ 637.00 | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 33,583.00 |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 33,505.00 |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 33,673.00 |
| ALR6817 | R-TIRE LSW610R470 R3 TF STL RADL AA | 227 | \$ 872.00 | |

** Standard Tires

L4760HSTC

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-E4-GL5/GL6
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
4 Cyl., 148.5 cu. in.
+ 47.0 Net Eng. HP
+ 39.5 PTO HP
@ 2600 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2756 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

HST PLUS
3 Forward / 3 Reverse
Hi-Med-Low Range
Mech. Wet Disc Brakes
Differential Lock
Cruise Control

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 7.9 qts.
Crankcase 8.7 qts
Transmission and
Hydraulics 11.4 gal.
Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/Cab 91.9"
Overall Length w/3pt. 129.5"
Wheel Base 74.6"
Crop Clearance 15.6"

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols
HST Mode Selection

STANDARD EQUIPMENT

ROPS Certified Cab w/Retractable
Seat Belt
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Safety Start Switches
Operator Presence Control System
Parking Brakes
Flat Deck w/Hanging Pedals
Electric Key Shut-off
2 Front Work Lights
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Operator Presence Control System
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
12V Outlet and Cup Holder
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response Control
Throttle-UP Switch
Front Wiper w/ Washer
60 Amp Alternator
Interior Light
AC/Heater with Internal/External
Ventilation
Speakers and Radio Wired
Horn

TIRES AND WHEELS

Front 8.3 – 16 R1 AG
Rear 14.9 – 24 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

L4760HSTC **L4760HSTC 4WD CAB TRACTOR** \$ 41,057.00
with ROPS Certified Factory Cab (91.9" High)

| L4760HSTC | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | | | |
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| ABR8753B** | F/R-TIRE 8.3-16 R1 AG Steel Bias BA | 68 | \$ 246.00 | \$ 41,057.00 |
| ALR6809B** | R-TIRE 14.9-24 R1 6PLY BIAS HI-PWR | 233 | \$ 637.00 | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 41,649.00 |
| ALR6803 | R-TIRE 44x18-20 R3 Titan MultiTrac 6stud | 229 | \$ 825.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 41,571.00 |
| ALR6807 | R-TIRE 17.5L-24 R4 Firestone ATU | 259 | \$ 788.00 | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 41,739.00 |
| ALR6817 | R-TIRE LSW610R470 R3 TF STL RADL AA | 227 | \$ 872.00 | |

** Standard Tires

L5060GST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-TE4-GL1
Tier 4 Final Engine
Common Rail Direct Injection
Turbo Charged Engine
w/ DPF and EGR
4 Cyl. 148.5 cu. in.
+ 50.0 Net Eng. HP
+ 44.0 PTO HP
@ 2700 Eng. rpm
12V 40Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.9 gpm Power Steering
9.8 gpm Remote/3 Pt. Hitch
14.7 gpm Total Hyd. Flow
Category I 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2976 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

Glide Shift w/ Synchro Shuttle
12 Forward Speeds / 8 Reverse
Speeds
Mech. Wet Disc Brakes
Clutch - Single Dry Plate
Differential Lock

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 8.7 qts.
Crankcase 9.9 qts
Transmission and
Hydraulics 11.9 gal.
Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ROPS 98.0"
Overall Length w/3pt. 135.0"
Wheel Base 75.4"
Crop Clearance 16.7"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and
DPF system
Warning Symbols

TIRES AND WHEELS

Front 9.5 – 16 R1 AG
Rear 14.9 – 26 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------|--|--|--------------|
| L5060GST | L5060GST 4WD TRACTOR with 2 Post Foldable ROPS (98.0" High) | | \$ 33,341.00 |
|----------|--|--|--------------|

| L5060GST | | Price with Tire Option | | | |
|------------|--|------------------------|------------------|--------------|--|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST | |
| AMXR8860A | ** F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 33,341.00 | |
| AMXR8861 | ** R-TIRE 14.9-26 R1 6-PLY HI PWR LUG | 246 | \$ 825.00 | | |
| AMXR8860A | F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 33,341.00 | |
| AMXR8813A | R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC | 245 | \$ 825.00 | | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 33,483.00 | |
| ALR6802 | R-TIRE 44x18-20 R3 Titan MultiTrac 8stud | 221 | \$ 825.00 | | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 33,595.00 | |
| AMXR8862 | R-TIRE 17.5L-24 R4 Titan Ind Cont TL | 280 | \$ 883.00 | | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 33,573.00 | |
| ALR6819 | R-TIRE LSW610R470 R3 TF STL RADAL AA | 227 | \$ 872.00 | | |

** Standard tires.

L5460HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-TE4-GL2/GL3
 Tier 4 Final Engine
 Common Rail Direct Injection
 w/ DPF and EGR
 Turbo Charged
 4 Cyl., 148.5 cu. in.
 + 54.0 Net Eng. HP
 + 46.5 PTO HP
 @ 2600 Eng. rpm
 12V 45Amp - 582CCA
 Radial Air Flow Cooling
 Dual Air Cleaner Element

HYDRAULICS

Open Center
 Tandem Pump Gear Type
 4.7 gpm Power Steering
 9.4 gpm Remote/3 Pt. Hitch
 14.1 gpm Total Hyd. Flow
 Category I & II 3-Pt. Hitch
 Lift Capacity —
 At lift Point 3858 lbs.
 24" Behind 2976 lbs.
 Position Control

FRONT AXLE

Hydrostatic Power Steering
 Cast iron 4WD front axle
 Tread Spacing – Non-adjustable
 Bevel Gear drive

DRIVE TRAIN

HST PLUS
 3 Forward Speeds / 3 Reverse
 Speeds
 High-Med-Low
 Mech. Wet Disc Brakes
 Differential Lock
 Cruise Control

FLUID CAPACITY

Fuel Tank 13.5 gal.
 Cooling System 8.7 qts.
 Crankcase 9.9 qts
 Transmission and
 Hydraulics 11.9 gal.
 Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
 540 rpm @ 2550 Eng. rpm
 SAE 1-3/8 6 Splines
 Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ROPS 98.0"
 Overall Length w/3pt. 135.0"
 Wheel Base 75.4"
 Crop Clearance 16.7"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
 Safety Start Switch
 Highback Adj. Swivel Seat w/ Deluxe
 Suspension w/Arm Rests
 Operator Presence Control System
 Parking Brakes
 Flat Deck w/ Hanging Pedals
 Electric Key Shut-off
 Tilt Steering
 Wide Anti-Slip Step
 ISO Mounted Platform
 Turn Signals / Hazard Flashers
 SMV Sign
 Telescoping Lower Links
 2 Tier Halogen Head Lights
 4 Position Loader Valve
 One Piece Metal Hood
 Cup Holder
 Auto Throttle Advance
 Hydro Dual Speed (H-DS)
 HST Response Control
 Throttle-UP Switch

IntelliPanel™

Lighted Communications Symbols
 Standard Tachometer
 Digital Read for Speed, MPH, PTO
 speeds, diagnostics system and DPF
 system
 Warning Symbols
 HST Mode Selection

TIRES AND WHEELS

Front 9.5 – 16 R1 AG
 Rear 14.9 – 26 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|----------|--|--|--------------|
| L5460HST | L5460HST 4WD TRACTOR with 2 Post Foldable ROPS (98.0" High) | | \$ 34,817.00 |
|----------|--|--|--------------|

| L5460HST | | Price with Tire Option | | |
|--------------|--|------------------------|------------------|--------------|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| AMXR8860A ** | F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 34,817.00 |
| AMXR8861 ** | R-TIRE 14.9-26 R1 6-PLY HI PWR LUG | 246 | \$ 825.00 | |
| AMXR8860A | F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 34,817.00 |
| AMXR8813A | R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC | 245 | \$ 825.00 | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 34,959.00 |
| ALR6802 | R-TIRE 44x18-20 R3 Titan MultiTrac 8stud | 221 | \$ 825.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 35,071.00 |
| AMXR8862 | R-TIRE 17.5L-24 R4 Titan Ind Cont TL | 280 | \$ 883.00 | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 35,049.00 |
| ALR6819 | R-TIRE LSW610R470 R3 TF STL RADAL AA | 227 | \$ 872.00 | |

** Standard tires.

L5460HSTC

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-TE4-GL2/GL3
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
Turbo Charged
4 Cyl., 148.5 cu. in.
+ 54.0 Net Eng. HP
+ 46.5 PTO HP
@ 2600 Eng. rpm
12V 60Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I & II 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2976 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

+ Manufacturer Estimate

DRIVE TRAIN

HST PLUS
3 Forward Speeds / 3 Reverse
Speeds
High-Med-Low
Mech. Wet Disc Brakes
Differential Lock
Cruise Control

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 8.7 qts.
Crankcase 9.9 qts
Transmission and
Hydraulics 11.9 gal.
Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/Cab 92.5"
Overall Length w/3pt. 135.0"
Wheel Base 75.4"
Crop Clearance 16.7"

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols
HST Mode Selection

STANDARD EQUIPMENT

ROPS Certified Cab w/Retractable
Seat Belt
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Safety Start Switches
Operator Presence Control System
Parking Brakes
Flat Deck w/Hanging Pedals
Electric Key Shut-off
2 Front Work Lights
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Operator Presence Control System
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
12V Outlet and Cup Holder
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response Control
Throttle-UP Switch
Front Wiper w/ Washer
60 Amp Alternator
Interior Light
AC/Heater with Internal/External
Ventilation
Speakers and Radio Wired
Horn

TIRES AND WHEELS

Front 9.5 – 16 R1 AG
Rear 14.9 – 26 R1 AG

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

L5460HSTC

L5460HSTC 4WD CAB TRACTOR
with ROPS Certified Factory Cab (92.5" High)

\$ 42,883.00

| L5460HSTC | | Price with Tire Option | | | |
|-------------------------------------|--|------------------------|------------------|--------------|--|
| TIRES AND WHEELS (priced per piece) | | | | | |
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST | |
| AMXR8860A | ** F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 42,883.00 | |
| AMXR8861 | ** R-TIRE 14.9-26 R1 6-PLY HI PWR LUG | 246 | \$ 825.00 | | |
| AMXR8860A | F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 42,883.00 | |
| AMXR8813A | R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC | 245 | \$ 825.00 | | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 43,025.00 | |
| ALR6802 | R-TIRE 44x18-20 R3 Titan MultiTrac 8stud | 221 | \$ 825.00 | | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 43,137.00 | |
| AMXR8862 | R-TIRE 17.5L-24 R4 Titan Ind Cont TL | 280 | \$ 883.00 | | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 43,115.00 | |
| ALR6819 | R-TIRE LSW610R470 R3 TF STL RADAL AA | 227 | \$ 872.00 | | |

** Standard tires.

L6060HST

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-TE4-GL4/GL5
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
Turbo Charged
4 Cyl., 148.5 cu. in.
+ 60.0 Net Eng. HP
+ 53.0 PTO HP
@ 2600 Eng. rpm
12V 45Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I & II 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2976 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

DRIVE TRAIN

HST PLUS
3 Forward Speeds / 3 Reverse
Speeds
High-Med-Low
Mech. Wet Disc Brakes
Differential Lock
Cruise Control

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 8.7 qts.
Crankcase 9.9 qts
Transmission and
Hydraulics 11.9 gal.
Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ROPS 98.0"
Overall Length w/3pt. 135.0"
Wheel Base 75.4"
Crop Clearance 16.7"

STANDARD EQUIPMENT

ROPS w/Retractable Seat Belt
Safety Start Switch
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Operator Presence Control System
Parking Brakes
Flat Deck w/ Hanging Pedals
Electric Key Shut-off
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
Cup Holder
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response Control
Throttle-UP Switch

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols
HST Mode Selection

TIRES AND WHEELS

Front 9.5 – 16 R1 AG
Rear 14.9 – 26 R1 AG

+ Manufacturer Estimate

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

| | | | |
|-----------------|---|----|-----------|
| L6060HST | L6060HST 4WD TRACTOR with 2 Post Foldable ROPS (97.4" High) | \$ | 36,726.00 |
|-----------------|---|----|-----------|

| L6060HST | | Price with Tire Option | | |
|-------------------------------------|--|------------------------|------------------|--------------|
| TIRES AND WHEELS (priced per piece) | | | | SUGG. LIST |
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST |
| AMXR8860A | ** F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 36,726.00 |
| AMXR8861 | ** R-TIRE 14.9-26 R1 6-PLY HI PWR LUG | 246 | \$ 825.00 | |
| AMXR8860A | F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 36,726.00 |
| AMXR8813A | R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC | 245 | \$ 825.00 | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 36,868.00 |
| ALR6802 | R-TIRE 44x18-20 R3 Titan MultiTrac 8stud | 221 | \$ 825.00 | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 36,980.00 |
| AMXR8862 | R-TIRE 17.5L-24 R4 Titan Ind Cont TL | 280 | \$ 883.00 | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 36,958.00 |
| ALR6819 | R-TIRE LSW610R470 R3 TF STL RADAL AA | 227 | \$ 872.00 | |

** Standard tires.

L6060HSTC

*** EQUIPMENT IN STANDARD MACHINE ***

DIESEL ENGINE

Model # V2403-CR-TE4-GL4/GL5
Tier 4 Final Engine
Common Rail Direct Injection
w/ DPF and EGR
Turbo Charged
4 Cyl., 148.5 cu. in.
+ 60.0 Net Eng. HP
+ 53.0 PTO HP
@ 2600 Eng. rpm
12V 45Amp - 582CCA
Radial Air Flow Cooling
Dual Air Cleaner Element

HYDRAULICS

Open Center
Tandem Pump Gear Type
4.7 gpm Power Steering
9.4 gpm Remote/3 Pt. Hitch
14.1 gpm Total Hyd. Flow
Category I & II 3-Pt. Hitch
Lift Capacity —
At lift Point 3858 lbs.
24" Behind 2976 lbs.
Position Control

FRONT AXLE

Hydrostatic Power Steering
Cast iron 4WD front axle
Tread Spacing – Non-adjustable
Bevel Gear drive

+ Manufacturer Estimate

DRIVE TRAIN

HST PLUS
3 Forward Speeds / 3 Reverse
Speeds
High-Med-Low
Mech. Wet Disc Brakes
Differential Lock
Cruise Control

FLUID CAPACITY

Fuel Tank 13.5 gal.
Cooling System 8.7 qts.
Crankcase 9.9 qts
Transmission and
Hydraulics 11.9 gal.
Front Axle Differential 9.5 qts.

POWER TAKE OFF

1 Speed Rear Live — HYD. IND.
540 rpm @ 2550 Eng. rpm
SAE 1-3/8 6 Splines
Electric over Hydraulic PTO Switch

DIMENSIONS

Overall Height w/ROPS 98.0"
Overall Length w/3pt. 135.0"
Wheel Base 75.4"
Crop Clearance 16.7"

IntelliPanel™

Lighted Communications Symbols
Standard Tachometer
Digital Read for Speed, MPH, PTO
speeds, diagnostics system and DPF
system
Warning Symbols
HST Mode Selection

STANDARD EQUIPMENT

ROPS Certified Cab w/Retractable
Seat Belt
Highback Adj. Swivel Seat w/ Deluxe
Suspension w/Arm Rests
Safety Start Switches
Operator Presence Control System
Parking Brakes
Flat Deck w/Hanging Pedals
Electric Key Shut-off
2 Front Work Lights
Tilt Steering
Wide Anti-Slip Step
ISO Mounted Platform
Turn Signals / Hazard Flashers
SMV Sign
Operator Presence Control System
Telescoping Lower Links
2 Tier Halogen Head Lights
4 Position Loader Valve
One Piece Metal Hood
12V Outlet and Cup Holder
Auto Throttle Advance
Hydro Dual Speed (H-DS)
HST Response Control
Throttle-UP Switch
Front Wiper w/ Washer
60 Amp Alternator
Interior Light
AC/Heater with Internal/External
Ventilation
Speakers and Radio Wired
Horn

TIRES AND WHEELS

Front 9.5 – 16 R1 AG
Rear 14.9 – 24 R1 AG

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|-------------|------------------|----------------------|
|------------|-------------|------------------|----------------------|

*** STANDARD MACHINE ***

L6060HSTC

L6060HST 4WD CAB TRACTOR
with ROPS Certified Factory Cab (92.5" High)

\$ 44,792.00

| L6060HSTC | | TIRES AND WHEELS (priced per piece) | | | Price with Tire Option | |
|------------|--|-------------------------------------|------------------|--------------|------------------------|--|
| ORDER CODE | DESCRIPTION | APPROX SHIP WT. | SUGG. LIST PRICE | SUGG. LIST | | |
| AMXR8860A | ** F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 44,792.00 | | |
| AMXR8861 | ** R-TIRE 14.9-26 R1 6-PLY HI PWR LUG | 246 | \$ 825.00 | | | |
| AMXR8860A | F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud | 76 | \$ 283.00 | \$ 44,792.00 | | |
| AMXR8813A | R-TIRE 13.6-28 R1 6-PLY BIAS HI TRAC | 245 | \$ 825.00 | | | |
| ALR8708 | F-TIRE 29 X 12.50-15 R3 Titan Turf | 73 | \$ 354.00 | \$ 44,934.00 | | |
| ALR6802 | R-TIRE 44x18-20 R3 Titan MultiTrac 8stud | 221 | \$ 825.00 | | | |
| ALR8869A | F-TIRE 10-16.5 R4 IN Steel Bias AA | 83 | \$ 352.00 | \$ 45,046.00 | | |
| AMXR8862 | R-TIRE 17.5L-24 R4 Titan Ind Cont TL | 280 | \$ 883.00 | | | |
| ALR6818A | F-TIRE LSW305R343 R3 TF STL RADAL AA | 116 | \$ 352.00 | \$ 45,024.00 | | |
| ALR6819 | R-TIRE LSW610R470 R3 TF STL RADAL AA | 227 | \$ 872.00 | | | |

** Standard Tires

Grand L - 60 Series Attachment Chart

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications

| | L3560 | L4060 | L4760 | L5060 | L5460 | L6060 |
|---|---|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| Foldable ROPS & Seat Belt | SFL-F356 | SLF-F476 | SLF-F476 | SLF-F606 | SLF-F606 | SLF-F606 |
| Sunshade for ROPS | E1133 Std. E1134 Deluxe | E1133 Std. E1134 Deluxe | E1133 Std. E1134 Deluxe | E1133 Std. E1134 Deluxe | E1133 Std. E1134 Deluxe | E1133 Std. E1134 Deluxe |
| Rear Wheel Weight ① (Max. 3/Wheel) | L8066A① | L8066A① | L8066A① | LM8124⑤ | LM8124⑤ | LM8124⑤ |
| Front Weight Bracket ② | MX8068 | MX8068 | MX8068 | MX8068 | MX8068 | MX8068 |
| Rear Work Light (ROPS) | L8329 | L8329 | L8329 | L8329 | L8329 | L8329 |
| Front Bumper Weight(s) Max. 7 ⑩ | BL8060-1 | BL8060-1 | BL8060-1 | BL8060-1 | BL8060-1 | BL8060-1 |
| Rear Remote Hydraulics Sectional stackable valves Select double acting or Float Detent | See "Rear Remote Hydraulics" Section in corresponding Dealer Installed Options price pages. | | | | | |
| Draft Control | L8395 | L8395 | L8395 | L8395 | L8395 | L8395 |
| Swinging Drawbar | L8325 | L8325 | L8325 | L8325 | L8325 | L8325 |
| Drawbar Clevis | L9496G | L9496G | L9496G | L9496G | L9496G | L9496G |
| Front Grille Guard② | L2257 | L2257 | L2257 | L2257 | L2257 | L2257 |
| Creep Speed Kit③ | L8382 | L8382 | L8382 | L8382 | N/A | N/A |
| 3-pt Top-N-Tilt Kit④ | L8388 | L8388 | L8388 | L8388 | L8388 | L8388 |
| Mid-PTO Kit⑥ | L8387 | L8387 | L8387 | L8387 | L8387 | L8387 |
| Loader Valve Diverter Kit | L8397 | L8397 | L8397 | L8397 | L8397 | L8397 |
| Ballast Box | L8170 | L8170 | L8170 | L8170 | L8170 | L8170 |

CAB MODELS

L8333 Rear Work Light Kit (2 Lights)
L8364 Rear Wiper Kit, Washer connects to Front -Wiper's Washer.
L8340 Defogger Kit (Rear Window)
L8381 Defogger Kit (Corner Windows)

RADIOS

E9276B AM / FM / Weather Band / CD
E9299A AM/FM with Aux input

- ① Up to 3 wheel weights can be mounted together when using the L8067 Bolt Kit.
- ② Front Grille Guard for non-loader applications. Not compatible with L4455A K1 Manual-Hitch or L4554A K3 Auto-Hitch.
- ③ Not applicable to HST models.
- ④ Requires 2 or 3 Rear Hydraulic Remote depending on implement application. Please review Rear Remote Hydraulic section to select the correct remote configuration. Top-N-Tilt not compatible with ALL BH sub-frames.
- ⑤ LM8124 is 2 weights per set. Up to 3 weights max per wheel
- ⑥ Requires Mid-PTO Internal Gear installation on L3560DT/GST/HST, L4060DT/GST/HST, L4760GST/HST, L5060GST, L5460HST, L6060HST.
- ⑦ MX8068 Front Weight Bracket not compatible with L2257 Grille Guard.
- ⑩ Weights must be removed from bracket when Loader is installed.

KUBOTA

Grand L - 60 Series Dealer Installed Options

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------------------------|---|------------------|-----------------------------------|
| LISTED ALPHABETICALLY | | | |
| AIR RIDE SEAT | | | |
| L6023 | ① Air Ride Seat (Vinyl for ROPS models) | 58 | \$832.00 |
| BLOCK HEATER | | | |
| 70000-00297 | Block Heater | | (Order from the Parts Department) |
| BALLAST BOX | | | |
| L8170 | Ballast Box (1000 lb. cap. with dry sand) (All Grand L-60 Series) | 168 | \$449.00 |
| CAB MODEL OPTIONS | | | |
| L8333 | Rear Work light Kit (2 lights, Cab) | 3 | \$131.00 |
| L8364 | Rear Wiper Kit | 4 | \$143.00 |
| L8340 | Defogger Kit (Rear Window) | 18 | \$281.00 |
| L8381 | Defogger Kit (Corner Windows) | 18 | \$307.00 |
| E9299A | ② AM/FM Radio with MP3 Port and 7-Channel Weather Band. | 4 | \$310.00 |
| E9276B* | ② AM/FM Radio CD/MP3 Player with 7-Channel Weather Band. | 4 | \$440.00 |
| E9276C | ② AM/FM Radio CD/MP3/WB and Bluetooth w/ hands free connectivity | 4 | \$361.00 |
| L6026 | ① Air Ride Seat (Cloth for CAB) | 58 | \$852.00 |
| Jensen Radios | Three Radios Available | | (Order from the Parts Department) |
| CREEP SPEED KIT | | | |
| L8382 | Creep Speed Kit (All Grand L60 Series except HST Models) | 24 | \$602.00 |
| DRAFT CONTROL | | | |
| L8395 | Draft Control all Grand L 60 Series | 25 | \$561.00 |
| DRAWBAR OPTIONS | | | |
| L9496G | Drawbar Clevis | 8 | \$67.00 |
| L8325 | Swinging Drawbar | 20 | \$145.00 |
| FRONT GRILLE GUARD | | | |
| L2257 | ③④ Front Grille Guard (Non-Loader Applications) | 45 | \$269.00 |
| FRONT WEIGHTS | | | |
| MX8068 | ③④ Front Weight Bracket Kit All Grand L 60 Models | 25 | \$96.00 |
| BL8060-1 | ⑤ Front Suitcase Weight (55 lbs. each) Requires 1 BL8060B Bolt Kit Per weight, Max. 7 weights | 55 | \$71.00 |
| BL8060B | Bolt Kit (1 per weight required) Use with MX8068 Weight Bracket | 1 | \$2.00 |

- ① When the air ride seat is installed, the stationary PTO function is disabled. The operator can not tilt the seat forward on the air ride seat. Also, the swivel function will not work with the air ride installed.
- ② Radios have a 2-year warranty.
- ③ MX8068 Front Weight Bracket is not compatible with L2257 Grille Guard.
- ④ Front Grille Guard and the weight bracket are not compatible with L4455(A) Manual Quick Hitch or L4554(A) Fully Auto Quick Hitch. They must be removed before installation of the Quick Hitch.
- ⑤ Front weights must be removed when the loader is installed, the weight bracket may remain on the tractor.
- * Subject to availability

KUBOTA

Grand L - 60 Series Dealer Installed Options

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|-------------------------------|---|------------------|----------------------|
| HYDRAULIC DIVERTER KIT | | | |
| L8397 | ① Hydraulic Diverter Kit enables standard Loader Valve to be used as (2) rear hydraulic remotes, one remote will be float detent and one will be standard double-acting | 20 | \$562.00 |
| MID-PTO KITS | | | |
| L8387 | Mid-PTO Kit All Grand L-60 Series (ROPS Models L3560DT/GST/HST, L4060DT/GST/HST, L4760GST/HST, L5060GST, L5460HST, L6060HST require Internal Gear Kit L8316) | 22 | \$377.00 |
| L8316 | ② Mid-PTO Internal Gear Kit For installation of L8387 Mid-PTO Kit L3560DT/GST/HST, L4060DT/GST/HST, L4760GST/HST, L5060GST, L5460HST, L6060HST (Standard on Cab Tractors) | 25 | \$248.00 |

REAR REMOTE HYDRAULICS

| | | ROPS MODELS | |
|--|---|--------------------|----------|
| Must order Base Kit and one Valve Section to complete installation. | | | |
| L8398 | Base Kit and First Lever Requires L8308 or L8309 Valve to complete Assembly | 21 | \$587.00 |
| L8393 | Second Position Stacking Kit Includes Hardware and 2nd Lever Requires: Additional L8308 or L8309 Valve Section | 7 | \$316.00 |
| L8394 | Third Position Stacking Kit Includes Hardware and 3rd Lever Requires: Additional L8308 or L8309 Valve Section (For Triple Remotes, Second Position Stacking Kit also required) | 8 | \$316.00 |
| L8308 | Double Acting Valve Section Requires: Base Kit and First Lever | 4 | \$240.00 |
| L8309 | FD Float Detent Valve Section Requires: Base Kit and First Lever | 6 | \$302.00 |

- ① Not compatible with Front Loader or L8308/L8309 Hydraulic Valves.
- ② Allow approximately 10 hours for installation time.

KUBOTA

Grand L - 60 Series Dealer Installed Options

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|---|------------------|----------------------|
| REAR REMOTE HYDRAULICS | | | |
| CAB MODELS | | | |
| Must order Base Kit and one Valve Section to complete installation. | | | |
| L8396 | Base Kit and 1st Lever Requires L8308 or L8309 Valve to complete Assembly | 16 | \$587.00 |
| L8393 | Second Position Stacking Kit Includes Hardware and 2nd Lever Requires: Additional L8308 or L8309 Valve Section | 7 | \$316.00 |
| L8394 | Third Position Stacking Kit Includes Hardware and 3rd Lever Requires: Additional L8308 or L8309 Valve Section (For Triple Remotes, Second Position Stacking Kit also required) | 35 | \$316.00 |
| L8308 | Double Acting Valve Section Requires: Base Kit and First Lever | 4 | \$240.00 |
| L8309 | FD Float Detent Valve Section Requires: Base Kit and First Lever | 6 | \$302.00 |
| REAR WHEEL WEIGHTS | | | |
| L3560, L4060, L4760 all ROPS and CAB Models | | | |
| L8066A | ① Rear Wheel Weights (64 lbs. each) One, two, or three weights per wheel. Mount to 24" wheels with 10.24" wheel weight bolt hole centers. Set of 2 weights, Requires L8067A Bolt Kit, max. 3 Sets | 128 | \$124.00 |
| L8067A | Bolt Kit for L8066A (Max. 3 sets) | 5 | \$33.00 |
| L5060, L5460, L6060 all ROPS and CAB Models | | | |
| LM8124 | ① Rear Wheel Weights (103 lbs. each) One, two or three weights per wheel. Mount to 24", 26", or 28" wheels with steel discs. Set of 2 weights, requires LM8125A Bolt Kit, max. 3 sets (not turf tire compatible) | 105 | \$279.00 |
| LM8125A | Bolt Kit for 1st set of LM8124 weights (one kit will accept one set of weights) for 24", 26" and 28" steel wheels | 6 | \$67.00 |
| M8121A | Bolt Kit for 2nd and 3rd set of LM8124 Weights | 6 | \$21.00 |
| REAR WORK LIGHT KIT (ROPS) | | | |
| L8329 | Rear Work Light Kit (One light) | 5 | \$89.00 |
| REPLACEMENT CABS | | | |
| L8392 | ① Replacement Cab for: L3560HSTC | 850 | \$8,380.00 |
| L8391 | ① Replacement Cab for: L4060HSTC, and L4760HSTC | 850 | \$8,380.00 |
| L8390 | ① Replacement Cab for: L5460HSTC, and L6060HSTC | 850 | \$8,380.00 |

① Not compatible with Turf Tires.

Grand L - 60 Series Dealer Installed Options

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|-----------------------------|---|-----------------------------------|----------------------|
| REPLACEMENT ROPS | | | |
| SFL-F356A | ② Replacement ROPS for: L3560DT, L3560GST, L3560HST | 227 | \$785.00 |
| SFL-F476A | ② Replacement ROPS for: L4060DT, L4060GST, L4060HST, L4760GST, L4760HST | 218 | \$785.00 |
| SEAT BELT KIT | | | |
| 70002-06605 | Extra Length Seat Belt Kit | (Order from the Parts Department) | |
| SUNSHADE FOR ROPS | | | |
| E1133 | Standard Sunshade | 63 | \$437.00 |
| E1134 | Deluxe Sunshade Requires E1136 Mounting Bracket Kit | 63 | \$387.00 |
| E1136 | Mounting Bracket Kit for E1134 | 30 | \$191.00 |
| E1138 | Front Work Light Kit for E1134 (includes 2 lights) | 10 | \$125.00 |
| TNT (Top-N-Tilt Kit) | | | |
| L8388 | ① Top (Cylinder) & Tilt (Cylinder) Kit | 44 | \$871.00 |

① Requires 2 or 3 Rear Hydraulic Remote depending on implement application. Please review Rear Remote Hydraulic section to select the correct remote configuration. Not compatible with Backhoes.

② Replacement Cab packages include Cab assembly, mounting hardware, installation manual, left and right hand external rear view mirrors, all standard exterior lights, air-conditioning controls and hoses. Cab packages DO NOT include steering wheel.

L Series Implement Charts

STANDARD L IMPLEMENT CHART

| TRACTOR | L2501 | L3301 | L3901 | L4701 |
|--|------------------|------------------|------------------|--------|
| Front Loader | LA525 LA525FL | LA525 LA525FL | LA525 LA525FL | LA765 |
| 2-Lever Quick Coupler | L2216 | L2216 | L2216 | STD |
| 66" 2-Lever Quick Attach Square Back Bucket | L2256 | L2256 | L2256 | N/A |
| 60" Pin-On Bucket | L2242 | L2242 | L2242 | N/A |
| 72" 2-Lever Quick Attach Square Back Bucket | N/A | N/A | N/A | L2235A |
| 72" 2-Lever Quick Attach Heavy Duty Bucket | N/A | N/A | N/A | L2296 |
| 72" 2-Lever Quick Attach Light Material Bucket | N/A | N/A | N/A | L2236 |
| 2-Lever Quick Attach Pallet Fork Frame | L2238 | L2238 | L2238 | L2238 |
| 36" Pallet Forks | K9048 | K9048 | K9048 | K9048 |
| 2-Lever Quick Attach Bale Spear | L2237 | L2237 | L2237 | L2237 |
| Bucket Level Indicator (Rod) | L2130 | L2130 | L2130 | L2130 |
| Backhoe | BH77 | BH77 | BH77 | BH92 |
| Snowblower (Rear) | BL2664 | BL2664 | BL2664 | BL2664 |
| | L2674 | L2674 | L2674 | L2674 |

| TRACTOR | L3200F | L3200DT | L3200HST | L3800F | L3800DT | L3800HST | L4600F/DT/ HST |
|-------------------|--|--|--|--|--|--|-------------------|
| Front Loader | LA524 LA524FL LA525 ① LA525FL ① | LA524 LA524FL LA525 ① LA525FL ① | LA524 LA524FL LA525 ① LA525FL ① | LA524 LA524FL LA525 ① LA525FL ① | LA524 LA524FL LA525 ① LA525FL ① | LA524 LA524FL LA525 ① LA525FL ① | LA764 LA765 ① |
| Backhoe | BH77 | BH77 | BH77 | BH77 | BH77 | BH77 | BH92 |
| Rotary Tiller | FL1021C/RD | FL1021C/RD | FL1021C/RD | FL1021C/RD | FL1021C/RD | FL1021C/RD | FL1021C/RD |
| | FL1271C/RC | FL1271C/RC | FL1271C/RC | FL1271C/RC | FL1271C/RC | FL1271C/RC | FL1271C/RC |
| | FL1521C | FL1521C | FL1521C | FL1521C | FL1521C | FL1521C | FL1521C |
| Snowblower (Rear) | BL2664 | BL2664 | BL2664 | BL2664 | BL2664 | BL2664 | BL2664 |
| | L2674 | L2674 | L2674 | L2674 | L2674 | L2674 | L2674 |

① See wholegoods section for required grille guard.

**See Prior Model Section at the end of this section for Prior Model Matching Charts
Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications**

L Series Implement Charts

GRAND L-60 Loader Chart with Compatible Implement and Attachments

| MODEL | L3560 | | L4060 | L4760 | L5060 | L5460 | L6060 |
|--|---------------|----------|-------------|-------------|-------------|-------------|-------------|
| | LA555 | LA805 | LA805 | LA1055 | LA1055 | LA1055 | LA1055 |
| Front Loader | | | | | | | |
| 66" 2-Lever Quick Attach Sq. Back Bucket | L2256 | N/A | N/A | N/A | N/A | N/A | N/A |
| 72" 2-Lever Quick Attach Sq. Back Bucket | N/A | L2235A | L2235A | L2235A | L2235A | L2235A | L2235A |
| 72" 2-Lever Quick Attach Light Material Bucket | L2236 | | L2236 | L2236 | L2236 | L2236 | L2236 |
| 72" 2-Lever Quick Attach H.D. Round Back Bucket | N/A | L2296 | L2296 | L2296 | L2296 | L2296 | L2296 |
| 60" 2-Lever Quick Coupler Type 4 in 1 Bucket | L2244 | L2244 | L2244 | N/A | N/A | N/A | N/A |
| 72" 2-Lever Quick Coupler Type 4 in 1 Bucket | N/A | L2245 | L2245 | L2245 | L2245 | L2245 | L2245 |
| 66" Bolt on Cutting Edge | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 72" Bolt on Cutting Edge | N/A | TL1748 ② | TL1748 ② | TL1748 ② | TL1748 ② | TL1748 ② | TL1748 ② |
| 36" Pallet Forks | K9048 | | K9048 | K9048 | K9048 | K9048 | K9048 |
| 42" Pallet Forks | N/A | N/A | N/A | K9058 | K9058 | K9058 | K9058 |
| 2-Lever Quick Attach Bale Spear | L2237 | | L2237 | L2237 | L2237 | L2237 | L2237 |
| 2-Lever Quick Attach Pallet Fork Frame | L2238 | | L2238 | L2238 | L2238 | L2238 | L2238 |
| 3 RD Function Control Valve ⑥ | L2247 | L2265 | L2265 | L2265 | L2265 | L2265 | L2265 |
| 3 RD Function Control Valve ⑥ & 2-Lever Quick Coupler | N/A | L2272 | L2272 | L2272 | L2272 | L2272 | L2272 |
| Hydraulic 2-Lever Quick Coupler ⑥ | N/A | L2270 | L2270 | L2270 | L2270 | L2270 | L2270 |
| Hydraulic Spill Guard | N/A | L2261 | L2261 | L2271 | L2271 | L2271 | L2271 |
| Single Lever Hose Quick Coupler (4Hoses) | N/A | L2252 | L2252 | L2252 | L2252 | L2252 | L2252 |
| Single Lever Hose Quick Coupler (8Hoses) | N/A | L2262 | L2262 | L2262 | L2262 | L2262 | L2262 |
| 3 RD Function Hose Quick Coupler | N/A | L2260 | L2260 | L2260 | L2260 | L2260 | L2260 |
| Front Grill Guard Non-Loader | L2257 | | L2257 | L2257 | L2257 | L2257 | L2257 |
| Mid Mount Mower | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Backhoe⑥ | BH77 ⑤ | BH92 ③ | BH92 | BH92 | BH92 | BH92 | BH92 |
| Front Quick Hitch Attachments & Rear Implements | | | | | | | |
| 60" Front Rotary Sweeper (22" Diameter) ⑦ | L4467 | | N/A | N/A | N/A | N/A | N/A |
| 72" Front Rotary Sweeper (22" Diameter) ⑦ | N/A | | L4477 | L4477 | L4477 | L4477 | L4477 |
| 72" Front Rotary Sweeper (32" Diameter) ⑧ | N/A | | TBA | TBA | TBA | TBA | TBA |
| 64" Utility Snowblower ⑦ | L4469 | | L4469 | L4469 | L4469 | L4469 | L4469 |
| 74" Utility Snowblower ⑦ | L4479 | | L4479 | L4479 | L4479 | L4479 | L4479 |
| 74" Commercial Snowblower ⑦ | N/A | | L4474 | L4474 | L4474 | L4474 | L4474 |
| 80" Commercial Snowblower ⑦ | N/A | | L4485 | L4485 | L4485 | L4485 | L4485 |
| Rear Snow Blower | BL2664 (64") | | L2674 (74") | L2674 (74") | L2674 (74") | L2674 (74") | L2674 (74") |
| 60" Front Blade ⑦ | L4466 | | N/A | N/A | N/A | N/A | N/A |
| 72" Front Blade ⑦ | L4476 / L2172 | | | | | | |
| 84" Front Blade ⑦ | L4486 / L2184 | | | | | | |
| 72" Front Flail Mower ⑦ | N/A | | L4457 | L4457 | L4457 | L4457 | L4457 |
| Ground Pressure Relief | L4456 | | L4456 | L4456 | L4456 | L4456 | L4456 |

② Does not fit L2236 72" Q.A. Bucket or L2244 60" 4 in 1 Bucket

③ The BH92 is only compatible with LA805 Loader on a L3560 due to weight balance.

⑤ BH77 Backhoe is compatible with L3560 ROPS Only. Must use a BH92 Backhoe with a LA805 Loader for L3560HSTC.

⑥ If customer wants both the 3rd Function Control Valve and Hydraulic 2-Lever Quick Coupler, they must order L2272. L2265 and L2270 are not compatible together.

⑦ Although the use of the Ground Pressure Relief (GPR) is not required it is strongly recommended for use on the above implements.

⑧ The GPR will be required for use on the Front 72x32" Front Broom

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications

L Series Loader Matching Charts

| STANDARD L SERIES TRACTORS | LOADER and VALVE | BUCKET STRUCK / HEAPED CAPACITY | OPTIONAL ATTACHMENTS |
|----------------------------|--|---|--|
| L2501 L3301 L3901 | LA525FL/LA524FL Complete, includes Loader valve, bucket, mounting kit, grille guard, bucket, and hydraulic block | LA525FL L2242 (Std) - 60" width Pin-On 7.8 cu. ft. struck 9.2 cu. ft. heaped | L2130 Bucket Rod Indicator Kit L2216 2-Lever Quick Coupler |
| | LA525/LA524 Includes loader valve, mounting kit, grille guard, hydraulic block, and 2 lever coupler | L2256 - 66" width 2-Lever Quick Attach 8.1 cu. ft. struck 9.9 cu. ft. heaped | L2130 Bucket Rod Indicator Kit |
| L4701 | LA765/LA764 Includes Loader Valve, Grille Guard, and Quick Coupler | L2296 – 72" Round Back Quick Attach 10.9 cu. ft. / 13.1 cu. ft. L2236 – 72" Light Material 12.7 cu. ft. / 16.0 cu. ft. | 7J289-90500 Quick Coupler ② L2237 Bale Spear L2130 Bucket Rod Indicator Kit TL1748 Cutting Edge ① |

① TL1748 for L2296 Bucket only.

② Order from the Parts Department for replacement. Standard with Loader.

* Subject to availability.

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications

L Series Loader Matching Charts

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications
All Grand L-60 Series Loaders and Options

| Tractor Models | Loader Model | Bucket Struck / Heaped Capacity | Optional Quick Attachments | Loader Options Kits | 3 RD Function Control Valve |
|----------------------------------|---|---|--|---|---|
| L3560 | LA555 with Mechanical 2 Lever Quick Coupler and Grille Guard | L2256 – 66" 2-Lever Quick Attach Sq. Bucket - 8.1cu.ft / 9.9cu.ft L2236 – 72" 2-Lever Quick Attach Light Material Bucket – 12.7cu.ft / 16cu.ft L2244 – 60" 2-Lever Q. A. Attach 4 in 1 Bucket – 8.9cu.ft / 11.0cu.ft | L2237 2-Lever Quick Attach Bale Spear L2238 2-Lever Quick Attach Pallet Fork Frame K9048 36" Pallet Fork Set L2216 2-Lever Quick Coupler (Replacement) | N/A | L2247 – 3 rd Function Control Valve |
| | LA805 with Mechanical 2 Lever Quick Coupler and Grille Guard | L2235A – 72" 2-Lever Quick Attach Sq. Bucket – 10.9cu.ft / 13.1cu.ft L2236 – 72" 2-Lever Quick Attach Light Material Bucket – 12.7cu.ft / 16cu.ft L2296 ① – 72" 2-Lever Quick Attach HD Bucket – 10.9cu.ft / 13.1cu.ft L2244 – 60" 2-Lever Quick Attach 4 in 1 Bucket – 8.9cu.ft / 11.0cu.ft L2245 – 72" 2-Lever Quick Attach 4 in 1 Bucket – 10.9cu.ft / 13.1cu.ft | L2237 2-Lever Quick Attach Bale Spear L2238 2-Lever Quick Attach Pallet Fork Frame K9048 36" Pallet Fork Set L2226 2-Lever Quick Coupler (Replacement) | L2261 Hydraulic Spill Guard L2270 Hydraulic 2-Lever Quick Coupler L2252 Single Lever Hose Quick Coupler (4 Hoses) L2262 Single Lever Hose Quick Coupler (8 Hoses) L2260 3 rd Function Hose Quick Coupler | L2265 – 3 rd Function Control Valve L2272 – 3 rd Function Control Valve with Hydraulic 2-Lever Quick Coupler |
| L4060 | LA805 with Mechanical 2 Lever Quick Coupler and Grille Guard | L2235A – 72" 2-Lever Quick Attach Sq. Bucket – 10.9cu.ft / 13.1cu.ft L2236 – 72" 2-Lever Quick Attach Light Material Bucket – 12.7cu.ft / 16cu.ft L2296 ① – 72" 2-Lever Quick Attach HD Bucket – 10.9cu.ft / 13.1cu.ft L2244 – 60" 2-Lever Quick Attach 4 in 1 Bucket – 8.9cu.ft / 11.0cu.ft L2245 – 72" 2-Lever Quick Attach 4 in 1 Bucket – 10.9cu.ft / 13.1cu.ft | L2237 2-Lever Quick Attach Bale Spear L2238 2-Lever Quick Attach Pallet Fork Frame K9048 36" Pallet Fork Set L2226 2-Lever Quick Coupler (Replacement) | L2261 Hydraulic Spill Guard L2270 Hydraulic 2-Lever Quick Coupler L2252 Single Lever Hose Quick Coupler (4 Hoses) L2262 Single Lever Hose Quick Coupler (8 Hoses) L2260 3 rd Function Hose Quick Coupler | L2265 – 3 rd Function Control Valve L2272 – 3 rd Function Control Valve with Hydraulic 2-Lever Quick Coupler |
| L4760 L5060 L5460 L6060 | LA1055 with Mechanical 2 Lever Quick Coupler and Grille Guard | L2235A – 72" 2-Lever Quick Attach Sq. Bucket – 10.9cu.ft / 13.1cu.ft L2236 – 72" 2-Lever Quick Attach Light Material Bucket – 12.7cu.ft / 16cu.ft L2296 ① – 72" 2-Lever Quick Attach HD Bucket – 10.9cu.ft / 13.1cu.ft L2245 – 72" 2-Lever Quick Attach 4 in 1 Bucket – 10.9cu.ft / 13.1cu.ft | L2237 2-Lever Quick Attach Bale Spear L2238 2-Lever Quick Attach Pallet Fork Frame K9048 36" Pallet Fork Set K9058 42" Pallet Fork Set L2226 2-Lever Quick Coupler (Replacement) | L2271 Hydraulic Spill Guard L2270 Hydraulic 2-Lever Quick Coupler L2252 Single Lever Hose Quick Coupler (4 Hoses) L2262 Single Lever Hose Quick Coupler (8 Hoses) L2260 3 rd Function Hose Quick Coupler | L2265 – 3 rd Function Control Valve L2272 – 3 rd Control Function Valve with Hydraulic 2-Lever Quick Coupler |

① Heavy Duty Buckets are pre-drilled to accept optional bolt-on reversible cutting edges.

Standard L-Series Front Loaders

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|---|-----------------------------------|----------------------|
| CURRENT L-SERIES FRONT LOADERS | | | |
| LA525FL | ① HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard and 60" Bucket. | 1029 | \$4,313.00 |
| LA525 | HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard Hydraulic Block and 2-Lever style coupler plate. Does not include bucket. | 900 | \$4,270.00 |
| LA765 | HEAVY DUTY FRONT LOADER Includes Mounting Kit, 2-Lever type Quick Coupler, Valve and Grille Guard. Bucket must be ordered separately | 1098 | \$4,942.00 |
| STANDARD L SERIES FRONT LOADER BUCKETS AND PALLET FORKS | | | |
| QA = Quick Attach, PO = Pin On Type | | | |
| L2256 | 66" Square Back QA LA463-1 / LA524 / LA525 | 212 | \$623.00 |
| L2235A | 72" Square Back QA LA703A / LA764 / LA765 | 247 | \$691.00 |
| L2296 | 72" Round Back QA LA703A / LA764 / LA765 | 400 | \$1,071.00 |
| L2236 | 72" Light Material QA LA703A / LA764 / LA765 | 323 | \$649.00 |
| L2238 | Pallet Fork Frame QA | 165 | \$677.00 |
| K9048 | 36" Pallet Forks | 176 | \$407.00 |
| L2237 | Bale Spear | 165 | \$642.00 |
| TL1748 | Bottom Cutting Edge for L2240/L2245/L2273/ L2296 72" Buckets | 65 | \$227.00 |
| L2242 | 60" Pin-on Bucket (Replacement for LA524 / LA525) | 200 | \$510.00 |
| 7J289-90500 | 2-Lever Quick Attach Coupler (Replacement for LA764 Loader) | (Order from the Parts Department) | |
| L2216 | 2-Lever Quick Coupler (Replacement for LA524, LA525) | 76 | \$441.00 |
| L2130 | Bucket Rod Lever Indicator Kit for LA703(A), LA463FL, LA463-1, LA524FL, LA524, LA764 LA525 / LA525FL / LA765 | 2 | \$65.00 |
| L SERIES GRILLE GUARD | | | |
| L2251 | Grille Guard (L2800/L3400/L3700SU/ L4400/L4400-1) | 36 | \$275.00 |
| L2267 | Foldable Grille Guard for L4600 (non-loader application) | 61 | \$326.00 |
| MX8190 | Grille Guard (L3200, L3800) for all loader and non-loader applications | 50 | \$275.00 |
| L2258 | Grille Guard (L3301 / L3901) for non loader and loader applications | 35 | \$326.00 |
| MX2268 | Grille Guard (L4701) for non loader and loader applications | 50 | \$275.00 |

① FL = Full Loader, Cylinders and Hoses are pre-installed. FL packaged buckets are NOT returnable.

Standard L-Series Front Loaders

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|---|------------------|----------------------|
| REPLACEMENT STANDARD L-SERIES LOADERS | | | |
| LA524FL | ①② HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard and 60" Bucket. | 710 | \$4,225.00 |
| LA524 | ② HEAVY DUTY FRONT LOADER Includes Mounting Kit, Valve, Grille Guard Hydraulic Block and 2-Lever style coupler plate. Does not include bucket. | 845 | \$4,182.00 |
| LB552-1 | * LIGHT DUTY FRONT LOADER Includes Mounting Kit, Hydraulic Block, Valve and 60" Bucket (L4300F/DT) | 835 | \$3,601.00 |
| LA764 | HEAVY DUTY FRONT LOADER Includes Mounting Kit, 2-Lever type Quick Coupler, Valve and Grille Guard. Bucket must be ordered separately | 970 | \$4,942.00 |
| LA682-1 | * FRONT LOADER Includes Mounting Kit and Grille Guard (L1766). Does not include Bucket or Joystick Control. | 1000 | \$3,491.00 |
| LA852-2 | * FRONT LOADER Includes Mounting Kit and Grille Guard Does not include Bucket or Joystick Control | 1275 | \$3,353.00 |
| LA450A | * FRONT LOADER Includes Mounting Kit. Does not include Bucket, Joystick Control Valve or Grille Guard. | 870 | \$2,796.00 |
| LA650A | * FRONT LOADER Includes Mounting Kit. Does not include Bucket, Joystick Control Valve or Grille Guard. | 1070 | \$3,308.00 |
| LA1150A | * FRONT LOADER Includes Mounting Kit and Hydraulic Valve. Bucket not included with Loader. | 1500 | \$4,877.00 |

OPTIONAL WIDE LOADER PARKING STANDS

75548-47551 ③ (2 Required per Loader) (Order from the Parts Department)

* Subject to availability.

① FL = Full Loader, Cylinders and Hoses are pre-installed. FL packaged buckets are NOT returnable.

② Requires subframe kit L4691 to be used with BL4690B Backhoe.

③ 75548-47551 Wider Parking Stands are used for Loader applications in combination with the RC72-29 and RC72-36 Mid Mount Mower, or other applications where additional clearance is desired. Two Stands are required for proper application.

L-Series Loader Attachments

| ORDER CODE | DESCRIPTION | | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|--|--|------------------|----------------------|
| REPLACEMENT L SERIES GRILLE GUARD MOUNTING KIT/ NOT EQUIPPED WITH LOADERS | | | | |
| L1785 | Grille Guard Mounting Kit For L2050 - L3250 and L2350 - L3650 Tractors | | 15 | \$102.00 |
| L1765 | Grille Guard Stay Kit for L1766 Grille Guard For Grand L-Series Tractors (except L4610) | | 25 | \$88.00 |
| REPLACEMENT L SERIES FRONT LOADER BUCKETS AND PALLET FORKS | | | | |
| L1701 | 60" Pin-on Bucket | Replacement for LA463 | 212 | \$474.00 |
| L1746 | 60" Square Back Repl. | LB400A, LB402 | 212 | \$417.00 |
| L1740A | 60" Square Back | LA450S, LA452S, LA480, LA481, LA482 | 212 | \$474.00 |
| L1780 | 66" Square Back | LA481, LA482 | 308 | \$594.00 |
| L1741A | 60" H.D. Round Back | LA450A, LA452S, LA480, LA481, LA482 | 308 | \$780.00 |
| L1703 | 60" Square Back | LB552 | 212 | \$474.00 |
| L1742A | 60" Square Back | LA650A, LA680, LA681, LA682, LB552 | 247 | \$576.00 |
| L1743A | 60" H.D. Round Back | LA650A, LA680, LA681, LA682, LB552 | 308 | \$951.00 |
| L1790 | 66" Square Back | LA681, LA682 | 308 | \$660.00 |
| L1750 | 70" Light Material | LB400, LB402, LA450S, LA452S, LA480, LA481, LA482, LA680, LA681, LA682, LB552 | 212 | \$646.00 |
| L1769 | 72" Square Back | LA852 -- LA852-1 | 400 | \$677.00 |
| L1779 | 72" H.D. Round Back | LA852 -- LA852-1 | 400 | \$1,106.00 |
| L1774A | 70" Square Back | LA950A | 404 | \$627.00 |
| L1770A | 70" H.D. Round Back | LA950A, LA1150A | 583 | \$1,122.00 |
| L2264 | 72" Square Back PO | LA703 / LA703A | 247 | \$667.00 |
| TL1756 | Bolt on Cutting Edge | L2239/L2253/L2266 66" Buckets | 65 | \$210.00 |

Grand L-60 Series Loaders

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|---|------------------|----------------------|
| GRAND L-60 SERIES FRONT LOADERS | | | |
| LA555 | ① Loader for L3560 All Includes Grille Guard, Mounting Kit, Mechanical 2 Lever Quick Coupler, and Bucket Level Indicator. Does not include Bucket. Loader valve is standard equipment on all Grand L60 Tractors. | 970 | \$3,753.00 |
| Bucket and Attachment Options for LA555 Loader (Must order to one to complete.) | | | |
| Mechanical 2-Lever Quick-Attach Options for LA555 | | | |
| L2256 | 66" Square Back Bucket 8.1 cu. ft. Struck, 9.9 cu. ft. Heaped | 212 | \$623.00 |
| L2236 | 72" Light Material Bucket 12.7 cu. ft. Struck, 16.0 cu. ft. Heaped | 323 | \$649.00 |
| L2238 | Pallet Fork Frame | 165 | \$677.00 |
| K9048 | 36" Pallet Forks | 176 | \$407.00 |
| L2237 | Bale Spear | 165 | \$642.00 |
| L2244 | ② 60" 4-in-1 Bucket Requires 3rd Function Control Valve | 450 | \$2,025.00 |
| L2216 | 2-Lever Quick-coupler for LA555 (Replacement) | 79 | \$441.00 |
| Third Function Valve for LA555 | | | |
| L2247 | 3rd Function Control Valve - for L3560 models for Hydraulic Loader Implements | 25 | \$899.00 |

① In the case of using a BH92 on L3560, Tractor is required to use LA805 Front Loader. BH92 is not compatible with LA555 Front Loader.

② Requires 3rd Function Valve

Grand L-60 Series Loaders

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|------------------|----------------------|
| GRAND L-60 SERIES FRONT LOADERS(continued) | | | |
| LA805 | Loader for L3560, L4060 Includes Grille Guard, Mounting Kit, Mechanical 2 Lever Quick Coupler, and Bucket Level Indicator. Does not include Bucket. Loader valve is standard equipment on all Grand L60 Tractors. | 970 | \$4,486.00 |
| LA1055 | Loader for L4760, L5060, L5460, L6060 Includes Grille Guard, Mounting Kit, Mechanical 2 Lever Quick Coupler, and Bucket Level Indicator. Does not include Bucket. Loader valve is standard equipment on all Grand L60 Tractors. | 970 | \$4,898.00 |
| Bucket and Attachment Options for LA805 & LA1055 Loaders (Must order one to complete.) | | | |
| 2-Lever Style Quick-Coupler Options for LA805 & LA1055 Loaders | | | |
| L2235A | 72" Square Back Bucket 10.9 cu. ft. Struck, 13.1 cu. ft. Heaped | 247 | \$691.00 |
| L2236 | 72" Light Material Bucket 12.7 cu. ft. Struck, 16.0 cu. ft. Heaped | 323 | \$649.00 |
| L2296 | 72" Heavy Duty Round Back 10.9 cu. ft. Struck, 13.1 cu. ft. Heaped (Pre-Drilled for Opt. TL1748 Edge) | 400 | \$1,071.00 |
| TL1748 | Bolt-on Reversible Cutting Edge (72") for L2296 | 65 | \$227.00 |
| L2244 | ① 60" 4-in-1 Bucket (LA805 only) Requires 3rd Function Control Valve | 450 | \$2,025.00 |
| L2245 | ① 72" 4-in-1 Bucket (LA805 and LA1055) Requires 3rd Function Control Valve | 640 | \$2,140.00 |
| L2238 | Pallet Fork Frame | 165 | \$677.00 |
| K9048 | 36" Pallet Forks for LA805 & LA1055 | 176 | \$407.00 |
| K9058 | 42" Pallet Forks for LA1055 only | 196 | \$476.00 |
| L2237 | Bale Spear | 165 | \$642.00 |
| L2226 | 2-Lever Quick-coupler for LA805 & LA1055 (Replacement) | 116 | \$452.00 |

① Requires 3rd Function Control Valve

Grand L-60 Series Loaders

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|---|------------------|----------------------|
| Loaders (Continued) | | | |
| Hydraulic 2-Lever Quick Coupler for LA805 & LA1055 | | | |
| L2270 | ① Hydraulic 2-Lever Quick Coupler | 116 | \$1,499.00 |
| Third Function Valve for LA805 & LA1055 Loaders | | | |
| L2265 | ① 3rd Function Control Valve for Hydraulic Loader Implements | 25 | \$899.00 |
| L2272 | ① 3rd Function Control Valve & Hydraulic 2-Lever Quick Coupler | 143 | \$2,398.00 |
| Hydraulic Spill Guard for LA805 Loader | | | |
| L2261 | Hydraulic Spill Guard, anti-spill feature for buckets | 38 | \$599.00 |
| Hydraulic Spill Guard for LA1055 Loader | | | |
| L2271 | Hydraulic Spill Guard, anti-spill feature for buckets | 38 | \$599.00 |
| Loader Hose Quick Coupler for LA805 & LA1055 | | | |
| L2260 | 3rd Function Hose Quick Coupler | 11 | \$596.00 |
| L2252 | ② Single Lever Hose Quick Coupler for Loader hoses (4 Hoses) | 17 | \$696.00 |
| L2262 | ② Single Lever Hose Quick Coupler for Loader, 3rd Function Control Valve, and Hydraulic 2-Lever Quick Coupler (8 Hoses) | 116 | \$896.00 |

① If customer wants both the 3rd Function Control Valve and Hydraulic 2-Lever Quick Coupler, they must order L2272. L2270 Hydraulic 2-Lever Quick Coupler is not compatible with L2265 3rd Function Control Valve.

② When installed with L4455(A) K1 Manual-Hitch or L4554(A) K3 Auto-Hitch. Hydraulic hoses will be connected and disconnect on the tractor. The Single lever coupler can not be connected due to hose lengths.

L Series Backhoe Matching Chart

BACKHOE APPLICATION CHART

To be used for quick reference only, check Whole Good numbers for proper applications

| BH77 | TRACTOR MODELS | MOUNT KIT | SUB-FRAME KIT | BUCKETS | ROPS |
|-----------------|-----------------------------------|-----------|---------------|--|-------------------------|
| STANDARD L | L2800, L3400, L3700SU | Included | BH4976A | 10" - BT1950A 12" - BT1951A 16" - BT1952A 24" - BT1953A | All ROPS are Acceptable |
| STANDARD L | L2501, L3200, L3800, L3301, L3901 | Included | BH4988 | | |
| GL40-1/2 (ROPS) | L3240, L3540 | Included | BH4996A | | |
| GL40-3 (ROPS) | L3240, L3540 | Included | BH4986 | | |
| GL60 ROPS | L3560 | Included | BH4985 | | |

| BH92 | TRACTOR MODELS | MOUNT KIT | SUB-FRAME KIT | BUCKETS |
|------------|--|----------------------------------|---------------|--|
| STANDARD L | L4600, L4701 | Included | BH4946 | PIN ON BUCKETS 12" - BT3001 16" - BT3002A 18" - BT3003A 24" - BT3004 30" - BT3005A 36" - BT3006 QUICK COUPLER BUCKETS 12" - BT4552 16" - BT4553 18" - BT4554 24" - BT4555 36" - BT4557 |
| | | L4400F-1, L4400DT-1, L4400 HST-1 | Included | |
| GL40 ROPS | L3240, L3540 | BH4941 | BH4945 | |
| | L3940, L4240, L4740 L5040, L5240, L5740 | BH4943 | | |
| GL40-1 CAB | L3240, L3540, L3940, L4240, L4740, L5240, L5740 | N/A | N/A | |
| GL40-3 CAB | L3240, L3540, | BH4942 | BH4945 | |
| | L3940, L4240, L4740, L5240, L5740 | BH4944 | | |
| GL60 ROPS | L3560 (LA805 Only) | BH4987 | BH4999 | |
| GL60 ROPS | L4060, L4760 | BH4989 | | |
| | L5060, L5460, L6060 | | | |
| GL60 CAB | L3560 (LA805 Only) | BH4983 | | |
| GL60 CAB | L4060, L4760 | BH4982 | | |
| | L5460, L6060 | | | |

L Series Backhoes

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|---|------------------|----------------------|
| NOTE: When backhoe is installed tractor must be equipped with a loader | | | |
| BH77 ①②③⑧⑨ | 4-Pt. mounted quick-attach, easy-on easy-off, no tools design. Requires integral subframe kit/ mounting kit. Backhoe seat is part of subframe for L2800/DT/HST(-1), L3400/DT/HST(1), L3700SU, L3200F/DT/HST, L2501F/DT/HST, L3301F/DT/HST, L3800F/DT/HST, L3901F/DT/HST, L3240(-1/-2/-3), and L3540(-1/-2/-3) L3560DT, L3560GST, L3560HST Model Tractors. | 1085 | \$6,844.00 |
| BH77 MOUNTING KITS and SUBFRAME KITS | | | |
| BH4976A | * Subframe required for BH77 to mount on L2800/DT/HST(-1), L3400/DT/HST(-1) and L3700SU. Includes regular fixed seat. Requires LA463 Loader | 200 | \$754.00 |
| BH4996A | Subframe required for BH77 to mount on L3240(-1)(-2) and L3540(-1)(-2). Includes regular fixed seat. Mounting Kit included. Requires LA514/LA724 Loader | 292 | \$1,071.00 |
| BH4986 | Subframe required for BH77 to mount on L3240-3, L3540-3. Includes seat. Mounting Kit Included. Requires LA514/LA724 Loader | 292 | \$1,071.00 |
| BH4988 | Subframe required for BH77 to mount on L3200, L3800 (requires LA524/LA524FL Loader) and L2501, L3301, L3901 (requires LA525/LA525FL Loader). Includes fixed seat and Mounting Kit. | 200 | \$754.00 |
| BH4985 | ⑧ Subframe Kit required for BH77 to mount on L3560DT, L3560GST, L3560HST. Requires LA555 Loader | 292 | \$1,240.00 |
| BH77 BACKHOE BUCKETS & THUMBS | | | |
| BT1950A | 10" Bucket — 3 Teeth | 69 | \$415.00 |
| BT1951A | 12" Bucket — 3 Teeth | 69 | \$491.00 |
| BT1952A | 16" Bucket — 4 Teeth | 84 | \$648.00 |
| BT1953A | 24" Bucket — 5 Teeth | 118 | \$847.00 |
| BH1976 | 6 Position Mechanical Thumb for BH76/77 | 52 | \$475.00 |
| L9467 | Rubber stabilizer flip pads (Set) for BH77, Two required per owner's manual | 16 | \$79.00 |

①These Backhoes are not compatible with Top-N-Tilt Kits.

② Not compatible with Grand L Cab Models.

③ Not compatible with Mid-mount Mower RC72-38.

⑧ Not compatible with L3560HSTC, this Models requires a BH92 w/ LA805 Loader

L Series Backhoes

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|---|------------------|----------------------|
| BH92 ②⑤⑦⑧ | Easy-on, Easy-off, No Tools Design Performance matched, requires applicable Mounting Kit and Subframe Kit, works with the tractor supplied hydraulics. -see below (L4400-1, L4600, L4701 GL40 ROPS, GL40-3 Cab, GL-30 ROPS.) (All L3560, L4060, L4760, L5060, L5460, L6060 Models require applicable Mounting Kit and BH4999 Subframe Kit.) | 1800 | \$7,659.00 |
| Subframe and Mounting Kits for BH92 on Grand L 60 Series | | | |
| BH4987 | Mounting Kit required for L3560DT/GST/HST Models. requires LA805 Loader & BH4999 | 88 | \$331.00 |
| BH4989 | Mounting Kit required for L4060DT/GST/HST, L4760GST/HST, L5060GST, L5460HST, L6060HST. requires LA805/LA1055 Loader & BH4999 | 67 | \$364.00 |
| BH4983 | Mounting Kit required for L3560HSTC Requires LA805 Loader & BH4999 | 292 | \$531.00 |
| BH4982 | Mounting Kit required for L4060HSTC, L4760HSTC, L5460HSTC, L6060HSTC requires LA805/LA1055 Loader & BH4999 Subframe Kit | 292 | \$564.00 |
| BH4999 | Subframe kit required for BH92 Backhoe on all Grand L 60 Models. | 88 | \$942.00 |
| Subframe and Mounting Kits for BH92 Grand L40 ROPS and Grand L40-3 Cab | | | |
| BH4941 | Mounting kit for L3240/L3540 (-1/-2/-3) ROPS Models with BH92 backhoe. Requires LA724/LA514 loader & BH4945 Subframe Kit | | |
| BH4942 | Mounting kit for L3240-3/L3540-3 Cab Models with LA724/LA514 loader & BH4945 Subframe Kit. | 50 | \$542.00 |
| BH4943 | Mounting kit for L3940/L4240/L4740/L5040/L5240/L5740 (-1/-2/-3) ROPS Models with BH92 backhoe Requires LA724/LA854 loader & BH4945 Subframe Kit | | |
| BH4944 | Mounting kit for L3940/L4240/L4740/L5040/L5240/L5740 (-3) CAB Models Requires LA724/LA854 loader & BH4945 Subframe Kit | 228 | \$576.00 |
| BH4945 | Subframe Kit required to mount BH92 L3240/3540/L3940/L4240/ L4740/L5040/L5240/L5740 ROPS and (-3) CAB models with LA514 / LA724 / LA854 | 383 | \$768.00 |

② Not compatible with Top-N-Tilt Link Kits.

⑤ BH92 Mounting Kits do not interfere with 3 point hitch operation. 3-Point linkage must be removed for Backhoe operation. Not compatible with mid-mount mower RC72-38.

⑦ Not compatible with L4400, must have L4400-1 with LA703(A) Loader.

⑧ Not compatible with GL30 Cab models, GL40, GL40-1 Cab tractors

L Series Backhoes

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|--|------------------|----------------------|
| Subframe and included Mounting Kits for BH92 - L4701 / L4600 / L4400 | | | |
| BH4946 | Subframe including Mounting Kit required for BH92 to mount on L4600F/DT/HST, L4701F/DT/HST L4600 requires LA764 / L4701 requires L765 | 383 | \$1,139.00 |
| BH4979 | ② Subframe including Mounting kit required for BH92 to mount on L4400DT-1/ L4400HST-1 | 383 | \$1,139.00 |
| <u>Subframe Mounting Kits for BH92 on GL30 ROPS</u> | | | |
| BH4990 | ① Mounting kit for L3130/L3430 ROPS Models with LA723 loader. | 46 | \$293.00 |
| BH4991 | ① Mounting kit for L3830/L4330/L4630/L5030 ROPS Models with BH92 backhoe. Requires LA723/853 loader. Requires LA723 or LA853 Loader. | 67 | \$293.00 |
| * Subject to availability. | | | |
| ① Tractor Requirements: Tractors with the Serial Numbers below (Serial Number list provided by model of tractor) will require a ROPS Frame Kit to update the tractor to be able to accept the backhoe subframe kit. The ROPS frame kit will be provided at No Charge . Please order the correct ROPS frame kit for the tractors specified. | | | |
| BH4992 -- L3130F (Serial #10005 and below) L3130DT/GST/HST (Serial #30115 and below) L3430DT/GST/HST (Serial #30017 and below) | | | |
| BH4993 -- L3830F (Serial #10002 and below) L3830DT/GST/HST (Serial #30016 and below) L4330DT/GST/HST (Serial #30035 and below) L4630DT/GST/HST (Serial #30028 and below) | | | |
| BH4994 -- L5030GST/HST (Serial #30020 and below) | | | |
| ② Not compatible with L4400, must have L4400-1 with LA703(A) Loader. | | | |
| <u>PRIOR MODEL WHOLEGOODS SUBJECT TO AVAILABILITY</u> | | | |
| BH76 Seat Kit | | | |
| BH7681 | * Seat kit for BH76 Backhoe when mounted with the following BH75A Subframes: BH4974, BH4975A, BH4976, and BH4996 | 50 | \$260.00 |
| Mounting and Subframe Kits BH90(A) | | | |
| BH4990* | Mounting Kit for L3130 and L3430 Tractors with BH90(A) Backhoe. Requires LA723 Loader. | 46 | \$293.00 |
| BH4991* | Mounting Kit for L3830, L4330, L4630, and L5030 Tractors with BH90(A) Backhoe. Requires LA723 or LA853 Loader. | 67 | \$293.00 |
| BH4977 | * Subframe required for BH90A only to mount on GL30 and GL40 ROPS tractors. | 354 | \$768.00 |
| BH4979 | * Subframe and Mounting Kit required for BH90A to mount on L4400-1. | 383 | \$1,139.00 |

L Series Backhoes

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|------------------|----------------------|
| BH92 Backhoe "PIN ON" Buckets | | | |
| BT3001 | 12" Bucket | 117 | \$656.00 |
| BT3002A | 16" Bucket | 140 | \$744.00 |
| BT3003A | 18" Bucket | 151 | \$794.00 |
| BT3004 | 24" Bucket | 172 | \$923.00 |
| BT3005A | 30" Bucket | 205 | \$1,065.00 |
| BT3006 | 36" Bucket | 226 | \$1,191.00 |
| BH92 Backhoe "Quick Coupler & Quick Coupler" Buckets | | | |
| BT4550 | BH92 Quick Coupler | 19 | \$660.00 |
| BT4552 | 12" Bucket | 69 | \$797.00 |
| BT4553 | 16" Bucket | 69 | \$841.00 |
| BT4554 | 18" Bucket | 151 | \$885.00 |
| BT4555 | 24" Bucket | 140 | \$1,045.00 |
| BT4557 | 36" Bucket | 140 | \$1,331.00 |
| BH92 Thumb Options & Flip Pads | | | |
| BH4948 | Hydraulic Valve Kit | 55 | \$880.00 |
| BT4598 | Hydraulic Thumb, requires BH4948 Valve kit | 56 | \$2,033.00 |
| BH4949 | 6 Position Mechanical Thumb | 56 | \$893.00 |
| L9467 | Flip Pads, Street Shoes. Two Required per order. | 16 | \$79.00 |
| BH90A Backhoe Buckets | | | |
| BT2901 | 12" Bucket | 117 | \$655.00 |
| BT2902 | 16" Bucket | 140 | \$729.00 |
| BT2903 | 18" Bucket | 151 | \$777.00 |
| BT2904 | 24" Bucket | 172 | \$923.00 |
| BT2905 | 30" Bucket | 205 | \$1,044.00 |
| BT2906 | 36" Bucket | 226 | \$1,191.00 |

L Series Rotary Tiller Matching Chart

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications

| <i>CURRENT</i> Model Tractors | Rotary Tiller Models |
|--|---|
| L2800 L3400 L3700SU L3200 L3800 L2501 L3301 L3901 | FL1021C or FL1021RC (40") FL1271C or FL1271RC (50") FL1521C (60") |
| L4400 L4600 L4701 | FL1521C (60") |
| L3240 L3540 L3940 L4240 L4740 L6040 L5240 L5740 | FL1521C (60") |
| Grand L60 | FL1521C (60") |

L Series Rotary Tillers

L SERIES

NOTE: 3 POINT HITCH MOUNTED IMPLEMENTS REQUIRE FRONT COUNTER WEIGHT
IN THE FORM OF FRONT MOUNTED IMPLEMENTS OR FRONT BUMPER WEIGHTS.

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|---|---------------------|-------------------------|
| *** L SERIES ROTARY TILLERS *** | | | |
| FL1021C | * 40" CUTTING WIDTH Offset or Center Mounted/Skid Shoe Depth Control/ 17.3" dia. Rotor. | 466 | \$2,719.00 |
| FL1021RC | * 40" CUTTING WIDTH Reverse Cutting Rotation/Offset or Center Mounting/ Skid Shoe Depth Control/17.3" diameter Rotor. | 500 | \$2,861.00 |
| FL1271C | * 50" CUTTING WIDTH Offset or Center Mounted/Skid Shoe Depth Control/ 17.3" diameter Rotor. | 493 | \$3,005.00 |
| FL1271RC | * 50" CUTTING WIDTH Reverse Cutting Rotation/Offset or Center Mounting/ Skid Shoe Depth Control/17.3" diameter Rotor. | 493 | \$3,025.00 |
| FL1521C | * 60" CUTTING WIDTH Offset or Center Mounted/Friction Slip Clutch Skid Shoe Depth Control. | 625 | \$3,727.00 |

L Series Front Quick Hitch Mounted Blades

FRONT QUICK HITCH BLADE MATCHING CHART

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications

| | L4466 | L4476 | L4486 | L2172A | L2184 |
|-------|-------|-------|-------|--------|-------|
| L3560 | X | X | X | X | X |
| L4060 | N/A | X | X | X | X |
| L4760 | N/A | X | X | X | X |
| L5060 | N/A | X | X | X | X |
| L5460 | N/A | X | X | X | X |
| L6060 | N/A | X | X | X | X |
| L3240 | X | X | X | X | X |
| L3540 | X | X | X | X | X |
| L3940 | N/A | X | X | X | X |
| L4240 | N/A | X | X | X | X |
| L4740 | N/A | X | X | X | X |
| L5040 | N/A | X | X | X | X |
| L5240 | N/A | X | X | X | X |
| L5740 | N/A | X | X | X | X |

NOTE: THIS IS FOR QUICK REFERENCE ONLY; PLEASE REFER TO THE WHOLE GOOD SELECTIONS TO IDENTIFY WHAT OTHER ITEMS ARE NEEDED FOR THE INSTALLATION OF THE BLADES.

BLADES MAY NOT COVER TRACTOR TREAD WIDTH

L Series Front Quick Hitch Mounted Blades

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|--|------------------|----------------------|
| GRAND L-60 SERIES & GRAND L-40 - FRONT BLADES | | | |
| L4466 | 60" Front Blade - Hyd. Lift and Angle Requires one Quick Hitch (L3240, L3540, L3560) | 500 | \$2,140.00 |
| L4476 | 72" Front Blade - Hyd. Lift and Angle Requires one Quick Hitch (All Grand L40 and L60 Series) | 555 | \$2,273.00 |
| L4486 | 84" Front Blade - Hyd. Lift and Angle Requires one Quick Hitch (All Grand L40 and L60 Series) | 590 | \$2,613.00 |
| L2172A | ② 72" Front Blade - Hyd. Lift and Angle Requires one Quick Hitch and Adapter Kit (All Grand L40 and L60 Series) | 485 | \$2,186.00 |
| L2184 | ② 84" Front Blade - Hyd. Lift and Angle Requires one Quick Hitch and Adapter Kit (All Grand L40 and L60 Series) | 570 | \$2,620.00 |
| Requires One Quick Hitch | | | |
| L4455* | ①③ K1 Manual-Hitch (does not include driveline) ④⑥⑦ | 555 | \$2,000.00 |
| L4554* | ①③④ K3 Auto-Hitch - Equipped with Auto Module ⑤⑥ (includes 4 cylinder driveline) | 720 | \$7,995.00 |
| L4455A | ①③ K1 Manual-Hitch (does not include driveline) ④⑥⑦ | 555 | \$2,000.00 |
| L4554A | ①③④ K3 Auto-Hitch - Equipped with Auto Module ⑤⑥ (includes 4 cylinder driveline) | 720 | \$7,995.00 |
| Grand L-60 Quick Hitch Options | | | |
| L4472 | Auto Module Kit - Required when upgrading a K1 Manual-Hitch L4455(A) to an K3 Auto-Hitch | 160 | \$5,248.00 |
| L4473 | ① Grand L-40 Mount Kit for use of L4554(A) or L4455(A) Quick Hitch on Grand L-40 Series. (Includes shims to mount 4 Point Quick Hitch on tractor) Two kits required if tractor is not equipped with Loader Subframe | 15 | \$53.00 |
| L4456 | ⑦ GPR - Ground Pressure Relief System (requires one Quick Hitch either L4554(A) or L4455(A)) | 150 | \$1,778.00 |
| L4449 | ⑦ GPR Hose Kit & Control Box - (Required when installing L4456 GPR on L4455(A) Manual Hitch) | 22 | TBA |

① To use K1 Manual-Hitch L4455(A) or K3 Auto-Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit(s) L4473. Two kits are required if tractor is not equipped with a loader.

② Requires L4446 Blade Adapter Kit.

③ L4455(A) or L4554(A) Quick Hitch not compatible with RC72-38 Mid-mount Mower.

④ L4455(A) or L4554(A) Quick Hitch not compatible with L2224, L2233A, L2257 Grille Guard or MX8068 Weight Bracket.

⑤ To install on K3 Auto-Hitch L4554(A) a Blade Upgrade Kit L4482 is required

⑥ The use of the Ground Pressure Relief L4456 is not required but recommended for easier maneuverability

⑦ If the GPR is used on L4455(A) K1 Manual-Hitch, L4449 Kit is required.

* Subject to availability.

KUBOTA

L Series Front Quick Hitch Mounted Blades

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|----------------------------|--|---------------------|-------------------------|
| Front Blade Options | | | |
| L4482 | Blade Upgrade Kit - Auto Module Required to upgrade blade to work on K3 Auto-Hitch L4554(A) | 22 | \$799.00 |
| B2766 | 60" Front Blade Rubber Cutting Edge | 50 | \$206.00 |
| B2776 | 72" Front Blade Rubber Cutting Edge | 60 | \$243.00 |
| L2777 | 84" Front Blade Rubber Cutting Edge | 60 | \$275.00 |
| L4446 | Blade Adapter Kit to convert (L2712A or L2184) Blade for use on K1 Manual-Hitch L4455(A). For use on K3 Auto-Hitch L4554(A) will also require Blade Upgrade Kit L4482 | 85 | \$597.00 |

L Series Front Quick Hitch Mounted Blades

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|------------------|----------------------|
| PRIOR MODEL | | | |
| FRONT BLADES (GRAND L-10, L-30, L-40) | | | |
| L2172A | ⑦ 72" Front Blade Hydraulic Lift & Angle. Includes Skid Shoes and single Piece moldboard design. NOTE: Grand L-30 Series requires Quick-Hitch and Control Valve. Grand L-40 Series requires Quick-Hitch only. | 485 | \$2,186.00 |
| L2184 | ⑦ 84" Front Blade Hydraulic Lift & Angle. Includes Skid Shoes and single Piece moldboard design. NOTE: Grand L-30 Series requires Quick-Hitch and Control Valve. Grand L-40 Series requires Quick-Hitch only. | 570 | \$2,620.00 |
| Required for Grand L-40 / L-30 Series Front Blades | | | |
| L2180-1 | ④⑤⑥ Quick-hitch for Grand L30 and L40 Series | 535 | \$1,682.00 |
| L2213A | Joystick Control Valve - Grand L30 Series (4-position ROPS) With Loader installed | 38 | \$705.00 |
| L2223A | Joystick Control Valve - Grand L30 Series (4-position CAB) without Loader Requires: L2187 Valve Mounting Kit | 42 | \$1,022.00 |
| L2187 | Valve Mounting Kit (without Loader) Grand L30 Series for L2223A Valve | 17 | \$80.00 |
| Requires Both Subframe and Joystick For L2172A | | | |
| L2054B | ①② Quick Hitch | 335 | \$1,257.00 |
| L2206 | * Joystick/Hyd. Valve Kit (All Grand L (Ten) Series). Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab) | 42 | \$1,022.00 |
| L2207-1 | ③ Joystick/Hyd. Valve Kit (All Grand L (Ten) Series). Two Spool Valve with Float. * Compatible with Loader ((4) Position) | 25 | \$705.00 |
| L2071 | ② BRACKET/BRACE SUPPORT KIT for Loader compatibility. | 25 | \$109.00 |
| B2776 | 72" Rubber Cutting Edge | 60 | \$243.00 |

- ① The L2054B Quick Hitch is compatible with the LA482(FL) or LA682(FL) Loaders.
- ② L2071 Bracket/Brace Kit replaces single piece Front Loader bracket on LA481/LA681 to provide Loader compatibility.
- ③ Loader must also be installed.
- ④ Prior model, L2180, requires L2188 Upgrade Support Frame Kit.
- ⑤ L2180-1 Quick Hitch not compatible with RC72-38 Mid-mount Mower.
- ⑥ L2180-1 Quick Hitch not compatible with L2224 and L2233A Grille Guard unless lower cross member is removed.

L4554(A)

Fully Auto Hitch).See Grand L-60 & L-40 Series Front Quick Hitch Mounted Blade Section

L Series Snowblower Matching Chart

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications

| | Current Tractor Model | Order Code - Description | Mounting Kit Requirements | Completion Kit | OPTIONAL |
|---|--|---|---|--|--|
| FRONT SNOWBLOWERS | L3240, L3540, L3940 Requires: Tractor Mid-PTO Installation | L2194A ① 62" Front Snowblower (Includes Blower and Chute Rotator) ① Requires L8338 for Mid PTO installation in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST **Can be used on GL-60 see Grand L-60 Series Section** | L2180-1 Quick Hitch L2182 Driveline Kit (L3240, L3540, L3130, L3430, L3830) L2186 Driveline Kit (L3940) | Not required with L2180-1 Quick Hitch | L2179 Electric Chute Deflector L2177 Side Extension Kit (adds 5" overall cut) BL2666A Hydraulic Chute Deflector Kit |
| | L4240, L4740, L5040, L5240, L5740 Requires: Tractor Mid-PTO Installation | L2195A ① 72" Front Snowblower (Includes Blower and Chute Rotator) ① Requires L8338 for Mid PTO installation in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST **Can be used on GL-60 see Grand L-60 Series Section** | L2180-1 Quick Hitch L2186 Driveline Kit (L4240, L4740, L5040, L5240, L5740, L4330, L4630, L5030) | Not required with L2180-1 Quick Hitch | L2179 Electric Chute Deflector L2177 Side Extension Kit (adds 5" overall cut) BL2666A Hydraulic Chute Deflector Kit |
| | L3560, L3240/L3540 Requires: Tractor Mid-PTO Installation on all models and an Internal Gears on ROPS GL60 models. | L4469 ②③ 64" Utility Snowblower (Includes Manual Chute Deflector and Hyd. Chute Rotator) L4479 ②③ 74" Utility Snowblower (Includes Manual Chute Deflector and Hyd. Chute Rotator) | L4554(A) K3 Auto-Hitch and #70001-00623 OR L4455(A) K1 Manual-Hitch And L4483 Driveline Kit (3cyl) | L4432 when using on L4554(A) Hitch OR L4431 when using on L4455(A) Hitch OR | L2177 Side Extension Kit (adds 5" overall cut) BL2666A Hydraulic Chute Deflector Kit L4456 Ground Pressure Relief |
| | L3940 – L5740, L4060, L4760, L5060, L5460, L6060 Requires: Tractor Mid-PTO Installation on all models and an Internal Gears L4240-L5740 ROPS and L4060-L6060 ROPS models. | L4479 ①②③ 74" Utility Snowblower (Includes Manual Chute Deflector and Hyd. Chute Rotator) L4474 ①②③ 74" Commercial Snowblower (Includes Hyd. Chute Deflector and Hyd. Chute Rotator) L4485 ①②③ 80" Commercial Snowblower (Includes Hyd. Chute Deflector and Hyd. Chute Rotator) | L4554(A) K3 Auto-Hitch OR L4455(A) K1 Manual-Hitch And L4484 Driveline Kit (4cyl) | L4479 – requires L4432 when using on L4554(A) Hitch OR L4431 when using on L4455(A) Hitch L4474/L4485 requires L4434 when using L4554(A) OR L4433 when using L4455(A) | L2177 (L4479 only) Side Extension Kit (adds 5" overall cut) BL2666A (L4479 only) Hydraulic Chute Deflector Kit L2470 L2471 74" Teflon Cutting Edge for L4474 80" Teflon Cutting Edge for L4485 L4456 Ground Pressure Relief |
| BL2664: L3200, L3800, L2501, L3301, L3901 L4400, L3240, L3540, L4600, L4701, L3560 L2674: L3940, L4240, L4740, L5040, L5240, L5740, L4060, L4760, L5060, L5460, L6060 | Must order both BL2664 64" REAR Snowblower or L2674 74" REAR Snowblower and BL2665 Manual Chute Rotator or B2784A Hydraulic Chute Rotator | No mounting kit required, units mount to 3-Pt. Hitch. Without Front Loader: (3) Front Weights recommended for BL2664 (4) Front Weights recommended for L2674 | Completion kits not required on rear mounted snowblowers | BL2666A Hyd. Chute Deflector with Electric Selector Valve M2686 Hyd. Chute Deflector B2516A Electric Chute Deflector L2177 Side Extension Kit (Adds 5" to overall cut) | |

- ① Requires L8338 for Mid PTO installation all models and in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST requires L8316 Internal gear kit.
 ② Requires L8387 Mid PTO on all models; Also L8316 internal gear Kit on all Non-Cab L60 Series.
 ③ Grand L40 Series tractors require mount kits L4473 for mounting the hitch on the tractor. Refer to wholegoods numbers.

NOTE: Check all tractor and implement references for proper counter weight requirements.

L Series Front Quick Hitch Mounted Snowblowers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|------------------|----------------------|
| GRAND L-60 & L-40 FRONT QUICK HITCH MOUNTED UTILITY SNOWBLOWERS <i>(Mid PTO Install Required)</i> | | | |
| L4469 | 64" Two-Stage Utility Snowblower - Requires: Completion Kit, Quick Hitch, and Driveline Kit (L3240, L3540, L3560) | 532 | \$4,625.00 |
| L4479 | 74" Two-Stage Utility Snowblower - Requires: Completion Kit, Quick Hitch and Driveline Kit All Grand L40 & L60 Models | 916 | \$5,055.00 |
| L2194A | ① 62" Two-stage Utility Snowblower Requires: L4445 Adapter Kit, Quick Hitch, Driveline Kit, and a Completion Kit (L3240, L3540, L3560, L3940) | 796 | \$4,860.00 |
| L2195A | ① 72" Two-stage Utility Snowblower Requires: L4445 Adapter Kit, Quick Hitch, Driveline Kit and a Completion Kit (L4240 - L5740) (L4060 - L6060) | 835 | \$5,272.00 |
| Requires One Quick Hitch | | | |
| L4455* | ②⑤ ⑥⑦⑧ K1 Manual-Hitch (Does not include driveline - must order either L4483 or L4484 to install) | 555 | \$2,000.00 |
| L4554* | ②⑤ ⑥⑦ K3 Auto-Hitch - Equipped with Auto Module (includes 4 cyl. Driveline, for install on 3 cyl. Model order - #70001-00623 from the parts department instead of complete driveline kit L4483.) | 720 | \$7,995.00 |
| L4455A | ②⑤ ⑥⑦⑧ K1 Manual-Hitch (Does not include driveline - must order either L4483 or L4484 to install) | 555 | \$2,000.00 |
| L4554A | ②⑤ ⑥⑦ K3 Auto-Hitch - Equipped with Auto Module (includes 4 cyl. Driveline, for install on 3 cyl. Model order - #70001-00623 from the parts department instead of complete driveline kit L4483.) | 720 | \$7,995.00 |
| Requires One Completion Kit and One Driveline Kit | | | |
| L4431 | Completion Kit for Utility Snowblower (L4469 or L4479) or (L2194A or L2195A) for use on K1 Manual-Hitch L4455(A) (includes Male Half Driveline and Hyd. Hoses) | 20 | \$263.00 |
| L4432 | Completion Kit for Utility Snowblower (L4469 or L4479) or (L2194A or L2195A) for use on K3 Auto-Hitch L4554(A) (includes Auto Module, Hyd. Cylinder for Chute Deflector, Hyd. Hoses, and PTO Coupler.) | 35 | \$1,137.00 |
| L4483 | 3 Cylinder Driveline Kit for use on L3560-L3240-L3540 | 30 | \$747.00 |
| L4484 | ④ 4 Cylinder Driveline Kit for use on L4060-L6060 and L3940-L5740 Tractors | 31 | \$747.00 |

- ① The L2194A and L2195A Snowblowers can be used on the Grand L-60 Hitches. Requires L4445 Adapter Kit, Driveline Kit, and one Completion Kit for Snowblower
- ② To use K1 Manual-Hitch L4455(A) or K3 Auto-Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit(s) L4473. Two kits are required if tractor is not equipped with a loader.
- ④ Fully Auto Hitch includes 4 cylinder driveline.
- ⑤ L4455(A) or L4554(A) Quick Hitch not compatible with RC72-38 Mid-mount Mower.
- ⑥ L4455(A) or L4554(A) Quick Hitch not compatible with L2224, L2233A, L2257 Grille Guard or MX8068 Weight Bracket
- ⑦ The use of the Ground Pressure Relief L4456 is not required but recommended for easier maneuverability.
- ⑧ If the GPR is used on L4455(A) K1 Manual-Hitch, L4449 Kit is required.

* Subject to availability.

KUBOTA

L Series Front Quick Hitch Mounted Snowblowers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---------------------------------------|---|------------------|----------------------|
| Grand L-60 Quick Hitch Options | | | |
| L4472 | Auto Module Upgrade Kit - Required to upgrade K1 Manual-Hitch L4455(A) to K3 Auto-Hitch | 160 | \$5,248.00 |
| L4456 | ⑧ GPR - Ground Pressure Relief System (requires one Quick Hitch either L4554(A) or L4455(A)) | 150 | \$1,778.00 |
| L4473 | ② Grand L-40 Mount Kit for use of L4554(A) or L4455(A) Quick Hitch on Grand L-40 Series. | 15 | \$53.00 |
| L4449 | ⑧ GPR Hose Kit & Control Box - (Required when installing L4456 GPR on L4455(A) K1 Manual-Hitch) | 22 | \$399.00 |
| Utility Snowblower Options | | | |
| L2177 | Drift Cutter Kit (adds 5" overall cut) | 27 | \$108.00 |
| BL2666A | Hydraulic Chute Deflector Kit (with electric selector valve) | 21 | \$902.00 |
| L4445 | Snowblower Adapter Kit - Required to convert L2194A or L2195A Snowblower for use on K1 Manual-Hitch Requires: Quick Hitch, Driveline Kit, and a Completion Kit | 60 | \$460.00 |

- ② To use K1 Manual-Hitch L4455(A) or K3 Auto-Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit(s) L4473. Two kits are required if tractor is not equipped with a loader.
- ⑧ If the GPR is used on L4455(A) K1 Manual-Hitch, L4449 Kit is required.

KUBOTA

L Series Front Quick Hitch Mounted Snowblowers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|---|------------------|----------------------|
| FRONT QUICK HITCH MOUNTED COMMERCIAL SNOWBLOWERS FOR GRAND L-60 & L-40 SERIES - (Mid PTO Installation Required) | | | |
| L4474 | ③ 74" Commercial Snowblower (Includes 3-piece Hyd. Chute Deflector and Chute Rotation Motor) Requires Snowblower Completion Kit, Mid PTO, Quick Hitch and Driveline Kit (L3940 - L5740) (L4060 - L6060) | 1280 | \$7,725.00 |
| L4485 | ③ 80" Commercial Snowblower (Includes 3-piece Hyd. Chute Deflector and Chute Rotation Motor) Requires Snowblower Completion Kit, Mid PTO, Quick Hitch and Driveline Kit (L3940 - L5740) (L4060 - L6060) | 1320 | \$7,927.00 |
| Requires One Quick Hitch | | | |
| L4455* | ②⑤ ⑥⑦⑧ K1 Manual-Hitch (Does not include driveline - must order either L4483 or L4484 to install) | 555 | \$2,000.00 |
| L4554* | ②⑤ ⑥⑦ K3 Auto-Hitch - Equipped with Auto Module (includes 4 cyl. Not compatible on 3 cylinder models) | 720 | \$7,995.00 |
| L4455A | ②⑤ ⑥⑦⑧ K1 Manual-Hitch (Does not include driveline - must order either L4483 or L4484 to install) | 555 | \$2,000.00 |
| L4554A | ②⑤ ⑥⑦ K3 Auto-Hitch - Equipped with Auto Module (includes 4 cyl. Not compatible on 3 cylinder models) | 720 | \$7,995.00 |
| Requires One Completion Kit and One Driveline Kit | | | |
| L4433 | Completion Kit for Commercial Snowblower (L4474 or L4485) for use on K1 Manual-Hitch L4455(A) (includes Female Driveline and Hyd. Hoses) | 20 | \$263.00 |
| L4434 | Completion Kit for Commercial Snowblower (L4474 or L4485) for use on K3 Auto-Hitch L4554(A) (includes Auto Module, Hyd. Cylinder for Chute Deflector, Hyd. Hoses, and PTO Coupler.) | 35 | \$877.00 |
| L4484 | ④ 4 Cylinder Driveline Kit for use on L4060-L6060 and L3940-L5740 Tractors | 31 | \$747.00 |

- ② To use K1 Manual-Hitch L4455(A) or K3 Auto-Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit(s) L4473. Two kits are required if tractor is not equipped with a loader.
- ③ Commercial Snowblower is not to be used on 3 Cylinder Models L3560, L3240, L3540
- ④ K3 Auto-Hitch includes a 4 cylinder driveline kit.
- ⑤ L4455(A) or L4554(A) Quick Hitch not compatible with RC72-38 Mid-mount Mower.
- ⑥ L4455(A) or L4554(A) Quick Hitch not compatible with L2224, L2233A, L2257 Grille Guard or MX8068 Weight Bracket.
- ⑦ The use of the Ground Pressure Relief L4456 is not required but recommended for easier maneuverability.
- ⑧ If the GPR is used on L4455(A) K1 Manual-Hitch, L4449 Kit is required.

* Subject to availability.

KUBOTA

L Series Front Quick Hitch Mounted Snowblowers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---------------------------------------|---|------------------|----------------------|
| Grand L-60 Quick Hitch Options | | | |
| L4472 | Auto Module Upgrade Kit - Required to upgrade K1 Manual-Hitch L4455(A) to K3 Auto-Hitch | 160 | \$5,248.00 |
| L4456 | ⑧ GPR - Ground Pressure Relief System (requires one Quick Hitch either L4554(A) or L4455(A)) | 150 | \$1,778.00 |
| L4473 | ② Grand L-40 Mount Kit for use of L4554(A) or L4455(A) Quick Hitch on Grand L-40 Series. | 15 | \$53.00 |
| L4449 | ⑧ GPR Hose Kit & Control Box - (Required when installing L4456 GPR on L4455(A) K1 Manual-Hitch) | 22 | \$399.00 |
| Commercial Snowblower Options | | | |
| L2470 | 74" Teflon Cutting Edge - For Commercial Snowblowers | 15 | \$283.00 |
| L2471 | 80" Teflon Cutting Edge - For Commercial Snowblowers | 15 | \$315.00 |

- ② To use Manual 4 Point Quick Hitch L4455(A) or Fully Auto 4 Point Quick Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit(s) L4473. Two kits are required if tractor is not equipped with a loader.
- ⑧ If the GPR is used on L4455(A) Manual Quick Hitch, L4449 Kit is required.

KUBOTA

L Series Front Quick Hitch Mounted Snowblowers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|---|------------------|----------------------|
| FRONT SNOWBLOWERS FOR GRAND L-40, GRAND L-30 SERIES TRACTORS ① | | | |
| L3240, L3540, L3940, L3130, L3430, L3830 | | | |
| L2194A | ⑤ 62" Two-stage Commercial Snowblower Requires: L2180-1 Quick Hitch, Mid PTO Kit and Drive Line Kit L-40 Series | 796 | \$4,860.00 |
| L4240, L4740, L5040, L5240, L5740, L4330, L4630, L5030 | | | |
| L2195A | ⑤ 72" Two-stage Commercial Snowblower Requires: L2180-1 Quick Hitch, Mid PTO Kit and Drive Line Kit L-40 Series | 835 | \$5,272.00 |
| L3130, L3430, L3830, L4330, L4630, L5030 (Mid-PTO KIT Installation Required) | | | |
| L2174A* | 62" Two-stage Commercial Snowblower Requires: L2175B Chute Kit. Also must order L2180-1 Quick-hitch Sub-frame, Drive Line Kit (see selection) And Valve kit for complete installation. | 430 | \$2,221.00 |
| L2185* | 72" Two-stage Commercial Snowblower. Requires: L2175B Chute Kit. Also must order L2180-1 Quick-hitch Sub-frame, Drive Line Kit (see selection) and Valve kit for complete installation. | 430 | \$2,564.00 |
| L2175B* | Chute Kit. Required for L2174A or L2185. Hydraulic Chute rotation standard. | 180 | \$1,988.00 |
| <u>Required and Optional Accessories</u> | | | |
| L2180-1 | ②③④ Quick-hitch for "ALL" GL30 and GL40 Series | 535 | \$1,682.00 |
| L2213A | Joystick Control Valve (4-position ROPS) With Loader installed | 38 | \$705.00 |
| L2223A | Joystick Control Valve (4-position CAB) without Loader Requires: L2187 Valve Mounting Kit | 42 | \$1,022.00 |
| L2187 | * Valve Mounting Kit (without Loader) Requires: L2223 Joystick Control Valve | 17 | \$80.00 |
| L2182 | Drive Line Kit Required for L2194A L3240, L3540, L3130, L3430, L3830 | 32 | \$618.00 |
| L2186 | Drive Line Kit Required for L2195A L3940, L4240, L4740, L5040, L5240, L5740, L4330, L4630, L5030 | 33 | \$682.00 |
| L2179 | Electric Chute Deflector For L2174A, L2185, L2194 or L2195 | 16 | \$773.00 |
| L2177 | Drift Cutter Kit (adds 5" overall cut) | 27 | \$108.00 |
| L2188 | * Upgrade Support Frame Kit for L2180 only (L2180-1 includes L2188) | 5 | \$101.00 |
| BL2666A | Hydraulic Chute Deflector for BL2664 or L2674 | 21 | \$902.00 |
| B2516A | Electric Chute Deflector for BL2664 or L2674 | 8 | \$597.00 |

* Subject to availability

① Track width may not be covered with all tire combinations.

② Prior model L2180 requires L2188 Upgrade Support Frame Kit.

③ L2180-1 Quick Hitch not compatible with RC72-38 Mid-mount Mower.

④ L2180-1 Quick Hitch not compatible with L2224 and L2233A Grille Guard unless lower cross member is removed.

⑤ The Grand L40 Series snowblowers can also be used on the Grand L40 with the Grand L60 Quick Hitches (L4455(A) Manual Hitch and L4554(A) Fully Auto Hitch). See Grand L-60 & L-40 Series Front Quick Hitch Mounted Snowblower Section

Prices and specifications subject to change without notice. F.O.B. KTC designated shipping point.
Complete revision November 14, 2014.

KUBOTA

L Series Front Quick Hitch Mounted Snowblowers

| ORDER CODE | | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|---|---|------------------|----------------------|
| SNOWBLOWERS FOR 10 SERIES TRACTORS | | | | |
| L2174A | * | SNOWBLOWER (Must order L2175B) 62", Two-Stage Commercial Front Snowblower. Requires L2054B Quick-Hitch Subframe, L2175A Chute Kit, L2076 or L2086, L2206, L2207 (only with LA482 or LA682 Loader) Joystick/Hyd Valve Kit and L2051A Mid-PTO Kit. | 430 | \$2,221.00 |
| L2175B | * | Chute Kit, requires L2174A Snowblower. Hydraulic chute rotation standard. | 180 | \$1,988.00 |
| L2179 | | Electric Chute Deflector | 16 | \$773.00 |
| L2177 | | Drift Cutter Kit | 27 | \$108.00 |

SUBFRAME, CONTROL VALVE, AND MID-PTO KIT FOR L2174A (1 Each Required)

| | | | | |
|---------|---|---|-----|------------|
| L2054B | * | Quick Hitch | 335 | \$1,257.00 |
| L2206 | * | Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab) | 42 | \$1,022.00 |
| L2207-1 | * | Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST. Two Spool Valve with Float (requires LA482/LA682 Loader). Compatible with Loader. ((4) Position) | 25 | \$705.00 |
| L2086 | * | Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab) | 56 | \$907.00 |
| L2051A | * | Mid-PTO Kit | 25 | \$485.00 |
| L2071 | * | Front Support Kit | 25 | \$109.00 |

* Subject to availability.

- ① Requires Rear Remote and BL2666 electric selector valve kit if only one rear remote is used when installing Hydraulic Deflector and Chute Rotator on the same Snowblower.
- ② Prior model L2180 requires L2188 Upgrade Support Frame Kit.
- ③ L2180-1 Quick Hitch not compatible with RC72-38 Mid-mount Mower.
- ④ L2180-1 Quick Hitch not compatible with L2224 and L2233A Grille Guard unless lower cross member is removed.

L Series Rear Mount Snowblowers

Rear-Mount Snowblowers for L2501, L2800, L3301, L3400, L3700SU, L3200, L3800, L3901, L4400, L4400-1, L4600, L4701, Grand L-30, Grand L-40 Series, and Grand L-60 Series^{① ②}

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|------------|--|------------------|----------------------|
| BL2664 | 64" Two-stage Commercial Snowblower Mounts to Category I 3-point hitch Requires BL2665 Manual Rotator chute or B2784A hydraulic chute rotator. | 681 | \$2,677.00 |
| L2674 | 74" Two-stage Commercial Snowblower Mounts to Category I 3-point hitch Requires BL2665 Manual Rotator chute or B2784A hydraulic chute rotator. | 760 | \$3,377.00 |
| BL2665 | Manual chute Rotator for BL2664 or L2674 | 11 | \$161.00 |
| B2784A | ③ Hydraulic Chute Rotator for BL2664 or L2674 | 12 | \$787.00 |
| BL2666A | Hydraulic Chute Deflector Kit (with electric selector valve) for B2674 and BL2664) Requires B2784A | 21 | \$902.00 |
| B2516A | Electric Chute Deflector for BL2664 or L2674 | 8 | \$597.00 |
| M2686 | Hydraulic Chute Deflector Kit (Requires second rear remote hydraulic outlet if B2784A Chute Rotation Kit is ordered | 21 | \$342.00 |
| L2177 | Drift Cutter Kit (adds 5" overall cut) | 27 | \$108.00 |

* Subject to availability

① Track width may not be covered with all tire combinations.

② If mounting snowblowers without a loader, the use of front weights is recommended. (3) weights are recommended for the BL2664 and (4) weights for the L2674.

③ Requires rear remote. BL2666A has an electric selector valve, so only one rear remote is required if installing hydraulic deflector and hydraulic chute rotator on the same snowblower. See rear remote section.

L Series Rotary Sweepers

ROTARY SWEEPER MATCHING CHART

| Current Tractor Model | Order Code - Description | Mounting Kit Requirements | Completion Kit | OPTIONAL |
|---|---|---|---|--|
| L3240, L3540 Requires: Tractor Mid-PTO Installation | L2160 Ⓞ 60" Rotary Sweeper (51.25" at full angle) | L2180-1 Quick Hitch L2182 Driveline Kit (L3240, L3540) | Not required with L2180-1 Quick Hitch | BL2178 Side Caster Wheels B2168 60" Rubber Dust Deflector |
| L3240, L3540, L3940, L4240, L4740 L5040, L5240 L5740 Requires: Tractor Mid-PTO Installation | L2164 Ⓞ 72" Rotary Sweeper (62.5 at full angle) Ⓞ Requires L8338 for Mid PTO installation in L4240DT/GST/HST, L4740GST/HST, L5040GST, L5240HST, and L5740HST. | L2180-1 Quick Hitch L2182 Driveline Kit (L3240, L3540) L2186 Driveline Kit (L4240, L4740, L5040, L5240, L5740 L4330, L4630, L5030) | Not required with L2180-1 Quick Hitch | BL2178 Side Caster Wheels B2169 72" Rubber Dust Deflector |
| L3560 L3240/L3540 Requires: Tractor Mid-PTO Installation on all models and an Internal Gears on ROPS GL60 models. | L4467 60" Rotary Sweeper – 22" Diameter | L4554(A) K3 Auto- Hitch and #70001-00623 OR L4455(A) K1 Manual-Hitch And L4483 Driveline Kit (3cyl) | L4475 when using on L4554(A) Hitch OR L4488 when using on L4455(A) Hitch | BL2178 Side Caster Wheels B2168 60" Rubber Dust Deflector 4456 Ground Pressure Relief |
| L3240 – L5740 L3560 - L6060 Requires: Tractor Mid-PTO Installation on all models and an Internal Gears L4240-L5740 ROPS and L4060- L6060 ROPS models. | L4477 72" Rotary Sweeper – 22" Diameter | L4554(A) K3 Auto- Hitch and #70001-00623 On 3 Cylinder models (4 Cyl. Driveline Kit include with L4554(A)) L4455(A) K1 Manual-Hitch and L4484 Driveline Kit (4cyl) Or L4483 Driveline Kit (3cyl) | L4475 when using on L4554(A) Hitch OR L4488 when using on L4455(A) Hitch | BL2178 Side Caster Wheels B2169 72" Rubber Dust Deflector L4456 Ground Pressure Relief |

FRONT ROTARY SWEEPERS

Charts for Quick Reference Only, Please refer to Wholegoods Numbers for proper applications

L Series Rotary Sweepers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|---|------------------|----------------------|
| ROTARY SWEEPER GRAND L-60 & L-40 SERIES (Mid PTO Installation Required) | | | |
| L4467 | 60" Rotary Broom w/ 22" Diameter Power Angle Standard, Includes Hitch Lift Limiter Requires Quick-Hitch, Driveline Kit, and Completion Kit (L3560, L3240, L3540) | 460 | \$3,922.00 |
| L4477 | 72" Rotary Broom w/ 22" Diameter Power Angle Standard, Includes Hitch Lift Limiter Requires Quick-Hitch, Driveline Kit, and Completion Kit (All Grand L40 and Grand L60 Models) | 550 | \$4,566.00 |
| Requires One Quick Hitch | | | |
| L4455* | ①② K1 Manual-Hitch (Does not include driveline - ③⑤⑥ must order either L4483 or L4484 to install) | 555 | \$2,000.00 |
| L4554* | ①② K3 Auto-Hitch - Equipped with Auto Module ③⑤ (includes 4 cyl. Driveline, for install on 3 cyl. Model order - #70001-00623 from the parts department instead of complete driveline kit L4483.) | 720 | \$7,995.00 |
| L4455A | ①② K1 Manual-Hitch (Does not include driveline - ③⑤⑥ must order either L4483 or L4484 to install) | 555 | \$2,000.00 |
| L4554A | ①② K3 Auto-Hitch - Equipped with Auto Module ③⑤ (includes 4 cyl. Driveline, for install on 3 cyl. Model order - #70001-00623 from the parts department instead of complete driveline kit L4483.) | 720 | \$7,995.00 |
| Requires One Completion Kit and One Driveline Kit | | | |
| L4488 | Completion Kit for Broom for use on K1 Manual-Hitch. Includes Female Driveline, and Hyd. Hoses. | 20 | \$406.00 |
| L4475 | Completion Kit for Broom for use on K3 Auto-Hitch. Includes Auto Module, Hyd. Hoses, and PTO Coupler | 22 | \$866.00 |
| L4483 | 3 Cylinder Driveline Kit for use on L3560-L3240-L3540 | 30 | \$747.00 |
| L4484 | ④ 4 Cylinder Driveline Kit for use on L4060-L6060 and L3940-L5740 Tractors | 31 | \$747.00 |

- ① To use K1 Manual-Hitch L4455(A) or K3 Auto-Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit(s) L4473. Two kits are required if tractor is not equipped with a loader.
- ② L4455(A) or L4554(A) Quick Hitch not compatible with RC72-38 Mid-mount Mower.
- ③ L4455(A) or L4554(A) Quick Hitch not compatible with L2224, L2233A, L2257 Grille Guard or MX8068 Weight Bracket.
- ④ K3 Auto-Hitch includes 4 cylinder driveline kit.
- ⑤ The use of the Ground Pressure Relief L4456 is not required but recommended for easier maneuverability.
- ⑥ If the GPR is used on L4455(A) K1 Manual-Hitch, L4449 Kit is required.

* Subject to availability.

L Series Rotary Sweepers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|--|------------------|----------------------|
| Grand L-60 Series Quick Hitch Options | | | |
| L4472 | Auto Module Upgrade Kit - Required to upgrade K1 Manual-Hitch (L4455) to K3 Auto-Hitch | 160 | \$5,248.00 |
| L4456 | ⑥ GPR - Ground Pressure Relief System (requires one Quick Hitch either L4554 or L4455) | 150 | \$1,778.00 |
| L4473 | ① Grand L-40 Mount Kit for use of L4554 or L4455 Quick on Grand L-40 Series (Includes shims to mount on GL-40) 2 Kits required if tractor is not equipped with Loader Subframe | 15 | \$53.00 |
| L4449 | ⑥ GPR Hose Kit & Control Box - (Required when installing L4456 GPR on L4455(A) K1 Manual-Hitch) | 22 | \$399.00 |
| Rotary Sweeper Options | | | |
| BL2178 | Side Caster Wheel Kit | 47 | \$439.00 |
| L2168 | Rubber Dust Deflector 60" | 31 | \$153.00 |
| L2169 | Rubber Dust Deflector 72" | 36 | \$180.00 |

- ① To use K1 Manual-Hitch L4455(A) or K3 Auto-Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit(s) L4473. Two kits are required if tractor is not equipped with a loader.
- ⑥ If the GPR is used on L4455(A) K1 Manual-Hitch, L4449 Kit is required.

L Series Rotary Sweepers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|------------------|----------------------|
| PRIOR MODELS | | | |
| ROTARY SWEEPERS Grand L-40, L-30, L-10 (Mid-PTO KIT Installation Required) | | | |
| L2162 | 60" Rotary Sweeper Power Angle Standard Requires Quick-Hitch, Driveline Kit Grand L30/L10 also requires Control Valve | 570 | \$3,539.00 |
| L2164 | 72" Rotary Sweeper Power Angle Standard Requires Quick-hitch, Drive Line Kit Grand L30/L10 also requires Control Valve. | 570 | \$4,009.00 |
| Required for Grand L-40 Series Rotary Sweepers | | | |
| L2180-1 | ①②③ Quick-hitch for "ALL" 40 Series | 535 | \$1,682.00 |
| L2182 | Drive Line Kit (Required for L3240, L3540) | 32 | \$618.00 |
| L2186 | Drive Line Kit (Required for L3940, L4240, L5040, L5240, L5740) | 33 | \$682.00 |
| Required for Grand L-30 Series Rotary Sweepers | | | |
| L2180-1 | ①③ Quick-hitch for "ALL" 30 Series | 535 | \$1,682.00 |
| L2213A | * Joystick Control Valve (4-position ROPS) With Loader installed | 38 | \$705.00 |
| L2223A | * Joystick Control Valve (4-position CAB) without Loader Requires: L2187 Valve Mounting Kit | 42 | \$1,022.00 |
| L2187 | * Valve Mounting Kit (without Loader) Requires: L2223(A) Joystick Control Valve | 17 | \$80.00 |
| L2182 | Drive Line Kit Required for L3130, L3430, L3830 | 32 | \$618.00 |
| L2186 | Drive Line Kit Required for L4330, L4630, L5030 (Replaces L2183) | 33 | \$682.00 |
| Rotary Sweeper Options | | | |
| L2168 | Rubber Dust Deflector for L2162 | 31 | \$153.00 |
| L2169 | Rubber Dust Deflector for L2164 | 36 | \$180.00 |

① Prior model L2180 requires L2188 Upgrade Support Frame Kit.

② L2180-1 Quick Hitch not compatible with RC72-38 Mid-mount Mower.

③ L2180-1 Quick Hitch not compatible with L2224 and L2233A Grille Guard unless lower cross member is removed.

* Subject to Availability

L Series Rotary Sweepers

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|--|--|------------------|----------------------|
| PRIOR MODELS | | | |
| <u>Required for Grand L-10 Series Rotary Sweepers</u> | | | |
| L2206 | * Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab) | 42 | \$1,022.00 |
| L2207-1 | * Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), and L3710HST. Two Spool Valve with Float (requires LA482/LA682 Loader). Compatible with Loader. ((4) Position) | 25 | \$705.00 |
| L2086 | * Joystick/Hyd. Valve Kit For L3010 (all), L3410 (all), L3710HST/HSTC. Two Spool Valve with Float. Compatible with Loader. ((4) Position Cab) | 56 | \$907.00 |
| L2054B | * Quick Hitch | 335 | \$1,257.00 |
| L2051A | * Mid-PTO Kit | 25 | \$485.00 |
| <u>Optional Attachments</u> | | | |
| BL2178 | * Side Caster Wheels (Kit) for L2062C Sweeper | 47 | \$439.00 |
| L2188 | * Upgrade Support Frame Kit for L2180 only (L2180-1 includes L2188) | 5 | \$101.00 |

* Subject to availability.

L Series Front Flail Mower

| ORDER CODE | DESCRIPTION | APPROX. SHIP WT. | SUGGESTED LIST PRICE |
|---|--|------------------|----------------------|
| FRONT FLAIL MOWER - GRAND L60 & GRAND L40 SERIES (Mid PTO Installation Required) | | | |
| L4457 | 72" Front Flail Mower - Includes Y-Knives Requires - Quick Hitch, Completion Kit, and Driveline Kit. (All Grand L60 & L40 4 Cylinder Models) | 1400 | \$7,292.00 |
| Requires One Quick Hitch | | | |
| L4455 | ①② K1 Manual-Hitch (Does not include driveline - ③⑤⑥ must order L4484 to install) | 555 | \$2,000.00 |
| L4554 | ①② K3 Auto-Hitch - Equipped with Auto Module ③⑤ (includes 4 cylinder driveline) | 720 | \$7,995.00 |
| L4455A | ①② K1 Manual-Hitch (Does not include driveline - ③⑤⑥ must order L4484 to install) | 555 | \$2,000.00 |
| L4554A | ①② K3 Auto-Hitch - Equipped with Auto Module ③⑤ (includes 4 cyl. Driveline) | 720 | \$7,995.00 |
| Requires One Completion Kit and One Driveline Kit | | | |
| L4448 | Completion Kit for Flail for use on K1 Manual-Hitch Hitch. Includes Female Driveline, and Hyd. Hoses. | 20 | \$297.00 |
| L4458 | Completion Kit for Flail for use on K3 Auto-Hitch Hitch. Includes Auto Module, Hyd. Hoses, and PTO Coupler | 22 | \$632.00 |
| L4484 | 4 Cylinder Driveline Kit for use on L4060-L6060 and L3940- L5740 Tractors | 31 | \$747.00 |
| Grand L-60 Series Quick Hitch Options | | | |
| L4472 | Auto Module Upgrade Kit - Required to upgrade Manual K1 Manual-Hitch L4455(A) to K3 Auto-Hitch | 160 | \$5,248.00 |
| L4473 | ① Grand L-40 Mount Kit for use of L4554(A) or L4455(A) Quick on Grand L-40 Series (Includes shims to mount on GL-40) 2 Kits required if tractor is not equipped with Loader Subframe | 15 | \$53.00 |
| L4456 | ⑥ GPR - Ground Pressure Relief System (Requires one Quick Hitch either L4554(A) or L4455(A)) | 150 | \$1,778.00 |
| L4449 | ⑥ GPR Hose Kit & Control Box - (Required when installing L4456 GPR on L4455(A) K1 Manual-Hitch) | 22 | \$399.00 |
| Front Flail Mower Options | | | |
| L4437 | Replacement Y-Knife Set - includes 68 Knives | 380 | \$472.00 |
| L4438 | Replacement Hammer Knife Set - includes 34 Knives | 380 | \$606.00 |
| L4439 | Replacement Duck Foot Knife Set - includes 34 Knives | 380 | \$518.00 |

① To use K1 Manual-Hitch L4455(A) or K3 Auto-Hitch L4554(A) on Grand L-40 Series, it requires Grand L-40 Mount Kit L4473. Two kits required if tractor is not equipped with Loader Subframe.

② L4455(A) or L4554(A) Quick Hitch not compatible with RC72-38 Mid-mount Mower.

③ L4455(A) or L4554(A) Quick Hitch not compatible with L2224, L2233A, L2257 Grille Guard or MX8068 Weight Bracket

⑤ The use of the Ground Pressure Relief L4456 is not required but recommended for easier maneuverability

⑥ If the GPR is used on L4455(A) K1 Manual-Hitch, L4449 Kit is required.