PB1001 Integral One Bottom Turning Plow

Equipment for Base Machine

```
Hitch:
  Lift-type, Category I,
  not iMatch Compatible
One, 14 In. (355.6 mm) Moldboard
Transport Length:
  45 In. ( 1,143 mm)
Transport Width:
  33 In. (838.2 mm)
Transport Height:
  40.5 In. (1,028.7 mm)
Tractor Engine HP Range:
  25 - 50 HP
```

```
Moldboard Dimensions:
  14 In. (355.6 mm) (W) x
  21 In. (533.4 mm) (L) x
  16 In. (406.4 mm) (H)
Parking Stand Included
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3431XF		PB1001 Integral One Bottom Turning Plow *Order in multiples of two.*	758.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TITE511154	French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals *PB1001 and PB1002*	14.10

PB1001 Integral One Bottom Turning Plow
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PB1002 Integral Two Bottom Turning Plow

Equipment for Base Machine

```
Hitch:
  Lift-type, Category I,
  not iMatch Compatible
Two, 14 In. (355.6 mm) Moldboards
Transport Length:
  71 In. ( 1,803.4 mm)
Transport Width:
  40 In. (1,016 mm)
Transport Height:
  40.5 In. (1,028.7 mm)
Tractor Engine HP Range:
  25 - 50 HP
Moldboard Dimensions:
  14 In. (355.6 mm) (W) x
  21 In. (533.4 mm) (L) x
  16 In. (406.4 mm) (H)
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3432XF		PB1002 Integral Two Bottom Turning Plow *Order in multiples of two.*	1,243.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TITE511154	French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals *PB1001 and PB1002*	14.10

PB1002 Integral Two Bottom Turning Plow
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB2048 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
iMatch Compatible: Yes
Working Width: 48 In.
Tractor HP: 17 to 45 HP
Tailgate: Fixed
Shipping Weight:
  758 lbs. - (Pair)
Shanks: (4) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Assembly/Set up Time:
  30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 355 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1041XF		BB2048 Standard Duty Box Blade *Order in multiples of two.*	979.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	31.60

BB2048 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB2048L Limited Category I Standard Duty Box Blade

Equipment for Base Machine

Capacity:
  6.6 Cubic Foot
Tractor HP (Maximum): 25 HP
Cutting Edges:
  (2) 1/2 In. x 6 Reversible
Scarifier Shanks:
  3-Position with Holes
Scarifier Shank Points:
  3 Replaceable, Hardened Points
Beam Size: 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  3/8 In. x 1 In. Bar Inside Tube
End Plate Thickness: 3/16 In.
Working Width: 48 In.
Height: 14 In.
Depth: 17 In.
Tailgate: Fixed

3-Point Hitch:
  Limited Category I (Aftermarket
  Category 0 Lift Pins Available)
Mast Design:
  Bolt-up with 1/4 In. Plates
Moldboard Thickness: 7 Gauge
Assembly/Set-up Time:
  30 Minutes (Approximate)
Approximate Operating Weight: 275 lbs.
Shipping Weight: 636 lbs.
Packaged 2 per Pallet

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1051XF		BB2048L Limited Category I Standard Duty Box Blade *Order in multiples of two.*	801.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	31.60

BB2048L Limited Category I Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB2060 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
iMatch Compatible: Yes
Working Width: 60 In.
Tractor HP: 19 to 55 HP
Tailgate: Fixed
Shipping Weight:
  918 lbs. - (Pair)
Shanks: (4) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
  30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 425 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1042XF		BB2060 Standard Duty Box Blade *Order in multiples of two.*	1,047.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	31.60

BB2060 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB2065 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
IMatch Compatible: Yes
Working Width: 66 In.
Tractor HP: 23 to 55 HP
Tailgate: Fixed
Shipping Weight:
  988 lbs. - (Pair)
Shanks: (4) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Assembly/Set up Time:
  30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 460 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1043XF		BB2065 Standard Duty Box Blade *Order in multiples of two.*	1,154.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	31.60

BB2065 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB2072 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
iMatch Compatible: Yes
Working Width: 72 In.
Tractor HP: 27 to 55 HP
Tailgate: Fixed
Shipping Weight:
  1056 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Replaceable, Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt-up with 1/4 In. Plates
Duty: Standard Duty
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Assembly/Set up Time:
  30 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 494 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1044XF		BB2072 Standard Duty Box Blade *Order in multiples of two.*	1,200.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	31.60

BB2072 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB2172 Medium Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
Working Width: 72 In.
Height: 33-1/2 In.
Depth: 31 In.
Capacity:
  19 Cubic Foot
Tractor HP: 70 HP Maximum
Tailgate:
  Floating/Removable
Shanks:
  (6) Replaceable
Beam Size:
  4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1 In. x 3/8 In. Backing Strip
End Plate Thickness:
  3/8 In. with a 3/8 In. x 3 In.
  Reinforced Bottom Edge

Moldboard Thickness: 3/16 In.
Duty: Medium
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate)
Operating Weight:
  585 lbs. (Approximate)
Shipping Weight:
  675 lbs. (Approximate)
Packaged 1 Per Pallet
Mast: Bolt-up with 3/8 In. Plates
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1061XF		BB2172 Medium Duty Box Blade	1,667.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	31.60

BB2172 Medium Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB2184 Medium Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I, iMatch Compatible
  (Quick-Attach System)
Working Width: 84 In.
Height: 33-1/2 In.
Depth: 31 In.
Capacity: 22.3 Cubic Foot
Tractor HP (Maximum): 70 HP
Tailgate:
  Floating/Removable
Shanks: (7) Replaceable
Beam Size: 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1 In. x 3/8 In. Backing Strip
End Plate Thickness:
  3/8 In. with a 3/8 In. x 3 In.
  Reinforced Bottom Edge
Duty: Medium

Moldboard Thickness: 3/16 In.
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate)
Operating Weight:
  667 lbs. (Approximate)
Shipping Weight:
  757 lbs. (Approximate)
Packaged 1 Per Pallet
Mast: Bolt-up with 3/8 In. Plates
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1062XF		BB2184 Medium Duty Box Blade	1,826.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101371	French Operator's Manual and Decal Kit (BB20, BB21 and BB20L Series)	31.60

BB2184 Medium Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB3272 - 6 Ft. Construction Grade Box Blade with Scarifiers

Equipment for Base Machine

Tailgate:
  Hinged Tailgate
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Balanced Design
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design:
  High Capacity Box, No Gussets
  or Obstructions
Hydraulic Opening: NA
Hydraulic Kit: NA
Capacity (Cubic Foot):
  21 Cubic Foot
Tractor HP: 80 HP Maximum
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (7) Replaceable
Beam Size:
  4 In. x 4 In. x 3/8 In.
Beam Reinforcement: Yes
End Plate Thickness: 1/2 In.
Working Width: 72 In.
Height: 20 In.
Depth: 26-1/2 In.
Duty: Construction Grade
Hitch Type:
  Category I and Category II
  Quick Hitch Compatible
Mast Design: Welded
Assembly/Set-Up Time: 15 Minutes
Operating Weight: 790 lbs.
Shipping Weight: 830 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: New
Paint Color: Construction Yellow

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1081XF		BB3272 - 6 Ft. Construction Grade Box Blade with Scarifiers *Construction yellow.*	2,330.00

BB3272 - 6 Ft. Construction Grade Box Blade with Scarifiers
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB3284 - 7 Ft. Construction Grade Box Blade with Scarifiers

Equipment for Base Machine

Tailgate:
  Hinged Tailgate
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Balanced Design
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design:
  High Capacity Box, No Gussets
  or Obstructions
Hydraulic Opening: NA
Hydraulic Kit: NA
Capacity (Cubic Foot):
  24.50 Cubic Foot
Tractor HP: 80 HP Maximum
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (8) Replaceable
Beam Size:
  4 In. x 4 In. x 3/8 In.
Beam Reinforcement: Yes
End Plate Thickness: 1/2 In.
Working Width: 84 In.
Height: 20 In.
Depth: 26-1/2 In.
Duty: Construction Grade
Hitch Type:
  Category I and Category II
  Quick Hitch Compatible
Mast Design: Welded
Assembly/Set-Up Time: 15 Minutes
Operating Weight: 885 lbs.
Shipping Weight: 925 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: New
Paint Color: Construction Yellow

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1082XF		BB3284 - 7 Ft. Construction Grade Box Blade with Scarifiers *Construction yellow.*	2,562.00

BB3284 - 7 Ft. Construction Grade Box Blade with Scarifiers
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB3296 - 8 Ft. Construction Grade Box Blade with Scarifiers

Equipment for Base Machine

Tailgate:
  Hinged Tailgate
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Balanced Design
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design:
  High Capacity Box, No Gussets
  or Obstructions
Hydraulic Opening: NA
Hydraulic Kit: NA
Capacity (Cubic Foot):
  28 Cubic Foot
Tractor HP: 80 HP Maximum
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (9) Replaceable
Beam Size:
  4 In. x 4 In. x 3/8 In.
Beam Reinforcement: Yes
End Plate Thickness: 1/2 In.
Working Width: 96 In.
Height: 20 In.
Depth: 26-1/2 In.
Duty: Construction Grade
Hitch Type:
  Category I and Category II
  Quick Hitch Compatible
Mast Design: Welded
Assembly/Set-Up Time: 15 Minutes
Operating Weight: 1010 lbs.
Shipping Weight: 1050 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: New
Paint Color: Construction Yellow

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1083XF		BB3296 - 8 Ft. Construction Grade Box Blade with Scarifiers *Construction yellow.*	2,841.00

BB3296 - 8 Ft. Construction Grade Box Blade with Scarifiers
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4160 - 5 Ft. Hydraulic Scarifier Box Blade - Low Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I iMatch Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: Low Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit And Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  21.8 Cubic Foot
Tractor HP: Up to 50 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (6) Replaceable
Beam Size:
  Main Beam - 4 In. x 4 In. x 1/4 In.
  Shank Beam - 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 3/4 In. Bar
End Plate Thickness: 3/8 In.
Working Width: 60 In.
Height: 20 In.
Depth: 33 In.
Duty: Medium
Hitch Type:
  Category I iMatch Compatible
Mast Design:
  Welded 3/8 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 725 lbs.
Shipping Weight: 765 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 3/16 In.
Manufacturer Model: TB30-60H
Paint Color: Green

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1101XF	BB4160 - 5 Ft. Hydraulic Scarifier Box Blade - Low Back *Green only.*	2,955.00

BB4160 - 5 Ft. Hydraulic Scarifier Box Blade - Low Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4166 - 5 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I iMatch Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: Low Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  24 Cubic Foot
Tractor HP: Up to 50 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (6) Replaceable
Beam Size:
  Main Beam - 4 In. x 4 In. x 1/4 In.
  Shank Beam - 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 3/4 In. Bar
End Plate Thickness: 3/8 In.
Working Width: 66 In.
Height: 20 In.
Depth: 33 In.
Duty: Medium
Hitch Type:
  Category I iMatch Compatible
Mast Design:
  Welded 3/8 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 772 lbs.
Shipping Weight: 812 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 3/16 In.
Manufacturer Model: TB30-66H
Paint Color: Green

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1102XF	BB4166 - 5 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back *Green only.*	3,148.00

BB4166 - 5 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4172 - 6 Ft. Hydraulic Scarifier Box Blade - Low Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I iMatch Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: Low Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  26.2 Cubic Foot
Tractor HP: Up to 50 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (6) Replaceable
Beam Size:
  Main Beam - 4 In. x 4 In. x 1/4 In.
  Shank Beam - 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 3/4 In. Bar
End Plate Thickness: 3/8 In.
Working Width: 72 In.
Height: 20 In.
Depth: 33 In.
Duty: Medium
Hitch Type:
  Category I iMatch Compatible
Mast Design:
  Welded 3/8 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 815 lbs.
Shipping Weight: 855 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 3/16 In.
Manufacturer Model: TB30-72H
Paint Color: Green

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1103XF		BB4172 - 6 Ft. Hydraulic Scarifier Box Blade - Low Back *Green only.*	3,250.00

BB4172 - 6 Ft. Hydraulic Scarifier Box Blade - Low Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4178 - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I and II, iMatch and
  Quick Coupler Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: Low Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  28.3 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (8) Replaceable
Beam Size:
  Main Beam - 4 In. x 4 In. x 1/4 In.
  Shank Beam - 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 3/4 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 78 In.
Height: 20 In.
Depth: 33 In.
Duty: Heavy
Hitch Type:
  Category I and II, iMatch and
  Quick Coupler Compatible
Mast Design:
  Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1016 lbs.
Shipping Weight: 1056 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB30-78H
Paint Color:
  Construction Yellow (Optional Green)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1104XF	BB4178 - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back	3,755.00

MACHINE COLOR

1000	Green	In Base Price
1010	Construction Yellow	Same Price

BB4178 - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - Low Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4184 - 7 Ft. Hydraulic Scarifier Box Blade - Low Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading And Leveling
Tractor Compatibility:
  Category I and II, iMatch and
  Quick Coupler Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: Low Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  30.5 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (8) Replaceable
Beam Size:
  Main Beam - 4 In. x 4 In. x 1/4 In.
  Shank Beam - 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 3/4 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 84 In.
Height: 20 In.
Depth: 33 In.
Duty: Heavy
Hitch Type:
  Category I and II, iMatch and
  Quick Coupler Compatible
Mast Design:
  Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1052 lbs.
Shipping Weight: 1092 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB30-84H
Paint Color:
  Construction Yellow (Optional Green)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1105XF	BB4184 - 7 Ft. Hydraulic Scarifier Box Blade - Low Back	3,866.00

MACHINE COLOR

1000	Green	In Base Price
1010	Construction Yellow	Same Price

BB4184 - 7 Ft. Hydraulic Scarifier Box Blade - Low Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4196 - 8 Ft. Hydraulic Scarifier Box Blade - Low Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I and II, iMatch and
  Quick Coupler Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: Low Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  34.9 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (8) Replaceable
Beam Size:
  Main Beam - 4 In. x 4 In. x 1/4 In.
  Shank Beam - 4 In. x 4 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 3/4 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 96 In.
Height: 20 In.
Depth: 33 In.
Duty: Heavy
Hitch Type:
  Category I and II, iMatch and
  Quick Coupler Compatible
Mast Design:
  Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1146 lbs.
Shipping Weight: 1186 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB30-96H
Paint Color:
  Construction Yellow (Optional Green)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1106XF	BB4196 - 8 Ft. Hydraulic Scarifier Box Blade - Low Back	3,983.00

MACHINE COLOR

1000	Green	In Base Price
1010	Construction Yellow	Same Price

BB4196 - 8 Ft. Hydraulic Scarifier Box Blade - Low Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4278H - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - High Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I and II, iMatch and
  Quick Coupler Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: High Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  32 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (8) Replaceable
Beam Size:
  Main Beam - 5 In. x 5 In. x 1/4 In.
  Shank Beam - 5 In. x 5 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 1 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 78 In.
Height:
  20 In. Front, 26 In. Rear
Depth: 33 In.
Duty: Heavy
Hitch Type:
  Category I and II, iMatch and
  Quick Coupler Compatible
Mast Design:
  Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1160 lbs.
Shipping Weight: 1200 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB40-78H
Paint Color:
  Construction Yellow (Optional Green)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1111XF	BB4278H - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - High Back	4,012.00

MACHINE COLOR

1000	Green	In Base Price
1010	Construction Yellow	Same Price

BB4278H - 6 Ft. 6 In. Hydraulic Scarifier Box Blade - High Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4284H - 7 Ft. Hydraulic Scarifier Box Blade - High Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I and II, iMatch and
  Quick Coupler Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: High Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  34.5 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (8) Replaceable
Beam Size:
  Main Beam - 5 In. x 5 In. x 1/4 In.
  Shank Beam - 5 In. x 5 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 1 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 84 In.
Height:
  20 In. Front, 26 In. Rear
Depth: 33 In.
Duty: Heavy
Hitch Type:
  Category I and II, iMatch and
  Quick Coupler Compatible
Mast Design:
  Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1200 lbs.
Shipping Weight: 1240 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB40-84H
Paint Color:
  Construction Yellow (Optional Green)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1112XF	BB4284H - 7 Ft. Hydraulic Scarifier Box Blade - High Back	4,077.00

MACHINE COLOR

1000	Green	In Base Price
1010	Construction Yellow	Same Price

BB4284H - 7 Ft. Hydraulic Scarifier Box Blade - High Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB4296H - 8 Ft. Hydraulic Scarifier Box Blade - High Back

Equipment for Base Machine

Tailgate:
  Hinged, Floating
Grading and Leveling:
  Fine, Precision Grading and Leveling
Tractor Compatibility:
  Category I and II, iMatch and
  Quick Coupler Compatible
Beam Type:
  Tubular Scarifier Beam
Scarifier Shanks:
  Notched 3 Position
Points:
  Heat Treated Points
Box Design: High Back
Hydraulic Opening:
  Hydraulically Operated Scarifier Bar
Hydraulic Kit:
  Pin Kit and Hydraulic Hose Kit Included
Capacity (Cubic Foot):
  39.4 Cubic Foot
Tractor HP: Up to 90 HP
Cutting Edges:
  (2) 1/2 In. x 6 In. Reversible
Scarifier Shanks:
  (8) Replaceable
Beam Size:
  Main Beam - 5 In. x 5 In. x 1/4 In.
  Shank Beam - 5 In. x 5 In. x 1/4 In.
Beam Reinforcement:
  1/2 In. x 1 In. Bar
End Plate Thickness: 1/2 In.
Working Width: 96 In.
Height:
  20 In. Front, 26 In. Rear
Depth: 33 In.
Duty: Heavy
Hitch Type:
  Category I and II, iMatch and
  Quick Coupler Compatible
Mast Design:
  Welded 1/2 In. Plate
Assembly/Set-Up Time: 30 Minutes
Operating Weight: 1310 lbs.
Shipping Weight: 1350 lbs.
Shipping per Crate:
  Packaged 1 Per Pallet
Warranty: 1 Year Warranty
Moldboard Thickness: 1/4 In.
Manufacturer Model: TB4096H
Paint Color:
  Construction Yellow (Optional Green)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1113XF	BB4296H - 8 Ft. Hydraulic Scarifier Box Blade - High Back	4,265.00

MACHINE COLOR

1000	Green	In Base Price
1010	Construction Yellow	Same Price

BB4296H - 8 Ft. Hydraulic Scarifier Box Blade - High Back
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB5060 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
iMatch Compatible: Yes
Working Width: 61.5 In.
Tractor HP: 56 PTO HP max;
  see compatibility charts for
  specific model of tractors
Tailgate: Fixed
Shipping Weight:
  894 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
  (2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 418 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1641XF	BB5060 Standard Duty Box Blade *Order in multiples of two.*	925.00

BB5060 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB5072 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
iMatch Compatible: Yes
Working Width: 73.5 In.
Tractor HP: 56 PTO HP max;
  see compatibility charts for
  specific model of tractors
Tailgate: Fixed
Shipping Weight:
  1,006 lbs. - (Pair)
Shanks: (6) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
  (2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 474 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1642XF	BB5072 Standard Duty Box Blade *Order in multiples of two.*	1,070.00

BB5072 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB5084 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
iMatch Compatible: Yes
Working Width: 88.5 In.
Tractor HP: 56 PTO HP max;
  see compatibility charts for
  specific model of tractors
Tailgate: Fixed
Shipping Weight:
  1,078 lbs. - (Pair)
Shanks: (6) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
  (2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 510 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1643XF	BB5084 Standard Duty Box Blade *Order in multiples of two.*	1,223.00

BB5084 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB5096 Standard Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
iMatch Compatible: Yes
Working Width: 97.5 In.
Tractor HP: 56 PTO HP max;
  see compatibility charts for
  specific model of tractors
Tailgate: Fixed
Shipping Weight:
  1,262 lbs. - (Pair)
Shanks: (7) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Hardened Steel
End Plate Thickness: 3/8 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Welded
Duty: Standard Duty
Cutting Edges:
  (2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 602 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1644XF	BB5096 Standard Duty Box Blade *Order in multiples of two.*	1,369.00

BB5096 Standard Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB5048L Limited Category 1 Economy Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Limited Category I
iMatch Compatible: Yes
Working Width: 50 In.
Tractor HP: 18 PTO HP max;
  see compatibility charts for
  specific model of tractors
Tailgate: Fixed
Shipping Weight:
  778 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Hardened Steel
End Plate Thickness: 5/16 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt On
Duty: Economy Duty
Cutting Edges:
  (2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 360 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1741XF		BB5048L Limited Category 1 Economy Duty Box Blade *Order in multiples of two.*	753.00

BB5048L Limited Category 1 Economy Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BB5060L Limited Category 1 Economy Duty Box Blade

Equipment for Base Machine

3-Point Hitch:
  Limited Category I
iMatch Compatible: Yes
Working Width: 62 In.
Tractor HP: 18 PTO HP max;
  see compatibility charts for
  specific model of tractors
Tailgate: Fixed
Shipping Weight:
  868 lbs. - (Pair)
Shanks: (5) Replaceable
Shank Type:
  3-Position with Holes and 1/2 In. Pin
Scarifier Points:
  Hardened Steel
End Plate Thickness: 5/16 In.
Moldboard Thickness: 3/16 In.
Moldboard Type: Formed Back
Mast: Bolt On
Duty: Economy Duty
Cutting Edges:
  (2) 3/8 In. x 6 In. Reversible
Assembly/Set-Up Time:
  15 Minutes (Approximate) - Per Pair
Approximate Operating Weight: 405 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1742XF		BB5060L Limited Category 1 Economy Duty Box Blade *Order in multiples of two.*	821.00

BB5060L Limited Category 1 Economy Duty Box Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LL1160 - 5 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 60 In.
Machine Width: 61 In.
Machine Length: 98 In.
Machine Height: 29.5 In.
Approximate Operating Weight: 612 lbs.
Tractor HP (Maximum): 20 to 50 HP
Tailgate: Fixed
Shanks: 6 (Replaceable)
End Plate Thickness: 3/8 In.
Single Hydraulic Cylinder:
  3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic
Wheels (2):
  6 In. Wide x 10 In. Diameter

Cutting Edge:
  5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
  15 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1471XF	LL1160 - 5 Ft. Drawn Box Scraper	4,482.00

LL1160 - 5 Ft. Drawn Box Scraper
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LL1172 - 6 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 72 In.
Machine Width: 73 In.
Machine Length: 98 In.
Machine Height: 29.5 In.
Approximate Operating Weight: 735 lbs.
Tractor HP (Maximum): 20 to 50 HP
Tailgate: Fixed
Shanks: 6 (Replaceable)
End Plate Thickness: 3/8 In.
Single Hydraulic Cylinder:
  3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic
Wheels (2):
  6 In. Wide x 10 In. Diameter

Cutting Edge:
  5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
  15 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1472XF	LL1172 - 6 Ft. Drawn Box Scraper	4,409.00

LL1172 - 6 Ft. Drawn Box Scraper
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LL1208 - 8 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 96 In.
Machine Width: 96.3 In.
Machine Length: 144 In.
Machine Height: 36 In.
Approximate Operating Weight: 1500 lbs.
Tractor HP (Maximum): 35 to 100 HP
Tailgate: Fixed
Lift Axle: Standard Lift Rockshaft
End Plate Thickness: 3/8 In.
Hydraulic Lift Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic -9.5L15 Implement Tires
Wheels (2):
8 In. Wide x 15 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
60 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1541XF		LL1208 - 8 Ft. Drawn Box Scraper	6,309.00
		AXLE OPTION	
1000		LL12 Standard Lift Axle	In Base Price
1010		LL1208 Tilt Axle with Turnbuckle	684.00
1020		LL1208 Tilt Axle with Cylinder	1,057.00
		LIFT CYLINDER AND HOSES	
2000		LL12 Lift Cylinder, Hoses, and Tips Kit	In Base Price
2095		Less LL12 Lift Cylinder, Hoses, and Tips Kit	-595.00
		TRANSPORT WHEELS AND TIRES	
3000		9.5L-15 Tires on 6-Bolt Rims (2)	In Base Price
3095		Less 9.5L-15 Tires on 6-Bolt Rims (2)	-823.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5DDA00100	9.5L-15 Tires on 6-Bolt Rims (2)	947.79
	5DDA00096	LL12 Series - Lift Cylinder Kit	685.11
	5DDA00098	LL12 Series - Tilt Cylinder Kit	716.53
	5DDA00097	LL12 Series - Turnbuckle	230.90

LL1208 - 8 Ft. Drawn Box Scraper
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LL1210 - 10 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 120 In.
Machine Width: 120.3 In.
Machine Length: 144 In.
Machine Height: 36 In.
Approximate Operating Weight: 1600 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
Lift Axle: Standard Lift Rockshaft
End Plate Thickness: 3/8 In.
Hydraulic Lift Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic -9.5L15 Implement Tires
Wheels (2):
8 In. Wide x 15 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
60 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1542XF		LL1210 - 10 Ft. Drawn Box Scraper	6,879.00
		AXLE OPTION	
1000		LL12 Standard Lift Axle	In Base Price
1010		LL1210/12 Tilt Axle with Turnbuckle	591.00
1020		LL1210/12 Tilt Axle with Cylinder	1,088.00
		LIFT CYLINDER AND HOSES	
2000		LL12 Lift Cylinder, Hoses, and Tips Kit	In Base Price
2095		Less LL12 Lift Cylinder, Hoses, and Tips Kit	-595.00
		TRANSPORT WHEELS AND TIRES	
3000		9.5L-15 Tires on 6-Bolt Rims (2)	In Base Price
3095		Less 9.5L-15 Tires on 6-Bolt Rims (2)	-823.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5DDA00100	9.5L-15 Tires on 6-Bolt Rims (2)	947.79
	5DDA00096	LL12 Series - Lift Cylinder Kit	685.11
	5DDA00098	LL12 Series - Tilt Cylinder Kit	716.53
	5DDA00097	LL12 Series - Turnbuckle	230.90

LL1210 - 10 Ft. Drawn Box Scraper
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LL1212 - 12 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 144 In.
Machine Width: 143 In.
Machine Length: 144 In.
Machine Height: 36 In.
Approximate Operating Weight: 1700 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
Lift Axle: Standard Lift Rockshaft
End Plate Thickness: 3/8 In.
Hydraulic Lift Cylinder:
3 In. Bore x 8 In. Stroke
Tires (2): Pneumatic -9.5L15 Implement Tires
Wheels (2):
8 In. Wide x 15 In. Diameter

Cutting Edge:
5/8 In. Thick x 6 In. Tall
Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
60 Minutes (Approximate)
Duty: Standard Duty
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1543XF		LL1212 - 12 Ft. Drawn Box Scraper	6,898.00
		AXLE OPTION	
1000		LL12 Standard Lift Axle	In Base Price
1010		LL1210/12 Tilt Axle with Turnbuckle	591.00
1020		LL1210/12 Tilt Axle with Cylinder	1,088.00
		LIFT CYLINDER AND HOSES	
2000		LL12 Lift Cylinder, Hoses, and Tips Kit	In Base Price
2095		Less LL12 Lift Cylinder, Hoses, and Tips Kit	-595.00
		TRANSPORT WHEELS AND TIRES	
3000		9.5L-15 Tires on 6-Bolt Rims (2)	In Base Price
3095		Less 9.5L-15 Tires on 6-Bolt Rims (2)	-823.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5DDA00100	9.5L-15 Tires on 6-Bolt Rims (2)	947.79
	5DDA00096	LL12 Series - Lift Cylinder Kit	685.11
	5DDA00098	LL12 Series - Tilt Cylinder Kit	716.53
	5DDA00097	LL12 Series - Turnbuckle	230.90

LL1212 - 12 Ft. Drawn Box Scraper
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LL1372 - 6 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 72 In.
Machine Width: 74 In.
Machine Length: 165 In.
Machine Height: 49 In.
Approximate Operating Weight: 1600 lbs.
Tractor HP (Maximum): 35 to 100
Tailgate: Fixed
End Plate Thickness: 1/2 In.
Dual Hydraulic Cylinders: 3 In. Bore x
  8 In. Stroke (1 Rear SCV Required)
Tires (4): Pneumatic
Wheels (4):
  6 In. Wide x 10 In. Diameter
Cutting Edge:
  5/8 In. Thick x 6 In. Tall

Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Shipping Configuration:
  2 Pieces (Box Blade and Tongue)
Duty: Medium Duty
Warranty: 6 Months

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1481XF		LL1372 - 6 Ft. Drawn Box Scraper	8,621.00
		SCARIFIER BAR	
1000		6 Ft. Scarifier Bar Attachment	2,468.00
1095		Less Scarifier Bar Attachment	In Base Price
		REAR SMOOTH ROLLER	
2000		6 Ft. Rear Smooth 12 In. Drum Roller Attachment	2,962.00
2095		Less Rear Smooth Roller	In Base Price
		ATTACHMENTS - ORDER AS DESIRED	
9000		Rear Hitch Assembly	246.00
9030		6 Ft. Double Rear 12 In. Diameter Basket Roller Pulverizer	2,963.00
9040		6 Ft. 3 Bar Spring Tine Harrow	2,346.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5DDA00020	3 Bar Spring Tine Harrow - 6 Ft.	2,533.85
	5DDA00017	Double Rear 12 In. Diameter Basket Roller Pulverizer - 6 Ft.	3,199.93
	5DDA00007	Rear Hitch Assembly (LL13 Series)	265.68
	5DDA00023	Rear Smooth 12 In. Drum Roller Attachment - 6 Ft.	3,412.32
	5DDA00029	Scarifier Bar Attachment - 6 Ft.	2,843.60

LL1372 - 6 Ft. Drawn Box Scraper
Continued

LL1384 - 7 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 84 In.
Machine Width: 86 In.
Machine Length: 165 In.
Machine Height: 49 In.
Approximate Operating Weight: 1866 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
End Plate Thickness: 1/2 In.
Dual Hydraulic Cylinders: 3 In. Bore x
  8 In. Stroke (1 Rear SCV Required)
Tires (4): Pneumatic
Wheels (4):
  6 In. Wide x 10 In. Diameter
Cutting Edge:
  5/8 In. Thick x 6 In. Tall

Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Shipping Configuration:
  2 Pieces (Box Blade and Tongue)
Duty: Medium Duty
Warranty: 6 Months

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1482XF		LL1384 - 7 Ft. Drawn Box Scraper	8,755.00
		SCARIFIER BAR	
1000		6 Ft. Scarifier Bar Attachment	2,468.00
1095		Less Scarifier Bar Attachment	In Base Price
		REAR SMOOTH ROLLER	
2000		7 Ft. Rear Smooth 12 In. Drum Roller Attachment	3,129.00
2095		Less Rear Smooth Roller	In Base Price
		ATTACHMENTS - ORDER AS DESIRED	
9000		Rear Hitch Assembly	246.00
9030		7 Ft. Double Rear 12 In. Diameter Basket Roller Pulverizer	3,126.00
9040		7 Ft. 3 Bar Spring Tine Harrow	2,549.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5DDA00021	3 Bar Spring Tine Harrow - 7 Ft.	2,753.34
	5DDA00018	Double Rear 12 In. Diameter Basket Roller Pulverizer - 7 Ft.	3,376.58
	5DDA00007	Rear Hitch Assembly (LL13 Series)	265.68
	5DDA00024	Rear Smooth 12 In. Drum Roller Attachment - 7 Ft.	3,604.27
	5DDA00029	Scarifier Bar Attachment - 6 Ft.	2,843.60

LL1384 - 7 Ft. Drawn Box Scraper
Continued

LL1396 - 8 Ft. Drawn Box Scraper

Equipment for Base Machine

Working Width: 96 In.
Machine Width: 98 In.
Machine Length: 165 In.
Machine Height: 49 In.
Approximate Operating Weight: 2133 lbs.
Tractor HP (Maximum): 35 to 125 HP
Tailgate: Fixed
End Plate Thickness: 1/2 In.
Dual Hydraulic Cylinders: 3 In. Bore x
  8 In. Stroke (1 Rear SCV Required)
Tires (4): Pneumatic
Wheels (4):
  6 In. Wide x 10 In. Diameter
Cutting Edge:
  5/8 In. Thick x 6 In. Tall

Safety Chains: Yes - Required
Color: Construction Yellow
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Shipping Configuration:
  2 Pieces (Box Blade and Tongue)
Duty: Medium Duty
Warranty: 6 Months

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1483XF		LL1396 - 8 Ft. Drawn Box Scraper	9,130.00
		SCARIFIER BAR	
1000		8 Ft. Scarifier Bar Attachment	2,387.00
1095		Less Scarifier Bar Attachment	In Base Price
		REAR SMOOTH ROLLER	
2000		8 Ft. Rear Smooth 12 In. Drum Roller Attachment	3,374.00
2095		Less Rear Smooth Roller	In Base Price
		ATTACHMENTS - ORDER AS DESIRED	
9000		Rear Hitch Assembly	246.00
9030		8 Ft. Double Rear 12 In. Diameter Basket Roller Pulverizer	3,293.00
9040		8 Ft. 3 Bar Spring Tine Harrow	2,741.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5DDA00022	3 Bar Spring Tine Harrow - 8 Ft.	2,959.95
	5DDA00019	Double Rear 12 In. Diameter Basket Roller Pulverizer - 8 Ft.	3,556.28
	5DDA00007	Rear Hitch Assembly (LL13 Series)	265.68
	5DDA00025	Rear Smooth 12 In. Drum Roller Attachment - 8 Ft.	3,887.28
	5DDA00028	Scarifier Bar Attachment - 8 Ft.	2,749.54

LL1396 - 8 Ft. Drawn Box Scraper
Continued

CA2048E - 4 Ft. Economy Core Aerator

Equipment for Base Machine

Reduces Hard Layer Compaction and
  Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
2 Bronze Bushings per Rotor for
  Wear Resistance on Shaft
3-Point Hitch: Category I
Working Width: 48 In.
Tractor HP: 20 to 50 HP
Spoons:
  (48) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.
Spoons Per Hub: 6
Approximate Shipping Weight: 400 lbs.

Overall Width: 54 In.
iMatch Compatible (Quick-Attach System)
Assembly/Set-Up Time:
  10 Minutes (Approximate)
Approximate Operating Weight: 284 lbs.
1 Year Warranty

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1141XF		CA2048E - 4 Ft. Economy Core Aerator *Order optional weight tanks as attachments.*	2,303.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Steel Weight Tank CA2048E, Quantity 2 (2 Required per Machine) *For sand only.*	577.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950958B	French Manual Decal (CA20 Series)	0.00
	5BP0099731	Steel Weight Tank CA2048E, Quantity 1 (2 Required Per Machine) *For sand only.*	311.46

CA2048E - 4 Ft. Economy Core Aerator
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

CA2060 - 5 Ft. Standard Duty Core Aerator

Equipment for Base Machine

Reduces Hard Layer Compaction and
  Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
  - Can Hold (2) 170 lb. Sand
  Containers - OPTIONAL
2 Bronze Bushings per Rotor for
  Wear Resistance on Shaft
3-Point Hitch: Category I and Category II
Working Width: 60 In.
Weight Tray: (2) 19 In. x 21 In.
Tractor HP: 25 to 70 HP
Spoons:
  (80) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.
Spoons Per Hub: 8
iMatch Compatible (Quick-Attach System)
Shipping Weight: 500 lbs.
Overall Width: 65 In.
Assembly/Set-Up Time:
  10 Minutes (Approximate)
1 Year Warranty

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1131XF		CA2060 - 5 Ft. Standard Duty Core Aerator *Order optional weight tanks as attachments.*	3,084.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Steel Weight Tank CA2060, Quantity 2 (2 Required per Machine) *For sand only.*	682.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950958B	French Manual Decal (CA20 Series)	0.00
	5BP0099734	Steel Weight Tank CA2060, Quantity 1 (2 Required Per Machine) *For sand only.*	368.46

CA2060 - 5 Ft. Standard Duty Core Aerator
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

CA2060E - 5 Ft. Economy Core Aerator

Equipment for Base Machine

Reduces Hard Layer Compaction and
  Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
  - Can Hold (2) 125 lb. Sand
  Containers - OPTIONAL
2 Bronze Bushings per Rotor for
  Wear Resistance on Shaft
3-Point Hitch: Category I
Working Width: 60 In.
Weight Tray: (2) 19 In. x 15 In.
Tractor HP: 20 to 50 HP
Spoons:
  (60) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.
Spoons Per Hub: 6
iMatch Compatible (Quick-Attach System)
Approximate Shipping Weight: 400 lbs.
Overall Width: 65 In.
Assembly/Set-Up Time:
  10 Minutes (Approximate)
Approximate Operating Weight: 357 lbs.
1 Year Warranty

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1142XF		CA2060E - 5 Ft. Economy Core Aerator *Order optional weight tanks as attachments.*	2,423.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Steel Weight Tank CA2060E, Quantity 2 (2 Required per Machine) *For sand only.*	608.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950958B	French Manual Decal (CA20 Series)	0.00
	5BP0099732	Steel Weight Tank CA2060E, Quantity 1 (2 Required Per Machine) *For sand only.*	328.53

CA2060E - 5 Ft. Economy Core Aerator
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

CA2072 - 6 Ft. Standard Duty Core Aerator

Equipment for Base Machine

Reduces Hard Layer Compaction and
  Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
  - Can Hold (2) 220 lb.
  Sand Containers - OPTIONAL
2 Bronze Bushings per Rotor for
  Wear Resistance on Shaft
3-Point Hitch:
  Category I and Category II
Working Width: 72 In.
Weight Tray: (2) 25 In. x 21 In.
Tractor HP: 25 to 70 HP
Spoons:
  (96) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.
Spoons Per Hub: 8
Shipping Weight: 600 lbs.
Overall Width: 78 In.
iMatch Compatible (Quick-Attach System)
Assembly/Set-Up Time:
  10 Minutes (Approximate)
Approximate Operating Weight: 549 lbs.
1 Year Warranty

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1132XF		CA2072 - 6 Ft. Standard Duty Core Aerator *Order optional weight tanks as attachments.*	3,458.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Steel Weight Tank CA2072, Quantity 2 (2 Required per Machine) *For sand only.*	735.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950958B	French Manual Decal (CA20 Series)	0.00
	5BP0099735	Steel Weight Tank CA2072, Quantity 1 (2 Required Per Machine) *For sand only.*	396.82

CA2072 - 6 Ft. Standard Duty Core Aerator
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

CA2072E - 6 Ft. Economy Core Aerator

Equipment for Base Machine

Reduces Hard Layer Compaction and
  Increases Turf Vitality
3/8 In. Formed Category I "A" Frame
  - Can Hold (2) 160 lb. Sand
  Containers - OPTIONAL
2 Bronze Bushings per Rotor for
  Wear Resistance on Shaft
3-Point Hitch: Category I
Working Width: 72 In.
Weight Tray: (2) 25 In. x 15 In.
Tractor HP: 20 to 50 HP
Spoons:
  (72) 3/4 In. Case Hardened Steel
Spoon Penetration: 4-1/2 In.
Spoons Per Hub: 6
iMatch Compatible (Quick-Attach System)
Approximate Shipping Weight: 450 lbs.
Overall Width: 78 In.
Assembly/Set-Up Time:
  10 Minutes (Approximate)
Approximate Operating Weight: 401 lbs.
1 Year Warranty

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1143XF		CA2072E - 6 Ft. Economy Core Aerator *Order optional weight tanks as attachments.*	2,689.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Steel Weight Tank CA2072E, Quantity 2 (2 Required per Machine) *For sand only.*	646.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950958B	French Manual Decal (CA20 Series)	0.00
	5BP0099733	Steel Weight Tank CA2072E, Quantity 1 (2 Required Per Machine) *For sand only.*	349.02

CA2072E - 6 Ft. Economy Core Aerator
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PC1001 Integral One Row Cultivator

Equipment for Base Machine

Hitch:
  Lift-type, Category I,
  iMatch Compatible
Working Row Width:
  30 to 60 In. (762 to 1524 mm)
Transport Length:
  37 In. (939.8 mm)
Transport Width:
  50.5 In. (1,282.7 mm)
Transport Height:
  36 In. (914.4 mm)
Tractor Engine HP Range:
  25 - 45 HP
Standard Tines:
  6 Curved and Reversible Tines,
  1.75 In. (44.45 mm) x 10 In. (254 mm)
Tine Spacing: Adjustable
Parking Stand Included

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3441XF		PC1001 Integral One Row Cultivator *Order in multiples of two.*	429.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TITE511154	French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals *PC1001 and PC1072*	14.10

PC1001 Integral One Row Cultivator
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PC1072 - 6 Ft. Integral Field Cultivator (13 S-tines)

Equipment for Base Machine

Hitch:
Lift-type, Category I,
iMatch Compatible
Working Width:
72 In. (1,828.8 mm)
Transport Length:
37.5 In. (952.5 mm)
Transport Width:
73.25 In. (1,860.6 mm)
Transport Height:
39 In. (990.6 mm)
Tractor Engine HP Range:
25 - 45 HP
Standard Tines:
13 Curved and Reversible Tines,
1.25 In. (31.75 mm) x 8 In. (203.2 mm)
Tine Spacing: Adjustable

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3442XF		PC1072 - 6 Ft. Integral Field Cultivator (13 S-tines) *Order in multiples of two.*	845.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TITE511154	French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals *PC1001 and PC1072*	14.10

PC1072 - 6 Ft. Integral Field Cultivator (13 S-tines)
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BL1130 - 3 Pt. Mount Debris Blower - U.S.

Equipment for Base Machine

Function: Debris Blower
Length: 47 1/8 In. (1,197 mm)
Width: 50 In. (1,270 mm)
Height: 48 3/4 In. (1,238.3 mm)
Operating Weight: 689 lb. (312.5 kg)
Fan Diameter: 29 1/2 In. (749.3 mm)
Fan Width: 10 in. (254 mm)
Number of Fan Blades: 12
Fan Speed: 1455 RPM
Air Flow: 6,061 cfm (171 cu. meter per minute)
Air Velocity: 141 mph (227 kph)
Air Velocity: 12,400 fpm (3,779.5 mpm)

Outlet Size: 10 5/8 x 6 5/8 In. (269.9 x 168.3 mm)
Air Direction: left or right by moving lever
Cat. 1 & 2, iMatch and Quick Hitch Compatible
Pneumatic gauge wheel standard
Approximate Set-Up Time: 30 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1571XF		BL1130 - 3 Pt. Mount Debris Blower - U.S.	5,260.00

BL1130 - 3 Pt. Mount Debris Blower - U.S.
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - U.S.

Equipment for Base Machine

Function: Debris Blower
Length: 47 1/8 In. (1,197 mm)
Width: 50 In. (1,270 mm)
Height: 48 3/4 In. (1,238.3 mm)
Operating Weight: 689 lb. (312.5 kg)
Fan Diameter: 29 1/2 In. (749.3 mm)
Fan Width: 10 in. (254 mm)
Number of Fan Blades: 12
Fan Speed: 1455 RPM
Air Flow: 6,061 cfm (171 cu. meter per minute)
Air Velocity: 141 mph (227 kph)
Air Velocity: 12,400 fpm (3,779.5 mpm)
Outlet Size: 10 5/8 x 6 5/8 In. (269.9 x 168.3 mm)
Air Direction: left or right by moving lever
Pneumatic gauge wheel standard
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1581XF		BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - U.S. *Must be used with HP2025 or HP2134 Hydraulic Power Pack Units.*	11,559.00
		HYDRAULIC POWER UNITS	
1000		HP2025 - Hydraulic Power Unit, 25 HP *Requires wiring harness, 5RDF0039, when changing front implement attachments.*	In Base Price
1010		HP2134 - Hydraulic Power Unit, 34 HP *Requires wiring harness, 5RDF0039, when changing front implement attachments.*	105.06
1095		Less HP2025 Hydraulic Power Unit	-6,499.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095		Less Oil Cooler	-1,660.00
		ATTACHMENTS - ORDER AS DESIRED	
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	92.00
		ATTACHMENTS FOR FIELD CONVERSION	

BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

BL1130 - 3 Pt. Mount Debris Blower - Canada

Equipment for Base Machine

Function: Debris Blower
Length: 47 1/8 In. (1,197 mm)
Width: 50 In. (1,270 mm)
Height: 48 3/4 In. (1,238.3 mm)
Operating Weight: 689 lb. (312.5 kg)
Fan Diameter: 29 1/2 In. (749.3 mm)
Fan Width: 10 in. (254 mm)
Number of Fan Blades: 12
Fan Speed: 1455 RPM
Air Flow: 6,061 cfm (171 cu. meter per minute)
Air Velocity: 141 mph (227 kph)
Air Velocity: 12,400 fpm (3,779.5 mpm)

Outlet Size: 10 5/8 x 6 5/8 In. (269.9 x 168.3 mm)
Air Direction: left or right by moving lever
Cat. 1 & 2, iMatch and Quick Hitch Compatible
Pneumatic gauge wheel standard
Approximate Set-Up Time: 30 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
157AXF		BL1130 - 3 Pt. Mount Debris Blower - Canada	5,340.10

BL1130 - 3 Pt. Mount Debris Blower - Canada
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - Canada

Equipment for Base Machine

Function: Debris Blower
Length: 47 1/8 In. (1,197 mm)
Width: 50 In. (1,270 mm)
Height: 48 3/4 In. (1,238.3 mm)
Operating Weight: 689 lb. (312.5 kg)
Fan Diameter: 29 1/2 In. (749.3 mm)
Fan Width: 10 in. (254 mm)
Number of Fan Blades: 12
Fan Speed: 1455 RPM
Air Flow: 6,061 cfm (171 cu. meter per minute)
Air Velocity: 141 mph (227 kph)
Air Velocity: 12,400 fpm (3,779.5 mpm)
Outlet Size: 10 5/8 x 6 5/8 In. (269.9 x 168.3 mm)
Air Direction: left or right by moving lever
Pneumatic gauge wheel standard
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
158AXF		BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - Canada *Must order HP2025 or HP2134 Hydraulic Power Pack Unit to complete the package.*	11,735.03
		HYDRAULIC POWER UNITS	
1000		HP2025 - Hydraulic Power Unit, 25 HP *Requires wiring harness, 5RDF0039, when changing front implement attachments.*	In Base Price
1010		HP2134 - Hydraulic Power Unit, 34 HP *Requires wiring harness, 5RDF0039, when changing front implement attachments.*	116.09
1095		Less HP2025 Hydraulic Power Unit	-6,793.60
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095		Less Oil Cooler	-1,735.25
		ATTACHMENTS - ORDER AS DESIRED	
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	101.66

BL2130 - Hydraulic Loader Mount Debris Blower with HP2025 Hydraulic Power Unit - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

LP1048 Standard Drawn Land Plane

Equipment for Base Machine

Working Width: 48 In.
Shipping Weight: 445 lbs.
End Plate Thickness: 3/16 In.
Duty: Light Duty
Cutting Edges: (2)
Assembly/Set-Up Time: 15 Minutes
Approximate Operating Weight: 365 lbs.

Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1441XF	LP1048 Standard Drawn Land Plane	1,358.00

LP1048 Standard Drawn Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1060 Standard Drawn Land Plane

Equipment for Base Machine

Working Width: 60 In.
Shipping Weight: 495 lbs.
End Plate Thickness: 3/16 In.
Duty: Light Duty
Cutting Edges: (2)
Assembly/Set-Up Time: 15 Minutes
Approximate Operating Weight: 415 lbs.

Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1442XF		LP1060 Standard Drawn Land Plane	1,376.00

LP1060 Standard Drawn Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1160 - 5 Ft. 3-Point Land Plane

Equipment for Base Machine

3-Point Hitch: Category I
iMatch Compatible (Quick-Attach System)
Working Width: 60 In.
Tractor HP Recommendation: 18 to 50 HP
Skid Shoes: Weld on, 3/16 In.
Shipping Weight: 573 lbs.
End Plate Thickness: 3/16 In.
Duty: Standard Duty
Cutting Edges: (2) Reversible

Assembly/Set-Up Time: 10 Minutes
Approximate Operating Weight: 520 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1451XF		LP1160 - 5 Ft. 3-Point Land Plane	1,393.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TL15746	French Kit - Includes Operator's Manual and Safety Decals (LP11 Series)	42.38

LP1160 - 5 Ft. 3-Point Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1172 - 6 Ft. 3-Point Land Plane

Equipment for Base Machine

3-Point Hitch: Category I
iMatch Compatible (Quick-Attach System)
Working Width: 72 In.
Tractor HP Recommendation: 18 to 50 HP
Skid Shoes: Weld on, 3/16 In.
Shipping Weight: 628 lbs.
End Plate Thickness: 3/16 In.
Duty: Standard Duty
Cutting Edges: (2) Reversible

Assembly/Set-Up Time: 10 Minutes
Approximate Operating Weight: 548 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1452XF		LP1172 - 6 Ft. 3-Point Land Plane	1,470.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TL15746	French Kit - Includes Operator's Manual and Safety Decals (LP11 Series)	42.38

LP1172 - 6 Ft. 3-Point Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1184 - 7 Ft. 3-Point Land Plane

Equipment for Base Machine

3-Point Hitch: Category I and II
iMatch Compatible (Quick-Attach System)
Working Width: 84 In.
Tractor HP Recommendation: 22 to 75 HP
Skid Shoes: Weld on, 3/16 In.
Shipping Weight: 684 lbs.
End Plate Thickness: 3/16 In.
Duty: Standard Duty
Cutting Edges: (2) Reversible

Assembly/Set-Up Time: 10 Minutes
Approximate Operating Weight: 604 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1453XF		LP1184 - 7 Ft. 3-Point Land Plane	1,618.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TL15746	French Kit - Includes Operator's Manual and Safety Decals (LP11 Series)	42.38

LP1184 - 7 Ft. 3-Point Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1196 - 8 Ft. 3-Point Land Plane

Equipment for Base Machine

3-Point Hitch: Category I and II
iMatch Compatible (Quick-Attach System)
Working Width: 96 In.
Tractor HP Recommendation: 22 to 75 HP
Skid Shoes: Weld on, 3/16 In.
Shipping Weight: 732 lbs.
End Plate Thickness: 3/16 In.
Duty: Standard Duty
Cutting Edges: (2) Reversible
Assembly/Set-Up Time:

Unit Arrives Fully Assembled
Approximate Operating Weight: 652 lbs.
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1454XF		LP1196 - 8 Ft. 3-Point Land Plane	1,660.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous:

	5TL15746	French Kit - Includes Operator's Manual and Safety Decals (LP11 Series)	42.38

LP1196 - 8 Ft. 3-Point Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1207 - 7 Ft. Heavy Duty 3-Point Land Plane

Equipment for Base Machine

Working Width: 84 In.
Shipping Weight: 1,048 lbs.
Operating Weight: 998 lbs.
3 Pt. Cat. 1 & 2
iMatch Compatible (Quick-Attach System)
Cat. 2 Quick Couple Compatible (Quick-Attach System)
Implement Code: 57.6
End Plate Thickness: 3/16 In.
Duty: Heavy Duty
Cutting Edges: (2) 1/2 x 6 in. Reversible
Adjustable Skid Shoes
Skid Shoe Thickness: 3/8 in.
Scarifier Shanks: (4) Available -Optional
Assembly/Set-Up Time: 15 Minutes
Warranty: 1 Year

Ballasting may be required. Please see your tractor operator's manual and your John Deere dealer.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1631XF		LP1207 - 7 Ft. Heavy Duty 3-Point Land Plane	2,694.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TL1207KT	Scarifier Kit (LP1207)	182.93

LP1207 - 7 Ft. Heavy Duty 3-Point Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1208 - 8 Ft. Heavy Duty 3-Point Land Plane

Equipment for Base Machine

Working Width: 96 In.
Shipping Weight: 1,160 lbs.
Operating Weight: 1,110 lbs.
3 Pt. Cat. 1 & 2
iMatch Compatible (Quick-Attach System)
Cat. 2 Quick Couple Compatible (Quick-Attach System)
Implement Code: 64.1
End Plate Thickness: 3/16 In.
Duty: Heavy Duty
Cutting Edges: (2) 1/2 x 6 in. Reversible
Adjustable Skid Shoes
Skid Shoe Thickness: 3/8 in.
Scarifier Shanks: (6) Available -Optional
Assembly/Set-Up Time: 15 Minutes
Warranty: 1 Year

Ballasting may be required. Please see your tractor operator's manual and your John Deere dealer.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1632XF		LP1208 - 8 Ft. Heavy Duty 3-Point Land Plane	3,023.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TL1208KT	Scarifier Kit (LP1208)	294.72

LP1208 - 8 Ft. Heavy Duty 3-Point Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LP1210 - 10 Ft. Heavy Duty 3-Point Land Plane

Equipment for Base Machine

Working Width: 120 In.
Shipping Weight: 1,304 lbs.
Operating Weight: 1,254 lbs.
3 Pt. Cat. 2
Cat. 2 Quick Couple Compatible (Quick-Attach System)
Implement Code: 72.4
End Plate Thickness: 3/16 In.
Duty: Heavy Duty
Cutting Edges: (2) 1/2 x 6 in. Reversible
Adjustable Skid Shoes
Skid Shoe Thickness: 3/8 in.
Scarifier Shanks: (8) Available -Optional
Assembly/Set-Up Time: 15 Minutes
Warranty: 1 Year

Ballasting may be required. Please see your tractor operator's manual and your John Deere dealer.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1633XF		LP1210 - 10 Ft. Heavy Duty 3-Point Land Plane	3,502.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TL1210KT	Scarifier Kit (LP1210)	392.71

LP1210 - 10 Ft. Heavy Duty 3-Point Land Plane
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR2060L - 5 Ft. Standard Duty Landscape Rake - Limited Category I

Equipment for Base Machine

Tine Dimensions:
  5/16 In. x 1 In. x 12 In. Spring Steel
Tine Spacing: 30 at 1 In.
Working Width: 60 In.
Tractor HP (Maximum): 25 HP
Parking Stand - Standard
Raking Positions:
  5 Forward (0, 15, 30 Degrees),
  5 Reverse (0, 15 Degrees)
3-Point Hitch:
  Limited Category I (Aftermarket
  Category 0 Lift Pins Available)
Pivot: 360 Degrees

Operating Weight: 168 lbs.
Shipping Weight:
  422 lbs. (Quantity of 2)
Assembly/Set-Up Time: 30 Minutes
Packaged Two Per Crate
Gauge Wheels: Optional
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1191XF		LR2060L - 5 Ft. Standard Duty Landscape Rake - Limited Category I *Order in multiples of two.*	781.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5WS343465	Dual Gauge Wheel Kit (LR2060L)	448.64

LR2060L - 5 Ft. Standard Duty Landscape Rake - Limited Category I
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR2072 - 6 Ft. Standard Duty Landscape Rake

Equipment for Base Machine

Duty: Standard Duty
Rake Width: 72 In.
3-Point Hitch:
  Category I
Tractor HP:
  19 to 40 HP
Tine Dimension:
  5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
  5 Forward (0, 15, 30 Degree) Each Side
  - 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 200 lbs.
Shipping Weight:
  486 lbs. (Quantity 2)
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit
  (Includes Two Wheels and Arms): Optional
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1181XF		LR2072 - 6 Ft. Standard Duty Landscape Rake *Order in multiples of two.*	886.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS341775	Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)	481.80

LR2072 - 6 Ft. Standard Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR2084 - 7 Ft. Standard Duty Landscape Rake

Equipment for Base Machine

Duty: Standard Duty
Rake Width: 84 In.
3-Point Hitch:
  Category I
Tractor HP:
  19 to 40 HP
Tine Dimension:
  5/16 In. x 1 In. Spring Steel
Tine Spacing: 42 at 1 In.
Raking Positions:
  5 Forward (0, 15, 30 Degree) Each Side
  - 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Pivot: 360 Degrees
Approximate Operating Weight:
  221 lbs.
Approximate Shipping Weight:
  528 lbs. (Quantity 2)
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Packaged 2 per Crate
Gauge Wheel Kit
  (Includes Two Wheels and Arms): Optional
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1182XF		LR2084 - 7 Ft. Standard Duty Landscape Rake *Order in multiples of two.*	999.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS341775	Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)	481.80

LR2084 - 7 Ft. Standard Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR2172 - 6 Ft. Medium Duty Landscape Rake

Equipment for Base Machine

Duty: Medium Duty
Rake Width: 72 In.
3-Point Hitch:
  Category I
Tractor HP:
  23 to 55 HP
Tines Dimension:
  5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
  5 Forward (0, 15, 30 Degree) Each Side
  - 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 282 lbs.

Approximate Shipping Weight: 368 lbs.
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Gauge Wheel Assembly Kit
  (Two Wheels and Arms): Optional
6 Ft. Flip Down Grader Blade: Optional
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1201XF		LR2172 - 6 Ft. Medium Duty Landscape Rake	1,273.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5WS341986	6 Ft. Flip Down Blade (LR2172)	314.93
	5WS341775	Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)	481.80

LR2172 - 6 Ft. Medium Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR2184 - 7 Ft. Medium Duty Landscape Rake

Equipment for Base Machine

Duty: Medium Duty
Rake Width: 84 In.
3-Point Hitch:
  Category I
Tractor HP:
  23 to 55 HP
Tine Dimension:
  5/16 In. x 1 In. Spring Steel
Tine Spacing: 42 at 1 In.
Raking Positions:
  5 Forward (0, 15, 30 Degree) Each Side
  - 3 Reverse (0, 15 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 307 lbs.

Approximate Shipping Weight: 393 lbs.
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Gauge Wheel Assembly Kit
  (Two Wheels and Arms): Optional
7 Ft. Flip Down Grader: Optional
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1202XF		LR2184 - 7 Ft. Medium Duty Landscape Rake	1,370.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS341987	7 Ft. Flip Down Blade (LR2184)	327.95
	5WS341775	Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)	481.80

LR2184 - 7 Ft. Medium Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR2196 - 8 Ft. Medium Duty Landscape Rake

Equipment for Base Machine

Duty: Medium Duty
Rake Width: 96 In.
3-Point Hitch:
  Category I
Tractor HP: 27 to 55 HP
Tines Dimension:
  5/16 In. x 1 In. Spring Steel
Tine Spacing: 48 at 1 In.
Raking Positions:
  5 Forward (0, 15, 30 Degree) Each Side
  - 3 Reverse (0, 15 Degree) Each Side
Approximate Operating Weight: 332 lbs.
Approximate Shipping Weight: 418 lbs.

Parking Stand: Standard
Assembly/Set-Up Time:
  30 Minutes (Approximate)
Gauge Wheel Assembly Kit
  (Two Wheels and Arms): Optional
8 Ft. Flip Down Grader: Optional
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1203XF		LR2196 - 8 Ft. Medium Duty Landscape Rake	1,463.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS341988	8 Ft. Flip Down Blade (LR2196)	375.27
	5WS341775	Dual Gauge Wheel Kit (LR2072, LR2084, LR2172, LR2184 and LR2196)	481.80

LR2196 - 8 Ft. Medium Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR5060 - 5 Ft. Standard Duty Landscape Rake

Equipment for Base Machine

Duty: Standard Duty
Rake Width: 60 In.
3-Point Hitch:
Category I
Tractor HP:
15 to 35 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 248 lbs.

Shipping Weight:
554 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: NA
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1661XF		LR5060 - 5 Ft. Standard Duty Landscape Rake *Order in multiples of two.*	727.00

LR5060 - 5 Ft. Standard Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR5072 - 6 Ft. Standard Duty Landscape Rake

Equipment for Base Machine

Duty: Standard Duty
Rake Width: 72 In.
3-Point Hitch:
Category I
Tractor HP:
20 to 38 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 272 lbs.

Shipping Weight:
602 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: NA
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1662XF		LR5072 - 6 Ft. Standard Duty Landscape Rake *Order in multiples of two.*	787.00

LR5072 - 6 Ft. Standard Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR5084 - 7 Ft. Standard Duty Landscape Rake

Equipment for Base Machine

Duty: Standard Duty
Rake Width: 84 In.
3-Point Hitch:
Category I
Tractor HP:
20 to 50 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 287 lbs.

Shipping Weight:
632 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: NA
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1663XF		LR5084 - 7 Ft. Standard Duty Landscape Rake *Order in multiples of two.*	828.00

LR5084 - 7 Ft. Standard Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR5096 - 8 Ft. Standard Duty Landscape Rake

Equipment for Base Machine

Duty: Standard Duty
Rake Width: 96 In.
3-Point Hitch:
Category I
Tractor HP:
20 to 50 HP
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 36 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 324 lbs.

Shipping Weight:
706 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate)
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: NA
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1664XF		LR5096 - 8 Ft. Standard Duty Landscape Rake *Order in multiples of two.*	894.00

LR5096 - 8 Ft. Standard Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR5048L - 4 Ft. Limited Category 1 Economy Duty Landscape Rake

Equipment for Base Machine

Duty: Economy Duty
Rake Width: 48 In.
3-Point Hitch:
Limited Category I
Tractor HP: 18 PTO HP Max
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 24 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 186 lbs.
Shipping Weight:
430 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: Yes
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1761XF		LR5048L - 4 Ft. Limited Category 1 Economy Duty Landscape Rake *Order in multiples of two.*	614.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TITE511225	LR50L Gauge Wheel Kit *Includes two solid wheels, two mounting brackets, and hardware.*	267.80

LR5048L - 4 Ft. Limited Category 1 Economy Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

LR5060L - 5 Ft. Limited Category 1 Economy Duty Landscape Rake

Equipment for Base Machine

Duty: Economy Duty
Rake Width: 60 In.
3-Point Hitch:
Limited Category I
Tractor HP: 18 PTO HP Max
Tine Dimension:
5/16 In. x 1 In. Spring Steel
Tine Spacing: 30 at 1 In.
Raking Positions:
5 Forward (0, 15, 30 Degree) Each Side
- 5 Reverse (0, 15, 30 Degree) Each Side
Parking Stand: Standard
Approximate Operating Weight: 205 lbs.
Shipping Weight:
468 lbs. (Quantity 2)
Assembly/Set-Up Time:
15 Minutes (Approximate) - Per Pair
Pivot: 360 Degrees
Packaged 2 per Crate
Gauge Wheel Kit: Yes
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1762XF		LR5060L - 5 Ft. Limited Category 1 Economy Duty Landscape Rake *Order in multiples of two.*	707.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TITE511225	LR50L Gauge Wheel Kit *Includes two solid wheels, two mounting brackets, and hardware.*	267.80

LR5060L - 5 Ft. Limited Category 1 Economy Duty Landscape Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PM1001 Integral Middle Buster

Equipment for Base Machine

```
Hitch:
  Lift-type, Category I,
  iMatch Compatible
Working Depth:
  Up to 12 In. (304.8 mm)
Transport Length:
  15 In. (381 mm)
Transport Width:
  32 In. ( 812.8 mm)
Transport Height:
  32 In. (812.8 mm)
```

```
Tractor Engine HP Range:
  25 - 45 HP
Blade:
  Double-Wing Cutting Blade,
  19 In. (482.6 mm) x 11 In. (279.4 mm)
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3461XF		PM1001 Integral Middle Buster *Order in multiples of two.*	246.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TITE511154	French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals *PM1001*	14.10

PM1001 Integral Middle Buster
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

MF2204 - 42 in. Wide 3-Point Category I Hitch Mulch Finisher

Equipment for Base Machine

Machine Weight: 753 lbs.
Tractor HP Range: 30-50 HP
Working Width: 42 In.
Unit Length: 53 In.
Unit Height: 35 In.
Number of Blades: 6
Blade Diameter: 16 In.
Blade Thickness: 3 mm
Blade Spacing: 8.25 In.
Blade Type: Notched
Bearing Hanger:
.375 In. Formed Plate with Reinforcement,
2 Each .625 U-bolts per Hanger
Bearing Type: 1 In. Square Sealed Bearing
Gang Axle: 1 In. Square
Gang Adjustment: Pinned Adjustment

3-Point Hitch Type: Category I
iMatch Compatible: Yes
Number of S-Tines: 5
1.75 In. Reversible Chisel Point: 5 (Standard)
9 In. Sweep: 5 (Optional - Order Through Parts)
Right Turning Point: 4 (Optional - Order Through Parts)
Left Turning Point: 4 (Optional - Order Through Parts)
Approximate Set-Up Time: 1 Man Hour

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3521XF		MF2204 - 42 in. Wide 3-Point Category I Hitch Mulch Finisher *Includes two S-tine toolbars.*	2,528.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5PM50062698	French Kit - Includes Operator's Manual and Safety Decals (MF22 Series)	See Parts
	5PM50062291	Rolling Basket Attachment	1,754.62

MF2204 - 42 in. Wide 3-Point Category I Hitch Mulch Finisher
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

MF2206 - 60 in. Wide 3-Point Category I/II Hitch Mulch Finisher

Equipment for Base Machine

Machine Weight: 1066 lbs.
Tractor HP Range: 45-75 HP
Working Width: 60 In.
Unit Length: 74 In.
Unit Height: 35 In.
Number of Blades: 8
Blade Diameter: 18 In.
Blade Thickness: 3.5 mm
Blade Spacing: 7.50 In.
Blade Type: Notched
Bearing Hanger:
.375 Formed Plate with Reinforcement,
2 Each .625 U-bolts per hanger
Bearing Type: 1 In. Square Sealed Bearing
Gang Axle: 1 In. Square
Gang Adjustment: Pinned Adjustment

3-Point Hitch Type: Category I/II
iMatch Compatible: Yes
Number of S-Tines: 7
1.75 In. Reversible Chisel Point: 7 (Standard)
9 In. Sweep: 7 (Optional - Order Through Parts)
Right Turning Point: 3 (Optional - Order Through Parts)
Left Turning Point: 3 (Optional - Order Through Parts)
Approximate Set-Up Time: 1 Man Hour

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3523XF		MF2206 - 60 in. Wide 3-Point Category I/II Hitch Mulch Finisher *Includes two S-tine toolbars.*	3,935.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5PM50062698	French Kit - Includes Operator's Manual and Safety Decals (MF22 Series)	See Parts
	5PM50062292	Rolling Basket Attachment	1,904.21

THIS PAGE IS INTENTIONALLY LEFT BLANK

MF2208 - 82 in. Wide 3-Point Category I/II Hitch Mulch Finisher

Equipment for Base Machine

Machine Weight: 1242 lbs.
Tractor HP Range: 60-100 HP
Working Width: 82 In.
Unit Length: 74 In.
Unit Height: 35 In.
Number of Blades: 12
Blade Diameter: 18 In.
Blade Thickness: 3.5 mm
Blade Spacing: 7.50 In.
Blade Type: Notched
Bearing Hanger:
.375 In. Formed Plate with Reinforcement,
2 Each .625 U-bolts per Hanger
Bearing Type: 1 In. Square Sealed Bearing
Gang Axle: 1 In. Square
Gang Adjustment: Pinned Adjustment

3-Point Hitch Type: Category I/II
iMatch Compatible: Yes
Number of S-Tines: 9
1.75 In. Reversible Chisel Point: 9 (Standard)
9 In. Sweep: 9 (Optional - Order Through Parts)
Right Turning Point: 4 (Optional - Order Through Parts)
Left Turning Point: 4 (Optional - Order Through Parts)
Approximate Set-Up Time: 1 Man Hour

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3524XF		MF2208 - 82 in. Wide 3-Point Category I/II Hitch Mulch Finisher *Includes two S-tine toolbars.*	4,497.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5PM50062698	French Kit - Includes Operator's Manual and Safety Decals (MF22 Series)	See Parts
	5PM50062293	Rolling Basket Attachment	2,122.08

MF2208 - 82 in. Wide 3-Point Category I/II Hitch Mulch Finisher
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA006 Post Hole Auger 6 In. for PHD100

Equipment for Base Machine

```
Diameter: 6 In.
Length: 36 In.
Weight: 24 lbs.
Flighting Type: Single
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s): PHD100
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1211XF		PHA006 Post Hole Auger 6 In. for PHD100	311.00

PHA006 Post Hole Auger 6 In. for PHD100
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA009 Post Hole Auger 9 In. for PHD100

Equipment for Base Machine

```
Diameter: 9 In.
Length: 36 In.
Weight: 42 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s): PHD100
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1212XF		PHA009 Post Hole Auger 9 In. for PHD100	328.00

PHA009 Post Hole Auger 9 In. for PHD100
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA012 Post Hole Auger 12 In. for PHD100

Equipment for Base Machine

```
Diameter: 12 In.
Length: 36 In.
Weight: 52 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s): PHD100
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1213XF		PHA012 Post Hole Auger 12 In. for PHD100	416.00

PHA012 Post Hole Auger 12 In. for PHD100
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA106 Post Hole Auger 6 In. for PHD200/300/400

Equipment for Base Machine

```
Diameter: 6 In.
Length: 48 In.
Weight: 32 lbs.
Flighting Type: Single
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s):
  PHD200, PHD300, PHD400
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1214XF	PHA106 Post Hole Auger 6 In. for PHD200/300/400	314.00

PHA106 Post Hole Auger 6 In. for PHD200/300/400
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA109 Post Hole Auger 9 In. for PHD200/300/400

Equipment for Base Machine

```
Diameter: 9 In.
Length: 48 In.
Weight: 55 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s):
  PHD200, PHD300, PHD400
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1215XF		PHA109 Post Hole Auger 9 In. for PHD200/300/400	329.00

PHA109 Post Hole Auger 9 In. for PHD200/300/400
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA112 Post Hole Auger 12 In. for PHD200/300/400

Equipment for Base Machine

```
Diameter: 12 In.
Length: 48 In.
Weight: 55 lbs.
Flighting Type: Double
Flighting Thickness: 3/16 In.
Compatible With Digger Model Number(s):
  PHD200, PHD300, PHD400
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1216XF		PHA112 Post Hole Auger 12 In. for PHD200/300/400	401.00

PHA112 Post Hole Auger 12 In. for PHD200/300/400
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA118 Post Hole Auger 18 In. for PHD300/400

Equipment for Base Machine

```
Diameter: 18 In.
Length: 48 In.
Weight: 80 lbs.
Flighting Type: Double
Flighting Thickness: 1/4 In.
Compatible With Digger Model Number(s):
  PHD300, PHD400
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1217XF		PHA118 Post Hole Auger 18 In. for PHD300/400	542.00

PHA118 Post Hole Auger 18 In. for PHD300/400
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA124 Post Hole Auger 24 In. for PHD300/400

Equipment for Base Machine

```
Diameter: 24 In.
Length: 48 In.
Weight: 105 lbs.
Flighting Type: Double
Flighting Thickness: 1/4 In.
Compatible With Digger Model Number(s):
  PHD300, PHD400
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1218XF		PHA124 Post Hole Auger 24 In. for PHD300/400	731.00

PHA124 Post Hole Auger 24 In. for PHD300/400
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHA130 Post Hole Auger 30 In. for PHD300/400

Equipment for Base Machine

Diameter: 30 In.
Length: 44 In.
Weight: 213 lbs.
Flighting Type:
  Double (15 In. and 30 In.)
Flighting Thickness: 5/16 In.
Compatible With Digger Model Number(s):

PHD300, PHD400

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1219XF		PHA130 Post Hole Auger 30 In. for PHD300/400 *Tapered flighting for planting trees.*	1,539.00

PHA130 Post Hole Auger 30 In. for PHD300/400
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHD100 Post Hole Digger Up to 25HP Category I Hitch

Equipment for Base Machine

Boom OD: 2-7/8 In.
Yoke OD: 2-3/8 In.
Auger Speed: 180 RPM
Gearbox Gear Ratio: 3:1
Gearbox HP Rating: 25 HP
PTO HP Range: 18-25 HP
3-Point Hitch Category: Category I
Works with Auger Model Numbers:
PHA006, PHA009, PHA012

Weight: 112 lbs.
Shipping Weight (2 per Crate): 330 lbs.
Set-Up Time: 20 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1221XF		PHD100 Post Hole Digger Up to 25HP Category I Hitch *Order in multiples of two.*	1,038.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Hook-Up Stand *For customer use.*	471.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950960B	French OM & Decal Kit Post Hole Diggers *Destination of Quebec only. Includes French safety decals and manul.*	0.00
	5BP480099851	Post Hole Digger Hookup Stand *For customer use.*	508.68

PHD100 Post Hole Digger Up to 25HP Category I Hitch
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHD200 Post Hole Digger Up to 40HP Category I Hitch

Equipment for Base Machine

Boom OD: 3-1/2 In.
Yoke OD: 2-7/8 In.
Auger Speed: 180 RPM
Gearbox Gear Ratio: 3:1
Gearbox HP Rating: 40 HP
PTO HP Range: 18-40 HP
3-Point Hitch Category: Category I
Works with Auger Model Numbers:
PHA106, PHA109, PHA112

Weight: 200 lbs.
Shipping Weight (2 per Crate): 470 lbs.
Set-Up Time: 20 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1222XF		PHD200 Post Hole Digger Up to 40HP Category I Hitch *Order in multiples of two.*	1,117.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Hook-Up Stand *For customer use.*	471.00
9010		Post Hole Digger Down Force Kit for PHD200	634.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950960B	French OM & Decal Kit Post Hole Diggers *Destination of Quebec only. Includes French safety decals and manul.*	0.00
	5BP48PHD005	Post Hole Digger Down Force Kit PHD200	684.72
	5BP480099851	Post Hole Digger Hookup Stand *For customer use.*	508.68

PHD200 Post Hole Digger Up to 40HP Category I Hitch
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHD300 Post Hole Digger Up to 50HP Category I & II Hitch

Equipment for Base Machine

Boom OD: 3-1/2 In. Reinforced
Yoke OD: 2-7/8 In. Reinforced
Auger Speed: 154 RPM
Gearbox Gear Ratio: 3.5:1
Gearbox HP Rating: 50 HP
PTO HP Range: 18-50 HP
3-Point Hitch Category: Category I or II
Works with Auger Model Numbers:
PHA106, PHA109, PHA112,
PHA118, PHA124, PHA132

Weight: 230 lbs.
Shipping Weight (2 per Crate): 550 lbs.
Set-Up Time: 20 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1223XF		PHD300 Post Hole Digger Up to 50HP Category I & II Hitch *Order in multiples of two.*	1,377.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Hook-Up Stand *For customer use.*	471.00
9010		Post Hole Digger Down Force Kit for PHD300 and PHD400	654.00
9020		Post Hole Digger Auger Positioning Handle	169.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950960B	French OM & Decal Kit Post Hole Diggers *Destination of Quebec only. Includes French safety decals and manul.*	0.00
	5BP48PHD003	Post Hole Digger Auger Positioning Handle	182.52
	5BP48PHD002	Post Hole Digger Down Force Kit	706.32
	5BP480099851	Post Hole Digger Hookup Stand *For customer use.*	508.68

PHD300 Post Hole Digger Up to 50HP Category I & II Hitch
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PHD400 Post Hole Digger Up to 90HP Category I & II Hitch

Equipment for Base Machine

Boom OD: 3-1/2 In. Reinforced
Yoke OD: 2-7/8 In. Reinforced
Auger Speed: 135 RPM
Gearbox Gear Ratio: 4:1
Gearbox HP Rating: 90 HP
PTO HP Range: 40-90 HP
3-Point Hitch Category: Category I or II
Works with Auger Model Numbers:
PHA106, PHA109, PHA112,
PHA118, PHA124, PHA132

Weight: 260 lbs.
Shipping Weight (2 per Crate): 610 lbs.
Set-Up Time: 20 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1224XF		PHD400 Post Hole Digger Up to 90HP Category I & II Hitch *Order in multiples of two.*	1,668.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Hook-Up Stand *For customer use.*	471.00
9010		Post Hole Digger Down Force Kit for PHD300 and PHD400	654.00
9020		Post Hole Digger Auger Positioning Handle	169.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP950960B	French OM & Decal Kit Post Hole Diggers *Destination of Quebec only. Includes French safety decals and manul.*	0.00
	5BP48PHD003	Post Hole Digger Auger Positioning Handle	182.52
	5BP48PHD002	Post Hole Digger Down Force Kit	706.32
	5BP480099851	Post Hole Digger Hookup Stand *For customer use.*	508.68

THIS PAGE IS INTENTIONALLY LEFT BLANK

PR1148 - 48 In. Power Rake

Equipment for Base Machine

Function: Landscaping and
  Site Development
Hitch Compatibility:
  Category I and iMatch Compatible
Rotor: Cylindrical with
  Welded Carbide Teeth
Carbide Teeth per Rotor: 76
Depth Control: Dual Independently
  Adjustable Gauge Wheels
Gauge Wheel Description: 13 x 5.00-6
Gauge Wheel Height Adjustment:
  Manual Split Clamp
Angle Adjustment: Hydraulic
Hydraulic Cylinder Manufacturer:
  Best Metal Ind.
Hydraulic Cylinder Description: 1.50 In.
  Bore 0.75 In. Rod 6.00 In. Stroke
Working Angles R or L: 0-15 Degrees
Height: 34 In.
Transport Width: 54 In.
Working Width: 48 In.
Working Width at Maximum Angle: 46 In.
Roll-Back Barrier Range:
  5/16 In. to 3-3/16 In.
Length: 54 In.
Side Drive: Chain ASA 50-2
Chain Case Lube:
  Cenex 365 #00 Fluid grease
Tubing Size: 3 In. x 3 In.
Tubing Wall Thickness: 3/16 In.
Tractor PTO Speed (RPM): 540
Driveline Manufacturer: Weasler
Primary Driveline Description:
  14R with Cut-out Clutch
Secondary Driveline Description:
  1-3/8 In. - 6 Splines Direct to Chain Case
Clutch/Torque Setting (Number): 316
Tractor PTO HP Requirements
  Minimum-Maximum: 15-22 HP
Tractor Hydraulic Requirements: 1500 PSI
Gearbox Manufacturer: Weasler
Gearbox Description:
  Straight Bevel Gear in Oil Bath
Gearbox Oil Recommendation: 85-90W
Gearbox Reduction: 2:1
Rotor Speed (RPM): 285
Rotor Direction of Rotation: Against DOT
Approximate Operating Weight: 500 lbs.
Approximate Shipping Weight: 700 lbs.
Parking Stand: Standard
Approximate Set-Up Time: 20 Minutes
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1231XF	PR1148 - 48 In. Power Rake	8,849.00

PR1148 - 48 In. Power Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PR1160 - 60 In. Power Rake

Equipment for Base Machine

Function: Landscaping and Site Development
Hitch Compatibility: Category I and iMatch Compatible
Rotor: Cylindrical with Welded Carbide Teeth
Carbide Teeth per Rotor: 88
Depth Control: Dual Independently Adjustable Gauge Wheels
Gauge Wheel Description: 13 X 5.00-6
Gauge Wheel Height Adjustment: Manual Split Clamp
Angle Adjustment: Hydraulic
Hydraulic Cylinder Manufacturer: Best Metal Ind.
Hydraulic Cylinder Description: 1.50 In. Bore 0.75 In. Rod 6.00 In. Stroke
Working Angles R or L: 0-15 Degrees
Height: 36 In.
Transport Width: 64 In.
Working Width: 56 In.
Working Width at Maximum Angle: 54 In.
Roll-Back Barrier Range: 5/16 In. to 3-3/16 In.
Length: 55 In.
Side Drive: Chain ASA 50-2
Chain Case Lube: Cenex 365 #00 Fluid Grease
Tubing Size: 3 In. x 3 In.
Tubing Wall Thickness: 3/16 In.
Tractor PTO Speed (RPM): 540
Driveline Manufacturer: Weasler
Primary Driveline Description: 14R
Secondary Driveline Description: 1-3/8 In. 6 Splines to Chain Case with Friction Clutch
Clutch/Torque Setting (Number): 508
Tractor PTO HP Requirements Minimum-Maximum: 18-35 HP
Tractor Hydraulic Requirements: 1500 PSI
Gearbox Manufacturer: Superior
Gearbox Description: Straight Bevel Gear in Oil Bath
Gearbox Oil Recommendation: 85-90W
Gearbox Reduction: 2:1
Rotor Speed (RPM): 285
Rotor Direction of Rotation: Against DOT
Approximate Operating Weight: 550 lbs.
Approximate Shipping Weight: 750 lbs.
Parking Stand: Standard
Approximate Set-Up Time: 20 Minutes
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1232XF		PR1160 - 60 In. Power Rake	9,409.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Grass Seed Attachment for PR1160	6,119.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5SPPS50814	Grass Seed Attachment for PR1160	6,608.52

PR1160 - 60 In. Power Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PR1172 - 72 In. Power Rake

Equipment for Base Machine

Function: Landscaping and
  Site Development
Hitch Compatibility:
  Category I and iMatch Compatible
Rotor: Cylindrical with
  Welded Carbide Teeth
Carbide Teeth per Rotor: 114
Depth Control: Dual Independently
  Adjustable Gauge Wheels
Gauge Wheel Description: 16.5 x 6.5-8
Gauge Wheel Height Adjustment:
  Manual Split Clamp
Angle Adjustment: Hydraulic
Hydraulic Cylinder Manufacturer:
  Best Metal Ind.
Hydraulic Cylinder Description: 1.50 In.
  Bore 0.75 In. Rod 8.00 In. Stroke
Working Angles R or L: 0-15 Degrees
Height: 40 In.
Transport Width: 81 In.
Working Width: 72 In.
Working Width at Maximum Angle: 69.5 In.
Roll-Back Barrier Range:
  5/16 In. to 2-15/16 In.
Length: 62 In.
Side Drive: Chain ASA 60-2
Chain Case Lube:
  Cenex 365 #00 Fluid Grease
Tubing Size: 3 In. x 3 In.
Tubing Wall Thickness: 1/4 In.
Tractor PTO Speed (RPM): 540
Driveline Manufacturer: Weasler
Primary Driveline Description: 14R
Secondary Driveline Description:
  35R with Friction Clutch
Clutch/Torque Setting (Number): 1016
Tractor PTO HP Requirements
  Minimum-Maximum: 30-40 HP
Tractor Hydraulic Requirements: 1500 PSI
Gearbox Manufacturer: Superior
Gearbox Description:
  Straight Bevel Gear in Oil Bath
Gearbox Oil Recommendation: 85-90W
Gearbox Reduction: 2:1
Rotor Speed (RPM): 270
Rotor Direction of Rotation: Against DOT
Approximate Operating Weight: 830 lbs.
Approximate Shipping Weight: 1100 lbs.
Parking Stand: Standard
Approximate Set-Up Time:
  45 Minutes
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1233XF		PR1172 - 72 In. Power Rake	10,468.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Grass Seed Attachment for PR1172	6,449.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5SPPS60814	Grass Seed Attachment for PR1172	6,964.92

PR1172 - 72 In. Power Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

PR1184 - 84 In. Power Rake

Equipment for Base Machine

Function: Landscaping and
  Site Development
Hitch Compatibility:
  Category I, Category II,
  iMatch, Quick Coupler Compatible
Rotor: Cylindrical with
  Welded Carbide Teeth
Carbide Teeth per Rotor: 132
Depth Control: Dual Independently
  Adjustable Gauge Wheels
Gauge Wheel Description: 16.5 x 6.5-8
Gauge Wheel Height Adjustment:
  Manual Split Clamp
Angle Adjustment: Hydraulic
Hydraulic Cylinder Manufacturer:
  Best Metal Ind.
Hydraulic Cylinder Description: 2.00 In.
  Bore 1.25 In. rod 8.00 In. Stroke
Working Angles R or L: 0-15 Degrees
Height: 44 In.
Transport Width: 93 In.
Working Width: 84 In.
Working Width at Maximum Angle: 81 In.
Roll-Back Barrier Range:
  5/16 In. to 4-11/16 In.
Length: 70 In.
Side Drive: Chain ASA 60-2H
Chain Case Lube:
  Cenex 365 #00 Fluid Grease
Tubing Size: 4 In. x 4 In.
Tubing Wall Thickness: 5/16 In.
Tractor PTO Speed (RPM): 540
Driveline Manufacturer: Weasler
Primary Driveline Description: 35E
Secondary Driveline Description: 44E with
  Friction Clutch (1-3/4 In. 20 Splines)
Clutch/Torque Setting (Number): 1695
Tractor PTO HP Requirements
  Minimum-Maximum: 42-80 HP
Tractor Hydraulic Requirements: 1500 PSI
Gearbox Manufacturer: Superior
Gearbox Description:
  Straight Bevel Gear in Oil Bath
Gearbox Oil Recommendation: 85-90W
Gearbox Reduction: 2:1
Rotor Speed (RPM): 270
Rotor Direction of Rotation: Against DOT
Approximate Operating Weight: 1260 lbs.
Approximate Shipping Weight: 1700 lbs.
Parking Stand: Standard
Approximate Set-Up Time:
  60 Minutes
Warranty: 1 Year

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1234XF	PR1184 - 84 In. Power Rake	13,678.00

PR1184 - 84 In. Power Rake
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2060 - 5 Ft. Standard Duty Rear Blade

Equipment for Base Machine

3-Point Hitch: Category I
Working Width: 60 In.
Operational Weight: 249 lbs.
Tractor HP: 19 to 45 HP
Tilt Positions: Three
Offset: 12 In. Left or Right
Shipping Weight:
  588 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14 In.
Moldboard Length: 60 In.
Moldboard Thickness: 3/16 In.
Duty: Standard Duty

Cutting Edge:
  1/2 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0 and 15 Degrees Each Side
Skid Shoes: Optional

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1281XF		RB2060 - 5 Ft. Standard Duty Rear Blade *Order in multiples of two.*	717.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS346765	End Plate Kit (RB2060, RB2072 and RB2084)	164.82
	5WS101376	French Operator's Manual and Decal Kit (RB20 and RB20L Series)	31.60
	5WS346745	Skid Shoes Kit (RB2060, RB2072 and RB2084)	243.75

RB2060 - 5 Ft. Standard Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2060L - 5 Ft. Rear Blade - Limited Category I

Equipment for Base Machine

```
Cutting Edge:
  1/2 In. x 6 In. Reversible
Angle Pivot: 360 Degrees
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0, 15 and 30 Degrees Each Side
Moldboard Thickness: 7 Gauge
Moldboard Length: 60 In.
Moldboard Height: 11 In.
Tractor HP (Maximum): 25 HP
3-Point Hitch:
  Limited Category I (Aftermarket
  Category 0 Lift Pins Available)
Parking Stand - Standard
Skid Shoe Bundle: Optional
Operating Weight: 155 lbs.
Shipping Weight:
  402 lbs. (Quantity of 2)
Packaged Two Per Crate
Assembly/Set-Up Time: 30 Minutes
Warranty: 1 Year
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1291XF		RB2060L - 5 Ft. Rear Blade - Limited Category I *Order in multiples of two.*	515.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS101376	French Operator's Manual and Decal Kit (RB20 and RB20L Series)	31.60
	5WS343435	Skid Shoes Kit (RB2060L)	55.75

RB2060L - 5 Ft. Rear Blade - Limited Category I
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2072 - 6 Ft. Standard Duty Rear Blade

Equipment for Base Machine

3-Point Hitch: Category I
Shipping Weight:
  660 lbs. (Quantity 2)
Moldboard Height: 14 In.
Moldboard Length: 72 In.
Moldboard Thickness: 1/4 In.
Duty: Standard Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Angle: 360 Degrees
Angle - Reverse:
  0 and 15 Degrees Each Side
Approximate Operating Weight: 285 lb.
Offset: 12 In. Left or Right

Tractor HP: 23 to 55 HP
Tilt: 3-Positions
Angle - Forward:
  0, 15, and 30 Degrees Each Side
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Assembly/Set-Up Time:
  15 Minutes (Approximate)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1282XF		RB2072 - 6 Ft. Standard Duty Rear Blade *Order in multiples of two.*	797.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS346765	End Plate Kit (RB2060, RB2072 and RB2084)	164.82
	5WS101376	French Operator's Manual and Decal Kit (RB20 and RB20L Series)	31.60
	5WS346745	Skid Shoes Kit (RB2060, RB2072 and RB2084)	243.75

RB2072 - 6 Ft. Standard Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2084 - 7 Ft. Standard Duty Rear Blade

Equipment for Base Machine

3-Point Hitch: Category I
Tractor HP: 27 to 55 HP
Tilt: 3 Position
Shipping Weight:
  700 lbs. (Quantity 2)
Offset:
  12 Inches, Left or Right
Moldboard Thickness: 1/4 In.
Moldboard Length: 84 In.
Moldboard Height: 14 In.
Duty: Standard Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Approximate Operating Weight: 305 lbs.
Angle: 360 Degrees

Angle - Reverse:
  0 and 15 Degrees Each Side
Angle - Forward:
  0, 15, and 30 Degrees Each Side
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Assembly/Set-Up Time:
  15 Minutes (Approximate)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1283XF		RB2084 - 7 Ft. Standard Duty Rear Blade *Order in multiples of two.*	879.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5WS346765	End Plate Kit (RB2060, RB2072 and RB2084)	164.82
	5WS101376	French Operator's Manual and Decal Kit (RB20 and RB20L Series)	31.60
	5WS346745	Skid Shoes Kit (RB2060, RB2072 and RB2084)	243.75

RB2084 - 7 Ft. Standard Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2160 - 5 Ft. Medium Duty Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 60 In.
Working Weight: 392 lbs.
Tractor HP:
  65 HP (Maximum - 2WD)
  60 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 22 degrees Up or Down
Shipping Weight: 426 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  3 Positions, Up to 53 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 53 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 In. or 12 In. Left or Right

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1301XF		RB2160 - 5 Ft. Medium Duty Rear Blade	1,179.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200001	End Plates - Pair (RB21 Series)	113.49
	5TMC6100001	Skid Shoes - Pair (RB21 Series)	125.43

RB2160 - 5 Ft. Medium Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2172 - 6 Ft. Medium Duty Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 72 In.
Working Weight: 422 lbs.
Tractor HP:
  65 HP (Maximum - 2WD)
  60 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 22 degrees Up or Down
Shipping Weight: 456 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  3 Positions, Up to 53 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 53 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 In. or 12 In. Left or Right

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1302XF		RB2172 - 6 Ft. Medium Duty Rear Blade	1,250.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200001	End Plates - Pair (RB21 Series)	113.49
	5TMC6100001	Skid Shoes - Pair (RB21 Series)	125.43

RB2172 - 6 Ft. Medium Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2184 - 7 Ft. Medium Duty Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 84 In.
Working Weight: 448 lbs.
Tractor HP:
  65 HP (Maximum - 2WD)
  60 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 22 degrees Up or Down
Shipping Weight: 482 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  3 Positions, Up to 53 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 53 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset - 6 In. or 12 In. Left or Right

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1303XF		RB2184 - 7 Ft. Medium Duty Rear Blade	1,325.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200001	End Plates - Pair (RB21 Series)	113.49
	5TMC6100001	Skid Shoes - Pair (RB21 Series)	125.43

RB2184 - 7 Ft. Medium Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2196 - 8 Ft. Medium Duty Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 96 In.
Working Weight: 476 lbs.
Tractor HP:
  65 HP (Maximum - 2WD)
  60 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 22 degrees Up or Down
Shipping Weight: 510 lbs.
Angle/Pivot: 360 Degrees
Moldboard Height: 17 In.
Moldboard Thickness: 1/4 In.
Duty: Medium Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  3 Positions, Up to 53 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 53 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset - 6 In. or 12 In. Left or Right

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1304XF		RB2196 - 8 Ft. Medium Duty Rear Blade	1,384.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200001	End Plates - Pair (RB21 Series)	113.49
	5TMC6100001	Skid Shoes - Pair (RB21 Series)	125.43

RB2196 - 8 Ft. Medium Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2160H - 5 Ft. Medium Duty Hydraulic Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 60 in. (1,524 mm)
Working Weight: 379 lbs. (171.9 kg)
Tractor HP:
  50 HP (37.3 kW) (Maximum - 2WD)
  45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 20 degrees Up or Down
Shipping Weight: 459 lbs. (208.2 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
  1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
  Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1551XF		RB2160H - 5 Ft. Medium Duty Hydraulic Rear Blade *Includes one cylinder.*	1,354.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	72.00
9010		End Plates (Pair)	69.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMKMCN021	End Plates (Pair)	77.28
	5TMKHCN101	Hydraulic Cylinder Kit *Includes one cylinder.*	591.29
	5TMKMCN022	Skid Shoes (Pair)	80.64

RB2160H - 5 Ft. Medium Duty Hydraulic Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2172H - 6 Ft. Medium Duty Hydraulic Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 72 in. (1,828.8 mm)
Working Weight: 405 lbs. (183.7 kg)
Tractor HP:
  50 HP (37.3 kW) (Maximum - 2WD)
  45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 20 degrees Up or Down
Shipping Weight: 489 lbs. (221.8 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
  1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
  Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1552XF		RB2172H - 6 Ft. Medium Duty Hydraulic Rear Blade *Includes one cylinder.*	1,459.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	72.00
9010		End Plates (Pair)	69.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMKMCN021	End Plates (Pair)	77.28
	5TMKHCN101	Hydraulic Cylinder Kit *Includes one cylinder.*	591.29
	5TMKMCN022	Skid Shoes (Pair)	80.64

RB2172H - 6 Ft. Medium Duty Hydraulic Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2184H - 7 Ft. Medium Duty Hydraulic Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 84 in. (2,133.6 mm)
Working Weight: 431 lbs. (195.5 kg)
Tractor HP:
  50 HP (37.3 kW) (Maximum - 2WD)
  45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 20 degrees Up or Down
Shipping Weight: 515 lbs. (233.6 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
  1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
  Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1553XF		RB2184H - 7 Ft. Medium Duty Hydraulic Rear Blade *Includes one cylinder.*	1,546.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	72.00
9010		End Plates (Pair)	69.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMKMCN021	End Plates (Pair)	77.28
	5TMKHCN101	Hydraulic Cylinder Kit *Includes one cylinder.*	591.29
	5TMKMCN022	Skid Shoes (Pair)	80.64

RB2184H - 7 Ft. Medium Duty Hydraulic Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2196H - 8Ft. Medium Duty Hydraulic Rear Blade

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Width: 96 in. (2,438.4 mm)
Working Weight: 456 lbs. (206.8 kg)
Tractor HP:
  50 HP (37.3 kW) (Maximum - 2WD)
  45 HP (33.6 kW) (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 20 degrees Up or Down
Shipping Weight: 543 lbs. (246.3 kg)
Angle/Pivot: 360 Degrees
Moldboard Height: 15 in. (381 mm)
Moldboard Thickness: 1/4 in. 6.35 mm)
Duty: Medium Duty
Cutting Edge:
  1/2 x 6 in. Reversible (12.7 x 152.4 mm)

Assembly/Set-Up Time: 60 Minutes
Angle - Forward:
  Hydraulic, Up to 40 Degrees Each Side
Angle - Reverse:
  Hydraulic, Up to 40 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Offset: 6 in. or 12 in. Left or Right (152.4 mm or 304.8 mm)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1554XF		RB2196H - 8Ft. Medium Duty Hydraulic Rear Blade *Includes one cylinder.*	1,643.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	72.00
9010		End Plates (Pair)	69.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMKMCN021	End Plates (Pair)	77.28
	5TMKHCN101	Hydraulic Cylinder Kit *Includes one cylinder.*	591.29
	5TMKMCN022	Skid Shoes (Pair)	80.64

RB2196H - 8Ft. Medium Duty Hydraulic Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2272 - 6 Ft. Medium Plus Rear Blade

Equipment for Base Machine

Hitch:
  3 Point Category II and
  ASAE Category II Quick Coupler
Tractor HP:
  80 HP (Maximum - 2WD)
  70 HP (Maximum - 4WD)
Shipping Weight: 795 lbs.
Moldboard Height: 19 In.
Duty: Medium Plus Duty
Assembly/Set-Up Time: 120 Minutes
Cutting Edge:
  1/2 In. x 6 In. Reversible
Angle/Pivot: 360 Degrees
Moldboard Thickness: 1/4 In.
Moldboard Length: 72 In.
Approximate Operating Weight: 738 lb.
Offset: 9 In. or 18 In. Left or Right
Tilt: 3 Positions,
  Up to 23 Degrees, Up or Down
Angle-Forward:
  3 Positions, Up to 45 Degrees Each Side
Angle-Reverse:
  3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Hydraulic Offset Kit:
  Optional (Hoses and Fittings Included)
Parking Stand: Standard

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1311XF		RB2272 - 6 Ft. Medium Plus Rear Blade	2,116.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200003	End Plates - Pair	135.52
	5TMC6300073	Hydraulic Cylinder Kit	523.83
	5TMC6100002	Skid Shoes - Pair	126.56

RB2272 - 6 Ft. Medium Plus Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2284 - 7 Ft. Medium Plus Rear Blade

Equipment for Base Machine

Hitch:
  3 Point Category II and
  ASAE Category II Quick Coupler
Tractor HP:
  80 HP (Maximum - 2WD)
  70 HP (Maximum - 4WD)
Shipping Weight: 812 lbs.
Moldboard Height: 19 In.
Duty: Medium Plus Duty
Assembly/Set-Up Time: 120 Minutes
Cutting Edge:
  1/2 In. x 6 In. Reversible
Angle/Pivot: 360 Degrees
Moldboard Thickness: 1/4 In.
Moldboard Length: 84 In.
Approximate Operating Weight: 755 lbs.
Offset: 9 In. or 18 In. Left or Right
Tilt: 3 Positions,
  Up to 23 Degrees, Up or Down
Angle-Forward:
  3 Positions, Up to 45 Degrees Each Side
Angle-Reverse:
  3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Hydraulic Offset Kit:
  Optional (Hoses and Fittings Included)
Parking Stand: Standard

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1312XF		RB2284 - 7 Ft. Medium Plus Rear Blade	2,289.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200003	End Plates - Pair	135.52
	5TMC6300073	Hydraulic Cylinder Kit	523.83
	5TMC6100002	Skid Shoes - Pair	126.56

RB2284 - 7 Ft. Medium Plus Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2296 - 8 Ft. Medium Plus Rear Blade

Equipment for Base Machine

Hitch:
  3 Point Category II and
  ASAE Category II Quick Coupler
Tractor HP:
  80 HP (Maximum - 2WD)
  70 HP (Maximum - 4WD)
Shipping Weight: 829 lbs.
Moldboard Height: 19 In.
Duty: Medium Plus Duty
Assembly/Set-Up Time: 120 Minutes
Cutting Edge:
  1/2 In. x 6 In. Reversible
Angle/Pivot: 360 Degrees
Moldboard Thickness: 1/4 In.
Moldboard Length: 96 In.
Approximate Operating Weight: 772 lbs.
Offset: 9 In. or 18 In. Left or Right
Tilt: 3 Positions,
  Up to 23 Degrees, Up or Down
Angle-Forward:
  3 Positions, Up to 45 Degrees Each Side
Angle-Reverse:
  3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Hydraulic Offset Kit:
  Optional (Hoses and Fittings Included)
Parking Stand: Standard

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1313XF		RB2296 - 8 Ft. Medium Plus Rear Blade	2,394.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200003	End Plates - Pair	135.52
	5TMC6300073	Hydraulic Cylinder Kit	523.83
	5TMC6100002	Skid Shoes - Pair	126.56

RB2296 - 8 Ft. Medium Plus Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB2307 - 7 Ft. Heavy Duty Rear Blade

Equipment for Base Machine

```
Hitch:
  3-Point Category II and
  ASAE Category II Quick Coupler
Tractor HP:
  120 HP (Maximum - 2WD)
  110 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 23 Degrees Up or Down
Shipping Weight: 1117 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 84 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1060 lbs.
Assembly/Set-Up Time:
  120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
  3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
  Optional (Hoses and Fittings Included)
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1321XF		RB2307 - 7 Ft. Heavy Duty Rear Blade	2,549.00
		OPERATION	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt *Includes 3 cylinders.*	1,385.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	113.00
9010		End Plates (Pair)	121.00
9020		Hydraulic Diverter Kit	440.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMC6200003	End Plates - Pair	135.52
	5TMC0040025K	French Operator's Manual and Decal Kit *Rear Blades RB2307, RB2308, RB2309 and RB2310.*	6.82
	5TMC6300073	Hydraulic Cylinder Kit *Offset or Tilt - Includes 1 Cylinder (RB23 Series).*	523.83
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	536.77
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	475.20

RB2307 - 7 Ft. Heavy Duty Rear Blade
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5TMC6100002	Skid Shoes - Pair	126.56

RB2308 - 8 Ft. Heavy Duty Rear Blade

Equipment for Base Machine

```
Hitch:
  3-Point Category II and
  ASAE Category II Quick Coupler
Tractor HP:
  120 HP (Maximum - 2WD)
  110 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 23 Degrees Up or Down
Shipping Weight: 1196 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 96 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1139 lbs.
Assembly/Set-Up Time:
  120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
  3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
  Optional (Hoses and Fittings Included)
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1322XF		RB2308 - 8 Ft. Heavy Duty Rear Blade	2,700.00
		OPERATION	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt *Includes 3 cylinders.*	1,385.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	113.00
9010		End Plates (Pair)	121.00
9020		Hydraulic Diverter Kit	440.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMC6200003	End Plates - Pair	135.52
	5TMC0040025K	French Operator's Manual and Decal Kit *Rear Blades RB2307, RB2308, RB2309 and RB2310.*	6.82
	5TMC6300073	Hydraulic Cylinder Kit *Offset or Tilt - Includes 1 Cylinder (RB23 Series).*	523.83
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	536.77
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	475.20

RB2308 - 8 Ft. Heavy Duty Rear Blade
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5TMC6100002	Skid Shoes - Pair	126.56

RB2309 - 9 Ft. Heavy Duty Rear Blade

Equipment for Base Machine

```
Hitch:
  3-Point Category II and
  ASAE Category II Quick Coupler
Tractor HP:
  120 HP (Maximum - 2WD)
  110 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 23 Degrees Up or Down
Shipping Weight: 1297 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 108 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1240 lbs.
Assembly/Set-Up Time:
  120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
  3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
  Optional (Hoses and Fittings Included)
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1323XF		RB2309 - 9 Ft. Heavy Duty Rear Blade	2,829.00
		OPERATION	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt *Includes 3 cylinders.*	1,385.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	113.00
9010		End Plates (Pair)	121.00
9020		Hydraulic Diverter Kit	440.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMC6200003	End Plates - Pair	135.52
	5TMC0040025K	French Operator's Manual and Decal Kit *Rear Blades RB2307, RB2308, RB2309 and RB2310.*	6.82
	5TMC6300073	Hydraulic Cylinder Kit *Offset or Tilt - Includes 1 Cylinder (RB23 Series).*	523.83
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	536.77
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	475.20

RB2309 - 9 Ft. Heavy Duty Rear Blade
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5TMC6100002	Skid Shoes - Pair	126.56

RB2310 - 10 Ft. Heavy Duty Rear Blade

Equipment for Base Machine

```
Hitch:
  3-Point Category II and
  ASAE Category II Quick Coupler
Tractor HP:
  120 HP (Maximum - 2WD)
  110 HP (Maximum - 4WD)
Tilt: 3 Positions,
  Up to 23 Degrees Up or Down
Shipping Weight: 1357 lbs.
Offset: 9 In. or 18 In. Left or Right
Moldboard Thickness: 5/16 In.
Moldboard Length: 120 In.
Moldboard Height: 19 In.
Duty: Heavy Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Approximate Operating Weight: 1300 lbs.
Assembly/Set-Up Time:
  120 Minutes (Approximate)
Angle: 360 Degrees
Angle - Forward:
  3 Positions, Up to 45 Degrees Each Side
Angle - Reverse:
  3 Positions, Up to 45 Degrees Each Side
Skid Shoes (Pair): Optional
End Plates (Pair): Optional
Parking Stand: Standard
Hydraulic Tilt, Angle and Offset Kits:
  Optional (Hoses and Fittings Included)
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1324XF		RB2310 - 10 Ft. Heavy Duty Rear Blade	2,905.00
		OPERATION	
1000		Manual Kit	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt *Includes 3 cylinders.*	1,385.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	113.00
9010		End Plates (Pair)	121.00
9020		Hydraulic Diverter Kit	440.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMC6200003	End Plates - Pair	135.52
	5TMC0040025K	French Operator's Manual and Decal Kit *Rear Blades RB2307, RB2308, RB2309 and RB2310.*	6.82
	5TMC6300073	Hydraulic Cylinder Kit *Offset or Tilt - Includes 1 Cylinder (RB23 Series).*	523.83
	5TMC6300083	Hydraulic Cylinder Kit - Angle - Includes 1 Cylinder (RB23 Series)	536.77
	5TMC6300051	Hydraulic Diverter Kit (RB23 Series)	475.20

RB2310 - 10 Ft. Heavy Duty Rear Blade
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5TMC6100002	Skid Shoes - Pair	126.56

RB2408 - 8 Ft. Heavy Plus Rear Blade

Equipment for Base Machine

Hitch:
  3-Point Category II, III and
  ASAE Quick Coupler Category II, III
Tractor HP:
  160 HP (Maximum - 2WD)
  145 HP (Maximum - 4WD)
Tilt: 2 Positions,
  Up to 15 Degrees, Up or Down
Shipping Weight: 1554 lbs.
Offset:
  0 In. to 28 In. Right,
  0 In. to 26 In. Left
Moldboard Thickness: 5/16 In.
Moldboard Length: 96 In.
Moldboard Height: 19 In.
Duty: Heavy Plus Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
  180 Minutes (Approximate)

Approximate Operating Weight: 1451 lbs.
Angle: 360 Degrees
Angle Forward:
  4 Positions, Up to 26 Degrees Right
  5 Positions, Up to 38 Degrees Left
Angle Reverse:
  4 Positions, Up to 26 Degrees Right
  5 Positions, Up to 38 Degrees Left
Parking Stand: Standard
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Tailwheel: Optional
Hydraulic Tilt and Offset Kits:
  Optional (Hoses and Fittings Included)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1331XF		RB2408 - 8 Ft. Heavy Plus Rear Blade	4,468.00

OPERATION

1000		Manual Kit *Includes quantity 1 hydraulic angle cylinder, mechanical offset link, mechanical tilt link.*	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt *Includes 3 cylinders.*	902.00

ATTACHMENTS - ORDER AS DESIRED

9000		Skid Shoes (Pair)	37.00
9010		End Plates (Pair)	130.00
9020		Hydraulic Diverter Kit	417.00
9030		Hydraulic Relief Kit	662.00
9040		Hydraulic Tailwheel Kit, Single Gauge Wheel	1,072.00
9050		Hydraulic Tailwheel Kit, Dual Gauge Wheel	1,390.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200004	End Plates - Pair (RB24 Series)	145.60

RB2408 - 8 Ft. Heavy Plus Rear Blade

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5TMC6300053	Hydraulic Cylinder Kit - Offset or Angle - Includes 1 Cylinder (RB24 Series)	560.48
	5TMC6300063	Hydraulic Cylinder Kit - Tilt - Includes 1 Cylinder (RB24 Series)	398.80
	5TMC6600051	Hydraulic Diverter Kit (RB24 Series)	450.36
	5TMC6600061	Hydraulic Relief Kit (RB24 Series)	714.96
	5TMC6100003	Skid Shoes - Pair (RB24 Series)	41.44
	5TMC6600002	TailWheel Kit - Dual Gauge Wheel - Hydraulic (RB24 Series)	1,501.20
	5TMC6600001	TailWheel Kit - Single Gauge Wheel - Hydraulic (RB24 Series)	1,157.76

RB2409 - 9 Ft. Heavy Plus Rear Blade

Equipment for Base Machine

Hitch:
  3-Point Category II, III and
  ASAE Quick Coupler Category II, III
Tractor HP:
  160 HP (Maximum - 2WD)
  145 HP (Maximum - 4WD)
Tilt: 2 Positions,
  Up to 15 Degrees, Up or Down
Shipping Weight: 1604 lbs.
Offset:
  0 In. to 28 In. Right
  0 In. to 26 In. Left
Moldboard Thickness: 5/16 In.
Moldboard Length: 108 In.
Moldboard Height: 19 In.
Duty: Heavy Plus Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
  180 Minutes (Approximate)

Approximate Operating Weight: 1501 lbs.
Angle: 360 Degrees
Angle Forward:
  4 Positions, Up to 26 Degrees Right
  5 Positions, Up to 38 Degrees Left
Angle Reverse:
  4 Positions, Up to 26 Degrees Right
  5 Positions, Up to 38 Degrees Left
Parking Stand: Standard
Skid Shoe Bundle: Optional
End Plate Bundle: Optional
Tailwheel: Optional
Hydraulic Tilt and Offset Kits:
  Optional (Hoses and Fittings Included)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1332XF		RB2409 - 9 Ft. Heavy Plus Rear Blade	4,506.00

OPERATION

1000		Manual Kit *Includes quantity 1 hydraulic angle cylinder, mechanical offset link, mechanical tilt link.*	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt *Includes 3 cylinders.*	902.00

ATTACHMENTS - ORDER AS DESIRED

9000		Skid Shoes (Pair)	37.00
9010		End Plates (Pair)	130.00
9020		Hydraulic Diverter Kit	417.00
9030		Hydraulic Relief Kit	662.00
9040		Hydraulic Tailwheel Kit, Single Gauge Wheel	1,072.00
9050		Hydraulic Tailwheel Kit, Dual Gauge Wheel	1,390.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5TMC6200004	End Plates - Pair (RB24 Series)	145.60

RB2409 - 9 Ft. Heavy Plus Rear Blade

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5TMC6300053	Hydraulic Cylinder Kit - Offset or Angle - Includes 1 Cylinder (RB24 Series)	560.48
	5TMC6300063	Hydraulic Cylinder Kit - Tilt - Includes 1 Cylinder (RB24 Series)	398.80
	5TMC6600051	Hydraulic Diverter Kit (RB24 Series)	450.36
	5TMC6600061	Hydraulic Relief Kit (RB24 Series)	714.96
	5TMC6100003	Skid Shoes - Pair (RB24 Series)	41.44
	5TMC6600002	TailWheel Kit - Dual Gauge Wheel - Hydraulic (RB24 Series)	1,501.20
	5TMC6600001	TailWheel Kit - Single Gauge Wheel - Hydraulic (RB24 Series)	1,157.76

RB2410 - 10 Ft. Heavy Plus Rear Blade

Equipment for Base Machine

Hitch:
  3-Point Category II, III and
  ASAE Quick Coupler Category II, III
Tractor HP:
  160 HP (Maximum - 2WD)
  145 HP (Maximum - 4WD)
Tilt: 2 Positions,
  Up to 15 Degrees, Up or Down
Shipping Weight: 1653 lbs.
Offset:
  0 In. to 28 In. Right
  0 In. to 26 In. Left
Moldboard Thickness: 5/16 In.
Moldboard Length: 120 In.
Moldboard Height: 19 In.
Duty: Heavy Plus Duty
Cutting Edge:
  1/2 In. x 6 In. Reversible
Assembly/Set-Up Time:
  180 Minutes (Approximate)

Approximate Operating Weight: 1550 lbs.
Angle: 360 Degrees
Angle Forward:
  4 Positions, Up to 26 Degrees Right
  5 Positions, Up to 38 Degrees Left
Angle Reverse:
  4 Positions, Up to 26 Degrees Right
  5 Positions, Up to 38 Degrees Left
Parking Stand: Standard
Skid Shoe Bundle: Optional
End Plates Bundle: Optional
Tailwheel: Optional
Hydraulic Tilt and Offset Kits:
  Optional (Hoses and Fittings Included)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1333XF		RB2410 - 10 Ft. Heavy Plus Rear Blade	4,729.00
		OPERATION	
1000		Manual Kit *Includes quantity 1 hydraulic angle cylinder, mechanical offset link, mechanical tilt link.*	In Base Price
1010		Hydraulic Cylinder Kit, Angle - Offset - Tilt *Includes 3 cylinders.*	902.00
		ATTACHMENTS - ORDER AS DESIRED	
9000		Skid Shoes (Pair)	37.00
9010		End Plates (Pair)	130.00
9020		Hydraulic Diverter Kit	417.00
9030		Hydraulic Relief Kit	662.00
9040		Hydraulic Tailwheel Kit, Single Gauge Wheel	1,072.00
9050		Hydraulic Tailwheel Kit, Dual Gauge Wheel	1,390.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TMC6200004	End Plates - Pair (RB24 Series)	145.60

RB2410 - 10 Ft. Heavy Plus Rear Blade
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5TMC6300053	Hydraulic Cylinder Kit - Offset or Angle - Includes 1 Cylinder (RB24 Series)	560.48
	5TMC6300063	Hydraulic Cylinder Kit - Tilt - Includes 1 Cylinder (RB24 Series)	398.80
	5TMC6600051	Hydraulic Diverter Kit (RB24 Series)	450.36
	5TMC6600061	Hydraulic Relief Kit (RB24 Series)	714.96
	5TMC6100003	Skid Shoes - Pair (RB24 Series)	41.44
	5TMC6600002	TailWheel Kit - Dual Gauge Wheel - Hydraulic (RB24 Series)	1,501.20
	5TMC6600001	TailWheel Kit - Single Gauge Wheel - Hydraulic (RB24 Series)	1,157.76

RB5060 - 5 Ft. Standard Duty Rear Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
Working Width: 60 In.
Operational Weight: 308 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
  674 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 60 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
  3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0, 15 and 30 Degrees Each Side
Skid Shoes: NA

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1651XF	RB5060 - 5 Ft. Standard Duty Rear Blade *Order in multiples of two.*	697.00

RB5060 - 5 Ft. Standard Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB5072 - 6 Ft. Standard Duty Rear Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
Working Width: 72 In.
Operational Weight: 332 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
  722 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 72 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
  3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0, 15 and 30 Degrees Each Side
Skid Shoes: NA

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1652XF	RB5072 - 6 Ft. Standard Duty Rear Blade *Order in multiples of two.*	750.00

RB5072 - 6 Ft. Standard Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB5084 - 7 Ft. Standard Duty Rear Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
Working Width: 84 In.
Operational Weight: 348 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
  754 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 84 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
  3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0, 15 and 30 Degrees Each Side
Skid Shoes: NA

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1653XF	RB5084 - 7 Ft. Standard Duty Rear Blade *Order in multiples of two.*	802.00

RB5084 - 7 Ft. Standard Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB5096 - 8 Ft. Standard Duty Rear Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
Working Width: 96 In.
Operational Weight: 380 lbs.
Tractor HP: 20 to 56 HP
Tilt Positions: Seven
Offset: 12 In. Left or Right
Shipping Weight:
  818 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 96 In.
Moldboard Thickness: 1/4 In.

Duty: Standard Duty
Cutting Edge:
  3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0, 15 and 30 Degrees Each Side
Skid Shoes: NA

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1654XF	RB5096 - 8 Ft. Standard Duty Rear Blade *Order in multiples of two.*	862.00

RB5096 - 8 Ft. Standard Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB5048L - 4 Ft. Limited Category 1 Economy Duty Rear Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
Working Width: 48 In.
Operational Weight: 186 lbs.
Tractor HP: 18 PTO HP Max
Tilt Positions: None
Offset: None
Shipping Weight:
  430 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 48 In.
Moldboard Thickness: 1/4 In.
Duty: Economy Duty

Cutting Edge:
  3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
  (Approximate) - Per Pair
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0, 15 and 30 Degrees Each Side
Skid Shoes: NA

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1751XF	RB5048L - 4 Ft. Limited Category 1 Economy Duty Rear Blade *Order in multiples of two.*	472.00

RB5048L - 4 Ft. Limited Category 1 Economy Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RB5060L - 5 Ft. Limited Category 1 Economy Duty Rear Blade

Equipment for Base Machine

3-Point Hitch:
  Category I
Working Width: 60 In.
Operational Weight: 205 lbs.
Tractor HP: 18 PTO HP Max
Tilt Positions: None
Offset: None
Shipping Weight:
  468 lbs. for Quantity 2
Pivot: 360 Degrees
Parking Stand: Standard
Packaged 2 Per Crate
Moldboard Height: 14.5 In.
Moldboard Length: 60 In.
Moldboard Thickness: 1/4 In.
Duty: Economy Duty

Cutting Edge:
  3/8 In. x 6 In. Reversible
Assembly/Set-Up Time: 15 Minutes
  (Approximate) - Per Pair
Angle - Forward:
  0, 15 and 30 Degrees Each Side
Angle - Reverse:
  0, 15 and 30 Degrees Each Side
Skid Shoes: NA

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1752XF	RB5060L - 5 Ft. Limited Category 1 Economy Duty Rear Blade *Order in multiples of two.*	532.00

RB5060L - 5 Ft. Limited Category 1 Economy Duty Rear Blade
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SW2160 - 60 In. Hydraulic, 300 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S.

Equipment for Base Machine

Function: Sweeping
Working Width: 60 In. (1,524 mm)
Working Width at Max Angle: 55 In. (1,397 mm)
Transport Width: 72 In. (1,828.8 mm)
Operating Weight: 860 lb. (390 kg.)
Standard Bristle Material: Poly, 50/50 Steel/Poly
Available as Replacement
Brush Speed: 160 RPM
Brush Diameter: 32 In. (812.8 mm)
Angle Range: 23 degrees left or right
Hood Thickness: 14 gauge
Side Frame Thickness: 3/16 In. (4.8 mm)
Parking Stands Included
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1591XF		SW2160 - 60 In. Hydraulic, 300 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S. *Must only be used with HP2025 Hydraulic Power Pack Unit.*	12,522.00
		HYDRAULIC POWER UNITS	
1000		HP2025 - Hydraulic Power Unit, 25 HP *Includes wiring harness to control the loader mounted implement.*	In Base Price
1095		Less HP2025 Hydraulic Power Unit	-6,499.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095		Less Oil Cooler	-1,660.00
		ATTACHMENTS - ORDER AS DESIRED	
		Dust Deflector:	
9000		SW2160 Steel/Rubber Dust Deflector Kit	263.89
		Dust Suppression Kit:	
9010		SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,850.58

SW2160 - 60 In. Hydraulic, 300 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS - ORDER AS DESIRED ...Continued...	
		Gauge Wheel Kit:	
9020		SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	632.00
		Lawn Dethatching Kit:	
9030		SW21 Lawn Dethatching Kit *Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.*	395.51
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	92.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0035	SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,937.26
	5RDF0033	SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	661.61
	5RDF0034	SW21 Lawn Dethatching Kit *Requires gauge wheel kit, compatible with dust suppression kit.*	414.04
	5RDF0043	SW2160 50/50 Poly/Steel Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	612.05
	5RDF0030	SW2160 Dust Deflector Kit	276.25
	5RDF0040	SW2160 Poly Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	594.57
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S.

Equipment for Base Machine

Function: Sweeping
Working Width: 72 In. (1,828.8 mm)
Working Width at Max Angle: 66 In. (1,676.4 mm)
Transport Width: 84 In. (2,133.6 mm)
Operating Weight: 890 lb. (403.7 kg.)
Standard Bristle Material: Poly, 50/50 Steel/Poly
Available as Replacement
Brush Speed: 160 RPM
Brush Diameter: 32 In. (812.8 mm)
Angle Range: 23 degrees left or right
Hood Thickness: 14 gauge
Side Frame Thickness: 3/16 In. (4.8 mm)
Parking Stands Included
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes
Optional:
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1592XF		SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S. *Must be used with either the HP2025 or HP2134 Hydraulic Power Pack Units.*	12,784.00
		HYDRAULIC POWER UNITS	
1000		HP2025 - Hydraulic Power Unit, 25 HP *Includes wiring harness to control the loader mounted implement.*	In Base Price
1095		Less HP2025 Hydraulic Power Unit	-6,499.00
1010		HP2134 - Hydraulic Power Unit, 34 HP *Includes wiring harness to control the loader mounted implement.*	105.06
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095		Less Oil Cooler	-1,660.00

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS - ORDER AS DESIRED	
		Dust Deflector:	
9000		SW2172 Steel/Rubber Dust Deflector Kit	237.74
		Dust Suppression Kit:	
9010		SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,850.58
		Gauge Wheel Kit:	
9020		SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	632.00
		Lawn Dethatching Kit:	
9030		SW21 Lawn Dethatching Kit *Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.*	395.51
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	92.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0035	SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,937.26
	5RDF0033	SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	661.61
	5RDF0034	SW21 Lawn Dethatching Kit *Requires gauge wheel kit, compatible with dust suppression kit.*	414.04
	5RDF0044	SW2172 50/50 Poly/Steel Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	702.32
	5RDF0031	SW2172 Dust Deflector Kit	248.89

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0041	SW2172 Poly Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	702.32
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - U.S.

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2134 Hydraulic Power Unit - U.S.

Equipment for Base Machine

Function: Sweeping
Working Width: 84 In. (2,133.6 mm)
Working Width at Max Angle: 77 In. (1,955.8 mm)
Transport Width: 96 In. (2,438.4 mm)
Operating Weight: 920 lb. (417.3 kg.)
Standard Bristle Material: Poly, 50/50 Steel/Poly
Available as Replacement
Brush Speed: 160 RPM
Brush Diameter: 32 In. (812.8 mm)
Angle Range: 23 degrees left or right
Hood Thickness: 14 gauge
Side Frame Thickness: 3/16 In. (4.8 mm)
Parking Stands Included
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1593XF		SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2134 Hydraulic Power Unit - U.S. *Must only be used with HP2134 Hydraulic Power Pack Unit.*	13,504.00
		HYDRAULIC POWER UNITS	
1010		HP2134 - Hydraulic Power Unit, 34 HP *Includes wiring harness to control the loader mounted implement.*	In Base Price
1095		Less HP2134 Hydraulic Power Unit	-6,610.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095		Less Oil Cooler	-1,660.00
		ATTACHMENTS - ORDER AS DESIRED	
		Dust Deflector:	
9000		SW2184 Steel/Rubber Dust Deflector Kit	237.53
		Dust Suppression Kit:	
9010		SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,850.58

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2134 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS - ORDER AS DESIRED ...Continued...	
		Gauge Wheel Kit:	
9020		SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	632.00
		Lawn Dethatching Kit:	
9030		SW21 Lawn Dethatching Kit *Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.*	395.51
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	92.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0037	Hydraulic Power Unit Cooler Upgrade (HP2134) *Includes complete cooling unit and thermal by-pass manifold. Bolted support for manifold, hoses, fittings, wiring harness and installation instructions. Only for first year power units sold together with a SB2176. Recommended for application generating high heat.*	2,576.21
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0035	SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,937.26
	5RDF0033	SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	661.61
	5RDF0034	SW21 Lawn Dethatching Kit *Requires gauge wheel kit, compatible with dust suppression kit.*	414.04
	5RDF0045	SW2184 50/50 Poly/Steel Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	822.04
	5RDF0032	SW2184 Dust Deflector Kit	248.66
	5RDF0042	SW2184 Poly Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	820.28

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2134 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2134 Hydraulic Power Unit - U.S.

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SW2160 - 60 In. Hydraulic, 300 Series Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada

Equipment for Base Machine

Function: Sweeping
Working Width: 60 In. (1,524 mm)
Working Width at Max Angle: 55 In. (1,397 mm)
Transport Width: 72 In. (1,828.8 mm)
Operating Weight: 860 lb. (390 kg.)
Standard Bristle Material: Poly, 50/50 Steel/Poly
Available as Replacement
Brush Speed: 160 RPM
Brush Diameter: 32 In. (812.8 mm)
Angle Range: 23 degrees left or right
Hood Thickness: 14 gauge
Side Frame Thickness: 3/16 In. (4.8 mm)
Parking Stands Included
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
 and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
159AXF		SW2160 - 60 In. Hydraulic, 300 Series Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada *Must only be used with HP2025 Hydraulic Power Pack Unit.*	12,868.24
		HYDRAULIC POWER UNITS	
1000		HP2025 - Hydraulic Power Unit, 25 HP *Includes wiring harness to control the loader mounted implement.*	In Base Price
1095		Less HP2025 Hydraulic Power Unit	-6,793.60
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095		Less Oil Cooler	-1,735.25
		ATTACHMENTS - ORDER AS DESIRED	
		Dust Deflector:	
9000		SW2160 Steel/Rubber Dust Deflector Kit	291.60
		Dust Suppression Kit:	
9010		SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	2,044.89

SW2160 - 60 In. Hydraulic, 300 Series Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS - ORDER AS DESIRED ...Continued...	
		Gauge Wheel Kit:	
9020		SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	698.36
		Lawn Dethatching Kit:	
9030		SW21 Lawn Dethatching Kit *Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.*	437.04
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	101.66
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0035	SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,937.26
	5RDF0033	SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	661.61
	5RDF0034	SW21 Lawn Dethatching Kit *Requires gauge wheel kit, compatible with dust suppression kit.*	414.04
	5RDF0043	SW2160 50/50 Poly/Steel Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	612.05
	5RDF0030	SW2160 Dust Deflector Kit	276.25
	5RDF0040	SW2160 Poly Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	594.57
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada

Equipment for Base Machine

Function: Sweeping
Working Width: 72 In. (1,828.8 mm)
Working Width at Max Angle: 66 In. (1,676.4 mm)
Transport Width: 84 In. (2,133.6 mm)
Operating Weight: 890 lb. (403.7 kg.)
Standard Bristle Material: Poly, 50/50 Steel/Poly
Available as Replacement
Brush Speed: 160 RPM
Brush Diameter: 32 In. (812.8 mm)
Angle Range: 23 degrees left or right
Hood Thickness: 14 gauge
Side Frame Thickness: 3/16 In. (4.8 mm)
Parking Stands Included
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes
Optional:
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

159BXF	SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada *Must be used with either the HP2025 or HP2134 Hydraulic Power Pack Units.*	13,137.49

HYDRAULIC POWER UNITS

1000	HP2025 - Hydraulic Power Unit, 25 HP *Includes wiring harness to control the loader mounted implement.*	In Base Price
1095	Less HP2025 Hydraulic Power Unit	-6,793.60
1010	HP2134 - Hydraulic Power Unit, 34 HP *Includes wiring harness to control the loader mounted implement.*	116.09

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095	Less Oil Cooler	-1,735.25

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS - ORDER AS DESIRED	
		Dust Deflector:	
9000		SW2172 Steel/Rubber Dust Deflector Kit	262.71
		Dust Suppression Kit:	
9010		SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	2,044.89
		Gauge Wheel Kit:	
9020		SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	698.36
		Lawn Dethatching Kit:	
9030		SW21 Lawn Dethatching Kit *Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.*	437.04
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	101.66
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0035	SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,937.26
	5RDF0033	SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	661.61
	5RDF0034	SW21 Lawn Dethatching Kit *Requires gauge wheel kit, compatible with dust suppression kit.*	414.04
	5RDF0044	SW2172 50/50 Poly/Steel Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	702.32
	5RDF0031	SW2172 Dust Deflector Kit	248.89

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0041	SW2172 Poly Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	702.32
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

SW2172 - 72 In. Hydraulic, 300/400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2025 Hydraulic Power Unit - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2143 Hydraulic Power Unit - Canada

Equipment for Base Machine

Function: Sweeping
Working Width: 84 In. (2,133.6 mm)
Working Width at Max Angle: 77 In. (1,955.8 mm)
Transport Width: 96 In. (2,438.4 mm)
Operating Weight: 920 lb. (417.3 kg.)
Standard Bristle Material: Poly, 50/50 Steel/Poly
Available as Replacement
Brush Speed: 160 RPM
Brush Diameter: 32 In. (812.8 mm)
Angle Range: 23 degrees left or right
Hood Thickness: 14 gauge
Side Frame Thickness: 3/16 In. (4.8 mm)
Parking Stands Included
Approximate Set-Up Time: 30 Minutes
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature
and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

159CXF	SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2143 Hydraulic Power Unit - Canada *Must only be used with HP2134 Hydraulic Power Pack Unit.*	13,877.39

HYDRAULIC POWER UNITS

1010	HP2134 - Hydraulic Power Unit, 34 HP *Includes wiring harness to control the loader mounted implement.*	In Base Price
1095	Less HP2134 Hydraulic Power Unit	-6,909.63

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095	Less Oil Cooler	-1,735.25

ATTACHMENTS - ORDER AS DESIRED

	Dust Deflector:	
9000	SW2184 Steel/Rubber Dust Deflector Kit	262.47
	Dust Suppression Kit:	
9010	SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	2,044.89

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2143 Hydraulic Power Unit - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS - ORDER AS DESIRED ...Continued...	
		Gauge Wheel Kit:	
9020		SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	698.36
		Lawn Dethatching Kit:	
9030		SW21 Lawn Dethatching Kit *Includes support components, hardware and installation instruction. Gauge wheel kit required. Compatible with dust suppression kit.*	437.04
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.* *Not available with option Code 1095.*	101.66
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5RDF0038	Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	99.88
	5RDF0037	Hydraulic Power Unit Cooler Upgrade (HP2134) *Includes complete cooling unit and thermal by-pass manifold. Bolted support for manifold, hoses, fittings, wiring harness and installation instructions. Only for first year power units sold together with a SB2176. Recommended for application generating high heat.*	2,576.21
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	1,868.08
	5RDF0035	SW21 Dust Suppression Kit *Includes 60 gallon water tank, electric pump, nozzles, hoses and fittings, electrical harness with switch and installation instructions. Requires the steel/rubber dust deflector kit.*	1,937.26
	5RDF0033	SW21 Gauge Wheel Kit *Includes two pairs 8 In. diameter by 3.5 In. wide solid wheels, mounting brackets and hardware.*	661.61
	5RDF0034	SW21 Lawn Dethatching Kit *Requires gauge wheel kit, compatible with dust suppression kit.*	414.04
	5RDF0045	SW2184 50/50 Poly/Steel Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	822.04
	5RDF0032	SW2184 Dust Deflector Kit	248.66
	5RDF0042	SW2184 Poly Wafter Brush Replacement Kit *Includes required quantity of wafters to replace entire brush.*	820.28

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2143 Hydraulic Power Unit - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0039	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	91.04

SW2184 - 84 In. Hydraulic, 400 Series Carrier Loader Mount Rotary Broom with Hydraulic Angle Adjustment and HP2143 Hydraulic Power Unit - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1142 - 42 In. Standard Duty Rotary Tiller

Equipment for Base Machine

Working Width:
42 In. (1,066.8 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 10 HP (7.5 kW)
Tractor PTO HP (Minimum): 25 HP (18.6 kW)
Blade Shape: C
Skid Shoes: Adjustable
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 254 RPM
Rotor Flanges: 5
Drive Chain: ASA 80
Blades/Rotor: 4
Adjustable Offset:
4 In. (101.6 mm)

Max Working Depth:
6.3 In. (160 mm)
Outside to Outside Width:
46 In. (1,168.4 mm)
Driveline Protection: Shear Bolt
Tillage Depth Control: Skid Shoes
Hitch:
Category I, iMatch Compatible
Frame: Heavy Duty Single Layer

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1357XF		RT1142 - 42 In. Standard Duty Rotary Tiller	2,208.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5MHF20020375	French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	36.02

RT1142 - 42 In. Standard Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1149 - 49 In. Standard Duty Rotary Tiller

Equipment for Base Machine

Working Width:
49 In. (1,244.6 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 20 HP (14.9 kW)
Tractor PTO HP (Minimum): 25 HP (18.6 kW)
Blade Shape: C
Skid Shoes: Adjustable
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 208 RPM
Rotor Flanges: 6
Drive Chain: ASA 80
Blades/Rotor: 4
Adjustable Offset:
8 In. (203.2 mm)

Max Working Depth:
6.3 In. (160 mm)
Outside to Outside Width:
54 In. (1,371.6 mm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch:
Category I, iMatch Compatible
Frame: Heavy Duty Single Layer

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1358XF	RT1149 - 49 In. Standard Duty Rotary Tiller	2,358.00

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous:	
5MHF20020375	French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	36.02

RT1149 - 49 In. Standard Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1157 - 57 In. Standard Duty Rotary Tiller

Equipment for Base Machine

Working Width:
57 In. (1,447.8 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 25 HP (18.6 kW)
Tractor PTO HP (Maximum): 40 HP (29.8 kW)
Blade Shape: C
Skid Shoes: Adjustable
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 208 RPM
Rotor Flanges: 7
Drive Chain: ASA 80
Blades/Rotor: 6
Adjustable Offset:
19 In. (482.6 mm)
Max Working Depth:
7.0 In. (177.8 mm)
Outside to Outside Width:
62 In. (1,574.8 mm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch:
Category I or II, iMatch and
Quick Coupler Compatible
Frame:
Heavy Duty and Bent Frame with
Extra Thickness Above Rotor

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1359XF		RT1157 - 57 In. Standard Duty Rotary Tiller	2,920.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5MHF20020375	French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	36.02

RT1157 - 57 In. Standard Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1165 - 65 In. Standard Duty Rotary Tiller

Equipment for Base Machine

Working Width:
65 In. (1,651 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 30 HP (22.4 kW)
Tractor PTO HP (Maximum): 40 HP (29.8 kW)
Blade Shape: C
Skid Shoes: Adjustable
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 208 RPM
Rotor Flanges: 8
Drive Chain: ASA 80
Blades/Rotor: 6
Adjustable Offset:
23 In. (584.2 mm)
Max Working Depth:
7.0 In. (177.8 mm)
Outside to Outside Width:
70 In. (1,778 mm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch:
Category I or II, iMatch and
Quick Coupler Compatible
Frame:
Heavy Duty and Bent Frame with
Extra Thickness Above Rotor

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

135AXF	RT1165 - 65 In. Standard Duty Rotary Tiller	3,465.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous:

5MHF20020375	French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	36.02

RT1165 - 65 In. Standard Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1173 - 73 In. Standard Duty Rotary Tiller

Equipment for Base Machine

Working Width:
73 In. (1,854.2 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 45 HP (33.6 kW)
Tractor PTO HP (Maximum): 60 HP (44.7 kW)
Blade Shape: C
Skid Shoes: Adjustable
Rear Door Support: Spring
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 228 RPM
Rotor Flanges: 10
Side Drive: Gear
Blades/Rotor: 6
Adjustable Lower Hitches
Max Working Depth:
8.7 In. (221 mm)
Outside to Outside Width:
78 In. (1,981.2 mm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch:
Category II, Quick Coupler Compatible
Frame:
Heavy Duty and Bent Frame with
Extra Thickness Above Rotor

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

135BXF	RT1173 - 73 In. Standard Duty Rotary Tiller	4,426.00

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous:	
MHF20020376	French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	45.04

RT1173 - 73 In. Standard Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1181 - 81 In. Standard Duty Rotary Tiller

Equipment for Base Machine

Working Width:
81 In. (2,057.4 mm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum): 50 HP (37.3 kW)
Tractor PTO HP (Maximum): 60 HP (44.7kW)
Blade Shape: C
Skid Shoes: Adjustable
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 228 RPM
Rotor Flanges: 11
Side Drive: Gear
Blades/Rotor: 6
Rear Door Support: Spring

Max Working Depth:
7.9 In. (200.7 mm)
Outside to Outside Width:
86 In. (2,184.4 mm)
Driveline Protection: Friction Disc
Tillage Depth Control: Skid Shoes
Hitch:
Category II, Quick Coupler Compatible

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
135CXF		RT1181 - 81 In. Standard Duty Rotary Tiller	4,896.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	MHF20020376	French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	45.04

RT1181 - 81 In. Standard Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1265 - 65 In. Medium Duty Rotary Tiller

Equipment for Base Machine

Working Width:
65 In. (165 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
30 HP (22 kW)
Tractor PTO HP (Maximum):
60 HP (44 kW)
Blade Shape: L
Skid Shoes: Adjustable
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 208 RPM
Rotor Flanges: 8
Blades/Rotor: 6
Max Working Depth:
7.9 In. (20 cm)
Outside to Outside Width:
70 In. (178 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch: Category I or II, iMatch
and Quick Coupler Compatible
Frame:
Heavy Duty and Bent Frame with
Extra Thickness Above Rotor

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

136AXF		RT1265 - 65 In. Medium Duty Rotary Tiller *Skid shoes in base. No Roller Option.*	4,098.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5MHF20020375	French Kit - For RT1142, RT1149, RT1157, RT1165. and RT1265 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	36.02

RT1265 - 65 In. Medium Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT1273 - 73 In. Medium Duty Rotary Tiller

Equipment for Base Machine

Working Width:
73 In. (185 cm)
Tractor PTO speed: 540 RPM
Tractor PTO HP (Minimum):
30 HP (22 kW)
Tractor PTO HP (Maximum):
80 HP (59 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Single
Rotor Speed: 213 RPM
Rotor Flanges: 8
Blades/Rotor: 6
Adjustable Lower Hitches
Max Working Depth:
8.7 In. (22 cm)

Outside to Outside Width:
77 In. (196 cm)
Driveline Protection:
Friction Clutch
Tillage Depth Control:
Skid Shoes
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

136BXF		RT1273 - 73 In. Medium Duty Rotary Tiller *Skid shoes in base. No Roller Option.*	6,588.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	MHF20020376	French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	45.04

RT1273 - 73 In. Medium Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT2283 - 83 In. Medium Duty Rotary Tiller

Equipment for Base Machine

Working Width:
83 In. (210 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
60 HP (44kW)
Tractor PTO HP (Maximum):
100 HP (74 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: 140-714-215
(Factory Setting)-266 RPM
Rotor Flanges: 9
Blades/Rotor: 6
Adjustable Lower Hitches
Max Working Depth:
10.6 In. (27 cm)
Outside to Outside Width:
88 In. (224 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1671XF		RT2283 - 83 In. Medium Duty Rotary Tiller *Skid shoes in base. Roller Optional.*	8,465.00

TILLAGE DEPTH CONTROL

1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,087.00
1020		Cage Roller Hydraulic Adjustment	2,305.00

ATTACHMENTS - ORDER AS DESIRED

8000		Right Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00
8010		Left Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	MHF20020376	French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	45.04
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92
	5MH99500263	Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

RT2283 - 83 In. Medium Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT2293 - 93 In. Medium Duty Rotary Tiller

Equipment for Base Machine

Working Width:
93 In. (235 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
70 HP (52 kW)
Tractor PTO HP (Maximum):
100 HP (74 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support: Chain
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: 140-174-215
(Factory Setting)-266 RPM
Rotor Flanges: 10
Blades/Rotor: 6
Adjustable Lower Hitches
Max Working Depth:
10.6 In. (27 cm)
Outside to Outside Width:
98 In. (249 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1672XF		RT2293 - 93 In. Medium Duty Rotary Tiller *Skid shoes in base. Roller Optional.*	8,801.00

TILLAGE DEPTH CONTROL

1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,577.00
1020		Cage Roller Hydraulic Adjustment	2,670.00

ATTACHMENTS - ORDER AS DESIRED

8000		Right Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00
8010		Left Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	MHF20020376	French Kit - For RT1173, RT1181, RT2283, RT2283C, RT1273, and RT2293 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	45.04
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92
	5MH99500263	Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

RT2293 - 93 In. Medium Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT2383 - 82 In. Heavy Duty Rotary Tiller

Equipment for Base Machine

Working Width:
82 In. (208 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
60 HP (44 kW)
Tractor PTO HP (Maximum):
130 HP (96 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support:
Metal Rod with Double Spring
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed:
175-214-262 (Factory Setting)-143 RPM
Rotor Flanges: 9
Blades/Rotor: 6
Max Working Depth:
10.6 In. (27 cm)
Outside to Outside Width:
88 In. (224 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1683XF		RT2383 - 82 In. Heavy Duty Rotary Tiller	9,653.00

TILLAGE DEPTH CONTROL

1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,087.00
1020		Cage Roller Hydraulic Adjustment	2,305.00

ATTACHMENTS - ORDER AS DESIRED

8000		Right Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00
8010		Left Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	MHF20020454	French Kit - For RT2308, RT2383, and RT2310 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	39.83
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92
	5MH99500263	Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

RT2383 - 82 In. Heavy Duty Rotary Tiller
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

RT2308 - 102 In. Heavy Duty Rotary Tiller

Equipment for Base Machine

Working Width:
102 In. (260 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
80 HP (59 kW)
Tractor PTO HP (Maximum):
130 HP (96 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support:
Metal Rod with Double Spring
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: 175-214-262
(Factory Setting)-143 RPM
Rotor Flanges: 11
Blades/Rotor: 6
Max Working Depth:
10.6 In. (27 cm)
Outside to Outside Width:
108 In. (274 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1681XF		RT2308 - 102 In. Heavy Duty Rotary Tiller *Skid shoes in base. Roller Optional.*	10,734.00

TILLAGE DEPTH CONTROL

1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,452.00
1020		Cage Roller Hydraulic Adjustment	2,806.00

ATTACHMENTS - ORDER AS DESIRED

8000		Right Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00
8010		Left Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00
8020		Rotor Flange Reinforcement Kit	758.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	MHF20020454	French Kit - For RT2308, RT2383, and RT2310 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	39.83
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92
	5MH99500263	Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

RT2308 - 102 In. Heavy Duty Rotary Tiller
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5MH99525575	Rotor Flange Reinforcement Kit (RT2308)	818.64

RT2310 - 121 In. Heavy Duty Rotary Tiller

Equipment for Base Machine

Working Width:
121 In. (310 cm)
Tractor PTO Speed: 540 RPM
Tractor PTO HP (Minimum):
100 HP (75 kW)
Tractor PTO HP (Maximum):
130 HP (96 kW)
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support:
Metal Rod with Double Spring
Parking Stand Included
Gearbox Speed: Multi
Rotor Speed: 175-214-262
(Factory Setting)-143 RPM
Rotor Flanges: 13
Blades/Rotor: 6
Max Working Depth:
10.6 In. (27 cm)
Outside to Outside Width:
128 In. (325 cm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes,
Cage Roller Optional
Hitch: Category II,
Quick Coupler Compatible
Frame:
Double-Wall Frame Construction
Above Rotor for Strength and
Rock Protection

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1682XF		RT2310 - 121 In. Heavy Duty Rotary Tiller *Skid shoes in base. Roller Optional.*	12,151.00

TILLAGE DEPTH CONTROL

1000		Skid Shoe	In Base Price
1010		Cage Roller Manual Adjustment	2,765.00
1020		Cage Roller Hydraulic Adjustment	3,136.00

ATTACHMENTS - ORDER AS DESIRED

8000		Right Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00
8010		Left Disc *For RT22, RT23, and RC22 Series. Also for RT310R.*	774.00
8020		Rotor Flange Reinforcement Kit	959.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	MHF20020454	French Kit - For RT2308, RT2383, and RT2310 *Includes Operators Manual, Parts Catalog, and Safety Decals.*	39.83
	5MH99500264	Left Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92
	5MH99500263	Right Disc (RT22, RT23, RC22 Series and Also RT1310R)	835.92

RT2310 - 121 In. Heavy Duty Rotary Tiller
Continued

SP2048B - 4 Ft. Standard Duty Soil Pulverizer - Bar Type

Equipment for Base Machine

3-Point Hitch: Category I
Working Width: 48 In.
Tractor HP (Maximum): 30 to 45 HP
Approximate Shipping Weight: 550 lbs.
Scarifying Teeth - Rear:
(8) 1/2 In x 2 In. Bar Type
Scarifying Teeth - Front:
(9) 1/2 In. x 2 In. Bar Type
Roller Pins: 70
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 5-9/16 In.
Height: 39 In.
H-Beam Dimensions: 10 In. x 10 In.

Duty: Standard Duty
Compression Springs: (2) 160 lbs.
Assembly/Set-Up Time:
10 Minutes (Approximate)
Approximate Operating Weight: 496 lbs.
2nd Roller Assembly 48 In.: Optional

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1401XF		SP2048B - 4 Ft. Standard Duty Soil Pulverizer - Bar Type	2,078.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Second Roller Assembly (SP2048B) *5 In. diameter.*	384.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099887	Second Roller Assembly (SP2048B) *5 In. diameter.*	414.72

SP2048B - 4 Ft. Standard Duty Soil Pulverizer - Bar Type
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SP2060B - 5 Ft. Standard Duty Soil Pulverizer - Bar Type

Equipment for Base Machine

3-Point Hitch: Category I
Working Width: 60 In.
Tractor HP (Maximum): 30 to 45 HP
Approximate Shipping Weight: 702 lbs.
Scarifying Teeth - Rear:
(10) 1/2 In. x 2 In. Bar Type
Scarifying Teeth - Front:
(11) 1/2 In. x 2 In. Bar Type
Roller Pins: 88
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 5-9/16 In.
Height: 39 In.
H-Beam Dimensions: 10 In. x 10 In.

Duty: Standard Duty
Compression Springs: (2) 160 lbs.
Assembly/Set-Up Time:
10 Minutes (Approximate)
Approximate Operating Weight: 652 lbs.
2nd Roller Assembly 60 In.: Optional

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1403XF		SP2060B - 5 Ft. Standard Duty Soil Pulverizer - Bar Type	2,183.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Second Roller Assembly (SP2060B) *5 In. diameter.*	478.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099636	Second Roller Assembly (SP2060B) *5 In. diameter.*	516.24

SP2060B - 5 Ft. Standard Duty Soil Pulverizer - Bar Type
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SP2072B - 6 Ft. Standard Duty Soil Pulverizer - Bar Type

Equipment for Base Machine

```
3-Point Hitch: Category I
Working Width: 72 In.
Tractor HP (Maximum): 30 to 45 HP
Approximate Shipping Weight: 729 lbs.
Scarifying Teeth - Rear:
  (12) 1/2 In. x 2 In.  Bar Type
Scarifying Teeth - Front:
  (13)  1/2 In. x 2 In.  Bar Type
Roller Pins: 106
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 5-9/16 In.
Height: 39 In.
H-Beam Dimensions: 10 In. x 10 In.
Duty: Standard Duty
Compression Springs: (2) 160 lbs.
Assembly/Set-Up Time:
  10 Minutes (Approximate)
Approximate Operating Weight: 679 lbs.
2nd Roller Assembly 72 In.: Optional
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1402XF		SP2072B - 6 Ft. Standard Duty Soil Pulverizer - Bar Type	2,384.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Second Roller Assembly (SP2072B) *5 In. diameter.*	678.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099637	Second Roller Assembly (SP2072B) *5 In. diameter.*	732.24

SP2072B - 6 Ft. Standard Duty Soil Pulverizer - Bar Type
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SP2272B - 6 Ft. Heavy Duty Soil Pulverizer - Bar Type

Equipment for Base Machine

3-Point Hitch: Category I
Working Width: 72 In.
Tractor HP (Maximum): 30 to 70 HP
Shipping Weight: 846 lbs.
Scarifying Teeth - Rear:
(12) 1/2 In. x 2 In. Bar Type
Scarifying Teeth - Front:
(13) 1/2 In. x 2 In. Bar Type
Roller Pins: 106
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 6-5/8 In.
Height: 39 In.
H-Beam Dimensions: 12 In. x 11.5 In.

Duty: Heavy Duty
Compression Springs: (2) 160 lbs.
Assembly/Set-Up Time:
10 Minutes (Approximate)
Approximate Operating Weight: 781 lbs.
2nd Roller Assembly 72 In.: Optional

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1411XF		SP2272B - 6 Ft. Heavy Duty Soil Pulverizer - Bar Type	2,878.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Second Roller Assembly (SP2272B) *5-9/16 In. diameter.*	863.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099646	Second Roller Assembly (SP2272B) *5-9/16 In. diameter.*	932.04

SP2272B - 6 Ft. Heavy Duty Soil Pulverizer - Bar Type
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SP2284B - 7 Ft. Heavy Duty Soil Pulverizer - Bar Type

Equipment for Base Machine

3-Point Hitch: Category I
Working Width: 84 In.
Tractor HP (Maximum): 30 to 70 HP
Shipping Weight: 940 lbs.
Scarifying Teeth - Rear:
(14) 1/2 In. x 2 In. Bar Type
Scarifying Teeth - Front:
(15) 1/2 In. x 2 In. Bar Type
Roller Pins: 124
Roller Pin Size: 3/8 In. x 1 In.
Roller Diameter: 6-5/8 In.
Height: 39 In.
H-Beam Dimensions: 12 In. x 11.5 In.

Duty: Heavy Duty
Compression Springs: (2) 160 lbs.
Assembly/Set-Up Time:
10 Minutes (Approximate)
Approximate Operating Weight: 875 lbs.
2nd Roller Assembly 84 In.: Optional

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1412XF		SP2284B - 7 Ft. Heavy Duty Soil Pulverizer - Bar Type	3,182.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Second Roller Assembly (SP2284B) *5-9/16 In. diameter.*	923.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099647	Second Roller Assembly (SP2284B) *5-9/16 In. diameter.*	996.84

SP2284B - 7 Ft. Heavy Duty Soil Pulverizer - Bar Type
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SS1022B Broadcast Spreader - Pull Type Hitch

Equipment for Base Machine

Hopper Material: Steel
Hopper Weight Capacity: 226 lbs.
Hopper Volume Capacity: 3.5 Cubic Ft.
Machine Weight: 62 lbs.
Shipping Weight (Per Pair): 200 lbs.
Swath Spread: 20 Ft.
Hopper Width: 32 In.
Hopper Height: 39.6 In.
Tractor PTO HP Range: 16-30 HP
PTO RPM: NA (Ground Driven)
PTO Shaft Category (Heavy Duty Shielded 1-3/8 In.): NA (Ground Driven)
3-Point Hitch Category: Single Point
iMatch Compatible Note: Must be Ordered from Factory as iMatch: NA
(Single Point Hitch) iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3061XF		SS1022B Broadcast Spreader - Pull Type Hitch *226 lb. capacity. Order in multiples of two.*	744.00

ATTACHMENTS ORDER AS DESIRED

9010		Hopper Cover (SS1022B and SS1023B)	237.00
9070		Deflector Shield (SS1022B and SS1035B)	95.00
9080		Remote Gate Control (SS1022B, SS1023B and SS1035B)	337.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5BPAA1120	Deflector Shield (SS1022B/SS1035B)	106.40
	5BP0099720	Hopper Cover (SS1022B/SS1023B)	255.96
	5BP0099856	Remote Gate Control (SS1022B/SS1023B/SS1035B)	363.96

SS1022B Broadcast Spreader - Pull Type Hitch
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SS1023B Broadcast Spreader - 3-Point PTO Category I Non-iMatch

Equipment for Base Machine

Hopper Material: Steel
Hopper Weight Capacity: 226 lbs.
Hopper Volume Capacity: 3.5 Cubic Ft.
Machine Weight: 81 lbs.
Shipping Weight (Per Pair): 232 lbs.
Swath Spread: 23 Ft.
Hopper Width: 32 In.
Hopper Height: 31 In.
Tractor PTO HP Range: 16-30 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty Shielded 1-3/8 In.)
3-Point Hitch: Category 0 and I
iMatch Compatible Note: Must be Ordered from Factory as iMatch: NA
(Single Point Hitch) iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3062XF		SS1023B Broadcast Spreader - 3-Point PTO Category I Non-iMatch *226 lb. capacity. Order in multiples of two.*	738.00
		ATTACHMENTS ORDER AS DESIRED	
9010		Hopper Cover (SS1022B and SS1023B)	237.00
9070		Deflector Shield (SS1023B, SS1036B and SS2036B)	97.00
9080		Remote Gate Control (SS1022B, SS1023B and SS1035B)	337.00
9090		Tumbling Wheel Agitator (SS1023B)	76.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099524	Deflector Shield (SS1023B/SS1036B/SS2036B)	108.64
	5BP0099720	Hopper Cover (SS1022B/SS1023B)	255.96
	5BP0099856	Remote Gate Control (SS1022B/SS1023B/SS1035B)	363.96
	5BP0099979	Tumbling Style Wheel Agitator (SS1023B)	85.12

THIS PAGE IS INTENTIONALLY LEFT BLANK

SS1035B Broadcast Spreader - Pull Type Hitch

Equipment for Base Machine

Hopper Material: Steel
Hopper Weight Capacity: 362 lbs.
Hopper Volume Capacity: 5.6 Cubic Ft.
Machine Weight: 84 lbs.
Shipping Weight (Per Pair): 250 lbs.
Swath Spread: 20 Ft.
Hopper Width: 35 In.
Hopper Height: 45 In.
Tractor PTO HP Range: 16-45 HP
PTO RPM: NA (Ground Driven)
PTO Shaft Category (Heavy Duty Shielded 1-3/8 In.): NA (Ground Driven)
3-Point Hitch Category: NA (Single Point Hitch)
iMatch Compatible Note: Must be Ordered from Factory as iMatch: NA
(Single Point Hitch) iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3068XF		SS1035B Broadcast Spreader - Pull Type Hitch *362 lb. capacity. Order in multiples of two.*	1,000.00
		ATTACHMENTS ORDER AS DESIRED	
9010		Hopper Cover (SS1035B, SS1036B and SS2036B)	247.00
9070		Deflector Shield (SS1022B and SS1035B)	95.00
9080		Remote Gate Control (SS1022B, SS1023B and SS1035B)	337.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BPAA1120	Deflector Shield (SS1022B/SS1035B)	106.40
	5BP0099721	Hopper Cover (SS1035B/SS1036B/SS2036B)	266.76
	5BP0099856	Remote Gate Control (SS1022B/SS1023B/SS1035B)	363.96

SS1035B Broadcast Spreader - Pull Type Hitch
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

SS1036B Broadcast Spreader - 3-Point PTO Category I Non-iMatch

Equipment for Base Machine

Hopper Material: Steel
Hopper Weight Capacity: 362 lbs.
Hopper Volume Capacity: 5.6 Cubic Ft.
Machine Weight: 102 lbs.
Shipping Weight (Per Pair): 290 lbs.
Swath Spread: 23 Ft.
Hopper Width: 35 In.
Hopper Height: 34 In.
Tractor PTO HP Range: 16-45 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty Shielded 1-3/8 In.)
3-Point Hitch: Category 0 and I
iMatch Compatible Note: Must be Ordered from Factory as iMatch: No
(Single Point hitch) iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3069XF		SS1036B Broadcast Spreader - 3-Point PTO Category I Non-iMatch *362 lb. capacity. Order in multiples of two.*	776.00
		ATTACHMENTS ORDER AS DESIRED	
9010		Hopper Cover (SS1035B, SS1036B and SS2036B)	247.00
9070		Deflector Shield (SS1023B, SS1036B and SS2036B)	97.00
9080		Remote Gate Control (SS1036B, SS2036B, SS1067B and SS2067B)	337.00
9090		Tumbling Wheel Agitator (SS1036B, SS2036B, SS1067B and SS2067B)	76.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099524	Deflector Shield (SS1023B/SS1036B/SS2036B)	108.64
	5BP0099721	Hopper Cover (SS1035B/SS1036B/SS2036B)	266.76
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	363.96
	5BP0099978	Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	85.12

THIS PAGE IS INTENTIONALLY LEFT BLANK

SS1067B Broadcast Spreader - 3-Point PTO Category I

Equipment for Base Machine

Hopper Material: Steel
Hopper Weight Capacity: 678 lbs.
Hopper Volume Capacity: 10.6 Cubic Ft.
Machine Weight: 125 lbs.
Shipping Weight (Per Pair): 320 lbs.
Swath Spread: 46 Ft.
Hopper Width: 42 In.
Hopper Height: 40 In.
Tractor PTO HP Range: 16-55 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty Shielded 1-3/8 In.)
3-Point Hitch: Category I
iMatch Compatible (Note: Must be Ordered from Factory as iMatch): Optional

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3063XF		SS1067B Broadcast Spreader - 3-Point PTO Category I *678 lb. capacity. Order in multiples of two.*	832.00
		iMATCH COMPATIBILITY	
1000		iMatch Compatible *Leave quantity blank. The system will automatically populate the correct quantity.*	9.00
1010		Non-iMatch Compatible *Leave quantity blank. The system will automatically populate the correct quantity.*	In Base Price
		ATTACHMENTS ORDER AS DESIRED	
9010		Hopper Cover (SS1067B and SS2067B)	253.00
9070		Deflector Shield (SS1067B and SS2067B)	184.00
9080		Remote Gate Control (SS1036B, SS2036B, SS1067B and SS2067B)	337.00
9090		Tumbling Wheel Agitator (SS1036B, SS2036B, SS1067B and SS2067B)	76.00
9100		Siderow Discharge (SS1067B and SS2067B)	391.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099638	Deflector Shield (SS1067B/SS2067B)	198.72
	5BP0099722	Hopper Cover (SS1067B/SS2067B)	273.24
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	363.96
	5BPAA4120	Siderow Discharge (SS1067B/SS2067B)	422.28
	5BP0099978	Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	85.12

SS1067B Broadcast Spreader - 3-Point PTO Category I
Continued

SS2036B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch

Equipment for Base Machine

Hopper Material: Polyethylene
Hopper Weight Capacity: 362 lbs.
Hopper Volume Capacity: 5.6 Cubic Ft.
Machine Weight: 102 lbs.
Shipping Weight (Per Pair): 290 lbs.
Swath Spread: 23 Ft.
Hopper Width: 35 In.
Hopper Height: 34 In.
Tractor PTO HP Range: 16-45 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty Shielded 1-3/8 In.)
3-Point Hitch: Category 0 and I
iMatch Compatible Note: Must be Ordered from Factory as iMatch: No
(Single Point hitch) iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3071XF		SS2036B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch *Stainless steel bottom and nylon spreading disc. 362 lb. capacity. Order in multiples of two.*	1,000.00
		ATTACHMENTS ORDER AS DESIRED	
9010		Hopper Cover (SS1035B, SS1036B and SS2036B)	247.00
9070		Deflector Shield (SS1023B, SS1036B and SS2036B)	97.00
9080		Remote Gate Control (SS1036B, SS2036B, SS1067B and SS2067B)	337.00
9090		Tumbling Wheel Agitator (SS1036B, SS2036B, SS1067B and SS2067B)	76.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099524	Deflector Shield (SS1023B/SS1036B/SS2036B)	108.64
	5BP0099721	Hopper Cover (SS1035B/SS1036B/SS2036B)	266.76
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	363.96
	5BP0099978	Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	85.12

THIS PAGE IS INTENTIONALLY LEFT BLANK

SS2067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I

Equipment for Base Machine

Hopper Material: Polyethylene
Hopper Weight Capacity: 678 lbs.
Hopper Volume Capacity: 10.6 Cubic Ft.
Machine Weight: 125 lbs.
Shipping Weight (Per Pair): 320 lbs.
Swath Spread: 46 Ft.
Hopper Width: 42 In.
Hopper Height: 40 In.
Tractor PTO HP Range: 16-55 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty Shielded 1-3/8 In.)
3-Point Hitch: Category 1
iMatch Compatible (Note: Must be Ordered from Factory as iMatch): Optional

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

3072XF		SS2067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I *Stainless steel bottom and spreading disc. 678 lb. capacity. Order in multiples of two.*	1,297.00

iMATCH COMPATIBILITY

1000		iMatch Compatible *Leave quantity blank. The system will automatically populate the correct quantity.*	9.00
1010		Non-iMatch Compatible *Leave quantity blank. The system will automatically populate the correct quantity.*	In Base Price

ATTACHMENTS ORDER AS DESIRED

9010		Hopper Cover (SS1067B and SS2067B)	253.00
9070		Deflector Shield (SS1067B and SS2067B)	184.00
9080		Remote Gate Control (SS1036B, SS2036B, SS1067B and SS2067B)	337.00
9090		Tumbling Wheel Agitator (SS1036B, SS2036B, SS1067B and SS2067B)	76.00
9100		Siderow Discharge (SS1067B and SS2067B)	391.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5BP0099638	Deflector Shield (SS1067B/SS2067B)	198.72
	5BP0099722	Hopper Cover (SS1067B/SS2067B)	273.24
	5BP0099850	Remote Gate Control (SS1036B/SS2036B/SS1067B/SS2067B)	363.96
	5BPAA4120	Siderow Discharge (SS1067B/SS2067B)	422.28
	5BP0099978	Tumbling Style Wheel Agitator (SS1036B/SS2036B/SS1067B/SS2067B)	85.12

SS2067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I
Continued

SS1079P Pendular Spreader - 3-Point PTO Category I

Equipment for Base Machine

Hopper Weight Capacity: 576 or 820 lbs.
Hopper Volume Capacity: 9 Cubic Ft. or 12.8 Cubic Ft.
Machine Weight: 250 lbs.
Swath Spread Range: 17-47 Ft.
Load Height: 43 In.
Tractor HP Range: 20-60 HP
PTO RPM: 540 RPM

3-Point Hitch: Category I
iMatch Compatible: Yes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3064XF		SS1079P Pendular Spreader - 3-Point PTO Category I	2,691.00
		HOPPER SIZE	
6900		9 Cu. Ft. Hopper (SS1079P)	In Base Price
6912		12.8 Cu. Ft. Hopper (SS1079P)	338.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Agitator Extension (SS1079P)	174.00
9010		Hopper Cover (SS1079P)	262.00
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	299.00
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	107.00
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	72.00
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	48.00
9050		Hydraulic Control (SS1079P, SS1116P, SS1180P and SS1220P)	802.00
9060		Filter Grill (SS1079P)	462.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BPAZ1301	Agitator Extension (SS1079P)	187.92
	5BP0099913	Filter Grill (SS1079P)	See Parts
	5BP0099724	Hopper Cover (SS1079P)	282.96
	5BP0099456	Hydraulic Control (SS1079P)	See Parts
	5BP0095370	Left/Right Directional Attachment	80.64
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	53.76

SS1079P Pendular Spreader - 3-Point PTO Category I
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5BP0099451	Rubber Insert	119.84
	5BP0099452	Salt and Sand Spout	322.92

SS1116P Pendular Spreader - 3-Point PTO Category I or II

Equipment for Base Machine

Hopper Weight Capacity: 1168 lbs.
Hopper Volume Capacity: 22.5 Cubic Ft.
Machine Weight: 321 lbs.
Swath Spread Range: 17-47 Ft.
Load Height: 38 In.
Tractor HP Range: 20-60 HP
PTO RPM: 540 RPM
Three Point Hitch: Category I or II

iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3065XF		SS1116P Pendular Spreader - 3-Point PTO Category I or II *1168 lb. capacity.*	3,598.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Agitator Extension (SS1116P, SS1180P and SS1220P)	174.00
9010		Hopper Cover (SS1116P)	304.00
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	299.00
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	107.00
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	72.00
9050		Hydraulic Control (SS1079P, SS1116P, SS1180P and SS1220P)	802.00
9060		Filter Grill (SS1116P, SS1180P and SS1220P)	417.00
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	48.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099454	Agitator Extension (SS1116P/SS1180P/SS1220P)	187.92
	5BP0095410	Filter Grill (SS1116P/SS1180P/SS1220P)	450.36
	5BP0099725	Hopper Cover (SS1116P)	328.32
	5BP0099455	Hydraulic Control (SS1116P/SS1180P/SS1220P)	866.16
	5BP0095370	Left/Right Directional Attachment	80.64
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	53.76
	5BP0099451	Rubber Insert	119.84

SS1116P Pendular Spreader - 3-Point PTO Category I or II

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5BP0099452	Salt and Sand Spout	322.92

SS1180P Pendular Spreader - 3-Point PTO Category I or II

Equipment for Base Machine

Hopper Weight Capacity: 1808 lbs.
Hopper Volume Capacity: 34.7 Cubic Ft.
Machine Weight: 339 lbs.
Swath Spread Range: 17-47 Ft.
Load Height: 43 In.
Tractor HP Range: 20-60 HP
PTO RPM: 540 RPM
Three Point Hitch: Category I or II

iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3066XF		SS1180P Pendular Spreader - 3-Point PTO Category I or II *1808 lb. capacity.*	4,162.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Agitator Extension (SS1116P, SS1180P and SS1220P)	174.00
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	299.00
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	107.00
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	72.00
9050		Hydraulic Control (SS1079P, SS1116P, SS1180P and SS1220P)	802.00
9060		Filter Grill (SS1116P, SS1180P and SS1220P)	417.00
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	48.00
9550		Hopper Cover (SS1180P)	312.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099454	Agitator Extension (SS1116P/SS1180P/SS1220P)	187.92
	5BP0095410	Filter Grill (SS1116P/SS1180P/SS1220P)	450.36
	5BP0099726	Hopper Cover (SS1180P)	336.96
	5BP0099455	Hydraulic Control (SS1116P/SS1180P/SS1220P)	866.16
	5BP0095370	Left/Right Directional Attachment	80.64
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	53.76
	5BP0099451	Rubber Insert	119.84

SS1180P Pendular Spreader - 3-Point PTO Category I or II
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5BP0099452	Salt and Sand Spout	322.92

SS1220P Pendular Spreader - 3-Point PTO Category I or II

Equipment for Base Machine

Hopper Weight Capacity: 2205 lbs.
Hopper Volume Capacity: 42.4 Cubic Ft.
Machine Weight: 343 lbs.
Swath Spread Range: 17-47 Ft.
Load Height: 47 In.
Tractor HP Range: 20-60 HP
PTO RPM: 540 RPM
Three Point Hitch: Category I or II

iMatch Compatible: No

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3067XF		SS1220P Pendular Spreader - 3-Point PTO Category I or II *2205 lb. capacity.*	4,592.00
		ATTACHMENTS ORDER AS DESIRED	
9000		Agitator Extension (SS1116P, SS1180P and SS1220P)	174.00
9020		Salt and Sand Spout (SS1079P, SS1116P, SS1180P and SS1220P)	299.00
9030		Rubber Insert (SS1079P, SS1116P, SS1180P and SS1220P)	107.00
9040		L/R Direct Att (SS1079P, SS1116P, SS1180P and SS1220P)	72.00
9050		Hydraulic Control (SS1079P, SS1116P, SS1180P and SS1220P)	802.00
9060		Filter Grill (SS1116P, SS1180P and SS1220P)	417.00
9110		Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	48.00
9550		Hopper Cover (SS1220P)	327.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5BP0099454	Agitator Extension (SS1116P/SS1180P/SS1220P)	187.92
	5BP0095410	Filter Grill (SS1116P/SS1180P/SS1220P)	450.36
	5BP0099727	Hopper Cover (SS1220P)	353.16
	5BP0099455	Hydraulic Control (SS1116P/SS1180P/SS1220P)	866.16
	5BP0095370	Left/Right Directional Attachment	80.64
	5BP0014984	Lock Nut for Spout (SS1079P, SS1116P, SS1180P, SS1220P)	53.76
	5BP0099451	Rubber Insert	119.84

SS1220P Pendular Spreader - 3-Point PTO Category I or II
Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5BP0099452	Salt and Sand Spout	322.92

SS3067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch

Equipment for Base Machine

Hopper Material: Polyethylene
Hopper Weight Capacity: 860 lbs.
Hopper Volume Capacity: 10 Cubic Ft.
Machine Weight: 128 lbs.
Shipping Weight (Per Pair): 300 lbs.
Swath Spread: 49 Ft.
Hopper Width: 42 In.
Hopper Height: 42 In.
Tractor PTO HP Range: 20-60 HP
PTO RPM: 540 RPM
PTO Shaft Category I (Heavy Duty Shielded 1-3/8 In.)
3-Point Hitch: Category 1
iMatch Compatible: No
Ships to dealer assembled

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1621XF	SS3067B Broadcast Spreader - Poly Hopper - 3-Point PTO Category I Non-iMatch	737.00

THIS PAGE IS INTENTIONALLY LEFT BLANK

PS1001 Integral Subsoiler

Equipment for Base Machine

Hitch:
  Lift-type, Category I,
  iMatch Compatible
Working Depth:
  Up to 24 In. (609.6 mm)
Transport Length:
  16 In. (406.4 mm)
Transport Width:
  32.5 In. (825.5 mm)
Transport Height:
  49 In. (1,244.6 mm)

Tractor Engine HP Range:
  25 - 45 HP
Point:
  Reversible, Rectangular Sloped Point,
  2.5625 In. (65.1 mm) x 12 In. (304.8 mm)

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3451XF		PS1001 Integral Subsoiler *Order in multiples of two.*	276.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5TITE511154	French Kit - Includes Operator's Manual, Parts Catalog and Safety Decals *PS1001*	14.10

PS1001 Integral Subsoiler
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

DT1136 - 3 pt. Standard Duty Trencher

Equipment for Base Machine

Hitch: 3-Point Category I
  and iMatch
Working Depth at 65 Degree Digging angle: 36 in. (914.4 mm)
Chain Width: 6 in. (152.4 mm)
Working Weight: 650 lbs. (294.8 kg)
Tractor PTO HP:
  15 HP (11.2 kW) Minimum
  30 HP (22.3 kW) Maximum
Recommended Trenching Angle: 65 Degrees
Headshaft Height: 8.5 in. (215.9 mm)
Shipping Weight: 730 lbs. (331.1 kg)
Overall Length: 79 in. (2,006.6 mm)
Overall Width: 38 in. (965.2 mm)
Overall Height: 29 in. (736.6 mm)
Discharge Auger: 14 in. (355.6 mm)
Spoil Discharge Reach: 21 in. (533.4 mm)
540 RPM Rear PTO
Slip Clutch Overload Protection
Parking Stand: Standard
Rear Hydraulics Required

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1561XF	DT1136 - 3 pt. Standard Duty Trencher *Includes 36 in. boom, crummer, and chain.*	7,664.00

DT1136 - 3 pt. Standard Duty Trencher
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

WC1103 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 3 In. Capacity

Equipment for Base Machine

```
Using a Belt Drive System
  PTO Speed Increased from
  540 to 1380-1920 RPM's at Rotor
  (Depending on Model)
High Speed Design Requires Less Horsepower
  than Direct Drive Models
Double Sided A8 Tool Steel Knives
Adjustable Hardened Anvil
```

```
SMV is Standard Equipment
1 Year Parts and Labor Warranty
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1501XF		WC1103 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 3 In. Capacity	3,682.00

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
	5PQ903177	French Operators Manual & Decal Kit WC1103 Wood Chipper *Destination of Quebec only. Includes French safety decals and manual.*	47.04

WC1103 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 3 In. Capacity
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

WC1105 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 5 In. Capacity

Equipment for Base Machine

```
Using a Belt Drive System
  PTO Speed Increased from
  540 to 1380-1920 RPM's at Rotor
  (Depending on Model)
High Speed Design Requires Less Horsepower
  than Direct Drive Models
Double Sided A8 Tool Steel Knives
Adjustable Hardened Anvil
```

```
SMV is Standard Equipment
1 Year Parts and Labor Warranty
```

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)

Select One Code From Each Required Category

BASE MACHINE

1502XF		WC1105 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 5 In. Capacity	5,155.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous:

	5PQ903178	French Operators Manual & Decal Kit WC1105 Wood Chipper *Destination of Quebec only. Includes French safety decals and manual.*	54.88

WC1105 Wood Chipper, 3-Point, PTO Drive, Gravity Feed 5 In. Capacity
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

WC1205 Wood Chipper, 3-Point, PTO Drive, Hydraulic Feed 5 In. Capacity

Equipment for Base Machine

Using a Belt Drive System
  PTO Speed Increased from
  540 to 1380-1920 RPM's at Rotor
  (Depending on Model)
Hydraulic Feed
High Speed Design Requires Less Horsepower
  than Direct Drive Models
Double Sided A8 Tool Steel Knives
Adjustable Hardened Anvil

SMV is Standard Equipment
1 Year Parts and Labor Warranty

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1511XF		WC1205 Wood Chipper, 3-Point, PTO Drive, Hydraulic Feed 5 In. Capacity	7,624.00
		SPECIAL EQUIPMENT - FACTORY INSTALLED	
8000		WC1205 Self-Contained Hydraulics	909.00
8010		WC1205 Auto Feed (Speed Control)	1,028.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5PQ903179	French Operators Manual & Decal Kit WC1205 Wood Chipper *Destination of Quebec only. Includes French safety decals and manual.*	62.72

WC1205 Wood Chipper, 3-Point, PTO Drive, Hydraulic Feed 5 In. Capacity
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

WC1208 Wood Chipper, Pull Type, PTO Drive, Hydraulic Feed 8 In. Capacity

Equipment for Base Machine

Using a Belt Drive System
  PTO Speed Increased from
  540 to 2050 RPM's at Rotor
  (Depending on Model)
Hydraulic Feed
High Speed Design Requires Less Horsepower
  than Direct Drive Models
Drum-Style Rotor
Double Sided A8 Tool Steel Knives

Adjustable Hardened Anvil
SMV is Standard Equipment
1 Year Parts and Labor Warranty

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1513XF		WC1208 Wood Chipper, Pull Type, PTO Drive, Hydraulic Feed 8 In. Capacity	15,509.00
		SPECIAL EQUIPMENT - FACTORY INSTALLED	
8000		WC1208 Self-Contained Hydraulics	1,146.00
8010		WC1208 Auto Feed (Speed Control)	1,157.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous:	
	5PQ903185	French Operators Manual & Decal Kit WC1208 Wood Chipper *Destination of Quebec only. Includes French safety decals and manual.*	62.72

WC1208 Wood Chipper, Pull Type, PTO Drive, Hydraulic Feed 8 In. Capacity
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK